GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI-HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No. F6/DFS/MS/Hotel/NDZ/2022/ 127

Dated:-**2.5/03**/2022

FIRE SAFETY CERTIFICATE

Certified that the Hotel Hans Pvt Ltd, part building 15th to 21st floor -78 guest room) located at Hansalya Building, 15, Barakhamba Road, New Delhi comprised of Basement + Ground + 21 Upper floors, (ground floor - hotel reception lobby and fire control room, 1st floor- bank, 2nd floor- Restaurant & Banquet) & 15th to 21st hotel occupancy (78 guest room), was earlier granted FSC by this department vide letter No. F6 / DFS/ MS/ 2019/ NDZ/ 604 dated 25/03/2019. Now, The premises was re-inspected by the officer concerned of this department on 10/03/2022 in the presence of Sh. Satpal (Chief Engineer). Sh. Sushil Kumar (Estate Manager) & Sh. Gurmukh Singh, Fire consultant and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class – Hotel building Group –A with effect from 2.5. 221.202... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ...25 f. 0.3)21...... at New Delhi by.

Delhi Fire Service

Copy to:

- 1. The Chief Architect, NDMC, Palika Kendra, New Delhi
- 2. The Manager, Hotel Hans Pvt. ltd., Hansalya building 15- Barakhamba Road, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape staircase, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT

1. Name & address of the building: Hansalaya Properties Part building B+Gr.+14th

located at Hansalya Building, 15, Barakhamba

Road, New Delhi B+Gr.+21st floor

: Business Building (Mixed Occupancy) 2. Type of occupancy

(3rd floor to 14th floor commercial office, 2rd floor-restaurant & banquet, 1st floor- bank, ground floor- hotel reception lobby and fire control room), basement -parking and services & 15th to 21st hotel occupancy other portion

Old Case

(78 guest room)

: Renewal (12 point base inspection) 3. Type of case:-

: F6/DFS/MS/Hotel/2019/NDZ/667 dated 29.03.2019 4. Details of previous FSC

5. Fire safety directives No. : N/A

6. Date of inspection:-10/03/22

: Sh. Rajinder Atwal DO/CD & 7. Name of the inspecting officer Sh. Ravinder Singh ADO/CC

8. Name & designation of officer From the building side

: Sh. Pankaj (chief Engineer & Sh. Sushil Kumar (E.M), Sh. Gurmukh Singh, Fire consultant

9. Year of construction : 1979

: Nil dated 21/02/2022 10. Applicant's letter No

Provided at site Remarks S No Minimum Standards on fire Requirement

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	P	rovided at site		ir/NMR	
1.	Access to Building	5					
	1) Road width	Accessible	1	1.2 & 9.9 mtr.	M	R	
	2) Gate width	N/A	5	& 7 mtr.	N/	/A	
	3)Width of internal road	N/A		8 & 14 mtr (2 side)	N/	/A	
2.	Number, Width Type & Arrar	gement of Exits					
	A. Number of staircases						
	1. Upper floors	01 No.		1 No.	M	R	
	2. Basements	01 No		l No. & One amp	M	R 	
	B. Width of staircase						
	1. Upper floors	1.25 mtr.	_	.35 mtr.	M		
	2. Basements	1.25 mtr.	1.	.35 mtr.	M	R	
	C. Protection of exits						
	1. Fire check door	Required	_			R	
	2. Pressurization	NA		NA		A	
	D. No. of continuous staircase to terrace	01 No	0	1 No	M	R	
	E. Width of corridor	NA	1.	1.4 mtr.		N/A	
	F. Door size	1 Mtr.	1	1 Mtr.		MR	
3.	Compartmentation						
	1) Fire check door	Required	P	Provided		MR	
	2) Sealing of electrical shafts	Required	P	Provided		MR	
	3) Fire rating of shaft door	N/A	N	N/A		N/A	
	4) Water curtain	N/A	N	N/A		N/A	
	5) Fire Dampers	NA	N	A	N.	A	
4.	Smoke Management System						
	1) Basements	30 ACPH		Provided		MR	
	2) Upper floors	12 ACPH		Natural		MR	
5.	Fire Extinguishers						

80 Nos.

85 Nos.

MR

1) Total numbers

2) Types // // // // // // // // // // // // //	ABC & CO2	ABC, CO2 & W.CO2	MR			
3) 1SI marking	Required	Provided	MR			
First-Aid Hose Reel		and the second s				
1) Total number of each	1/2/3 Nos	02 nos at ground				
floor		03 in basemen and 01 no. at res				
		floors				
2) Length of hose reel hose	30 m	30 m	MR			
3) Nozzle diameter	5 mm	5 mm	MR			
Automatic Fire Detection & Alarming System						
1) Type of detectors(smoke	NA	Provided some	NΛ			
)	INZ	offices				
2) Location of main panel	NA	Provided some	NA			
22.1		offices	NA			
3) Location of repeater panel	NA	NA	NA			
4) Alternate source of power	NA	NA NA	NA			
5) Hooter's Location MOEFA	NA Paguinad	NA Provided	MR			
	Required	Provided	MR			
Public Address System Automatic Sprinkler System	Required	FTOVICE	IVIIC			
Automatic Sprinkler System 1) Basement	Required	Provided	MR			
2) Upper floors	Required	Provided	MR			
3) Sprinkler above false		NA	NA			
ceiling	NA					
Internal Hydrants						
1) Size of riser/down-comer	150 MM	150 MM	MR			
2) Number of hydrants per	1/2/3 nos	02 nos at ground,	MR			
floor		03 in basement and 01 no, at rest				
		floors				
3) Hose box each floor	01/02 / 03 nos	01/02 / 03 nos	MR			
Yard Hydrants						
1) Total number of hydrants	N/A	04	N/A			
2) Hose box	N/A	04	N/A			
Pumping Arrangement	Combined pump	serving to whole bui	lding			
Ground level Discharge of main	2850 LPM	2050 1 51 1				
pump	2030 LIW	2850 LPM	MR			
b) Head of main pump	130 mtr.	130 mtr.	N 445			
c) Number of main	02	02	MR			
pump		V m	MR			
d) Jockey pump out put	900 LPM	900 LPM	MR			
e) Jockey pump head	130 mtr.	130 mtr.	MR			
f) Stand by pump	2850 LPM	2850 LPM	MR			
output			IVIK			
g) Stand by pump head	130 mtr.	130 mtr.	MR			
h) Auto starting/Manual	Required	Provided	MR			
starting/Manual stopping			WIK			
3) Terrace level						
o, remace level			A STATE OF THE PARTY OF THE PAR			
a) Discharge of pump	N/A	N/A				
		I INLA	N/A			

NIA

1.1 Pump

	b) Head of pump	b) Head of pump N/A		N/A	
	Power supply	N/A		N/A	
	d) Auto starting of	N/A		N/A	
14.	Pump	1		IN/O	
14.	Captive Water Storage for El	re Fieb	tina		
	Under ground tank capacity		Required	1.00,000X3 =	MR
	ground tank capacity		Required	3,00,000 ltr.	
	a) Draw-off connection		Required	Provided	MR
	b) Fire service inlet		Required	Provided	MR
	c) Access to tank		Required	Provided	MR
	d) Over head tank come	ity	Required	40,000 Ltrs.	MR
5.	Exit Signage.	цy	Required	Provided	MR
			Required	Flovided	IVIIC
16.	Provision of Lifts.		4 Nos. Lift form Commercial 1 st floor to 1		4 floor.
			2 Nos. Lift from		
	a) Pressurization of lift shaft		1 Nos. Lift service from Gr. to 21st floor		NT/ 4
	b) Pressurization of lift lobby		N/A	N/A	N/A
	c) Communication in lift car		N/A	N/A	N/A
	d) Fireman's switch	car	Required	Provided	MR
	e) Lift signage		Required	Provided	MR
7.	Stand by Power Supply		Required	Provided	MR
8.	Refuge Area		Required	Provided	MR
-			Required	1177 M^2	MR
	Total area location		Required	15 th floor 352	MR
				M^2	
				23 rd floor 825	
19.	Fire Control Room		N1/A	M ²	
			N/A	Provided	N/A
	a) Detector system panel		N/A	N/A	N/A
	b) Flow quiteb				
	b) Flow switch panel		N/A	Provided	N/A
	c) PA system panel		N/A	Provided	N/A
	d) Battery backup		N/A	Provided	N/A
	a) Puilding floor !				
	e) Building floor plan		N/A	Provided	N/A
	Special Fire Protection System	for Pro	tection of spec	rial Dick if one	NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection. Further, in previous inspection report detector are mentioned where as in 12 point base inspection, either detectors or MCP are required.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, the FSC issued vide letter no. F6/DFS/ MS/ Hotel/ 2019/ NDZ/667 dated 29.03.2019, renewal of above building under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Rajinder Atwal Designation :- DO/CD

Name :- Ravinde

Designation :- ADO (CC)