

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2022/17-3

Dated: 30/03/2022

## FIRE SAFETY CERTIFICATE

Certified that the Hare Krishna Guest House located at 1572-73, Main Bazar, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Reception + lobby + 01 guest rooms), 1st floor to 3rd floor (06 guest rooms at each floor) & 4th floor (05 guest rooms), total 24 guest rooms was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH//NDZ/2019/807 dated 12/04/19. Now, the premises was re-inspected by the officer concerned of this department on 29/03/22 in the presence of Sh. Ankur Goel and found that the said guest house building having given an affidavit dated 28.11.2019 regarding not to use any floor above third floor, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (Reception + lobby + 01 guest rooms), 1st floor to 3rd floor (06 guest rooms at each floor ) total - 19 guest rooms up to third floor only with effect from ... 3.0.1.0.3. 2022.... for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued ..0.3.1.0.3.1.20.2.2...at New Delhi by.

(Dr. S.K.Tomar) Dy. Chief Fire Officer Delhi Fire Service

## Copy to:-

- 1. The Commissioner, North MCD, Civic Centre, New Delhi : to ensure the occupancy as detailed above
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi: -ID no. 2022032304026 dated 23.03.2022.
- 3. The Manager,
  - Hare Krishna Guest House at 1572-73, Main Bazar, Pahar Ganj, New Delhi.

## Conditions for the validity of Fire Safety Certificate

- This clearance/ FSC shall stand cancelled if guest house owner/occupier fails to comply all other conditions mentioned in the gazette notification dated 27.05.2019 & clarification issued on dated 20.12.2021, latest by 31.03.2022.
- 2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the
- The trained fire fighting staff should be available round the clock.
- Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 10. Any flammable material for interior decoration is prohibited.

	Name & address of the building  Type of occupancy:-  Type of case:-  Details of previous FSC:-  Name of the inspecting officer:-  Name of the inspecting officer:-  INSPECTION REPORT  Hare Krishna Guest House at 1572-73,  Main Bazar, Pahar Ganj, New Delhi  Residential, Sub Division-A-1  Gr. + 04 Upper floors (total 19 Guest rooms)  Ground floor (Reception + lobby + 01 guest rooms),  1st floor to 3rd floor (06 guest rooms) de 4th floor not in use as per affidavit dated 28.11.2019  Renewal  No. F6/DFS/MS/GH/2019/NDZ/807 dated  12/04/19.  N/A  29/03/22  Sh. Rajinder Atwal (ADO/CD)  Sh. Ravinder Singh (ADO/CC)						
;	<ol><li>Name &amp; designation of officer</li></ol>						
	From the building side:-	Sh. Ankur	Goel				
9	9. Year of construction:-	Year of construction:- 1991					
1	. Applicant's letter No:- ID no. 2022032304026 dated 23.03.2022.						
				Old Case			
S.No	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR			
1.	Access to Building						
	1) Road width	N/A	12 mtr.	MR			
	2) Gate width	N/A	N/A	MR			
	3)Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arrangement of Exits						
	A. Number of staircases						
	1. Upper floors	01 Nos.	02 Nos.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase						
	1. Upper floors	0.80 mtr.	1.10 Mtr. 0.90 mtr.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits						
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous staircase to terrace	N/A	N/A	N/A			
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	01 mtr.	01 mtr.	MR			
3.	Compartmentation						
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System	1		1 1/ / 1			
7.	1) Basements	30 ACPH	N/A	N/A			
	2) Upper floors	Required as per G.N dated 27.05.19	Not provided	Last dt. 31.03.22 of compliance extended vide order dt. 20.12.2021			

dt. 20.12.2021

1) Total numbers 2) Types 3) ISI marking First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & 1) Type of detectors CIO type	Required as		MR MR MR MR MR MR
2) Types 3) ISI marking First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & 1) Type of detectors CIO	ABC & CO2 Required  01 30 mtr. 05 mm  Alarming Syst Required as	ABC & CO2 Provided  01 30 mtr. 05 mm	MR MR MR MR
2) Types 3) ISI marking First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & 1) Type of detectors CIO	ABC & CO2 Required  01 30 mtr. 05 mm  Alarming Syst Required as	ABC & CO2 Provided  01 30 mtr. 05 mm	MR MR MR MR
3) ISI marking First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & 1) Type of detectors CIO	Required  01 30 mtr. 05 mm  Alarming Syst Required as	Provided  01 30 mtr. 05 mm	MR MR MR
First-Aid Hose Reel  1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter  Automatic Fire Detection & 1) Type of detectors CIO	01 30 mtr. 05 mm Alarming Syst	01 30 mtr. 05 mm	MR MR
Total number of eachfloor     Length of hose reel hose     Nozzle diameter     Automatic Fire Detection &     Type of detectors CIO	30 mtr. 05 mm Alarming Syst	30 mtr. 05 mm	MR
2) Length of hose reel hose     3) Nozzle diameter     Automatic Fire Detection &     1) Type of detectors CIO	30 mtr. 05 mm Alarming Syst	30 mtr. 05 mm	MR
3) Nozzle diameter  Automatic Fire Detection &  1) Type of detectors CIO	05 mm  Alarming Syst  Required as	05 mm	
Automatic Fire Detection &  1) Type of detectors CIO	Alarming Syst Required as	em	MR
1) Type of detectors CIO	Required as		
1			1 21 02 22 24
type		Not provided	Last dt. 31.03.22 of
	per G.N dated		extended vide order
	27.05.19		dt. 20.12.2021
2) Location of main panel	N/A	N/A	N/A
3) Location of repeater panel	N/A	N/A	N/A
		N/A	N/A
		N/A	N/A
			MR
			MR
		Tiovided	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
		N/A	N/A
/			N/A
			N/A
	18/73	1 1 7 1	
	100 mm	100 mm	MR
		01	MR
,	0.		
	01	01	MR
1) Total number of hydrants	N/A	N/A	N/A
		N/A	N/A
,			
	N/A	N/A	N/A
		N/A	N/A
b) Head of main numn	N/A	N/A	N/A
a) Number of main nump		N/A	N/A
d) Tookey nump out nut		N/A	N/A
a) Lookey pump head		N/A	N/A
		N/A	N/A
			N/A
. 01			N/A
	14/74		
	225 L.PM	225 LPM	MR
			MR
	50 111111		MR
c) Power supply	1000		MR
d) Auto starting of pump	Required	1 10 11404	
	4) Alternate source of power 5) Hooter's Location  MOEFA  Public Address System  Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling  Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box  Yard Hydrants 1) Total number of hydrants 2) Hose box  Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump	4) Alternate source of power 5) Hooter's Location  MOEFA Required Public Address System Automatic Sprinkler System  1) Basement N/A 2) Upper floors N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Vard Hydrants 1) Total number of hydrants 2) Hose box N/A  Pumping Arrangement 1) Ground level A) Discharge of main pump b) Head of main pump C) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump head N/A f) Stand by pump head N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump C) Power supply Required	4) Alternate source of power 5) Hooter's Location N/A N/A  MOEFA Required Provided  Public Address System Required Provided  Automatic Sprinkler System  1) Basement N/A N/A  2) Upper floors N/A N/A  3) Sprinkler above false ceiling  Internal Hydrants  1) Size of riser/down-comer 100 mm 100 mm  2) Number of hydrants per floor  3) Hose box 01 01  Yard Hydrants  1) Total number of hydrants N/A N/A  2) Hose box N/A N/A  Pumping Arrangement  1) Ground level N/A N/A  a) Discharge of main pump N/A N/A  b) Head of main pump N/A N/A  f) Stand by pump out put N/A N/A  b) Auto starting/Manual stopping  2) Terrace level  a) Discharge of pump 225 LPM  b) Head of pump  c) Power supply Required Provided



١.	Captive Water Storage for Fire	Eighting		
	Under ground tank     capacity	N/A	N/Λ	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5,000 ltr.	5,000 ltr.	MR
5.	Exit Signage.	Required	Provided	MR
6.	Provision of Lifts.	,		
,	Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syster if any:	NA		

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2019/NDZ/807 dated 12/04/2019 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended up to third floor only.

Signature of the inspecting officer

Signature of the Inspecting Officer

Name: - Rajinder Atwal Designation: - DO (CD)

Name: Ravinder Singh

Designation: ADO (CC)