FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE [Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No.F6/DFS/MS/SZ/2022/School/ 34-3

Dated: 30 /03/2022

FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Kanya Vidhalaya No-2, Located at Palam Village, New Delhi – 110045 having three blocks BL-A=Ground floor (Pota cabin), BL-B=G+1UF & BL-C=G+3UF, was issued FSC vide Letter No. F6/DFS/MS/School/2015/SZ/646, Dated-30/04/2015. The premises was re inspected by the officer concerned of this department on 23/02/2022 in the presence of Mr. Gajraj Singh (Estate Manager) and found that premises have deem complied with the fire prevention and fire safety requirements in accordance with DOE Circular 3298-3398 Dated 01/03/2011 issued by Directorate of Education, Govt. of NCT of Delhi and that the building is fit for occupancy class B "Educational building" with effect from 30/03/2022 for a period of three years, in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 30/03/2022 at New Delhi by.

(Sunil Chaudhary)
Dy. Chief Fire Officer
Delhi Fire Service.

Copy to:

1. Directorate of Education Old Secretariat Delhi – 110054.

2. The Principal, Sarvodaya Kanya Vidhalaya No 2, 110045.(School-ID-1821015)

Palam Village, New Delhi -

Following fire safety directives must be adhered to:-

- 1 All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3 The trained staff should be available round the clock.
- 4 Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5 The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6 The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7 Basement shall be used strictly as per building bye laws.
- 8 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

N//6 INSPECTION REPORT

1. Name & address of the building: Sarvodaya Kanya Vidhalaya No 2, Located at Palam Village, New Delhi – 110045.

2. Type of Occupancy : Educational (03 Blocks= BL-A=GF<u>(Pota cabin)</u>, BL-B=G+1UF & BL-C=G+3UF,

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/School/2015/SZ/646 Dated-

30/04/2015

5. Fire Safety directives Letter No.: DOE 3298-3398 dated 01-03-2011

6. Date of inspection

: 23-02-2022

7. Name of the Inspecting Officer: Udai vir Singh, ADO (DWK)

8. Name and designation of Officer

from the building side

: Ms. Sunita Sikri (HOS)

9. Year of Construction

: Old block Before 2010 & New block 2011

10. Applicant's letter No.

: Email Dated 10/02/2022

	••		Dated 10/02/2022		
S No	Minimum standards on fire prevention and fire safety U/R 33	As per N/4	Provided at site	Remarks MR/NMR	
1.	Access of building				
	 Road width 	06mtrs	18 mtrs	MR	
	Gate width	4.5mtrs	Provided	MR Old case	
	 Width of internal road 	NA	NA	. NA	
2.	Number, width, Type & Arrange	ements of exits			
	a. Number of staircases				
	Upper floors	02 each bloc	k 02 each bloc	k MR	
	Basements:	NA .	NA ·	· NA	
	b. Width of staircases				
	Upper floors		B=159cm &143cm C=2x145cm	MR(Old Case)	
	Basements	NA	NA	NA	
	c. Protection of exits				
	 Fire check door 	NA	NA	NA	
	 Pressurization 	NA	NA	NA	
	d. No of continuous	Required	01 No each block	MR	
	staircase to terrace				
	e. Width Of Corridor	1.5 mtr	240cm &165cm	MR(Old Case)	
	f. Door Size	Required	90cm 104cm	MR(Old Case)	
3.	Compartmentation			•	
	 Fire check door 	NA ·	NA ·	NA	
	Sealing of electrical shafts	NA	NA	NA	
	Fire Rating of shaft door	ŊA .	NA	NA	
	Water Curtain	NA ·	NA ·	NA	
	 Fire Dampers 	NA	NA	NA	



N/17

		•/\	111+		
4.	Smoke managements System		,		
	Basements	NA	NA	NA	,
	 Upper floors 	12 a/c per	Natural	MR	
		hour	ventilation	1	
5.	Fire Extinguishers			·	
	 Total numbers 	02 Nos each	14 Nos.	MR	
	• Types	floor,per	ABC & CO ₂	MR	
	IS marking	block	Provided Provided	MR	
	- manning	ABC & CO ₂	Tiovided	IVIK	
	,	ISI marked			
6.	First – Aid Hose Reels	191 marked			
	 Total numbers on each 	Required in	01	MD	
	floor	Each Block	01	MR	
	 Length of hose reel 	Buch Diock			, ·
	hose	30m	20	7.65	•
	Nozzle diameter		30 m	MR	
7.	Automatic fire detection 1.1	5mm	05 mm	MR	
′·	Automatic fire detection and alar	rming system			
	Type of detectors	NA	NA ·		NA ·
	 Location of Main Panel 	NA	NA		NA
	 Location of Repeater 	NA ·	NA		NA
	Panel				
	 Alternate source of 	NA	·NA		NA
	power				1771
	Hooters' Location	NA	NA ·		NA
8.	MOEFA	NA	· NA		NA
9.	Public Address System	NA	NA NA		NA NA
10	Automatic Sprinkler System		IVA		INA
			•		
	 Basements 	NA	. NA		NA
	Upper Floor	NA	NA		NA ·
	Sprinkler above false				
	ceiling	NA .	NA		NA
11	Internal Hydrants:				
	Size of riser/down-	NA.	100 mm		NIA .
	comer		100 11111		NA .
	 Number of hydrants per 	NA	NA :		
	floor	INA	. INA	v	NA
	Hose Box	NA	Provided) (D)
12	Yard Hydrants	INA	Provided		MR
12	rard Hydrants				
•	Tr. 1	NIA	7,		
	Total number of	NA	NA		NA
	hydrants				
	Hose Box	NA	NA		NA
			1		
					1



2	D.			*	1/18			
3	Pumpi	ng Arrangements:						
	•	Ground Level						
	•	Discharge of main pump						
	4	Head of main pump	NA		NA			NA
	4	Number of main pumps	NA		NA			NA
	4	Jockey pump out put	NA		NA			NA .
	4	Jockey pump head	NA		NA			NA
	>	Standby Pump out put	NA		NA			NA
	4	Standby Pump Head	NA		NA		·	NA
	. >	Auto Staring/Manual	NA		NA			NA .
		stopping	NA		NA			NA
	>	Tump House Access		NIA NIA				
	•	Terrace level	NA		NA			NA
	4	Discharge of pump	450		0.40	-0.1		MR
	>	Head of the pump		lpm		50 lpm		MR
	A	Power supply		quired	35 m			
	>	Auto starting of pump		quired		vided		MR
14	Captiv	e water Storage for fire fig	NA		NA			NA
	Cupity	e water storage for fire fig	gnting:					
	•	Underground tank	NA		NA	· · ·		NA
		capacity	INA		NA		•	INA
	4	Draw off connection .	NA		NA	•		NA
		Fire service inlet	INA		INA			1471
	1	Access to tank	NA		Provided			NA
		Overhead Tank	NA NA	· · · · · ·	NA	ieu ,		NA ·
		capacity	Requ	ired	10,000) ltr		MR
15	Exit S		Requ		Provid			MR
16		ion of Lifts	·	ncu	Tiovia	icu		17114
	110115	ion of Bitts _.						
	4	Pressurization of Lift Sha	ıft	NA NA		NA		NA
		Pressurization of lift lobb		NA		NA		NA
		Communication in lift Ca		NA		NA		NA
		Fireman's Grounding Sw		NA		NA		NA
٠.		Lift Signage		NA		NA		NA
17	Standl	by power supply		NA		NA		NA
							·	
18	Refuge Area					·		
	>	Total area		NA		NA		NA
	>	Location		NÅ		NA ·		NA _
19	Fire control room							
				İNTA				
		Detector system panel		NA		NA		NA
		Flow Switch PanelPA System Panel		NA		NA		NA
	1			. NA		NA		NA
	>	Battery backup		NA		NA		NA
	>	Building Floor Plans	٠.	NA		NA		NA
		•		, .				
		,						
		•						
			•					
				1 .				1

		•		•
		W/19		
20	Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA
	The fire protection systems provided	in the buil	ding were test	checked and found
func	tional at the time of inspection.			
	In view of the deemed compliance of			
safet	ty as required under the rules the NOC is	sued vide let	tter F6/DFS/MS/	School/2015/SZ/646

Dated-30/04/2015 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer
Name
Designation

solve Ws

2/3/22

Oyero (S2)

HOCOUK)

Linte botten is but up for eighty

Dycrolsz

MC W