GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No.F6/DFS/MS/2022/Metro/ 14 2

-

Dated 61 /04/2022

FIRE SAFETY CERTIFICATE

Certified that the Adarsh Nagar Metro Station (Line- 2), Delhi comprised of Ground Level + Concourse Level + Platform Level owned/occupied by Delhi Metro Rail Corporation Ltd. was granted NOC by this department vide letter no. F6/DFS/MS/2009/661 dated 05.03.2009. The premises was re-inspected by the officers concerned of this department on 23.03.2022 in the presence of Mr. Ashish Antil (Fire Inspector) and found that the building/premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules,2010 and the building/ premises is fit for occupancy class 'D' Assembly Building only with effect from Oloup 122 for a period of 03 (Three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(DharampalBhardwaj) Dy. Chief Fire Officer Ph-011-25156707

Copy to:-

1. Sh. Ashish Antil (Fire Inspector), Delhi Metro Rail Corporation Ltd. Azadpur Metro Station (Line- 2), Delhi

Conditions for the validity of Fire Safety Certificate:

- 1 All the means of escape/entry/exit shall be kept free from any obstruction.
- 2 All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3 All the staff members must know the correct method of operation of firefighting system.
- 4 The owner / occupier shall submit a declaration **every year** in **Form "K"** provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in./wps/wcm/connect/doit fire/FIRE/Home/Forms.
- 5 This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6 "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in **Form 'J'** [sub rule (1) of rule 37] along with a copy of this Certificate, **six months** prior to its expiry".

INSPECTION REPORT

1. Name & address of the building: Adarsh Nagar, Metro Station (Line-2), Delhi.

2. Type of Occupancy : Assembly-Group-D Sub division –D-7

3. Type of Case : Renewal (Ground Level + Concourse Level + Platform Level)

4. Details of previous NOC : F6/DFS/MS//2009/661 dated 05.03.2009

5. Fire Safety directives letter No : F6/DFS/MS/BP/2007/3707dated 13.12.2007.

6. Date of inspection : 23.03.20227. Name of the Inspecting Officers : ADO (RN)

8. Name and designation of officers

from the building side : Mr. Ashish Antil (Fire Inspector)

9. Year of Construction : 2009

10. Applicant's letter No. : Online E-mail ID dated: 08.03.2022

S. No	Minimum Standards on fire prevention and fire safety U/R 33	On NBC Requirement/ Clauserio 35(6) % DES Rules 2010	Provided at site	Remarks MR/NMI				
	Access to building							
	Road width	09m	Provided	MR				
	Gate width	NA	NA	NA				
	• Width of internal road	NA	NA	NA				
	Number, Width, Type & Arrangement of Exits							
	a. Number of staircases							
	Upper Floors	04nos Concourse to platform 04 nosground to Concourse	Provided	MR				
	Basements b. Width of staircases	NA	NA	NA				
	 Upper Floors concourse to platform 	2m each	4.00m x 2 no's 2.02 m x 2 no;s	MR				
	02 s/c concourse to ground 02 s/c platform to street 1.8 x2	2m each	4.00m x 2 no's 2.02 m x 2 no;s					
	• Basements	NA	NA	NA				
	c. Protection of exits							
	Fire check door	NA	NA	NA				
	 Pressurization 	NA	NA	NA				
	d. No. of continuous staircases to	02	Provided	MR				
	terrace	NA	NA	NA				
	e. Width of Corridor f. Door Size	1.0m	1.0m	MR				
	Compartmentation.							
	• Fire check door	Required	Provided	MR				
	Sealing of electrical shafts Fig. Bating of chaft door.	Required	Provided	MR				
	Fire Rating of shaft doorWater Curtain	Required	Provided	MR				
	Fire Dampers	NA	NA	NA				
		N/A	N/A	N/A				
	Smoke Management System.							
	Basements	30АСРН	NA	NA				
	Upper floors	12ACPH	Provided	MR				
	Fire Extinguishers							
	_	Q ₀						

	Total numbers	32nos	32nos	MR			
	• Types	1SI marked	Provided	MR			
	IS marking	Required	Provided	MR			
		Required					
6	First-Aid Hose Reels.	02 on each platform	MR				
	Total numbers on each floor	02 on each platform 04 on Concourse/ Plat form	04 on Concourse Plat form				
		45m	45m 25 mm .				
	Length of hose reel hose	25mm	45m	MR			
		45m					
	Nozzle diameter	5mm	5mm	MR			
7	Automatic fire detection and alarming sys		MD				
	Type of detectors	Smoke	Provided	MR			
	Location of Main Panel	Required	Provided	MR			
	Location of Repeater Panel	NA	NA	NA			
	Alternate source of power	Descriped	Provided	MR			
	Hooters' Location	Required					
		Required	Provided	MR			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	NA	NA	NA			
	Upper Floor	NA	NA	NA			
	Sprinkler above false ceiling	NA	NA	NA			
1	Internal Hydrants	100mm	100mm	MR			
	Size of riser/down-comer	Required	Same as col. no 6	MR			
	Number of hydrants per floor		Same as col. no 6	MR			
_	Hose Box	Required	Same as cor. no o	IVIK			
2	Yard Hydrants.						
	Total number of hydrants	02	02	MR			
	Hose Box	Required	Provided	MR			
3	Pumping Arrangements.						
	> Ground Level						
	Discharge of main Pump	1800 Lpm	1800 LPM	MR			
	Head of Main pump	60 mtr	60m	MR			
	Number of main pumps	01	01	MR			
	Jockey Pump out put	180 LPM	180 LPM	MR			
		60 m	60m	M/R			
	Jockey pump headStandby Pump out put	1800LPM	1800 LPM	MR			
	Standby Pump Head	60 mtr	60m	MR			
	Auto Starting/ Manual stopping	Required	Provided	MR			
	Pump House Access	Required	Provided	MR			
	• Terrace level						
	Discharge of pump	NA	NA	NA			
	Head of the pump	NA	NA	NA			
	> Power Supply	NA	NA	NA			
	Auto Starting of pump	NA	NA	NA			



14	Captive Water Storage for fire fighting.						
	Underground tank capacity	50,000ltrs	50,000ltrs	MR			
	Draw-off connection	Required	Provided	MR			
	Fire service inlet	Required	Provided	MR			
	Access to tank Overhead Tank capacity	Required	Provided	MR			
	Overhead Tank Capacity	NA	NA	NA			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	NA	NA	NΛ			
	Pressurization of Lift lobby	NA	NA	NA			
	Communication In lift Car Figure 2. Counting Springle	Required	Provided	MR			
	Fireman's Grounding SwitchLift Signage	Required	Provided	MR			
		Required	Provided	MR			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.						
	> Total Area	NA	NA	NA			
	Location	NA	NA	NA			
19	Fire Control Room						
	Detector System Panel	Required	Provided	MR			
	Flow Switch Panel	NA	NA	NA			
	PA System Panel	Required	Provided	MR			
	Battery backupBuilding Floor Plans	Required	Provided	MR			
	- Danding Floor Flans	NA	NA	NA			
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	Provided	MR			

The fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection. The metro management has complied all the observations which were issued earlier vide this office letter of even no.7843 dated 24.12.2019.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in NBC Part-IV the FSC issued vide letter of even no 661 dated 05.03.2009 renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

DO (NW) - ON Leave

Do (WETF) -

Signature of the Inspecting Officer

Name - C.L. Meena

Designation:- ADO/RN

Der (wz)

REN

Cont -- P.T.