017

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F. ODFS/MS/School/2022/SZ/ 4/7

Dated: 13/04/2022

FIRE SAFETY CERTIFICATE

Comprised of ground plus one upper floor was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/2019/SZ/358 Dated 08/02/2019. The said premise was re-inspected by officer concerned of this department on 06/04/2022 in presence of Mrs. Sumitra Bisht (Principal) the school and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education Circular No F.16//Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011 issued by Director of Education, Govt. of NCT of Delhi and that the building is fit for occupancy class "Educational Building Group – B" with effect from \(\frac{13}{9} \frac{9}{9} \frac{1}{9} \frac{2022}{9} \) for a period of Three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 13/04/2022 at New Delhi by

(SUNIL ĆHAWDHARY) DY. CHIEF FIRE OFFICER (SZ)

Copy to: -

1. The Principal, S.D.M.C Girls/Boys School locate at Sector- 6, R.K Puram, New Delhi 110022

2. The Director of Education, South MCD, Civic Centre, Minto Road, New Delhi-110002

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

NIIO

	INSPECT	ION REPORT				
1	Name & Address of the Building	S.D.M.C Girls	/Boys School, located a	t Sector-6,		
		R.K Puram, New Delhi 110022				
_2	Type of Occupancy	Educational, Group-B (School)				
3	Building Comprised of	Ground plus one upper floor				
4	Type of Case	Renewal				
5	Details of Previous NOC	F6/DFS/MS/School/2019/SZ/358 Dated 08/02/2019				
6	Fire Safety Directives Letter No	DOE Circular 01/03/2011				
7	Date of Inspection	06-04-2022				
8	Name of the Inspecting Officers	Sh. Rajesh Kumar, ADO (BCP)				
9	Name & Designation of Officers	Mrs. Sumitra Bisht (Principal)				
	from the building side					
10	Year of construction	1966	1966			
11	Applicant letter No.	Gmail of dated 2				
S. No	Minimum standards on Fire Prevention	Old NOC	Provided at Site	Remarks		
	and Fire Safety U/R 33	Requirement		MR/NMF		
1	Access to Building.		Y			
	Road width	6 mtr	9 mtr	MR		
	Gate width	4.5 mtr	4.5 mtr	MR		
	Width of internal road	-NA-	-NA-	-NA-		
2	Number, width, type & arrangement of exits.					
	a) Number of Staircase					
	> Upper floors.	02 Nos	05 Provided	MR		
	Basement floor.	-NA-	-NA-	-NA-		
	b) Width of Staircase					
	Upper floors	1.50m/0.75m	1.40 m, 1.40m, 1.10m,	MR		
			1.05m & 1.05 m			
	Basement floor	-NA-	-NA-	-NA-		
	c) Protection of exits					
	Fire check door	-NA-	-NA-	-NA-		
	> Pressurization	-NA-	-NA-	-NA-		
	d) No. of continuous staircase to terrace	01 Nos	Provided	MR		
	e) Width of corridor	1.50 m	Provided	MR		
	f) Door size	1 m	Provided			
3	Compartmentation.	1 111	riovided	MR		
	Compartmentation.					
	Fire check door.	-NA-	-NA-	-NA-		
	 Sealing of electrical shafts. 	-NA-	-NA-	-NA-		
	Fire rating of shaft door.	-NA-	-NA-	-NA-		
1	Water curtain	-NA-	-NA-	-NA-		
	• Fire dampers.	-NA-	-NA-			
4.	Smoke Management system.		-14/7-	-NA-		
	Basement	-NA-	-NA-	NI 4		
	Upper floors	-NA-	-NA-	-NA-		
5.	Fire Extinguishers.	-11/1-	-INA-	-NA-		
-	Total numbers	06 No's	Deani J. J	1.45		
	Types	ABC / Co2	Provided	MR		
	ISI Marking		ABC Type	MR		
6	First Aid Hose Reels.	ISI mark	Provided	MR		
6.		NT.				
-	Total numbers on each floor.	-NA-	-NA-	-NA-		
	 Length of hose-reel hose. 	-NA-	-NA-	-NA-		
	Nozzle Diameter	-NA-	-NA-	-NA-		
7	Automatic fire detection & alarming system.			1.71		

MI

	Type of detectors	***	1	
	Location of Main Panel	-NA-	-NA-	-NA
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	The state of the s	-NA-
	Hooter's location	-NA-	-NA-	-NA-
8.	MOEFA		-NA-	-NA-
9.	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System	-NA-	-NA-	-NA-
	Basement			
		-NA-	-NA-	-NA-
	• Upper floors	-NA-	-NA-	-NA-
11.	Sprinkler above false ceiling	-NA-	-NA-	-NA-
	Internal Hydrants.			
	Size of Riser/Down-comer	-NA-	-NA-	-NA-
	Number of Hydrant per floor	-NA-	-NA-	-NA-
	Hose box	-NA-	-NA-	-NA-
12.	Yard Hydrants.			
	 Total number of hydrants. 	-NA-	-NA-	-NA-
	Hose box	-NA-	-NA-	-NA-
13.	Pumping arrangements.			-
	Ground Level			
	 Discharge of main pump. 	-NA-	-NA-	-NA-
	 Head of main pump. 	-NA-	-NA-	-NA-
	 Number of main pumps. 	-NA-	-NA-	-NA-
	 Jockey Pump output. 	-NA-	-NA-	-NA-
	 Jockey Pump head. 	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping	-NA-	-NA-	-NA-
	 Pump house access. 	-NA-	-NA-	-NA-
	Terrace Level	,,,,	-5177-	-14/4-
	 Discharge of pump. 	-NA-	-NA-	N/ A
	➤ Head of pump.	-NA-	-NA-	-NA-
1	Power supply.	-NA-	-NA-	-NA-
	 Auto starting of pump. 	-NA-		-NA-
4.	Captive water storage for fire fighting.	-14/4-	-NA-	-NA-
	Underground tank capacity.	-NA-	-NA-	
	➤ Draw-off connection	-NA-		-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
1			-NA-	-NA-
	Overhead tank canacity	. N/ A	N. 7. 4	
	Overhead tank capacity. Exit Signage.	-NA-	-NA-	-NA-
	Exit Signage.	-NA- Required	-NA- Provided	-NA- MR
	Exit Signage. Provision of Lifts.	Required	Provided	MR
	Exit Signage. Provision of Lifts. Pressurization of lift shaft.	Required -NA-	Provided -NA-	MR -NA-
	Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby.	Required -NANA-	Provided -NANA-	MR
	Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car.	-NA- -NA- -NA-	Provided -NANANA-	MR -NA-
	Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch.	-NA- -NA- -NA- -NA-	Provided -NANA-	MR -NA-
	Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage.	-NA- -NA- -NA-	Provided -NANANA-	-NA- -NA- -NA-
. I	Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. itandby Power Supply	-NA- -NA- -NA- -NA-	Provided -NANANANA-	-NA- -NA- -NA- -NA- -NA-
. I	Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. itandby Power Supply Refuge Area	-NANANANANANA-	Provided -NANANANANA-	-NA- -NA- -NA- -NA-
. I	Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. itandby Power Supply	-NANANANANANA-	Provided -NANANANANANA-	-NA- -NA- -NA- -NA- -NA- -NA-
. I	Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. itandby Power Supply Refuge Area	Required -NANANANANANANA-	Provided -NANANANANANA-	-NA- -NA- -NA- -NA- -NA- -NA-
. S	Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area Total area Location	Required -NANANANANANA-	Provided -NANANANANANA-	-NA- -NA- -NA- -NA- -NA- -NA-
. S	Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage itandby Power Supply Refuge Area Total area	Required -NANANANANANANA-	Provided -NANANANANANA-	-NA- -NA- -NA- -NA- -NA- -NA-

N/12

	Flow switch panel.	-NA-	-NA-	-NA-
	PA system panel.	-NA-	-NA-	-NA-
	Battery backup. Building floor plan	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
20.	Special Fire Protection System for the Protection of special Risk, if any.	-NA-	-NA-	-NA-

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/School/2019/SZ/358 Dated 08/02/2019, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer
Name: Sh. Rajesh Kumar
Design: ADO (BCP)

DO (SD)

Liverin

A DOBOT

for jul syndrin

145