GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/School/WZ/2022/ 47/

Dated: 27, 4/2022

j,

1-33

FIRE SAFETY CERTIFICATE

Certified that the New Block, Govt. Sarvodaya Co-Ed. Vidyalaya (School ID-1617007). Located at New Multan Nagar, New Delhi-110056 comprised of Ground + 03 Upper Floors & M.P. Hall owned/ occupied by Govt. Sarvodaya Co-Ed. Vidyalaya have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officer concerned of Fire Service on 11.04.2022 in the presence of Ms. Archana Gupta (Vice Principal) and that the building/premises is fit for occupancy class " Educational Building" Group B with effect from $\frac{29}{10}$ $\frac{1}{10}$ $\frac{1}{10}$ for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on $\frac{29.1.9}{20.2.2}$ at New Delhi by.

104/2

Copy to:-

12

- 1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi 110054
- The Assistant Engineer (E), PWD Sub Div 1 Education Divn M 1 (N), ITI Campus, Pusa, New Delhi-110012.
- 3. The Principal, New Block, Govt. Sarvodaya Co-Ed. Vidyalaya (School ID-1617007), Located at New Multan Nagar, New Delhi-110056.

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- All comments / directions of licensing Department shall always be permitted and followed.
- The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

		<u>INSPECTIO</u>	N REPORT	N=19			
	 Name & address of New Multan Nagar Type of Occupancy 	, New Delhi.	Govt. Sarvodaya Vidy ducational,	y alaya Located at			
			3 Upper Floor & M.I	P. Hall			
			/DFS/MS/School/WZ/				
	4. Details of previous l		1.12.2021 (For Old Bu				
	5. Fire Safety directive	s Letter No. : as	per NBC Part-IV				
	6. Date of inspection	: 1	1.04.2022				
	7. Name of the Inspect	ing Officer : A	man Kumar Lathar, Al	DO (JWP)			
	8. Name and designation	on of Officer	A Lang Currento (Vio	Principal)			
	from the building side 9. Year of Construction	from the building side : Ms. Archana Gupta (Vice Principal) 2 Year of Construction : 2021-22					
	10. Applicant's letter N						
S	Minimum standards on fire	NBC Requirem	ent Provided at	Remarks			
No	prevention and fire safety	NDC Requirem	site	MR/NMR			
	U/R 33						
1.	Access of building Road width	06 mtrs.	Provided	MR			
	Road widthGate width	4.5 mtrs.	Direct accessible	MR			
			from road NA	NA			
	Width of internal road	NA	NA				
2.	Number, width, Type & Arran	gements of exits					
	a. Number of staircases		Provided	MR			
	Upper floors	02 NA	NA	NA			
	 Basements Width of staircases 		1.1.1				
	Upper floors	1.5 mtrs.	Provided	MR			
	• Basements	NA	NA	NA			
	c. Protection of exits	NA	NA	NA			
	Fire check doorPressurization	NA	NA	NA			
	d. No of continuous	02	Provided	MR			
	staircase to terrace	1.5 mtrs.	Provided	MR			
	e. Width Of Corridor f. Door Size	1.3 mtrs.	Provided	MR			
3.	Compartmentation						
5.	Fire check door	NA	NA NA				
	 Sealing of electrical shafts 	NA	NA NA				
	 Fire Rating of shaft door 	NA	NA	NA			
	Water Curtain	NA	NA	NA			
	Fire Dampers	NA	NA	NA			
4.	Smoke managements System						
	• Basements	NA	NA	NA			
	Upper floors	NA	NA	NA			
5.	Fire Extinguishers Total numbers	16 nos.	24 nos. ABC & 24	nos. CO ₂ MR			
	Total numbersTypes	ABC & CO_2	Provided	MR MR			
	 IS marking 	ISI marked	Provided	MR			
6.	First - Aid Hose Reels						
	• Total numbers on each		02 Provide				
	Length of hose reel hos	e , _	30m Provide 5mm Provide	and the second se			
	 Nozzle diameter 	M	5mm Provide				

-

		N. 20			
7.	Automatic fire detection and alarming syste	em		NA	
	• Type of detectors	NA	NA	NA	
	 Location of Main Panel 	NA	NA	NA	
	 Location of Repeater Panel 	NA	NA	NA	
	 Alternate source of power 	NA	NA	NA	
	 Hooters' Location 	NA	NA		
8.	MOEFA	NA	NA	NA	
9.	Public Address System	NA	NA	NA	
10.	Automatic Sprinkler System				
	Basements	NA	NA	NA	
	Upper Floor	NA	NA	NA	
	• Sprinkler above false ceiling	NA	NA	NA	
11.	Internal Hydrants				
	Size of riser/down- comer	NA	NA	NA	
	 Number of hydrants per floor 	NA	NA	NA	
	 Hose Box 	NA	NA	NA	
12.	Yard Hydrants				
12.	Total number of hydrants	NA	NA	NA	
	 Hose Box 	NA	NA	NA	
13.	Pumping Arrangements:	INA	1.1.2		
15.					
	Ground Level Discharge of main numm	NA	NA	NA	
	• Discharge of main pump		NA	NA	
	Head of main pump Number of main pump	NA NA	NA	NA	
	Number of main pumps		NA	NA	
	Jockey pump out put	NA	NA NA	NA	
	Jockey pump head	NA	NA NA	NA	
	Standby Pump out put Standby Pump Used	NA	NA	NA	
	Standby Pump Head Auto Storing/Manual storping	NA	NA NA	NA	
	 Auto Staring/Manual stopping Pump House Access 	NA	NA NA	NA	
		NA	INA		
	Terrace level				
	 Terrace level Discharge of pump 	450 lpm	450 lpm x 2	MR	
	 Terrace level Discharge of pump Head of the pump 	450 lpm 40Mtr	450 lpm x 2 Provided	MR MR	
	 Terrace level Discharge of pump Head of the pump Power supply 	450 lpm 40Mtr Required	450 lpm x 2 Provided Provided	MR MR MR	
	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump 	450 lpm 40Mtr	450 lpm x 2 Provided	MR MR	
14.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: 	450 lpm 40Mtr Required Required	450 lpm x 2 Provided Provided Provided	MR MR MR MR	
14.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity 	450 lpm 40Mtr Required Required NA	450 lpm x 2 Provided Provided Provided NA	MR MR MR NA	
14.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection 	450 lpm 40Mtr Required Required NA NA	450 lpm x 2 Provided Provided Provided NA NA	MR MR MR MR NA NA	
14.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet 	450 lpm 40Mtr Required Required NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA NA	MR MR MR MR NA NA	
14.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank 	450 lpm 40Mtr Required Required NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA NA NA	MR MR MR MR NA NA NA NA	
14.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity 	450 lpm 40Mtr Required Required NA NA NA NA 10,000Ltrs.	450 lpm x 2 Provided Provided Provided NA NA NA NA Provided.	MR MR MR MR NA NA NA NA NA NA MR	
	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity 	450 lpm 40Mtr Required Required NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA NA NA	MR MR MR MR NA NA NA NA	
15	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts 	450 lpm 40Mtr Required Required NA NA NA NA 10,000Ltrs. Required	450 lpm x 2 Provided Provided Provided NA NA NA NA Provided. Provided	MR MR MR MR NA NA NA NA MR MR	
15	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA	450 lpm x 2 Provided Provided Provided NA NA NA NA Provided. Provided NA	MR MR MR NA NA NA NA MR MR MR	
15	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA	MR MR MR NA NA NA NA MR MR MR NA NA	
15	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA NA NA NA	MR MR MR NA NA NA NA MR MR MR NA NA NA	
15	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA NA NA NA NA	MR MR MR MR NA NA NA MR MR MR NA NA NA	
15	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA NA NA NA	MR MR MR NA NA NA NA MR MR MR NA NA NA	
15	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA NA NA NA NA	MR MR MR MR NA NA NA MR MR MR NA NA NA	
15 16.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR MR NA NA NA MR MR MR MR NA NA NA NA NA	
15 6.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR MR NA NA NA MR MR MR MR NA NA NA NA NA	
15 6.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR NA NA NA MR MR MR NA NA NA NA NA NA	
15 6. 7. 8.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area Location 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR MR NA NA MR MR MR MR NA NA NA NA NA NA NA	
15 16. 17. 18.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Location Fire control room 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA NA NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR NA NA NA MR MR MR NA NA NA NA NA NA NA NA	
15 16. 17. 18.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Location Fire control room Detector system panel 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA NA NA NA NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided. Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR NA NA NA MR MR MR NA NA NA NA NA NA NA NA NA	
15 16. 17. 18.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area Location Fire control room Detector system panel Flow Switch Panel 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA NA NA NA NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR MR NA NA MR MR MR MR NA NA NA NA NA NA NA NA NA NA	
15 16. 17. 18.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area Location Fire control room Petector system panel Flow Switch Panel PA System Panel 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA NA NA NA NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA NA Provided Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR MR NA NA NA MR MR MR MR NA NA NA NA NA NA NA NA NA	
15 16. 17. 18.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area Location Fire control room Detector system panel Flow Switch Panel PA System Panel Battery backup 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA NA NA NA NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR MR NA NA NA MR MR MR MR MR NA NA NA NA NA NA NA NA NA NA NA	
14. 15 16. 17. 18.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area Location Fire control room Detector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans 	450 lpm 40Mtr Required Required NA NA NA 10,000Ltrs. Required NA NA NA NA NA NA NA NA NA NA NA NA NA	450 lpm x 2 Provided Provided Provided NA NA NA NA Provided. Provided Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR MR NA NA NA MR MR MR MR NA NA NA NA NA NA NA NA NA NA NA NA NA	
15 16. 17. 18.	 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area Location Fire control room Detector system panel Flow Switch Panel PA System Panel Battery backup 	450 lpm40MtrRequiredRequiredNANANAI0,000Ltrs.RequiredNA	450 lpm x 2 Provided Provided Provided NA NA NA Provided. Provided Provided NA NA NA NA NA NA NA NA NA NA	MR MR MR MR NA NA NA MR MR MR MR MR NA NA NA NA NA NA NA NA NA NA NA NA	

AFA (- 32

V

Contraction of the local division of the loc


The fire protection systems provided in the building were checked and found functional at the time of inspection.

Note: - Management has constructed a separate M. P. Hall, have provided 06 nos. exit doors (02 Nos. 2 m wide & 04 No. 1.25 m wide) & protected with hose reels & hydrant.

Keeping in view substantial compliance of the minimum standards on fire prevention and fire safety requirements under the rules, grant of Fire safety Certificate is recommended under rule 35 of the Delhi Fire service Rules 2010 under the DFS Act 2007.

18/4/2022

Aman Kumar Lathar, ADO (JWP)



VEP

(W2) Sir, as approved F.T. letter is put up for signature please. Brakash 28/4/2022 W. Directar

1