GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/CNG/WZ/2022/ 187

Dated: 27/04/2092

FIRE SAFETY CERTIFICATE

Certified that the CNG Station at Khasra No.142, Khata No.582/2, Plot No.276/2, Village & Tehsil Kanjhawala, Delhi-81, comprised of Single Story Building. The building was inspected by the officer concerned of this department on 04.04.2022 in the presence of Sh. Narender Kumar Dabas (Owner) and found that the building have complied with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and observed that the building is fit for occupancy Hazardous (Group-J) with effect from ... 27/29/29. for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 27/04/209 at New Delhi by

DIRECTOR
Ph; 011-23414000

Copy to:

1. Sh. Narender Kumar Dabas (Owner) DODO CNG Station, Kanjhawala, Delhi-110081.

 The Addl. Commissioner of Police (Lic), 1st Floor, Police Station, Defense Colony, Delhi

Conditions for the validity of fire safety certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/ http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms

INSPECT	TOND	EDODE
ET TOT LICT	TON I	JEPOK I

Name & address of the building: CNG Station at Khasra No.142, Khata No.582/2, Plot No.276/2,

Village & Tehsil Kanjhawala, Delhi-81.

)1

)}

5

u

ir

Type of Occupancy : Group J Hazardous Building (Single Story Building)

3. Type of Case : New Case

4. Details of Previous NOC : NA

5. Fire Safety directives letter No : F.6/DFS/MS/BP/2022/CNG/04 dated 05.01.2022.

6. Date of inspection : 04.04.2022

7. Name of Inspecting Officer : A.K.Sharma ADO(Rohini)

8. Name and designation of officers

From the building side : Sh. Narender Kumar Dabas (Owner)

9. Year of Construction

	Applicant's letter No. : Online e-ma	ail dated 14.02.2022		
S. No.	Minimum Standards on fire prevention	NBC	Provided at site	Remarks
	and fire safety U/R 33	Requirement		MR/NMR
1.	Access to building			
	Road width	25m	30m	MR
	Gate width	NA	NA	NA
	Width of internal road	NA	10%	NA
2.	Number, Width, Type & Arrangement of	Exits		
	a. Number of staircases			
	Upper Floors	NA	$\Sigma \Lambda$	NA
	Basements	NA	7. 1	NA
	b. Width of staircases	NA		NA
	Upper Floor	NA	$N\Lambda$	NA
	Basements	NA	NA	NA
	c. Protection of exits	NA	1	NA
	Fire check door	NA		NA
	 Pressurization 	NA	5. 7 h	NA
	d. No. of continuous staircases to terrace	NA	* .	NA
	e. Width of Corridor	NA	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	NA
	f. Door Size	1.0m	1 1	N'R
3.	Compartmentation			
J.	Fire check door	NA		MA
	Sealing of electrical shafts	NA		NΑ
	Fire Rating of shaft door	NA		NA
	Water Curtain	NA		. A
	 Fire Dampers 	NA		ΣA
4	Smoke Management System		-	
4.	4-	30 a/c per hour		A
		12 a/c per hour		
5.	Fire Extinguishers			

	Total numbers	75kg-14 10kg-25 4.5kg-04CO2	Provided	MR
		ABC/CO2/DCP	Provided	MR
	• Types	ISI marked	Yes	MR
	IS marking	101		
6.	First-Aid Hose Reels	NA NA		NA
	Total numbers on each floor	NA	NA	NA
	• Length of hose reel hose	NA NA	NA	NA
	Nozzle diameter			
7.	Automatic fire detection and alarming syst		200 NASed	NA
	Type of detectors	Conformation (NA)	NA	NA
	Location of Main Panel A section of Panel		NA	NA
	Location of Repeater PanelAlternate source of power	NA	NA	NA
	Hooters' Location	NA	NA NA	NA
		NA P	Provided	MR
8.	MOEFA	Required		NA
9.	Public Address System	NA .	NA	IVA
10.	Automatic Sprinkler System		D.T.A.	NA
	Basement	NA	NA	NA NA
	Ground & Upper Floors	NA	NA	
	Sprinkler above false ceiling	NA	NA	NA
11.	Internal Hydrants		27.4	NIA
	Size of riser/down-comer	NA	NA	NA
	Number of hydrants per floor	NA	NA	NA
	Hose Box	NA	NA	NA
12.	Yard Hydrants	77.	27.	
	Total number of hydrants	NA	NA	NA
10	Hose Box	NA	NA	NA
13.	Pumping Arrangements		22.	
	Ground Level	NA	NA	NA
	Discharge of main Pump	NA	NA	NA
	Head of Main pumpNumber of main pumps	NA	NA	NA
	Trained of main pumps	NA	NA	NA
	Jockey Pump out putJockey pump head	NA	NA	NA
	Standby Pump out put	NA	NA	NA
	> Standby Fump out put > Standby Pump Head	NA	NA	NA
	➤ Auto Starting/Manual Stopping	NA	NA	NA
	Pump House Access	NA	NA	NA
		NA	NA	NA
	Terrace level	NA	NA	NA
	Discharge of pump	NA	NA	NA
	Head of the pump	NA	NA	NA
	Power Supply	NA	NA	NA

_	> Auto Starting of pump	NA	VA	NA
	Captive Water Storage for fire fighting	L		
Λ_{i}		NA	۸V	NA
_ 1	> Draw-off connection	NA	٧V	NA
Mi	Fire service inlet	NA	VA	NA
ME	Access to tank	NA	1.1	NΛ
	Overhead Tank capacity	NA	VA	NA
	Exit Signage.	NA	1\	NA
15.	Provision of Lifts.			
6.		NA		$N\Lambda$
	 Pressurization of Lift Shaft 	NA	\	1 /
	 Pressurization of Lift lobby 	NA	\	$N\Lambda$
	 Communication In lift Car 			NA
	 Fireman's Grounding Switch 	NA		NA
	 Lift Signage 	NA	1	NI
7.	Standby power supply	NA		
8.	Refuge Area.			1:.1
	> Total Area	NA	1	1
	> Location	NA	\	\
).	Fire Control Room			X
-	Detector System Panel	NA		
	Flow Switch Panel	NA	·	
	PA System Panel	NA	i .	, /
	Battery backup	NA	\	, \
	Building Floor Plans	NA	à.	1.1
0	Special Fire Protection System for	Fire buckets filled with	ind, no	
20.	Special Fire Florection System for	smoking boards & emerge	io, were	1.5
	Protection of special Risks, if any:	found displayed in Hindi C.	11311. 1871 5 & CO	
		lose electric wiring seen pro- flooding system found provi	20000	

The fire protection systems provided in the building vere test ecked and foun functional at the time of inspection.

Keeping in view the substantial compliance of the minimum stand and fire safety required under the rules it is recommended to grarule 35 of the Delhi Fire Service Rule 2010.

Desim