

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2022/ 2/3

Dated 0.9/.05/2022

FIRE SAFETY CERTIFICATE

Certified that the Mayur Guest House located at 5611-18, Basant Road, Pahar Ganj, New Delhi comprised of Ground + 01 Upper floors, Ground floor (other's property), 1st floor (06 guest rooms + reception), total 06 guest rooms was earlier granted FSC by this department vide letter No.F6/MS/DFS/GH/NDZ/2019/137 dated 18/01/19. Now, the premises was re-inspected by the officer concerned of this department on 11/04/22 in the presence of Manger and found that the said guest house building comprised of ground and two upper floors and guest rooms at only first floor and second floor is for personnel use as per undertaking dated 17.12.2018, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 for 06 guest rooms at first floor only with effect from .0.1.05. https://openiod.of.com/perio rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below. Issued C-2-105-12012 at New Delhi by.

(Dr. S.K. Tomar) Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

- The Commissioner, North MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed above.
- 2. The Jt. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online id no.2022041306906 dated 13-04-2022 3. The Manager,

Mayur Guest House at 5611-18, Basant Road, Pahar Ganj, New Delhi.

Condition for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction,
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry". 9. Any flammable material for interior decoration is prohibited.

N /24

INSPECTION REPORT

Mayur Guest House at 5611-18, Basant 1. Name & address of the building

Road, Pahar Ganj, New Delhi

Residential, Sub Division-A-1 2. Type of occupancy:-

Gr. + 02 Upper floors (total 06 Guest rooms) Ground floor (other's property), 1st floor (06 guest rooms + reception), IInd floor - owner personnel

use as per undertaking 17.12.2018.

3. Type of case:-Renewal

No. F6/MS/DFS/GH/NDZ/2019/137 dated 4. Details of previous FSC:-

18/01/19.

5. Fire safety directives No.-N/A 6. Date of inspection:-11/04/22

Sh. Ravinder Singh (ADO/CC) 7. Name of the inspecting officer:-

Sh. Rajinder Atwal (DO/CD)

8. Name & designation of officer

From the building side:-9. Year of construction:-

Manger 2001

Online id no.2022020701761 dated 07-02-2022. 10. Applicant's letter No:-

	-FF			Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			
	1) Road width	N/A	06 mtr.	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arra	angement of Ex	its	
	A. Number of staircases			
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	0.80 mtr.	0.81 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous	N/A	N/A	N/A
	staircase to terrace		1	
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	01 mtr.	01 mtr.	MR
3.	Compartmentation	T		
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System		T	1
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 ACPH	Exhaust fan	MR
5.	Fire Extinguishers			

A COLUMN TO A SECOND TO A COLUMN TO A COLU	1) Total numbers	08 Nos.	08 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
5.	First-Aid Hose Reel			
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	Alarming Syste	em	
	1) Type of detectors CO	Required	Provided	MR
	2) Location of main panel	Required	Provided	MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Ground floor	Provided	MR
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System	14/12		
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	- "		
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor			
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main pump	N/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual stopping	N/A	N/A	N/A
	2) Terrace level			
	a) Discharge of pump	180 LPM	180 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR

١.	Captive Water Storage for F	ire Fighting		N/A
	 Under ground tank 	N/A	N/A	
	a) Draw-off connection	N/A	N/A	N/A
	a) Draw-off connectionb) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank	2500 ltr.	2500 ltr.	MR
	capacity			MR
15.	Exit Signage.	Required	Provided	IVIIC
16.	Provision of Lifts.			3.7/A
	a) Pressurization of lift	N/A	N/A	N/A
	shaft b) Pressurization of lift	N/A	N/A	N/A
	c) Communication in	N/A	N/A	N/A
	lift car	27/4	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A Promised	Provided	MR
17.	Stand by Power Supply	Required	N/A	N/A
18.	Refuge Area	N/A		N/A
	Total area location	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any:	stem for Prote	ection of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire required under the rules the FSC issued vide letter no. F6/MS/DFS/GH/NDZ/2019/137 dated 18/01/19, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval up to first floor only.

Signature of the inspecting officer

Signature of the Inspecting Officer

Name: - Rajinder Atwal Designation: - DO (CD) Name: Ravinder Singh Designation: ADO (CC)

Sepontine Gran

Sepontine Gran

Operator

Oper

uploaded on most Post