

# OF DELHI II-110001 Dated: [2] 05/2022 GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/School/WZ/2022/ 518

## FIRE SAFETY CERTIFICATE

Certified that the B.V.M. Model (Sr. Sec.) School, Rajiv Nagar, Begumpur, Opp. Sec-22, Rohini, Delhi-110086, comprised of Ground + 03upper floors owned/ occupied by B.V.M. Model Sr. Sec. School have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of fire service on dated 25.04.2022 in the presence of Smt. Kanta Sharma (Principal) and that the building/ premise is fit for occupancy Group B Educational with effect from 12. 195 9022 for a period of three years, in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 12 05 2022 at New Delhi by

Ph; 011-23414000

ola any

#### Copy to:

- 1. The Director of Education, GNCT of Delhi Old Secretariat, Delhi-110054.
- 2. The Principal, B.V.M. Model (Sr. Sec.) School, Rajiv Nagar, Begumpur, Opp. Sec-22, Rohini, Delhi-110086,

### Conditions for validity of Fire Safety Certificate;

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Fire+Safety+Acts+and+Rul es/ http://www.delhi.gov.in/wps/wcm/connect/doit fire/FIRE/Home/Forms





1. Na	ime & ad	ldress of the building	INSPECTIO B.V.M. Model		Rajiv Nagar, Begum	our, Opp. Sec-22			
		c	Rohini Delhi 1		, c, c,				
		cupancy	: Educational						
3. Ty	pe of Ca	ise		. + 3 upper floors					
			(Previous NOC	C –Gr. + 2 upper fl	oors)				
		Previous NOC	: F.6/DFS/MS/S	School/WZ/2015/1	694 dated 07.05.2015	5)			
5. Fi	re Safety	directives letter No							
		pection : 25.04.2022							
7. N	ame of	nspecting Officer	: A.K.Sharma	ADO(Rohini)					
		designation of officer							
				arma (Principal)					
			: 2013, 2016 &						
		's letter No. m Standards on fire			D. 114.4	D			
			prevention	NBC/UBBL	Provided at site	Remarks			
		safety U/R 33		requirement		MR/NMR			
Ι.		to building							
		Road width		Accessible	Accessible	MR (Old case)			
		Gate width		Accessible	Provided	MR (Old case)			
	•	Width of internal road		NA	NA	NA			
2.	Numbe	r, Width, Type & Ar	rangement of E	xits					
	a. Nu	mber of staircases							
	•	Upper Floors		02	03	MR			
	•	Basements		NA	NA	NA			
	b. Wid	th of staircases							
	•	Upper Floor		1.5m	1.8, 1.5 & 1.25m	MR			
	•	Basements		NA	NA	NA			
	c. Prot	ection of exits							
	Fire	check door		NA	NA	NA			
	•	Pressurization		NA	NA	NA			
	d. No	of continuous stairca	ses to terrace	02	02	MR			
	e. W	idth of Corridor		Required	Provided	MR			
	f. D	oor Size		NA	NA	NA			
3.	Com	artmentation		14/4	1474				
5.		Fire check door		NA	NA	NA			
		Sealing of electrical s	shafts	NA	NA	NA			
		Fire Rating of shaft d		NA	NA	NA			
	•	Water Curtain							
	•	Fire Dampers		NA	NA NA	NA			
4	0	-		NA	INA	NA			
4.		ke Management Syste	ш	30 a/c per hour	NA	NA			
	•	Ductilitie		12 a/c per hour	NA Natural ventilation	MR			
	•	•FF		12 a/c per noui	Natural ventilation	IVIK			
5.		Extinguishers		15	15	LOD			
	•	rotar manieers		15nos.	15nos.	MR			
		Types IS marking		ABC/CO2	ABC-15	MR			
-		IS marking		ISI marked	Yes	MR			
6.	Firs	t-Aid Hose Reels	1.0	01	D				
		<ul><li>Total numbers on ea</li><li>Length of hose reel</li></ul>		01 30mm	Provided	MR			
		<ul> <li>Length of hose reel</li> <li>Nozzle diameter</li> </ul>	nose	30mm	Provided	MR			
7.			nd alaumi	5m	Provided	MR			
/.		omatic fire detection a	ing anarming sys	NA NA	NIA	NA			
		Type of detectors		INA	NA	11/4			

a an in the second second

## N/22

	N/22			
1	Location of Main Panel	NA	NA	NA
ļ	• Location of Repeater Panel	NA	NA	NA
1	Alternate source of power	NA	NA	NA
	Hooters' Location	NA	NA	NA
3.	MOEFA	NA	NA	
).	Public Address System	NA	NA NA	NA
10.	Automatic Sprinkler System		INA	NA
	Basement	NA	NA	
	Ground & Upper Floors	NA NA		NA
	<ul> <li>Sprinkler above false ceiling</li> </ul>	NA NA	NA	NA
11.	Internal Hydrants	INA	NA	NA
	Size of riser/down-comer		T	
	<ul> <li>Size of fiser/down-comer</li> <li>Number of hydrants per floor</li> </ul>	NA	NA	NA
	<ul> <li>Hour of nydrants per floor</li> <li>Hose Box</li> </ul>	NA	NA	NA
12.	Yard Hydrants	NA	NA	NA
14.		1		
	<ul><li>Total number of hydrants</li><li>Hose Box</li></ul>	NA	NA	NA
13.		NA	NA	NA
15.	Pumping Arrangements			
	Ground Level	NA	NA	NA
	<ul> <li>Discharge of main Pump</li> <li>Head of Main runn</li> </ul>	NA	NA	NA
	<ul> <li>Head of Main pump</li> <li>Number of main n</li> </ul>	NA	NA	NA
	Number of main pumps	NA	NA	NA
	Jockey Pump out put Jockey pump out put	NA	NA	NA
	<ul> <li>Jockey pump head</li> <li>Standby Durge</li> </ul>	NA	NA	NA
	Standby Pump out put	NA	NA	NA
	Standby Pump Head	NA	NA	NA
I.	<ul> <li>Auto Starting/Manual Stopping</li> <li>Pump House Access</li> </ul>	NA	NA	NA
	Pump House Access	NA	NA	NA
ł	Terrace level			
i	Discharge of pump	900 lpm	2 x 450lpm	MR
í .	Head of the pump	40m	40m	MR
l	Power Supply	Required	Provided	MR MR
L	Auto Starting of pump	Required	Provided	MR
14.	Captive Water Storage for fire fighting	· · ·		IVIIX
ĺ	Underground tank capacity	NA	NA	NA
l	Draw-off connection	NA	NA	NA
l	<ul> <li>Fire service inlet</li> <li>Access to tank</li> </ul>	NA	NA	NA
1	<ul> <li>Access to tank</li> <li>Overhead Tank capacity</li> </ul>	NA	NA	NA
		10,000ltr	2 x 5000ltr	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	·		
	Pressurization of Lift Shaft	NA	NA	NA
1	<ul> <li>Pressurization of Lift lobby</li> </ul>	NA	NA	NA NA
1	<ul> <li>Communication In lift Car</li> </ul>	NA	NA	NA NA
1	<ul> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> </ul>	NA	NA	NA NA
1	Lift Signage	NA	NA	
17.	Standby power supply	Required	Provided	NA
18.	Refuge Area.	Require	FIUVIACA	MR
18.	All and a set of the s		1	
18.	<ul> <li>Total Area</li> </ul>	NA	NA	NA



$\int$	Fire Co	ntrol Room				
f -		Detector System Panel	NA	NA	NA	
		Flow Switch Panel	NA	NA	NA	
		A System Panel	NA	NA	NA	
	• I	Battery backup	NA	NA	NA	
	• 1	Building Floor Plans	NA	NA	NA	
20.	Special	Fire Protection System for	NA	NA	NA	
		ion of special Risks, if any:				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer Ajay Kumar Sharma Name Designation ADO(Rohini) DOCNW 9105/202 102 101 1100 Aouf en FT letter is jour up for kind perusal and signature please he Director

n