GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE

NEW DELHI - 110001

No. F6/DFS/MS/WZ/EH/2022/ 195

Dated: 12 / 0 5 /2022

FIRE SAFETY CERTIFICATE

Certified that the M/s. Tippling street (A Unit of D.K. Plaza) located at A-12, Vishal Enclave, Rajouri Garden, New Delhi - 110027 running was at 1st floor, 2nd floor in a building comprised of Basement + Ground + 3 Upper Floors owned/occupied by D.K. Plaza was issued FSC vide this deptt. Letter no F6/DFS/MS/2018/EH/WZ/2475 dated 02.11.2018. Now the Management of restaurant added 3rd floor & inspected by the officers concerned of this department on 22.04.2022 in the presence of Sh. Kawaljeet Singh (Partner) and found that the owner have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Assembly" (Group D) for first, second & third floors with effect from 13 or sooner a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. Conditions mentioned below.

Issued on 12.05 2022 at New Delhi by.

Director

Delhi Fire Service

Copy to:

1. The owner/occupier, Tippling Street(A Unit of D.K.Plaza), A-12, Vishal Enclave, Rajouri Garden, New Delhi-110027 (Reference: - ID No. 2021072015507 dated: - 21/07/2021)

2. The Joint Commissioner of Police, Licensing Unit, 1st floor, Police Station, Defence Colony, New Delhi.

3. The Dy. Health Officer, West Zone, SDMC, Public Health Department, Vishal Enclave, New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used strictly as per Building Bye Laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

NOOG.

vice Rules 2010, form is available on

INSPECTION REPORT

1. Name & address of the building

: Tippling street (A Unit of D.K. Plaza), A-12, Vishal

Enclave, Rajouri Garden New delhi-110027

2. Type of Occupancy

: Class-D, (Assembly / Restaurant)

3. Type of Case

: New (Addition of 3rd floor)

4. Details of previous NOC

: Letter no F6/DFS/MS/2018/FH/WZ/2475 dated

02.112018(For 1st & 2nd floor)

5. Fire Safety directives Letter No.

: NIL

6. Date of inspection

:22.04.2022

7. Name of the Inspecting Officer

: DO(West) & ADO (MN)

8. Name and designation of Officer

From the building side

: Sh. Kawaljeet Singh (Partner)

9. Year of Construction

: 2004(As per MHA portal)

10. Applicant's letter No.

: Online Application No:- 2021072015507 dated 25-03-2022

The restaurant is running at 1st, 2nd & 3rd floor in a building comprised of Basement, ground plus three upper floors.

S N	Minimum standards on fire	BBL/NBC	Provided at site	Remarks MR/NMF		
	prevention and fire safety U/R	Requirements		IVIIO I VIVII		
1.	Access of building					
	Road width	09 m	Provided	MR		
	Gate width	5 m	On Main Road	MR		
	Width of internal road	NA	NA	NA		
2.	Number, width, Type & Arrangen	nents of exits				
	a. Number of staircases					
	Upper floors	2	Provided	MR		
	Basements	NA	NA	NA		
	b. Width of staircases	1x2mts,	1x2mts,1x1.5m	MR		
	Upper floors	1x1.5mts	ts &1x.90mts	IVIK		
		NA	NA NA	NA		
	Basements					
	c. Protection of exits	NA	NA	NA		
	Fire check door	NA	NA	NA		
	Pressurization	01	Provided	MR		
	d. No of continuous staircase					
	to terrace	NA NA	NA NA	NA_		
	e. Width Of Corridor f. Door Size	2m X 1, 1.5m X	T 1 Provided	MR		
3.	Compartmentation					
	Fire check door	NA Provided in		ment NA		
	Sealing of electrical shafts	NA	NA	NA NA		
	Fire Rating of shaft door	NA	NA	NA		
	Water Curtain	NA	NA	NA		
	Fire Dampers	NA	NA	NA		
4.	Smoke managements System					
	Basements	NA	NA	NA		
	Upper floors	12 a/c per hour	Natural ventilation(openable)Exha fan	ust MR		
	A					

N139

5.	Fire Extinguishers						
	Total numbers	09 nos.	Day				
	• Types	ABC & CO ₂	Provided	MR			
	 IS marking 	ISI marked	Provided	MR			
6.	First – Aid Hose Reels		Provided	MR			
	Total numbers on each	01	Provided				
	floor	30 m	Provided	MR			
	Length of hose reel hose	5 mm	Provided	MR			
7.	Nozzle diameter Automatic fire detection let		Trovided	MR			
-	Automatic fire detection and alarming system						
	Type of detectors	Smoke & Heat	Provided) (D			
	Location of Main Panel	Required	Provided	MR			
	 Location of Repeater Panel 	Required	Provided	MR			
	 Alternate source of power 	Required	Provided	MR			
0	 Hooters' Location 	Required	Provided	MR			
8.	MOEFA	Required	Provided	MR MR			
9.	Public Address System	NA	NA				
10	Automatic Sprinkler System		TVA	NA			
•	a Daniel I						
	Basements	NA	NA	NA			
	• Upper Floor	NA	Provided	NA NA			
11	Sprinkler above false ceiling	NA	NA	NA			
	Internal Hydrants	-		1471			
	Size of riser/down- comer	100mm	Provided				
	 Number of hydrants per floor 	01	Provided	MR			
	Hose Box	01	Provided	MR			
12	Yard Hydrants		Frovided	MR			
•	Total number of hydrants NA NA NA						
	Hose Box	NA	NA	NA			
13	Pumping Arrangements	IVA	NA	NA			
•	Ground Level						
	Discharge of main pump	2280 LPM					
	Head of main pump		provided	MR			
	Number of main pumps	40 mts	provided	MR			
	Jockey pump out put	01	provided	MR			
	Jockey pump head	180 lpm	provided	MR			
	Standby Pump out put	40 mts	provided	MR			
	Standby Pump Head	2280 LPM	provided	MR			
	Auto Staring/Manual stopping	40 mts	provided	MR			
	Pump House Access	Required	provided	MR			
	• Terrace level	Required	provided	MR			
	Discharge of pump	4501		1411/			
	Head of the pump Power supply	450 lpm	450 x 02	MR			
	s of supply	40 m	Provided	MR			
	Auto starting of pump	Required	Provided	MR			
		Required	Provided	MR			
14	Captive water Storage for fire fighting						

	Underground tank capacity	100000 lts	Provided	MR		
	Draw of connection	Required	Provided	MR		
	Fire service inlet	Required	Provided	MR		
	Access to tank	Required	Provided	MR		
	 Overhead Tank capacity 	5, 000 ltrs	Provided	MR		
15	Exit Signage	Required	Provided	MR		
16	Provision Of Lifts :					
`	Pressurization of Lift Shaft	NA	NA	NA		
	> Pressurization of lift lobby	NA	NA	NA		
	Communication in lift Car	Required	Provided	MR		
	➤ Fireman's Grounding Switch	Required	Provided	MR		
	➤ Lift Signage	Required	Provided	MR		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area					
•	> Total area	NA	NA	NA		
	> Location	NA	NA	NA		
19	Fire control room					
	> Detector system panel	NA	NA	NA		
	Flow Switch Panel	NA	NA	NA		
	> PA System Panel	NA	NA	NA		
	> Battery backup	NA	NA	NA		
	Building Floor Plans	NA	NA	NA		
20	Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA		

The fire protection systems provided in the building were checked and found functional at the time of inspection. The Shortcomings issued by this department vide Letter no. F6/DFS/MS/EH/WZ/2021/434 Dated- 05/10/2021 have been compiled.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

11.35/4/2021

Signature of the Inspecting Officer Name: - M. K. Chattopadhyay

Designation: - DO (West)

Signature of the Inspecting Officer

Name: - Sarabjeet Singh Designation: - ADO (MN)

CAD

10mg

Km rechte tu for the talogy