FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001**

No.F6/DFS/MS/NDZ/2022/ 9 2 5

Dated: 19 / 05/ 2020

FIRE SAFETY CERTIFICATE

Certified that the Old Boys hostel located at GTB Hospital Shahdara, Delhi -110095 comprised of Ground and 08 upper floors owned / occupied by GTB Hospital, was earlier issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/2014/NDZ/1536 dated 09/12/14. The premises was re-inspected by the officers concerned of this department on 28.04.2022 in the presence of Sh. A.K. Singh, A.E.(E) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with rule 33 of the Delhi Fire Service Rule, 2010 and that the building / premises is fit for occupancy class "Residential Building" (Group - 'A') with effect from 19105/2022 for a period of five years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010.

Issued on 19105/2022 at New Delhi by.

Copy to:-

1. The Medical Superintendent, GTB Hospital, Shahdara, Delhi-110095.

2. The Assistant Engineer (E), HE-1, HMED (East), PWD, GTB Hospital, Shahdara, Delhi-110095.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on WWW.dfs.Delhigovt.nic.in

411

INSPECTION REPORT

1. Name & address of the building: Old Boys Hostel, GTB Hospital, Shahdara,

Delhi-110095.

2. Type of Occupancy : Residential

3. Type of Case : Renewal (Ground, & Eight Upper Floors)

4. Details of previous NOC : F6/DFS/MS/2014/NDZ/1536 dated 09/12/2014

5. Fire Safety directivesLetterNo. : DFS Prevention Act 1986 & 1987

6. Date of inspection : 28/04/2022

7. Name of the Inspecting Officer: ADO (TP) & D.O. (East)

8. Name and designation of Officer

from the building side : Sh. A.K.Singh (AE(E))

		Sh. A.K.Sing 1983	h (AE(E))				
	pplicant's letter No. : 54(1)AE(E		ast)/PW	D/GTBH/2022-2	3/35 Dt 19/04/2			
S No	Minimum standards on fire prevention and fire safety U/R 33	As per Delhi Fire Prevention & Fire Safety		Provided at site	Remarks MR/NMR			
		Act 1986&1						
1.	Access of building							
	Road width	12 m		26 m	MR			
	Gate width	4.5 m		6 m	MR			
	Width of internal road	6 m		6 m	MR			
2.	Number, width, Type & Arrangements of exits							
	a. Number of staircases							
	Upper floors	4		4	MR			
	Basements	N/A		N/A	N/A			
	b. Width of staircases			1				
	Upper floors	1.00 m		1.10 m	MR			
	Basements	N/A		N/A	N/A			
	c. Protection of exits							
	Fire check door	N/A		N/A	N/A			
	Pressurization	N/A		N/A	N/A			
	d. No of continuous	4		4	MR			
	staircase to terrace	1.5 m		4	IVIK			
	e. Width Of Corridor			1.5 m	MR			
	f. Door Size	1 m	1 m		MR			
3.	Compartmentation	2			IVIIX			
	Fire check door	N/A N/A		1	N/A			
	Sealing of electrical shafts	Required		vided	MR			
	 Fire Rating of shaft door 	N/A	N/A	1	N/A			
	Water Curtain	N/A	N/A		N/A			
	Fire Dampers	N/A	N/A		N/A			
4.	Smoke managements System		<u> </u>		14/ A			
	Basements	NA NA			NA			
	Upper floors	N/A N/A			N/A			
5.	Fire Extinguishers		1.477		IV/ A			
	Total numbers	20		26	MR			
	• Types	ABC/CO ₂		Provided	MR			
	ISI marking	Required		Provided	MR			

6.	First - Aid Hose Reels			N			
·	Total numbers on	1			1		MR
	each floor						
	Length of hose reel	30 N	Λtr.		Prov	rided	MR
	hose						
	 Nozzle diameter 	20 mm			Provided		MR
7.	Automatic fire detection and a	larmii	no svs	stem			
	Type of detector		N/A	,,,,,,,		N/A	N/A
	Location of Main Pane	l	N/A			N/A	N/A
	Location of Repeater P					N/A	N/A
	Alternate source of	N/A				/A	N/A
	power	17/2			1177		'',
	Hooters' Location	N/A			N/A		N/A
8.	MOEFA	Pog	ulrad				
9.	Public Address System	-	uired uired		Provided Provided		MR MR
10.	Automatic Sprinkler System	neq	aneu			ovided	IVIK
	Ground Floor	N/A		N/A			N/A
	Upper Floor	N/A		N/A			N/A
	Sprinkler above false	N/A		N/A			N/A
	ceiling			','			. 7/15
11.	Internal Hydrants						
	Size of riser/down- comer	150	mm	150 mm		MR	
	 Number of hydrants 	1		Prov			MR
	per floor						
	Hose Box	1	Provided			MR	
12.	Yard Hydrants						
	 Total number of 	NA	NA NA				NA
	hydrants						
13.	Hose Box Pumping Arrangement	NA NA			NA		
	Pumping ArrangementsGround Level	Common for entire complex					
	 Discharge of main pump 	295	O I DNA	205	0.1.01		
	➤ Head of main pump				2850 LPM 70 m		MR
	 Number of main pumps 	-			2 nos.		MR
	 Jockey pump out put 			0 LPM		MR	
	Jockey pump head	70 m 70 m				MR	
	Standby Pump out put	THE RESERVE OF THE PARTY OF THE	2850 LPM 2850 LP		O LPN	1	MR
	Standby Pump HeadAuto Staring/Manual	70 n	-	70 1			MR
	stopping	Auto)	Aut	0		MR
	Pump House Access	Required Requ					
	Terrace level	Required Required MR				MR	
	 Discharge of pump 	N/A		N/A			
-	 Head of the pump 	-	N/A N/A			N/A	
	Power supply	N/A	Total Commence	N/A		N/A	
	 Auto starting of pump 	N/A					N/A
14.	Captive water Storage for fire						N/A
	Underground tank	righti	ng				
	capacity	2,00	2,00,000 Ltrs.		2	.00,000 Ltrs.	MR
	 Draw of connection 	Regi					
	Fire service inlet	Required Required Required Provided Required Required N/A N/A			Required		MR
	Access to tank					MR	
	 Overhead Tank capacity 						MR
	-apacity				N/A		
				8			
		1					

VIII

		N/3		
15	Exit Signage	Required	Provided	MR
16.	Provision of Lifts			
	 Pressurization of Lift Shaft 	N/A	N/A	N/A
	Pressurization of lift lobby	N/A	N/A	N/A
	 Communication in lift Car 	Required	Provided	MR
	 Fireman's Grounding Switch 	Required	Provided	MR
	➤ Lift Signage	Required	Provided	MR
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
10.	Total area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19.	Fire control room			
• / ·	Detector system panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	➤ PA System Panel	Required	Provided	MR
	Battery backup	Required	Provided	MR
	➤ Building Floor Plans	N/A	N/A	N/A
20.	Special Fire Protection Systems for Protection of	N/A	N/A	N/A
	special Risks, if any;			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name: Mehmood

Designation: A.D.O. (Tahirpur)

Signature of the Inspecting Officer Name : Ashok Kumar Jaiswal

Designation: D.O. (East Division)

Slive 14 is common for entire couplers This should be confirmed.

Derecter

Captine water storage for fine fighting is common for entire complex i.e. (G. T. B. Hospital complex.). F.T. is fut up for sign. please.