

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

Dated : 90/05/2022

No.F6/DFS/MS/GH/NDZ/2022/ 3 4 0

## FIRE SAFETY CERTIFICATE

Certified that the Aman Guest House located at 4/5, D.B. Gupta Road, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Commercial ply shops), 1<sup>st</sup> floor (07 guest rooms + reception + other property), 2<sup>nd</sup> floor to 3<sup>rd</sup> floor (07guest rooms at each floor), total 21 guest rooms was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2019/941 dated 06/05/19 ( for ground and three upper floor ) . Now, the premises was re-inspected by the officer concerned of this department on 09/05/22 in the presence of Manager and found that the said guest house building comprised of ground and four upper floor and given an undertaking dated 09.05.2022 regarding not to use fourth floor for any purpose, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 1st floor (Reception + 06 guest rooms), 2nd floor to 3rd floor (07 guest rooms at each floor), total 20 guest rooms up to third floor only with effect from 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 20/05/2022 at New Delhi by.

(Dr. S.K. Tomar) Dy. Chief Fire Officer Delhi Fire Service

## Copy to:-

- 1. The Commissioner, North MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed above & deviation if any.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online id no.2022031803753 dated 24.03.2022.
- 3. The Manager, Aman Guest House 4/5, D.B. Gupta Road, Pahar Ganj, New Delhi.

## Conditions for the validity of Fire Safety Certificate

- 1. This FSC shall stand null and void if number of lodgers are more than 10 at any one floor
- 2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- The trained fire fighting staff should be available round the clock.
- Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 10. Any flammable material for interior decoration is prohibited

1. Name & address of the building Aman Guest House at 4/5, D.B. Gupta Road, Pahar Ganj, New Delhi 2. Type of occupancy:-Residential, Sub Division-A-1 Gr. + 04Upper floors (total 20 Guest rooms) Ground floor (Commercial ply shops), 1<sup>st</sup> floor (06 guest rooms + reception + other property), 2<sup>nd</sup> floor to 3<sup>rd</sup> floor (07 guest rooms at each floor) and fourth floor not in use as per undertaking dated 09.05.2022 3. Type of case:-Renewal 4. Details of previous FSC:-No. F6/DFS/MS/GH/NDZ/2019/941 dated 06/05/19 5. Fire safety directives No.-N/A 6. Date of inspection:-09/05/22 7. Name of the inspecting officer:-Sh. Ravinder Singh (ADO/CC) 8. Name & designation of officer From the building side:-Manager 9. Year of construction:-2008 10. Applicant's letter No:-Online id no.2022031803753 dated 24.03.2022. Old Case S.No. Minimum Standards on fire Requirement/ Provided at site Remarks Prevention and fire safety Existing fire MR/NMR safety U/R 33 arrangements 1. Access to Building 1) Road width N/A 12 mtr. MR 2) Gate width N/A N/A N/A 3)Width of internal road N/A N/A N/A Number, Width Type & Arrangement of Exits A. Number of staircases 1. Upper floors 01 Nos. 01 Nos. MR 2. Basements N/A N/A N/A B. Width of staircase 1. Upper floors 0.80 mtr. 1.25 mtr. MR 2. Basements N/A N/A N/A Protection of exits 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous 01 01 MR staircase to terrace E. Width of corridor 1 mtr. 1 mtr. MR F. Door size 1 mtr. 1 mtr. MR Compartmentation 1) Fire check door N/A N/A N/A

N/A

N/A

N/A

N/A

hour

30 ACPH

12 a/c per

N/A

N/A

N/A

N/A

N/A

fan

Natural/Exhaust

N/A

N/A

N/A

N/A

N/A

MR

2.

3.

4.

2) Sealing of electrical shafts

Smoke Management System

3) Fire rating of shaft door

4) Water curtain

5) Fire Dampers

1) Basements

2) Upper floors

Morn

|     | , ,  |             |           |        |  |
|-----|--|-------------|-----------|--------|--|
| 5.  | Fire Extinguishers                         |             |           | 7      |  |
|     | 1) Total numbers                           | 10 Nos.     | 12 Nos.   | MR     |  |
|     | 2) Types                                   | ABC & CO2   | ABC & CO2 | MR     |  |
|     | 3) ISI marking                             | Required    | Provided  | MR     |  |
| 6.  | First-Aid Hose Reel                        | 1104        |           |        |  |
| 0.  | 1) Total number of eachfloor               | 01          | 01        | MR     |  |
|     | 2) Length of hose reel hose                | 30 mtr.     | 30 mtr.   | MR     |  |
|     | 3) Nozzle diameter                         | 05 mm       | 05 mm     | MR     |  |
| 7.  | Automatic Fire Detection & Alarming System |             |           |        |  |
|     | 1) Type of detectors CO                    | Required    | Provided  | MR     |  |
|     | 2) Location of main panel                  | Gr. Floor   | Provided  | MR     |  |
|     | 3) Location of repeater panel              | N/A         | N/A       | N/A    |  |
|     | 4) Alternate source of power               | Required    | Provided  | MR     |  |
|     | 5) Hooter's Location                       | Each floor  | Provided  | MR     |  |
| 8.  | MOEFA                                      | Required    | Provided  | MR     |  |
| 9.  | Public Address System                      | N/A         | N/A       | N/A    |  |
| 10. | Automatic Sprinkler System                 | IN/A        | IV/A      | IVA    |  |
| 10. | 1) Basement                                | N/A         | N/A       | N/A    |  |
|     | 2) Upper floors                            | N/A         | N/A       | N/A    |  |
|     | 3) Sprinkler above false                   | N/A         | N/A       | N/A    |  |
|     | ceiling                                    | IV/A        | IN/A      | IN/A   |  |
| 11. | Internal Hydrants                          |             |           |        |  |
| 11. | 1) Size of riser/down-comer                | N/A         | N/A       | N/A    |  |
|     | 2) Number of hydrants per                  | N/A         | N/A       | N/A    |  |
|     | floor                                      | 14/74       | 17/14     | 1777   |  |
|     | 3) Hose box                                | N/A         | N/A       | N/A    |  |
| 12. | Yard Hydrants                              | 1 1/1 1     | 14/11     | 1 11/1 |  |
|     | 1) Total number of hydrants                | N/A         | N/A       | N/A    |  |
|     | 2) Hose box                                | N/A         | N/A       | N/A    |  |
| 13. | Pumping Arrangement                        | T           |           |        |  |
|     | 1) Ground level                            | N/A         | N/A       | N/A    |  |
|     | a) Discharge of main                       | N/A         | N/A       | N/A    |  |
|     | pump                                       |             |           |        |  |
|     | b) Head of main pump                       | N/A         | N/A       | N/A    |  |
|     | c) Number of main pump                     | N/A         | N/A       | N/A    |  |
|     | d) Jockey pump out put                     | N/A         | N/A       | N/A    |  |
|     | e) Jockey pump head                        | N/A         | N/A       | N/A    |  |
|     | f) Stand by pump output                    | N/A         | N/A       | N/A    |  |
|     | g) Stand by pump head                      | N/A         | N/A       | N/A    |  |
|     | h) Auto starting/Manual                    | N/A         | N/A       | N/A    |  |
|     | stopping                                   |             |           |        |  |
|     | 2) Terrace level                           |             |           |        |  |
|     | a) Discharge of pump                       | 450 LPM     | 450 LPM   | MR     |  |
|     | b) Head of pump                            | 30 mtr.     | 30 mtr.   | MR     |  |
|     | c) Power supply                            | Required    | Provided  | MR     |  |
|     | d) Auto starting of pump                   | Required    | Provided  | MR     |  |
| 14. | Captive Water Storage for Fi               | re Fighting |           |        |  |
| 17. | 1) Under ground tank                       | N/A         | N/A       | N/A    |  |
|     | 1) Chase Broad with                        |             |           |        |  |



1126

|     |  | MI        | • 0       |       |
|-----|--|-----------|-----------|-------|
|     | a) Draw-off connection   | N/A       |           |       |
|     | Fire service inlet   | N/A       | N/A       | N/A   |
|     | c) Access to tank  | Required  | N/A       | N/A   |
|     | <ul> <li>d) Over head tank</li> </ul>  | 2500 ltr. | Provided  | MR    |
| 15. | capacity   | 2300 ltr. | 2500 ltr. | MR    |
|     | Exit Signage.  | Page 1    |           |       |
| 16. | Provision of Lifts.  | Required  | Provided  | MR    |
|     | a) Pressurization of lift  |           |           |       |
|     | shaft  | N/A       | N/A       | N/A   |
|     | b) Pressurization of lift  |           |           | IN/A  |
|     | lobby  | N/A       | N/A       | N/A   |
|     | c) Communication in  |           |           | N/A   |
|     | lift car   | N/A       | N/A       | 21/4  |
|     | d) Fireway   |           |           | N/A   |
|     | d) Fireman's switch  | N/A       | N/A       | 21/4  |
| 17. | e) Lift signage  | N/A       | N/A       | N/A   |
| 18. | Stand by Power Supply  | Required  | Provided  | N/A   |
| 10. | Refuge Area  | N/A       |           | MR    |
|     | Total area location  |           | N/A       | N/A   |
|     | i coution  | N/A       | N/A       | N/A   |
| 19. | Fire Control Room  | -         |           | 1.071 |
|     |  | N/A       | N/A       | N/A   |
|     | a) Detector system   | N/A       | N/A       |       |
|     | panel  |           | 1,771     | N/A   |
|     | b) Flow switch panel   | N/A       | N/A       | NI/A  |
|     | c) PA system panel   | N/A       | N/A       | N/A   |
|     | d) Battery backup  | N/A       | N/A       | N/A   |
|     |  | 1         | IN/A      | N/A   |
|     | e) Building floor plan   | N/A       | N/A       | 27/   |
| 20. | Special Fire Protection S  |           | IN/A      | N/A   |
|     | Special Fire Protection System for Protection of special Risk, if any: ABC & CO <sub>2</sub> |           |           | MR    |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2019/941 dated 06/05/19, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended up to third floor only.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

oleo

Signston Prairie