GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/Hospital/SZ/2022/ 250

Dated:

06/06/2022

FIRE SAFETY CERTIFICATE

Certified that **Sir Ganga Ram Hospital Complex located at Sir Ganga Ram Hospital Marg, Rajinder Nagar, New Delhi- 110060,** having four buildings namely Old Building, SSRB Building, Casualty Block and Special Ward Block respectively. Old Building is comprised of small basement, ground plus five upper floors, SSRB Building is comprised of basement, ground plus seven upper floors, Casualty Block is comprised of basement, ground plus six upper floors and Special Ward Block is comprised of ground plus four upper floors, was granted FSC by this department vide letter No. F.6/DFS/MS/Hospital/SZ/2019/276 dated 04.02.2019. The hospital complex was re-inspected by the officers concerned of this department on 28.05.2022 in the presence of Col. M.P Varghese, CSO and Shri Rakesh Shukla, Sr. Fire Supervisor and found that management have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class **Group-C Institutional Building** with effect from <u>o()=()=2-29</u> for a period of 03 years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010 and subject to compliance of the conditions under Rule 38 of the Delhi fire service Rules, 2010 subject to conditions printed below.

Issued on $\underline{oclocl2>29}$ at New Delhi by.

irector Delhi Fire Service de

Copy to: -

 The Chief Security Officer, Sir Ganga Ram Hospital, Sir Ganga Ram Hospital Marg, Rajinder Nagar, New Delhi- 110060.

Conditions for the validity of Fire Safety Certificate

- 1. 06 mts. wide access road all around the building shall be kept free at all the time for fire tender movement in case of any emergency.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 3. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 5. The trained staff should be available round the clock.
- 6. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 7. Basement shall be used as per the building bye laws.
- 8. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <u>www.dfs.delhigovt.nic.in</u>.
- 10. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first



INSPECTION REPORT

1.	Nan	e & address of the building : Sir Ganga Ram Hospital Complex, Rajender Nagar, New Delhi- 60.				
2.	Тур	e of Occupancy : Institutional (Hospital)				
3.	Тур	e of Case : Renewal	29			
4.	Deta	ils of previous NOC : F.6/DFS/MS/Hospital/SZ/2019/276 dated 04.02.2019				
5.	Fire	Safety directives letter No: F.6/DFS/MS/Hospital/BP/99/2974 dated 26.03.1999, F6/DFS/MS/BP/Hospital/2004/822 dated128.04.2004, F6/DFS/MS/BP/Hospital/2009/1786 dated 16.06.2009	rg, Ig,			
6.		of inspection : 28.05.2022	it,			
7.	Nan	e of the Inspecting Officers : Vedpal Chhikara, DO (SW) & P.V. Rathee, ADO (SRD)	3,			
8.	Nan	me and designation of officers				
	fron	the building side : Col. (Retd.) Vergeese, CSO, Shri Rakesh Shukla, Sr. Fire Supervisor	S			
9.	Year	of Construction : Before 1999, Before 2004 & 2009	·			
10.	App	icant's letter No. : SGRH/S&F/H/NOC/SDA/R/1006/2022 dated 21.05.2022				

The said hospital complex is having four buildings namely Old Building, SSRB building, Casualty Building & special ward building. Old Building is comprised of basement, ground plus five upper floors, SSRB building is comprised of basement, ground plus seven upper floors, Casualty block is comprised of basement, ground plus six upper floors and Special ward block is comprised of ground plus four upper floors.

S. No.		inimum Standards on fire ention and fire safety U/R 33	Requirement FSC dat 04.02.20	ed	r Provided at site	Rem MR/I	
1	Acces	s to building					
	•	Road width	06 mt	5	Provided	М	R
	•	Gate width	4.5 mt	s	Provided		MR
	•	Width of internal road	06 mt	S	Provided	Μ	IR
2	Num	ber, Width, Type & Arrangem	ent of Exits				
	a. Nu	mber of staircases	-		-		-
	•	Upper Floors	Old case	Casual	illding- 05 Nos, SSRB Bldg04 nos ty-01 No., Special Ward- 2 Nos.	5	MR
	•	Basements	Old case		uilding- 02 nos. Bldg04 nos., Casualty-02 Nos.		MR
	b. W	dth of staircases	-		-		-
	•	Upper Floors	Old case	Bldg	ldg- 1.60, 1.44-1.52, 1.37,1.23, 1.24 02 X 2.0 mts, 02 x 1.5 mts. lty-2.10 mts, Special Ward- 2.07, 2.		MR
	•	Basements	Old case	SSF	Building- 1.5 mts, 0.88 - 1.13 mts. RB Bldg2.0 mts x 02 nos., 1.5 mts sualty-1.48 mts & 2.10 mts.	x 02 nos.,	MR
	c. Pro	tection of exits					
	•	Fire check door	Required		Provided		MR
	•	Pressurization	Require	ł	Provided		MR
	e. No	of continuous staircases to terrace	04		04		MR
	g. W	dth of Corridor	Old Cas	e 2.5, 2.10 & 2.04 mts MR be		MR beir	ig old case
	-	or Size	Old case	e	0.90, 1.05, 1.37 mts MR be		ng old case
3	Com	partmentation.			Ducitat		MR
	•	Fire check door	Require		Provided		MR
	•	Sealing of electrical shafts	Require		Sealed		MR
	•	Fire Rating of shaft door	02 H		02 Hrs		
	•	Water Curtain	N/A		N/A		N/A
	•	Fire Dampers	Requi	ed	Provided		MR
4	Smo	ke Management System.			E. L. for movided		MR
	•	Basements	30 a/c pe				MR
	•	Upper floors	12 a/c pe	r hour	Exhaust fan provideu		
		8- m				I	


er

11

f

1

T	Fire Extinguishers					
	Total numbers	48	Provide	d		MR
	Types	CO ₂ , ABC type	Provide	ed		MR
	the first of the second of the second s	ISI marked	Provide	ed		MR
	• 1S marking	1.51 marked				
	First-Aid Hose Reels.		0			MR
	 Total numbers on each floor 	08	Provide			MR
	 Length of hose reel hose 	30 m	Provide			MR
	Nozzle diameter	5 mm	Provide	ed		
7	Automatic fire detection and alarmin					MR
	Type of detectors	Smoke detectors				MR
	Location of Main Panel	Required	Provide			MR
	• Location of Repeater Panel	Required	Provide			
	Alternate source of power	Required	Provide	d		MR
	Hooters' Location	Required	Provide	d		MR
v	MOEFA	Required	Provide	d		MR
8		Required	Provide			MR
9	Public Address System.	Required	1.0.1.40			
10	Automatic Sprinkler System. Basement	Required	Provide	d		MR
	Upper Floor	Required	Provided			MR
	Sprinkler above false ceiling	Required	Provide	d		MR
11	Internal Hydrants					
	Size of riser/down-comer	150 mm	Provide	d		MR
	 Number of hydrants per floor 	Old Bldg- 05 nos, SSRB		Provideo	1	MR
	Hose Box	Casualty- 01 No., Special Old Bldg- 05 nos, SSRB	Bldg- 02 Nos.,	Provi	ded	MR
12		Casualty- 01 No., Special	Ward- 02 Nos			
12	Yard Hydrants. Total number of hydrants	30 Nos.	Require	d	Pro	vided
	 Hose Box 	30 Nos.	Require			vided
13	Pumping Arrangements.	501105.	require			videu
15	Ground Level					_
	 Oround Level Discharge of main Pump 	2850 LPM	Provided		M	
	 Head of Main pump 	70 mts	Provided		M	
	 Number of main pumps 	02	Provided		M	
	 Jockey Pump out put 	180 LPM	Provided		M	
	 Jockey pump head 	70 mts	Provided		M	
	 Standby Pump out put 	2820 LPM	Provided		M	
	 Standby Pump Head 	70 mts	Provided		M	
	 Auto Starting/ Manual stopping 	Required	Provided		M	
	 Pump House Access 	Required	Provided		M	
	Terrace level					
	 Discharge of pump 	1620 LPM in SSRB BI	dg. Provid	led	M	
	Head of the pump	60 mts	Provided		M	
	 Power Supply 	Required	Provided		M	
	 Auto Starting of pump 	Required	Provided		M	
14	Captive Water Storage for fire fighting	0				
	Underground tank capacity	3,00,000 lts	Provided		M	2
	Draw-off connection	Required	Provided		MI	
	 Fire service inlet 	Required	Provided		MI	
	Access to tank	Required	Provided		M	
	Overhead Tank capacity	80,000 lts	Provided		MI	
15	Exit Signage.	Required	Provided		M	
	1 by					



16	Provision of Lifts.							
10	 Pressurization of Lift Shaft 	Required	Provided	MR				
	• Pressurization of Lift lobby	Required	Provided	MR				
	Communication In lift Car	Required	Provided	MR				
	• Fireman's Grounding Switch	Required	Provided	MR				
	Lift Signage	Required	Provided	MR				
17	Standby power supply	Required	Provided	MR				
18	Refuge Area.							
	Total Area (In SSRB Block)	Required	Provided	MR				
	Location	Required	Provided at 6 th Floor	MR				
19	Fire Control Room							
	 Detector System Panel 	Required	Provided	MR				
	 Flow Switch Panel 	Required	Provided	MR				
	 PA System Panel 	Required	Provided	MR				
	 Batter backup 	Required	Provided	MR				
	 Building Floor Plans 	Required	Provided	MR				
20	Special Fire Protection Systems for	Required	Automatic CO ₂ flooding system	MR				
	Protection of special Risks, if any:	1	provided in elect. panel	IVIK				
				1				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Note: All the shortcomings pointed out by this department vide letter F.6/DFS/MS/Hospital/SZ/2021/2674 dated 20.12.2021 have been compiled with by the management of Sir Ganga Ram Hospital.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No. F.6/DFS/MS/Hospital/SZ/2019/276, dated 04.02.2019, renewal under Rule 37 of the Delhi Fire Service rules 2010 is recommended.

Accordingly, reply in shape of DFA is put up for approval & signature please.

1/22

Signature of the Inspecting Officer Name- Vedpal Chhikara Divisional Officer (SW)

123 6

Signature of the Inspecting Officer Name- P.V. Rathee Divisional Asstt. Div. Officer (S.Rd)

Sivela 106 \mathcal{D}