GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F.6/DFS/MS/Metro/2022/NDZ/ 254

Dated: 09/06/2029

FIRE SAFETY CERTIFICATE

Issued on09.104/2022.... at New Delhi by

(Dr. S. K. Tomar) Dy. Chief Fire Officer

0/ح

To:-

Sr. DGM/E&M Metro Bhawan, Fire Brigade Lane New Delhi 110001

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipment and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry

INSPECTION REPORT

Name & address of the building
 Building is comprised of
 Type of Occupancy

4. Type of Case

5. Details of Previous NOC letter

6. Fire Safety direction letter No.

7. Date of Inspection

8. Name of the Inspecting officers

9. Name and designation of Officer from the building side

10. Year of Construction

11. Applicant's email ID

: Seelampur Metro Station, Line-1, Delhi,

: Ground Level Platform Level.

: Assembly Building

: Renewal

: F.6/DFS/MS/2003/2596 dated -22/10/2003

: F.6./DFS/MS/BP/2003/462 Dated 27/01/2003

: 24/05/2022

: ADO (Shd.)

: Mr. Sanyam Jain, (AM/Fire)

: sanyam.dmrc@gmail.com dated 04/05/2022

	Minimum Standards on Fire Prevention and Fire Safety U/R33	Directive Required	Provided at Site	Remarks MR/NMR			
o.	Access to Building						
			20tm	MR			
	Road width	6 m	20 mtr	N/A			
	Gate width	N/A	N/A	N/A N/A			
	 Width of internal road 	N/A	N/A	N/A			
2	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases						
	Upper floor	04 nos.	04 nos.	MR			
	Basement	N/A	N/A	N/A			
	B. Width of Staircases						
	Upper floor	02 mtr	2.40 mtr each	MR			
	Basement	N/A	N/A	N/A			
	c. Protection of Exits						
	 Fire check door 	Required	Provided	MR			
	 Pressurization 	N/A	N/A	N/A			
	d. No. of Continuous Staircases to	04 nos	04 nos.	MR			
	Terrace		21/4	- NT/A			
	e. Width of Corridor	N/A	N/A	N/A			
	f. Door Size	N/A	N/A	N/A			
03	Compartmentation.						
	Fire check door	Required	Provided	MR			
	 Sealing of electrical shafts 	Required	Provided	MR			
	Fire rating of shaft door	02 hrs.	02 hrs.	MR			
	Water curtain	N/A	N/A	N/A			
	Fire dampers	N/A	N/A	N/A			
04	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	Upper floor	N/A	N/A	N/A			
05.							
	Total numbers	30 nos.	30 nos.	MR			
	• Types	ABC /CO ₂	ABC /CO ₂	MR			
	IS marking	ISI marked	ISI marked	MR			

)6	First-Aid-Hose Reels.						
	Total numbers on each floor	04 nos.	04 nos.	MR			
	 Length of hose reel hose 	30 m	45 m	MR			
	 Nozzle diameter 	05 mm	6.50 mm	MR			
)7	Automatic Fire Detection and Alarming System.						
	Type of detectors	Heat or Smoke	Provided	MR			
	 Location of main panel 	Ground Level	Provided	MR			
	 Location of repeater panel 	N/A	N/A	N/A			
	Alternate source of power	Battery & DG Set	Provided	MR			
0	• Hooter	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
0	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	 upper floor 	N/A	N/A	N/A			
	sprinkler above false ceiling	N/A	N/A	N/A			
1	Internal Hydrants			1471			
	 size of riser/down-comer 	100 mm	100 mm	MR			
	 Number of hydrants per floor 	04 nos.	04 nos.	MR			
2	Hose box	04 nos.	04 nos.	MR			
	Yard Hydrants.	<u>'</u>					
	 Total number of hydrants 	N/A	N/A	N/A			
3	Hose box	N/A	N/A	N/A			
	Pumping Arrangements. > Ground Level						
	 Discharge of main pump 	1620 LPM	2400 LPM	MR			
	 Head of main pump 	70 mtr	70 mtr	MR			
	 Number of main pumps 	01 no.	01 no.	MR			
	 Jockey pump out put 	180 Lpm	180 Lpm	MR			
	 Jockey pump head 	70m	70m	MR			
	Standby pump out put Standby pump band	1620 Lpm	2850 Lpm	MR			
	Standby pump headAuto starting /manual stopping	70 mtr	70 mtr	MR			
	Pump house access	Auto	Provided	MR			
		Required	Provided	MR			
	F Terrace Level			WIK			
	Discharge of pump	N/A	N/A	NI/A			
	Head of the pump	N/A	N/A	N/A N/A			
	 Power supply 	Required	Provided	MR			
	 Auto starting of pump 	Required	Provided	MR			
	Captive Water Storage for Fire Fighting.			WIK			
	Underground tank capacity	1,00,000 Ltrs.	2,00,000 Ltrs.	MR			
	 Draw-off connection 	Required	Provided	MR			
	 Fire service inlet 	Required	Provided	MR			
- 1	 Access to tank 	Required	Provided	MR			
				IVIK			
	 Overhead tank capacity 	N/A	N/A	N/A			

	Pressurization of lift shaft	N/A	N/A	N/A		
	 Pressurization of lift lobby 	N/A	N/A	N/A		
	Communication in lift car	Required	Provided	MR		
	Firemen's grounding switch	Required	Provided	MR		
	Lift signage	Required	Provided	MR		
7	Standby Power Supply	Required	Provided	MR		
8	Refuge Area.					
	Total area	N/A	N/A	N/A		
	Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector system panel	N/A	N/A	N/A		
	 Flow switch panel 	N/A	N/A	N/A		
	 PA system panel 	N/A	N/A	N/A		
	 Battery backup 	N/A	N/A	N/A		
	 Building floor plans 	N/A	N/A	N/A		
0	Special Fire Protection Systems for Protection of Special Risks, if Any:	N/A	N/A	N/A		

The fire protection system provided in the building were tested, checked and found functional at the time of inspection. The shortcomings issued vide letter No. $F.6/DFS/MS/2019/NDZ/5203 \ dated \ -27/08/2019 \ have been rectified now.$

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rule. The FSC issued vide letter no. F.6/DFS/MS/2003/2596 dated -22/10/2003 renewal under rule 35 of the Delhi Fire Service Rules, 2010 is recommended.

Signature of the inspection Officer

Name

:- Deepak Kumar

Designation :- A.D.O (Shd)

DO(ED)

105/202

DY, CIP/(HD

17/15/122

ABO(shah)

FI letter is put up for your styrestine p

DCFO(HDZ)

Form/ 9/6/22

De 201 06 06 2022

TAS