

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2022/ND2 309

FIRE SAFETY CERTIFICATE

Certified that the Chander Palace Guest House located at 2689/8, Raj Guru Road, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (04 guest rooms + reception) and 1st floor to 2nd floor (04 guest rooms at each floor) and 3rd floor (02 guest rooms + 01 staff romms & DG set), total 14 guest rooms was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/2019/2208 dated 25/11/19. Now the premises was re-inspected by the officer concerned of this department on 22/06/22 in the presence of Manager and found that the said guest house building having deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (03 guest rooms) 1st floor to 2nd floor (04 guest rooms at each floor) and 3rd floor (02 guest rooms), total 13 guest rooms up to third floor only, with effect from . Apr. 6. .

Issued .297.6. 1.202.2. at New Delhi by.

(**Dr. S.K.Tomar**) Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Commissioner, MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed above.
- 2. The Addl.Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online id no.2022051210122 dated 22.05.2022.
- 3. The Manager, Chander Palace Guest House, 2689/8, Raj Guru Road, Pahar Ganj, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT

1. Name & address of the building Chander Palace Guest House located at 2689/8, Raj Guru Road, Pahar Ganj,

New Delhi

Type of Occupancy:-Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 13 Guest rooms) Ground floor (03 guest rooms + reception), 1st floor to 2nd floor (04 guest rooms at each floor) and 3rd floor (02 guest rooms + staff room + DG set)

3. Type of case:-Renewal

Details of previous FSC:-No. F6/DFS/MS/GH/2019/2208 dated

25/11/19.

5. Fire safety directives No.-N/A

6. Date of inspection:-22/06/22

7. Name of the inspecting officer:-Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer from the building side:-

Manager 2001

9. Year of construction:-10. Applicant's letter No:-

Online id no.2022051210122 dated 22.05.2022.

Old Case S.No. Minimum Standards on fire Requirement/ Provided at site Remarks Prevention and fire safety Existing fire MR/NMR U/R 33 safety arrangements 1. Access to Building 1) Road width 06 mtr. 09 mtr. MR 2) Gate width N/A N/A N/A 3)Width of internal road N/A N/A N/A 2. Number, Width Type & Arrangement of Exits A. Number of staircases 1. Upper floors 01 No. 01 No. MR 2. Basements N/A N/A N/A B. Width of staircase 1. Upper floors 01 mtr. 1.20 Mtr. MR 2. Basements N/A N/A N/A C. Protection of exits 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous 01 01 MR staircase to terrace E. Width of corridor N/A N/A N/A F. Door size 01 mtr. 01 mtr. MR 3. Compartmentation 1) Fire check door N/A N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A N/A 4. Smoke Management System 1) Basements 30 ACPH N/A N/A 2) Upper floors 12 a/c per hour Natural/ MR Exhaust fan 5. Fire Extinguishers 1) Total numbers 12 12 MR 2) Types ABC & CO2 ABC & CO2 MR





	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors CO	Required	Provided	MR		
	2) Location of main panel	Ground floor	Provided	MR		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	Required	Provided	MR		
	5) Hooter's Location	Each floor	Provided	MR		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System	required	Tioviaca	Trac		
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling	. 1/1 k	14/71	INA		
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor		1071	14/21		
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants		14/11	14/21		
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement	T	1,112	1,772		
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump	1,111	1071	IV/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump		N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping			1772		
	2) Terrace level					
	a) Discharge of pump	220 LPM	220 LPM	MR		
	b) Head of pump	20 mtr.	20 mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for F.		1	1		
- "	Under ground tank	N/A	N/A	N/A		
	capacity					
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	N/A	N/A	N/A		
	d) Over head tank	2,500 ltr.	2,500 ltr.	MR		
	capacity	,				
15.	Exit Signage.	Required	Provided	MR		
	0.0	1	1	1		

MDG

16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syster Risk, if any: 01 Co ₂ & 01 AE	MR		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2019/2208 dated 25/11/19, renewal under Rule 35 of the Delhi Fire Service Rules 2010, is recommended for approval up to third floor.

Signature of the Inspecting Officer

Name :- Ravinder Singh Designation :- ADO (CC)

Asopovin Priperty for keestendeland Syntim Please

uploaded