GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001 No. F6/DFS/MS/EH/SZ/2022/ 188 Dated: 29 06 2022

FIRE SAFETY CERTIFICATE

Certified that the M/s. WYLD Restaurant (a unit of Cuisineur Hospitality), located at First floor, 30B, Old Rajender Nagar, Pusa Road, New Delhi - 110005, running at first floor only of a building comprised of basement, stilt, ground plus three upper floors, owned/occupied by WYLD Restaurant (A unit of Cuisineur Hospitality) have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of Delhi Fire Service on 18.06.2022 in presence of Sh. Vikram Handa (Owner) and the building/premises is fit for occupancy class Assembly (Restaurant) at First floor Only with effect from 29 06 2022 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 29 06 2012 at New Delhi by.

Delhi Fire Service

Copy to: Authorized Signatory, M/S WYLD Restaurant (A Unit of Cuisineur Hospitality), located at First floor, 30B, Old Rajender Nagar, Pusa Road, New Delhi- 110005 w.r.t. Online Application id 2022050409349 dated 09.05.2022

Conditions for the validity of Fire Safety Certificate: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. All the means of escapes /exits shall not be locked/bolted/blocked at any time for safe evacuation of the occupants in case of any emergency.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : M/s. WYLD Restaurant (A Unit of Cuisineur Hospitality),

First floor, 30B, Old Rajender Nagar, Pusa Road, New Delhi.

2. Type of Occupancy : Assembly (Restaurant)

3. Building Composition : Restaurant running at First floor of a building comprised of

basement, stilt, ground plus three upper floors, and the building was

issued FSC vide letter No. F.6/DFS/MS/SZ/2021/409 dt. 23.08.2021

4. Type of Case : New Case

5. Details of previous NOC : N/A6. Fire Safety directives letter No : N/A

7. Date of inspection : 18.06.2022

8. Name of the Inspecting Officers: Vedpal Chhikara, DO (SW) & P.V. Rathee, ADO (SRD)

9. Name and designation of officers

vio vi from the building side : Sh. Vikram Handa (Owner)

9. Year of Construction : 2021

10. Applicant's letter No. : Online Application id 2022050409349 dated 09.05.2022

| | | | | 2022050409349 dated | | | |
|-----------|--|-------------------------------------|-----------------------------|----------------------------|-------------------|--|--|
| S. No. | | inimum Standards on fire | Requirement as per NBC/UBBL | Provided at site | Remarks MR/NMR | | |
| | - | ention and fire safety U/R 33 | per NBC/OBBL | 210 | WINTER | | |
| 1 | Acces | s to building | | | | | |
| | • | Road width | 06 mts | Provided | MR | | |
| | • | Gate width | N/A | N/A | N/A (on road) | | |
| | • | Width of internal road | N/A | N/A | N/A | | |
| 2 | Number, Width, Type & Arrangement of Exits | | | | | | |
| | a. Nur | mber of staircases | - | - | - | | |
| | | Upper Floors | 02 Nos. | 02Nos. | MR | | |
| | | Basements | N/A | N/A | N/A | | |
| | b. Wic | lth of staircases | - | - | - | | |
| | | Upper Floors | 2.0 &1.50 mts | 2.0 &1.50 mts | MR | | |
| | • | Basements | N/A | N/A | N/A | | |
| | c. Prot | ection of exits | - | - | - | | |
| | • | Fire check door | Required | Provided | MR | | |
| | • | Pressurization | N/A | N/A | N/A | | |
| | e. No. o | of continuous staircases to terrace | 02 | 02 | MR | | |
| | g. Wid | th of Corridor | N/A | N/A | N/A | | |
| | h. Door | r Size | 2m &1.50 m | 2.0 &1.50 mts | MR | | |
| | Compa | artmentation. | | | | | |
| | • | Fire check door | Required | Provided | MR | | |
| | • | Sealing of electrical shafts | Required | Sealed | MR | | |
| | • | Fire Rating of shaft door | N/A | N/A | N/A | | |
| | • | Water Curtain | N/A | N/A | N/A | | |
| | • | Fire Dampers | N/A | N/A | NA | | |
| | Smoke Management System. | | | | | | |
| | • | Basements | 30 a/c per hour | N/A | N/A | | |
| | • 1 | Upper floors | 12 a/c per hour | Exhaust Fans Provid | ed MR | | |
| | Fire Extinguishers | | | | | | |
| | • | Total numbers | Required | Provided | MR | | |
| | • | Гуреѕ | ABC & CO ₂ type | ABC & CO ₂ type | MR | | |
| | 1 | S marking | ISI marked | Provided | MR | | |



| | First-Aid Hose Reels. | | | | | | |
|----|---|--|---|-------------------------------------|--|--|--|
| | Total numbers on each floor | 01 nos. | 01 at each floor | MR | | | |
| | Length of hose reel hose | 30 m | Provided | MR | | | |
| | Nozzle diameter | 5 mm | Provided | MR | | | |
| 7 | Automatic fire detection and alarmi | ng system. | | IVIIC | | | |
| | Type of detectors | Smoke | Provided | MR | | | |
| | Location of Main Panel | Required With in | Provided | | | | |
| | Location of Repeater Panel | restaurant area N/A | | MR | | | |
| | | Required | N/A Provided | N/A | | | |
| | Alternate source of power | Required With in | Provided | MR | | | |
| | Hooters' Location | restaurant area | | MR | | | |
| 8 | MOEFA | Required | Provided | MR | | | |
| 9 | Public Address System. | N/A | N/A | N/A | | | |
| 10 | Automatic Sprinkler System. | | | | | | |
| | Basement | N/A | N/A | N/A | | | |
| | Entire Restaurant | N/A | Provided | N/A | | | |
| | Sprinkler above false ceiling | N/A | N/A | N/A | | | |
| 1 | Internal Hydrants | Provided & Maintai | ined by Bldg. manage | ment | | | |
| | | | | | | | |
| | Size of riser/down-comer | 100 mm | Provided | MR | | | |
| | Number of hydrants per floor | 01 No. | Provided | MR | | | |
| | Hose Box | 01 No. | Provided | MR | | | |
| 12 | Yard Hydrants. | | | | | | |
| | Total number of hydrants | N/A | N/A | N/A | | | |
| | Hose Box | N/A | N/A | N/A | | | |
| 3 | Pumping Arrangements. Provided & Maintained by Bldg. management | | | | | | |
| | Ground Level | | | | | | |
| | Discharge of main Pump | 2280 lpm | Provided | MR | | | |
| | ➤ Head of Main pump | 60m | Provided | MR | | | |
| | Number of main pumps | 01 | Provided | MR | | | |
| | > Jockey Pump out put | 180 LPM | Provided | MR | | | |
| | > Jockey pump head | 60m | Provided | MR | | | |
| | ➤ Standby Pump out put | 2280 LPM | 2280 LPM | MR | | | |
| | Standby Pump Head | 60m | 60 m | MR | | | |
| | > Auto Starting/ Manual | | 00 111 | IVII | | | |
| | | Required | Provided | MR | | | |
| | stopping | - | Provided Provided | MR MP | | | |
| | stopping > Pump House Access | Required Required | | MR MR | | | |
| | stopping > Pump House Access • Terrace level | Required | Provided | MR | | | |
| | stopping Pump House Access Terrace level Discharge of pump | Required450 LPM | Provided 900 LPM | MR MR | | | |
| | stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump | Required 450 LPM 45 mts | Provided 900 LPM 45 mts | MR MR MR | | | |
| | stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply | Required 450 LPM 45 mts Required | Provided 900 LPM 45 mts Provided | MR MR MR MR | | | |
| | stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump | Required 450 LPM 45 mts Required Required | Provided 900 LPM 45 mts Provided Provided | MR MR MR MR MR | | | |
| | stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply | Required 450 LPM 45 mts Required Required Required Provided & Ma | Provided 900 LPM 45 mts Provided Provided intained by Bldg. ma | MR MR MR MR MR MR | | | |
| | stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump | Required 450 LPM 45 mts Required Required | Provided 900 LPM 45 mts Provided Provided Provided intained by Bldg. ma | MR MR MR MR MR MR MR MR | | | |
| | stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting | Required 450 LPM 45 mts Required Required Required Provided & Ma | Provided 900 LPM 45 mts Provided Provided intained by Bldg. ma | MR MR MR MR MR MR | | | |
| | stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump Captive Water Storage for fire fighting • Underground tank capacity | Required 450 LPM 45 mts Required Required Required 3. Provided & Ma 1,00,000 lts | Provided 900 LPM 45 mts Provided Provided Provided intained by Bldg. ma | MR MR MR MR MR MR MR MR | | | |
| | stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection | Required 450 LPM 45 mts Required Required Required 1,00,000 lts Required | Provided 900 LPM 45 mts Provided Provided intained by Bldg. ma Provided Provided | MR | | | |
| | stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet | Required 450 LPM 45 mts Required Required 7. Provided & Ma 1,00,000 lts Required Required Required | Provided 900 LPM 45 mts Provided Provided Provided Provided Provided Provided Provided Provided Provided | MR | | | |



| | Lift Signage | Required | Provided | MR | | |
|----|--|----------|----------|-----|--|--|
| 7 | Standby power supply | Required | Provided | MR | | |
| 18 | Refuge Area. | | | | | |
| | > Total Area | N/A | N/A | N/A | | |
| | > Location | N/A | N/A | N/A | | |
| 19 | Fire Control Room | | | | | |
| | Detector System Panel | N/A | N/A | N/A | | |
| | Flow Switch Panel | N/A | N/A | N/A | | |
| | PA System Panel | N/A | N/A | N/A | | |
| | Batter backup | N/A | N/A | N/A | | |
| | Building Floor Plans | N/A | N/A | N/A | | |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any: | N/A | N/A | N/A | | |

satisfactory at the time of inspection. Note:- The total covered area of restaurant as per MHA CAF portal is 387 Sq mtr., so sitting

If agreed in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the Rules, it is recommended to grant fire safety certificate under Rule 35 of

Delhi Fire Service Act- 2007 & Rules- 2010. Accordingly, DFA is put up for approval & signature please.

Signature of the Inspecting Officer

PAR 20/6/22

Signature of the Inspecting Officer Name- P.V. Rathee Divisional Asstt. Div. Officer (S.Rd)

Name- Vedpal Chhikara Divisional Officer (SW)

Provision of Lifts.

16

capacity comes (387/1.8 = 215) 215 persons.

To letter is for up for sopen for DIRECTOR/DES 129/06/20 uploaded M.