

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/NDZ/2022/

Dated : ... /2022

FIRE SAFETY CERTIFICATE

Certified that the Sri Lanka Pilgrim Rest located at 7, Chelmsford Road, New Delhi comprised of Basement + Ground + 03 Upper floors was earlier granted NOC by this department vide letter No.F6/DFS/MS/2002/84 dated 14/01/2002. Now, the premises was re-inspected by the officenconcerned of this department on 30/06/22 in the presence of Sh. Rohan Toseph and found that the said building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential building (hostel) with effect from file 2/2 Profer period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

(S.K. Dua)

Dy. Chief Fire Officer Delhi Fire Service

Q_

Copy to:-

1. Sh. HGU Pushpakumara, Minister for High Commissioner of Democratic Socialist Republic of Sri Lanka, 27, Kautilya Marg, Diplomatic Enclave, Chankya Puri, New Delhi.

Conditions for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 9. Any flammable material for interior decoration is prohibited

MIII

INSPECTION REPORT

SMri Lanka Pilgrim Rest Name & address of the building :

7, Chelmsford Road, New Delhi : Residential Building(hostel)

2. Type of occupancy (B+ Gr. + 03 Upper floors)

: Renewal

3. Type of case:-:F6/ /DFS/ MS /2002/84 dated 4. Details of previous NOC

14.01.2002

:F6/ /DFS/ MS /BP/98/2256 dated Fire safety directives No.

12.11.98

: 30/06/2022 6. Date of inspection:-

: Sh. Ravinder Singh, ADO (CC) 7. Name of the inspecting officer

Sh. Rajinder Atwal, DO (CD)

8. Name & designation of officer From the building side

: Mr. Rohan Joseph (Defence Advisor)

9. Year of construction

: 1998

10. Applicant's letter No : No. SLHCND/SLBPR/15 dated

28.06.2022

	20.00.2022				
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirements/ Existing arrangements	Provided at site	Remarks MR/NMR	
1.	Approach to Building	arrangements			
	1) Road width	06 mtr.	Provided	MR	
	2) Gate width	NA	NA	NA	
	3)Width of internal road	NA	NA	NA	
2.	Number, Width Type & Arrai	ngement of Exits	1471	IVA	
	A. Number of staircases	Samuel of Ballo			
	1. Upper floors	03 nos	03 nos	MR	
	2. Basements	02nos	02nos	MR	
	B. Width of staircase		021103	IVIIX	
	1. Upper floors	1.25	1.25	MR	
		mtr.&.75mtr	mtr.&.75mtr	IVIIC	
	2. Basements	1.25mtr	1.25mtr	MR	
	C. Protection of exits			IVIIC	
	1. Fire check door	NA	NA	NA	
	2. Pressurization	NA	NA	NA	
	D. No. of continuous	02 No	02 No	MR	
	staircase to terrace			WIK	
	E. Width of corridor	1.25 mtr.	1.50 mtr.	MR	
	F. Door size	1.0 Mtr.	1.0 Mtr.	MR	
3.	Compartmentation				
	1) Fire check door (basement)	Required	Provided	MR	
	2) Sealing of electrical shafts	Required	Provided	MR	
	3) Fire rating of shaft door	N/A	NA	NA	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System			1071	
	1) Basements 12 ACPH	Required	Provided	MR	
	2) Upper floors	12 ACPH	Provided	MR	
5.	Fire Extinguishers				
	1) Total numbers	16 Nos.	16 Nos.	MR	
	2) Types	ABC & CO2	ABC, CO2 &	MR	

Deling

n 0.

er

gh

	3) ISI marking		W.CO2	
6.	First-Aid Hose Real	Required	Provided	-
	1)Total number of each		Tucu	MR
	Floor Common Auditorium	02 No.	Provided	
	2) Length of hose reel hose		- To Vided	MR
	3) Nozzle diameter	30 m	30 m	
7.	Automatic Fire P	5 mm	5 mm	MR
	Automatic Fire Detection & A	Alarming Syste	m J IIIII	MR
	1) Type of detectors	Required		
	2) Location of main panel	0	Provided	MR
	5) Location of repeater panel	N/A	Provided	MR
	4) Alternate source of nower		N/A	N/A
	J) Hooler's Location	Required	Provided	
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkle	Required	Provided	MR
	Automatic Sprinkler System 1) Basement		Tiovided	MR
	2) Upper G	Required	Duo	
	2) Upper floors	N/A	Provided	MR
	3) Sprinkler above false	N/A	N/A	N/A
11	Celling	1 11/1	N/A	N/A
11.	Internal Hydrants			11 11/1
	1) Size of riser/down comes	100 15		
	2) Number of hydrants non	100 MM	100 MM	MD
	11001	02	Provided	MR
	3) Hose box each floor		- Flacu	MR
12.	Yard Hydrants	02	Provided	
	1) Total number 2:		riovided	MR
	1) Total number of hydrants 2) Hose box	02	03	
13.	2) Hose box	02		MR
	Pumping Arrangement		03	MR
	Ground level			
	 a) Discharge of main 	2280 1 72 4		
	pump	2280 LPM /	Provided	MR
	b) Head of main nume	40		1711
	c) Number of main	40 mtr.	Provided	MR
	pump	01	Provided	
	d) Jockey pump out put	100		MR
	e) Jockey pump head	180 LPM	Provided	M
	f) Stand by pump	40 mtr.	Provided	MR
	output	2280 LPM	Provided	MR
	g) Stand I		1 TO VIUCU	MR
	g) Stand by pump head	40 mtr.	Provided	
	(i) Auto starting/Manual	Required	Provided	MR
	stopping	quiled	Provided	MR
	2) Terrace level			
	a) Discharge of pump	Require 1		
	b) Head of pump	Required	900 LPM	MR
	Famp	N/A	N/A	N/A
				1777
	c) Power supply	N. 1.		
	d) Auto starting of	N/A	N/A	N/A
	pump	N/A	N/A	N/A
	Continuation			N/A
	Capitye Water Ct			
	Captive Water Storage for Fire 1) Under ground tank	Fighting 50,000 ltr.		

			113		
	capacity				
	a) Draw-off connection	P.o.o.			
	b) Fire service inlet	required	Provided	MR	
	c) Access to tank	Required	Provided	MR	
	d) Over head tank	Required	Provided	MR	
	capacity	12500 ltrs.	15,000 ltrs.	MR	
	Exit Signage.	Paguin 1		IVIK	
15.	Provision of Lifts.	Required	Provided	MR	
16.	a) Pressurization of lift	11/1			
	shaft	N/A	N/A	N/A	
	b) Pressurization of lift			N/A	
	lobby	N/A	N/A	N/A	
	c) Communication in			IN/A	
		Required	Provided	MR	
	lift car			IVIK	
	d) Fireman's switch	Required	Provided	MR	
	e) Lift signage	Required	Provided	MR	
7.	Stand by Power Supply	Required	Provided	MR	
8.	Refuge Area	N/A	N/A		
	Total area location	NI/A		N/A	
	Total area location	N/A	N/A	N/A	
9.	Fire Control Room	21/4			
9. ———		N/A	N/A	N/A	
	a) Detector system	N/A	N/A	N/A	
	panel			IN/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A		
	,		13/74	N/A	
		N/A	N/A	N/A	
	Special Fire Protection System for Protection of special Risk, if any:				

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC/NOC issued vide letter no. F6/ /DFS/ MS /2002/84 dated 14.01.2002, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the Inspecting Officer

Name :- Sh. Rajinder Atwal

Designation:- DO (CD)

Signature of the Inspecting Officer

Name :- Sh. Ravinder Singh Designation: ADO (CC)

MRMR11 11

one, en putub ferkense 7.