## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2022/ 344

Dated 13.1.7.12022

## FIRE SAFETY CERTIFICATE

Certified that the Scot Guest House located at 4581, Main Bazar, Pahar Ganj, New Delhi comprised of Basement + Ground + 04 Upper floors, Basement (storage), Ground floor (reception + small luggage room), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (03 guest rooms at each floor) and 4<sup>th</sup> floor (Rooms sealed by MCD), total 09 guest rooms was earlier granted FSC by this department vide letter No. F6/DFS/MS/GH/NDZ/2019/749 dated 05/04/19.Now, the premises was reinspected by the officer concerned of this department on 28/06/22 in the presence of Manager and found that the said guest house building comprised of basement, ground and three upper floor and 4<sup>th</sup> floor has been demolished as per undertaking dated 13.11.2019 has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, (Sub Division-A-1) 1st floor to 3rd floor (03 guest rooms at each floor) total 09 guest rooms up to third floor only, with effect from .1.3.1.2014. For period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

3

(S.K. Dua) Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

A ABREAT AND

- 1. The Commissioner, MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed above.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online id no. 2022061212612 dated 12.06.2022.
- 3. The Manager, Scot Guest House, 4581, Main Bazar, Pahar Ganj, New Delhi Conditions for the validity of Fire Safety Certificate
  - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
  - Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
  - 3. The trained fire fighting staff should be available round the clock.
  - 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
  - 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
  - 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>www.dfs.delhigovt.nic.in</u>
  - 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
  - The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
  - 9. Any flammable material for interior decoration is prohibited.

		134				
1	INS Name & address of the buildi	PECTION REP		581 Main		
		÷	g Scot Guest House located at 4581, Main Bazar, Pahar Ganj, New Delhi			
2.	. Type of occupancy:-	Residentia	I, Sub Division-A-1	l		
		Upper floors (total 09 Guest rooms)				
	Basement (storage), Ground floor (recepting the storage) 1 <sup>st</sup> floor to 2 <sup>rd</sup> floor (0.3 gr					
	luggage room), 1 <sup>st</sup> floor to 3 <sup>rd</sup> floor (03 guest rooms & 01 store at each floor).					
3	. Type of case:-	Renewal	,			
	4. Details of previous FSC:- F6/DFS/MS/GH/NDZ/2019/749 dated					
	-	05/04/19.				
5	. Fire safety directives No	N/A				
	. Date of inspection:-	28/06/22				
7	. Name of the inspecting office		der Singh (ADO/CO			
			er Atwal ( DO/CD )	)		
8	. Name & designation of office					
	From the building side:-	Manager				
	. Year of construction:-	2001		022		
	10. Applicant's letter No:-	202206121	2612 dated 12.06.2	Old case		
			Duravidad at sita	Remarks		
S.No.		Requirement	Provided at site PSS	MR/NMR		
	Prevention and fire safety	Existing	r55			
	U/R 33					
1.	Access to Building			MR		
	1) Road width	N/A	06 mtr.	N/A		
	2) Gate width	N/A	N/A			
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Art	rangement of E	xits			
	A. Number of staircases		01.24	MR		
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	01 Nos.	01 Nos.	IVIK		
	B. Width of staircase	0.00	0.80 to 0.87 mtr.	MR		
	1. Upper floors	0.80 mtr.	0.80 10 0.87 1111.	IVIK		
	2. Basements	0.80 mtr.	0.80 to 0.87 mtr.	MR		
	2. Basements	0.00 ma.				
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	01	MR		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
3.	Compartmentation					
3.	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System		_L	_		
4.	1) Basements	30 a/c per	Exhaust fan	MR		
		12 a/c per	Natural Ventilation	MR		
	2) Unner floors					
	2) Upper floors					
5		hour				
5.	<ul> <li>2) Upper floors</li> <li>Fire Extinguishers</li> <li>1) Total numbers</li> </ul>		Provided	MR		

## MISS

ì

<ul> <li>3) ISI marking</li> <li>First-Aid Hose Reel</li> <li>1) Total number of eachfloor</li> <li>2) Length of hose reel hose</li> <li>3) Nozzle diameter</li> <li>Automatic Fire Detection &amp;</li> <li>1) Type of detectors CO</li> <li>2) Location of main panel</li> <li>3) Location of repeater panel</li> <li>4) Alternate source of power</li> <li>5) Hooter's Location</li> <li>MOEFA</li> <li>Public Address System</li> <li>Automatic Sprinkler System</li> </ul>	Required 01 30 mtr. 05 mm Alarming Syste Required Ground floor N/A Required Each floor N/A	Provided 01 30 mtr. 05 mm em Provided Provided N/A Provided	MR MR MR MR MR MR MR	
<ol> <li>Length of hose reel hose</li> <li>Nozzle diameter</li> <li>Automatic Fire Detection &amp;</li> <li>Type of detectors CO</li> <li>Location of main panel</li> <li>Location of repeater panel</li> <li>Alternate source of power</li> <li>Hooter's Location</li> <li>MOEFA</li> <li>Public Address System</li> </ol>	30 mtr. 05 mm Alarming Syste Required Ground floor N/A Required Each floor	30 mtr. 05 mm em Provided Provided N/A	MR MR MR MR	
<ol> <li>Length of hose reel hose</li> <li>Nozzle diameter</li> <li>Automatic Fire Detection &amp;</li> <li>Type of detectors CO</li> <li>Location of main panel</li> <li>Location of repeater panel</li> <li>Alternate source of power</li> <li>Hooter's Location</li> <li>MOEFA</li> <li>Public Address System</li> </ol>	30 mtr. 05 mm Alarming Syste Required Ground floor N/A Required Each floor	30 mtr. 05 mm em Provided Provided N/A	MR MR MR MR	
<ul> <li>3) Nozzle diameter</li> <li>Automatic Fire Detection &amp;</li> <li>1) Type of detectors CO</li> <li>2) Location of main panel</li> <li>3) Location of repeater panel</li> <li>4) Alternate source of power</li> <li>5) Hooter's Location</li> <li>MOEFA</li> <li>Public Address System</li> </ul>	05 mm Alarming Syste Required Ground floor N/A Required Each floor	05 mm em Provided Provided N/A	MR MR MR	
<ol> <li>Type of detectors CO</li> <li>Location of main panel</li> <li>Location of repeater panel</li> <li>Alternate source of power</li> <li>Hooter's Location</li> <li>MOEFA</li> <li>Public Address System</li> </ol>	Alarming Syste Required Ground floor N/A Required Each floor	em Provided Provided N/A	MR MR	
<ol> <li>Type of detectors CO</li> <li>Location of main panel</li> <li>Location of repeater panel</li> <li>Alternate source of power</li> <li>Hooter's Location</li> <li>MOEFA</li> <li>Public Address System</li> </ol>	Required Ground floor N/A Required Each floor	Provided Provided N/A	MR	
<ul> <li>3) Location of repeater panel</li> <li>4) Alternate source of power</li> <li>5) Hooter's Location</li> <li>MOEFA</li> <li>Public Address System</li> </ul>	Ground floor N/A Required Each floor	Provided N/A	MR	
<ul> <li>4) Alternate source of power</li> <li>5) Hooter's Location</li> <li>MOEFA</li> <li>Public Address System</li> </ul>	N/A Required Each floor	N/A		
<ul> <li>4) Alternate source of power</li> <li>5) Hooter's Location</li> <li>MOEFA</li> <li>Public Address System</li> </ul>	Required Each floor			
5) Hooter's Location MOEFA Public Address System	Each floor	TIOVILLEU		
Public Address System		Provided	MR	
Public Address System Automatic Sprinkler System		N/A	MR	
Automatic Sprinkler System	N/A	Provided	N/A	
	1.011	Flovided	N/A	
1) Basement	N/A	Dress 1 1		
2) Upper floors	N/A	Provided	N/A	
3) Sprinkler above false		N/A	N/A	
ceiling	1 1/ 23	N/A	N/A	
Internal Hydrants				
1) Size of riser/down-comer	N/A	21/1		
2) Number of hydrants per			N/A	
floor	IN/A	N/A		
3) Hose box	NI/A			
Yard Hydrants	IN/A	N/A	N/A	
1) Total number of hydrants	NI/A			
2) Hose box			N/A	
Pumping Arrangement	IN/A	N/A		
1) Ground level	21/1			
a) Discharge of main		N/A		/Δ
pumn	N/A	N/A		
b) Head of main must				А
c) Number of main	N/A	N/A	N	/ •
d) Jockey nume and	ip N/A	N/A		
e) Jockey nume by		N/A		
f) Stand by much	N/A	N/A		
g) Stand by pump outpu				
h) Auto startin 2	N/A			
stopping	N/A			
2) Terraca las l			N	/A
b) Head a	425 LPM	425 I DM		
c) Rows	30 mtr.	30 mtr		
d) And	D			R
a) Auto starting of pump			M	R
		riovided	M	IR
Captive Water Storage for	Fire Fighting			
	N/A			
capacity		N/A	N	/A
a) Draw-off connection	NUA			A
b) Fire service inlat		N/A		/ 4
c) Access to tert				/A
d) Over head is t				/A
a) over nead tank	5000 ltr.			/A
	Internal Hydrants         1) Size of riser/down-comer         2) Number of hydrants per         floor         3) Hose box         Yard Hydrants         1) Total number of hydrants         2) Hose box         Pumping Arrangement         1) Ground level         a) Discharge of main pump         b) Head of main pump         c) Number of main pump         c) Number of main pump         d) Jockey pump out put         e) Jockey pump nead         f) Stand by pump head         h) Auto starting/Manual stopping         2) Terrace level         a) Discharge of pump         b) Head of pump         c) Power supply         d) Auto starting of pump         b) Head of pump         c) Power supply         d) Auto starting of pump         b) Head of pump         c) Power supply         d) Auto starting of pump	3) Sprinkler above false       N/A         ceiling       Internal Hydrants         1) Size of riser/down-comer       N/A         2) Number of hydrants per       N/A         3) Hose box       N/A         Yard Hydrants       N/A         2) Hose box       N/A         Yard Hydrants       N/A         2) Hose box       N/A         Pumping Arrangement       N/A         1) Ground level       N/A         a) Discharge of main pump       N/A         b) Head of main pump       N/A         c) Number of main pump       N/A         d) Jockey pump out put       N/A         e) Jockey pump out put       N/A         g) Stand by pump head       N/A         h) Auto starting/Manual stopping       N/A         2) Terrace level       30 mtr.         a) Discharge of pump       425 LPM         b) Head of pump       30 mtr.         c) Power supply       Required         d) Auto starting of pump       Required         d) Auto starting of pump       N/A         b) Fire service inlet       N/A         b) Fire service inlet       N/A         b) Fire service inlet       N/A         d) O	3) Sprinkler above false       N/A       N/A         ceiling       Internal Hydrants       N/A       N/A         1) Size of riser/down-comer       N/A       N/A       N/A         2) Number of hydrants per floor       N/A       N/A       N/A         3) Hose box       N/A       N/A       N/A         2) Number of hydrants       N/A       N/A         3) Hose box       N/A       N/A         Yard Hydrants       N/A       N/A         1) Total number of hydrants       N/A       N/A         2) Hose box       N/A       N/A         Pumping Arrangement       Internal Hydrants       Internal Hydrants         1) Ground level       N/A       N/A         a) Discharge of main pump       N/A       N/A         pump       N/A       N/A         b) Head of main pump output       N/A       N/A         c) Number of main pump output       N/A       N/A         d) Jockey pump output       N/A       N/A         g) Stand by pump output       N/A       N/A         h) Auto starting/Manual stopping       N/A       N/A         a) Discharge of pump       30 mtr.       30 mtr.         c) Power supply	3) Sprinkler above false       N/A       N/A       N/A         ceiling       N/A       N/A       N/A         Internal Hydrants       N/A       N/A       N/A         1) Size of riser/down-comer       N/A       N/A       N/A         1) Size of riser/down-comer       N/A       N/A       N/A         2) Number of hydrants per       N/A       N/A       N/A         1) Size of riser/down-comer       N/A       N/A       N/A         1) Size of riser/down-comer       N/A       N/A       N/A         1) Size of riser/down-comer       N/A       N/A       N/A         Yard Hydrants       N/A       N/A       N/A       N/A         2) Hose box       N/A       N/A       N/A       N/A         2) Hose box       N/A       N/A       N/A       N/A         1) Ground level       N/A       N/A       N/A       N/A

			4 36	
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	NA		

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2019/1740 dated 06/09/19, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval up to third floor.

Signature of the Inspecting Officer

F.T.

Name: - Sh. Rajinder Atwal Designation: - DO (CD)

O(MOZ)

Signature of the Inspecting Officer

n

Name: - Sh. Ravinder Singh Designation: ADO (CC)

((CD))discussed DFA as fee F.T.

pertry

uploaded