GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELIII FIRE SERVICE : NEW DELHI - 110001

No. F6/DFS/MS/Club/NDZ/2022/ 1 4 5

Dated: 6//04/2022

FIRE SAFETY CERTIFICATE

Certified that the M/s MGM Club Society located at 4634/1, Building No. 19, Ansari Road, Darya Gang, New Delhi comprised of Basement + Ground + 05 upper floor owned / occupied by MGM Club Society was granted FSC by this department vide letter F6/DFS/MS/NDZ/2018/1711 dated 20.07.2018. The premises was re-inspected by the officer concerned of this department on 23.03.2022 in the presence of Mr.Abhishek Sharma (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010 and that the period is fit for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of conditions under Rule 38 of Delhi Fire Service Rules, 2010, printed below.

Delhi Fire Service Tel:-011-23414000

Copy to:-

- 1. The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New
- 2. The Licensee, M/s MGM Club Society located at 4634/1, Building No. 19, Ansari Road, Darya Gang, New Delhi.

Conditions for the validity of Fire Safety Certificate:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub Rule (I) of Rule 37] along with a copy of this Certificate, six month prior to its expiry. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.

			SPECTION REPO	ORT				
1	N:	ame & address of the building	M/s MGM C	lub Society located a	4634/1, Buildin			
2	Bı	ailding is comprised of		Road, Darya Ganj, N				
			Basement + Ground + 05 upper floors Ground floor Reception 1 st floor- & 2 nd floor- Office					
			1 1100r- & 2	floor- Office				
				3 rd floor - Restaurant + Party Hall				
			4th floor Lounge (Of Party Hall)					
3	T	pe of occupancy	5th floor Kitch					
4	Ty	/pe of occupancy		s / Assembly Occupancy	/			
5			Renewal					
	Do	etails of previous FSC	F6/DFS/MS/NI	F6/DFS/MS/NDZ/2018/1711 dated 20.07.2018				
6	Fi	re safety direction letter no.	12 Point require					
7	Da	ate of inspection	23.03.2022					
8	Na	ame of the inspecting officers	Rajender Atwal DO (CD)					
			Sumit Kumar ADO (SPM)					
9	Na	ame of the designation of officer						
	fro	om the building side	Mir. Abhishek S	Mr. Abhishek Sharma (Manager)				
10	Ye	ear of construction	1989	1000				
11		oplicant's letter no.						
S.No		inimum Standards on fire		Email dated 15.03.2022				
	Pr	evention and fire safety	Requirement/	Provided at Site	Remarks MR/			
	re	quirements U/R 33	Existing fire		NMR			
		1	safety					
1	Ac	ccess To Building:	arrangements					
	Ro	oad width	06 mtrs	00				
	Ga	ate width	NA	09 mtrs	MR			
		idth of internal road	NA	NA	NA			
2	Nu	imber, Width, Type and Arran	gement of Evitor	NA	NA			
	A	Number of staircases	gement of Exits:					
		a Upper floor	02 nos.	02				
		b Basement	02 nos.	02 nos.	MR			
	В	Width of staircases	02 1103.	02 nos.	MR			
		a Upper floor	1.25mtrs.	1.5				
		b Basement	1.25mtrs.	1.5 mtrs. , 1.25 mtrs.	MR			
	C	Protection of exits	1.2311113.	1.25mtrs.	MR			
		a Fire check door	NA	NIA				
		b Pressurization	NA	NA NA	NA			
	D	No. of continuous staircases	01 nos.	02 nos.	NA			
		to terrace		02 1108.	MR			
	E	Width of corridor	NA	NA				
	F	Door size	1.0 mtrs.	1.0 mtrs.	NA			
3	Co	mpartmentation:		1.0 mirs.	MR			
	A	Fire check door	Required	Describ				
-	В	Sealing of electrical shafts	NA	Provided NA	MR			
	C	Fire rating of shaft door	NΛ		NA			
				NA	NA			
	D	Water curtain	NA					
-	D E	Fire dampers	NA NA	NA	NA			
1	D E	Fire dampers	NA NA	NA NA	NA NA			
ı	D E							



5	. F	ire Extinguisher:					
	A		30 nos.	30 nos.	MF		
	В	Types	CO ₂ & ABC	CO ₂ & ABC	MR		
	C	ISI marking	ISI marked	ISI marked	MR		
6	F	irst-Aid-Hose Reels:	131 marked	151 marked	IVII		
	A		01 nos.	01 nos.	MR		
	В	Length of hose reel hose	30 mtrs.	30 mtrs.	MR		
	C	Nozzle diameter	5 mm	5 mm	MR		
7	A	utomatic Fire Detection And	l Alarming System		1.22		
	A	Type of detectors	Required	Provided	MR		
	В	Location of main panel	Gr. floor	Provided	MR		
	C	Location of repeater pane	d Gr. floor	Provided	MR		
	D	Alternate source of power		Provided	MR		
	E	Hooters	NA	NA	NA		
8	_	OEFA:	Required	Provided	MR		
9	Pu	blic Address System:	Required	Provided	MR		
10	Au	tomatic Sprinkler System:	-				
	A	Basement	Required	Provided	MR		
	B	Upper floor	Required	Provided	MR		
	C	Sprinkler above false	NA	NA	NA		
		ceiling			INZ		
1	Int	ternal Hydrants:					
	A	size of riser/down-comer	01 nos.	02 nos.	MR		
	В	Number of hydrants per floor	01	02	MR		
	C	Hose box	01	02	MR		
2	Yar	d Hydrants:		02	MIK		
	A	Total number of hydrants	NA	NA	NIA		
1	В	Hose box	NA	NA	NA		
3		nping Arrangements:	1474	INA	NA		
	A	Ground level					
-	a)	Discharge of main pump	1620 LPM	1620 I DN 4			
-	b)	Head of main pump	70 mtrs.	1620 LPM	MR		
-	c)	Number of main pumps	01	70 mtrs.	MR		
-	d)	Jockey pump out put	180 LPM	01	MR		
-	e)	Jockey pump head	NA	180 LPM	MR		
	f)	Standby pump out put	70 mtrs.	NA 70 metus	NA		
-	g)	Standby pump head	1620 LPM	70 mtrs.	MR		
	h)	Auto starting /manual	Required	1620 LPM Provided	MR		
		stopping		riovided	MR		
	i)	Pump house access	NA	NA	NA		
-	В	Terrace level			11/1		
	1)	Discharge of pump	900 LPM	900 LPM	MR		
_)	Head of the pump	40 mtrs.	40 mtrs.	MR		
C	:)	Power supply	Required	Provided	MR		
_	1)	Auto starting of pump					

4	Captive Water Storage For Fire Fighting:						
	A Underground tank capacity	50,000 ltrs.	50,000 ltrs.	MR			
	B Draw-off connection	Required	Provided	MR			
	C Fire service inlet	Required	Provided	MR			
1	D Access to tank	Required	Provided	MR			
	E Overhead tank capacity	10,000 ltrs.	25,000 ltrs.	MR			
	Exit Signage:	Required	Provided	MR			
16	Provision of Lifts:						
	A Pressurization of lift shaft	NΛ	NA	NA			
-	B Pressurization of lift lobby	NA	NA	NA			
	C Communication in lift car	Required	Provided	MR			
	D Firemen's grounding switch	Required	Provided	MR			
	E Lift signage	Required	Provided	MR			
17	Standby Power Supply:	Required	Provided	MR			
18	Refuge Area:						
	A Total area	NΛ	NΛ	NA			
	B Location	NA	NA	NA			
19	Fire Control Room:						
	A Detector system panel	NΛ	NΛ	NΛ			
-	B Flow switch panel	NA	NA	NA			
	C Pa system panel	NA	NA	NA			
	D Battery backup	NA	NA	NA			
20	E Building floor plans	NΛ	NΛ	NA			
20	Special Fire Protection Systems I Special Risks, If Any:	pecial Fire Protection Systems For Protection of					

Meeting requirement (MR), Not meeting requirement (NMR), Not applicable (NA), Provided but not functional (PNF).

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

If agreed and in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter no. F6/DFS/MS/NDZ/2018/1711 dated 20.07.2018 is recommended to be renewed under Rule 35 of

Signature of the Inspecting Officer

Name Rajinder Atwal

Designation DO (CD) Signature of the Inspec

Name Sumit Kumar

Designation ADO (SPM)