

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2022/ 338

Dated: 1.1.7.7./2022

## FIRE SAFETY CERTIFICATE

Certified that the Hotel Satya Palace located at 3386, Gali Hari Mandir, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (Reception + 03 guest rooms), 1st floor to 3rd floor (05 guest rooms at each floor) total 18 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2019/2199 dated 22/11/19. The premises was reinspected by the officers concerned of this department on 30/06/22 in the presence of Manager and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, (Sub Division-A-1) Ground floor (Reception + 03 Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Dy. Chief Fire Officer Delhi Fire Service

## Copy to:-

- 1. The Commissioner, MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online id no.2022042608376 dated 18.05,2022
- 3. The Manager, Hotel Satya Palace, 3386, Gali Hari Mandir, Pahar Ganj, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the
- The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any. 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

N/28

**INSPECTION REPORT** 

1. Name & address of the building Hotel Satya Palace located at 3386, Gali

Hari Mandir, Pahar Ganj, New Delhi

2. Type of Occupancy:- Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 18 Guest rooms) Ground floor ( Reception + 03 guest rooms), 1st floor to 3rd floor (05 guest rooms at each floor)

3. Type of case:- Renewa

4. Details of previous FSC:- No. F6/DFS/MS/GH/2019/2199 dated

22/11/19.

5. Fire safety directives No.-

6. Date of inspection:-

30/06/2022

7. Name of the inspecting officer:-

Sh. Rayinder Singh (ADO/CC) Sh. Rajinder Atwal, (DO/CD)

8. Name & designation of officer From the building side:-

Manager

9. Year of construction:-

2001

N/A

10. Applicant's letter No:-

Online id no.2022042608376 dated 18.05.2022.

			2022042006576 ua	Old Case		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements				
1.	Access to Building					
	1) Road width	N/A	12 mtr.	N/A		
	2) Gate width	N/A	05 mtr.	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases					
	1. Upper floors	01 Nos.	01 Nos.	MR		
[	2. Basements	N/A	N/A	N/A		
	B. Width of staircase		,			
	1. Upper floors	0.80 mtr.	0.80 Mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
_	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase to terrace	,01	01	MR		
r	E. Width of corridor	1.25 mtr.	1.5 mtr.	N/A		
	F. Door size	N/A	N/A	N/A		
	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
2	2) Sealing of electrical shafts	N/A	N/A	N/A		
	B) Fire rating of shaft door	N/A	N/A	N/A		
	1) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
	Smoke Management System					
	) Basements	30 ACPH	N/A	N/A		
_	) Upper floors	12 a/c per hour	Natural	MR		
F	Fire Extinguishers					
	) Total numbers	20	20	MR		
	) Types	ABC & CO2	ABC & CO2	MR		
	) ISI marking	Required	Provided	MR		

6.	First-Aid Hose Reel			2
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7	Automatic Fire Detection &		em	
7.	1) Type of detectors CO	Required	Provided	MR
	2) Location of main panel	Ground floor	Provided	MR
	3) Location of repeater panel		N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Each floor	Provided	MR
-		N/A	Provided	N/A
8.	MOEFA	N/A	Provided	N/A
9.	Public Address System		Tiovided	
10.	Automatic Sprinkler System		N/A	N/A
	1) Basement	N/A		N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	IV/A
	ceiling			
11.	Internal Hydrants			1.
4	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor			
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
3.	Pumping Arrangement	17/11	11/11	1 1 1
J,		NI/A	NI/A	N/A
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main	N/A	N/A	N/A
	pump			
İ	d) Jockey pump out put	N/A	N/A	N/A
ŀ	e) Jockey pump head	N/A	N/A	N/A
H	f) Stand by pump	N/A	N/A	
- 1		1 1 1 / / /	IN/A	NA
-	output	27/4		
L	g) Stand by pump head	N/A	N/A	N/A
1	h) Auto starting/Manual	N/A	N/A	NA
	stopping			
Γ	2) Terrace level		/	,
<u> </u>	a) Discharge of pump	450 LPM	450 LPM	MD
-	b) Head of pump	30 mtr.		MR
			30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of	Required	Provided	MR
	pump	-		T
(	Captive Water Storage for Fi	ire Fighting		
	1) Under ground tank	N/A	NI/A	
1	capacity	1 N/ /1	N/A	NA
- 1	capacity			
-				
	a) Draw-off connection	N/A	N/A	NA
		N/A N/A	N/A N/A	N/A N/A

H 2

		413	В	
	d) Over head tank capacity	2,500 ltr.	2,500 ltr.	MR
15.	Exit Signage.	Required	Provided	145
16.	Provision of Lifts.	1	Tiovided	MR
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	<ul> <li>c) Communication in lift car</li> </ul>	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	<ul><li>a) Detector system panel</li></ul>	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2019/2199 dated 22/11/19, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval up to third floor.

Signature of the Inspecting Officer

Name :- Rajinder Atwal

Signature of the Inspecting/Officer

Name :- Ravinder Singh Designation :- 'ADO (CC)

Designation :- DO (CD)

exported fry pertup for icus enetur Pleam.