

FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/SZ/2022/ 3/6

Dated: 9/07/2022

FIRE SAFETY CERTIFICATE

Certified that the building of YWCA of Delhi Hostel building located at Sector 10, Dwarka New Delhi – 110075 owned / occupied by Young Women's Christian Association of Delhi comprised of, Basement, ground + four upper floors was issued FSC by this department vide Letter No. F6/DFS/MS/2017/South/172 Dated 08/02/2017. The premises was re inspected by the officers concerned of this department on 29/06/2022 in the presence of. Ms. Ruby Rajeev (Admin Manager) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-5 with effect from 20/07/2012 for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 31/07/122 at New Delhi by.

Director

Delhi Fire Service.

Copy to:

- 1. Ms. Ruby Rajeev (Admin Manager) YWCA of Delhi Hostel building located at Sector 10, Dwarka New Delhi 110075.
- 2. The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

Name & address of the building: YWCA of Delhi Hoste Buliding located at Sector 10, Dwarka New Delhi-110075.

: Educational/ Hostel (Basement + Ground+ 4 U.F) Type of Occupancy

Type of Case

Details of previous NOC: F6/DFS/MS/2017/South/172 Dated 08/02/2017 : Renewal

Fire Safety directives Letter No.: F6/DFS/MS/BP/2010/3271 Dated 30/11/10

Date of inspection 6.

: 29/06/2022

Name of the Inspecting Officer :Udai vir singh, ADO (DWK)

Name and designation of Officer

: Ms. Ruby Rajeev (Admin Manager) from the building side

Year of Construction

: Email Dated 23/06/2022 10. Applicant's letter No.

: 2016

s A																						MK	MR	MR	NA	Ν		MR	NA		
Remarks MR/NMR		MR	MR	MR	MINI			MR	MR.					9	MIR	NA	MK			-											
Provided at	SIIC							3 Nos	Divided	2010	MR	1_	1		Provided in basement			M	MIR	MK		Provided in basement	Provided	Provided				Provided			
								7	+	\dashv	Drovided	Provided		:	/ided II		Provided	7	Provided	Provided		Provid	Prov	Prov	Y.	NA		Pro.	N A	<u> </u>	
r N/7		2	١.		D.					I Kallıp	Δ	+			Pro	NA	Pro	-	Pro	Pro				ing							
As per N/7		Provided	Daniidad	LIOVIG	Provided	to of ovite	IS OF CARE			04 Nos. +	4	11.5 III	1.2 JIII C. I		Required	NA	03 Nos.		1.5m	01mtr		Required	Required	2 Hrs. rating	NA	NAN AN		Required	NA	:	
5 E	. U/R 33	0 mtr		o mtr	06 mtr		Number, width, Type & Arrangements of exits		1						_1	•											tem		1		
Minimum standards on fire	prevention and fire safety U/R 33	guit	110		of	road	1, Type & /	Number of staircases	floors	ents	Width of staircases	floors	ents	Protection of exits	Fire check door	Pressurization	No of continuous staircase	e	Width Of Corridor	ize	tion	Eire check door	Sealing of electrical shafts	Fire Rating of shaft door	Water Curtain	Fire Dampers	System	2	ents Georg	floors	
imum stan	ention and	Access of building	Gote width	Calc	Width of	Internal road	ber, width	. Numbe	Upper floors	Basements	. Width	Upper floors	Basements	. Protect	Fire ch	Pressur	l. No of	to terrace	e. Width		Compartmentation	Fire oh	Sealing	Fire Ra	Water	Fire Da	Lo monag	NC IIIaiia	Basements	Upper Hoors	
Mini	prev	Acce	• •	•	•		Num	B	•	•	۵	•	•	<u> </u>	_	•	70		<u>е</u>	f	30	5 '		_	_	•		OHIC	•		
S	ဍိ	-					5.														,	<u>ب</u>						4.			



Total numbers 22 nos. Provided MR	5.	Fire Extinguishers							
Types ABC&CO2 Provided MR	5.		7	22 nos		Provid	led		MR
1			-		~O ₂				MR
6. First-Aid Hose Reels 02 Nos. Provided MR e. Integration of hose reel hose in Nozzle diameter 05 mm Provided MR 7. Automatic fire detection and alarming system NA NA NA e. Location of Main Panel in Location of Repeater Panel in Alternate source of power in Hooters Location NA NA NA e. Alternate source of power in Hooters Location Required Provided MR 8. MOEFA Required Provided MR 9. Public Address System Required Provided MR 10. Upper Floor NA NA NA • Upper Floor Na NA NA NA • Namber of hydrants per floor Required Provided MR • Size of riser/					-				MR
Total numbers on each floor Length of hose reel hose Nozzle diameter			١.	or man		131 1110	i koo		
1	6.)2 Nos		Provid	ed		MR
Length of hose reel hose									MR
Nozzle diameter							THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.		MR
7. Automatic fire detection and alarming system				, , , , , ,		110116	,		
NA	7.		ming	g systen	1				NIA
Location of Main Panel Location of Repeater Panel Location of Repeater Panel Alternate source of power Hooter's Location Required Provided MR MA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA									
Location of Repeater Panel Alternate source of power Hooter's Location Required Provided MR MA									
• Alternate source of power • Hooters Location • Required Provided MR			el						
NA NA NA NA NA NA NA NA		-							
MOEFA					NA				
9. Public Address System Required Provided MR 0 Automatic Sprinkler System • Basements Required Provided MR • Upper Floor • Sprinkler above false ceiling NA NA NA 11 Internal Hydrants: • Size of riser/down-comer 100 mm Provided MR • Number of hydrants or Hose Box 100 mm Provided MR 12 Yard Hydrants • Total number of hydrants or Hose Box 4 Provided MR 13 Pumping Arrangements: • Ground Level or Discharge of main pump or Head or Head of main pump or Head or Head of MR NA NA NA NA NA NA NA NA NA NA NA NA NA NA 13 Pumping Arrangements: • Ground Level or Head of main pump or Head or Head of main pump or Head or Head of main pump or Head or Head of MR NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA	8				Require	d			
Nationatic Sprinkler System Required Provided MR					Require	d	Provided		IVIK
Basements Upper Floor NA NA NA NA NA							1 - 11		MR
Upper Floor Sprinkler above false ceiling NA	. 0					d			
Sprinkler above false ceiling									
11 Internal Hydrants: Size of riser/down-comer			ling		NA		NA		1471
Size of riser/down-comer Number of hydrants per floor Hose Box 12 Yard Hydrants Total number of hydrants Hose Box 13 Pumping Arrangements: Ground Level Discharge of main pump Number of main pump Number of main pump Number of main pump Standby Pump out put Standby Pump Head Standby Pump Head And Standby Pump Head And Standby Pump Head And Standby Pump Head And And And And And And And And And An	11								MP
Number of hydrants per floor Hose Box 12 Yard Hydrants Total number of hydrants Hose Box 13 Pumping Arrangements: Ground Level Discharge of main pump Number of main			r						
Na									
12 Yard Hydrants		-			Requir	ed	Provided		IVIX
Total number of hydrants Hose Box Provided MR	12						T- 11 1		MD
Hose Box Ground Level Discharge of main pump Head of main pump Number of main pumper Number o	-12		3						
Oround Level Discharge of main pump Head of main pump Number of main pump Sockey pump out put Standby Pump out put Standby Pump Head MA					4		Provided		IVIK
• Ground Level • Discharge of main pump > Head of main pump > Number of main pumps > Jockey pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto staring/Manual stopping > Pump House Access • Discharge of pump > Head of the pump > Head of the pump > Auto starting of pump	13								
Discharge of main pump Head of main pump Number of main pumps Number of main pump Number of main pumper Number of main pum		Ground Level					27.4	NIA	
 Head of main pump Number of main pumps Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head NA NA		 Discharge of main pump 							
Number of main pumps Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto staring/Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Head of the pump Auto starting of pump Power supply Auto starting of pump Required Provided MR Required Provided MR Terrace level NA NA NA NA NA NA NA NA NA N									
Jockey pump head NA									
Standby Pump out put Standby Pump Head NA		Jockey pump out put							
Standby Pump Head Standby Pump Head Auto staring/Manual stopping Pump House Access NA Terrace level Discharge of pump Head of the pump Head of the pump Provided MR Power supply Required NA NA NA 14 Captive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet NA		→ Jockey pump head	_		1				
Auto staring/Manual stopping Pump House Access NA Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Required Auto starting of pump Required Provided MR Power supply Required Provided MR Auto starting of pump Required Provided MR Auto starting of pump Required Provided MR Value Storage for fire fighting: Under ground tank capacity Provided NA		> Standby Pump out put							
stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Head of the pump Auto starting of pump Required Provided MR									
 ➤ Pump House Access ■ Terrace level ➤ Discharge of pump ➤ Head of the pump ➤ Power supply ➤ Auto starting of pump ■ Under ground tank capacity ➤ Draw off connection ➤ Fire service inlet ➤ Access to tank ■ Overhead Tank capacity NA NA<td></td><td></td><td> NA</td><td>4</td><td></td><td></td><td>NA</td><td></td><td>`</td>			NA	4			NA		`
 Discharge of pump Head of the pump Power supply Auto starting of pump Required Provided MR Provided MR Required Provided MR Required Provided MR Provided MR Auto starting of pump Required Provided MR Id NA NA			N/	<u> </u>			NA	NA	1
 → Head of the pump → Power supply → Auto starting of pump 14 Captive water Storage for fire fighting: ■ Under ground tank capacity → Draw off connection → Fire service inlet → Access to tank ♠ Overhead Tank capacity 14 MR Provided MR Provided MR NA NA		Terrace level					•		
➤ Power supply Required Provided MR 14 Captive water Storage for fire fighting: • Under ground tank capacity NA NA NA ➤ Draw off connection NA NA NA NA ➤ Fire service inlet NA NA NA NA ➤ Access to tank NA NA NA NA • Overhead Tank capacity 25000 ltrs Provided MR		Discharge of pump	90	0 lpm			Provided	MI	}
National Starting of pump Required Provided MR 14 Captive water Storage for fire fighting: • Under ground tank capacity NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA NA							Provided	MI	3
➤ Auto starting of pump Required Provided MR 14 Captive water Storage for fire fighting: • Under ground tank capacity NA NA NA • Draw off connection NA NA NA NA • Fire service inlet NA NA NA • Access to tank NA NA NA • Overhead Tank capacity 25000 ltrs Provided MR							Provided	MI	3
 Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity NA Provided MR 			Re	quired	,		Provided	MI	}
 Draw off connection Fire service inlet Access to tank Overhead Tank capacity NA NA NA NA NA NA NA NA NA NA Provided MR 	14					T	NIA	N T 4	
 Fire service inlet NA Provided MR 			ity		*.				
 Access to tank Overhead Tank capacity NA NA NA Provided MR 									
Overhead Tank capacity 25000 ltrs Provided MR									
			20		1.				
I EXIL Signage Required Provided MR	1.5								
	13	Exit Signage		Requi	red	Provid	ed	MR	



10/	10
14/	10
/	_

				-	_				
Provision of Lifts					NI	A		NA	
Pressurization o	f Lift Shaft				N		MP	1421	
Pressurization o	f lift lobby								
> Communication	Communication in lift Car			unea					
Fireman's Grou	Fireman's Grounding Swit								
			Requ	ired					
			Requ	ired		DG set	MK		
			•						
			NA		N.	A			
					N	A	NA		
			INA						
		274.		NΙΛ				NA	
			. 1		.:.	ed.		MR	
								MR	
							MR		
Battery backup			uired Provid						
					vid	MR MR			
Special Fire Protection	Systems	Req	uired	AB	С,	Fire extinguisher	provided		
for Protection of spec	ial Risks,			nea	r el	ectric panel			
if any;									
	 Pressurization o Pressurization o Communication Fireman's Grou Lift Signage Standby power supply Refuge Area Total area Location Fire control room Potector system Flow Switch Pa PA System Pan Battery backup Building Floor Special Fire Protection for Protection of special 	 Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Swith Lift Signage Standby power supply Refuge Area Total area Location Fire control room Potector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans Special Fire Protection Systems for Protection of special Risks, 	 ➢ Pressurization of Lift Shaft ➢ Pressurization of lift lobby ➢ Communication in lift Car ➢ Fireman's Grounding Switch ➢ Lift Signage Standby power supply Refuge Area ➢ Total area ➢ Location Fire control room ➢ Detector system panel ➢ Flow Switch Panel ➢ PA System Panel ➢ Battery backup ➢ Building Floor Plans Special Fire Protection Systems for Protection of special Risks, 	 ➢ Pressurization of Lift Shaft ➢ Pressurization of lift lobby ➢ Communication in lift Car ➢ Fireman's Grounding Switch ➢ Lift Signage ─ Standby power supply ─ Required ☐ Required ☐ Required ☐ Required ☐ Required ☐ NA ☐ NA ☐ NA ☐ NA ☐ NA ☐ Required ☐ R	 ➢ Pressurization of Lift Shaft ➢ Pressurization of lift lobby ➢ Communication in lift Car ➢ Fireman's Grounding Switch ➢ Lift Signage ─ Standby power supply ─ Required ─ NA ─ NA ─ Fire control room ➢ Detector system panel ➢ Flow Switch Panel ➢ PA System Panel ➢ Battery backup ➢ Building Floor Plans ─ Special Fire Protection Systems for Protection of special Risks, 	 ➢ Pressurization of Lift Shaft ➢ Pressurization of lift lobby ➢ Communication in lift Car ➢ Fireman's Grounding Switch ➢ Lift Signage ─ Standby power supply ─ Required ─ NA ─ Required ─ Provid ─ Required ─ Required ─ Required ─ Provid ─ Required ─ Required ─ Provid ─ Required ─ Provid ─ Required ─ Pro	 ➢ Pressurization of Lift Shaft ➢ Pressurization of lift lobby ➢ Communication in lift Car ➢ Fireman's Grounding Switch ➢ Lift Signage ─ Standby power supply ─ Required ─ Required ─ Required ─ Provided ─ Required ─ Provided ─ Required ─ Provided ─ Required ─ DG set ─ NA ─ Provided ─ Required ─ Provided ─ Provided ─ Required <li< td=""><td> ▶ Pressurization of Lift Shaft ▶ Pressurization of lift lobby ▶ Communication in lift Car ▶ Fireman's Grounding Switch ▶ Lift Signage ▶ Lift Signage Standby power supply Required Required Provided MR NA <</td></li<>	 ▶ Pressurization of Lift Shaft ▶ Pressurization of lift lobby ▶ Communication in lift Car ▶ Fireman's Grounding Switch ▶ Lift Signage ▶ Lift Signage Standby power supply Required Required Provided MR NA <	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter F6/DFS/MS/2017/South/172 Dated 08/02/2017 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name Udai Vir Singh

Designation ADO/DWK