



FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

**NEW DELHI** 

No.F6/DFS/MS/SZ2022/ 7 7 7

Dated: 22/07/2022

## FIRE SAFETY CERTIFICATE

Certified that building of Govt. Sarvodaya Kanya Vidyalaya, (New Blocks) Located at No-01 Palam Enclave New Delhi.110045.(SKV No. 1 School ID-1821018),& (2<sup>nd</sup> shift SBV No. 2 School ID -1821001) having 02 blocks comprised of G+ 03 Upper Floors owned/ occupied By Govt. Sarvodaya Kanya Vidyalaya have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned of this department on 11/07/2022 in the presence of Mr. Punit Dutta and found that the said building is fit for occupancy class "Educational" Group B Sub Division B – 1 with effect from  $\frac{22}{12}$  for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .2.2./.2./.2.... at New Delhi.

Delhi Fire Service.

Note:- The FSC is valid for two new blocks comprised of Ground plus 03 Upper Floors only.

Copy to:

1. The Primcipal Govt. Sarvodaya Kanya Vidyalaya, Located at No-01 Palam Enclave New Delhi.110045. (SKV No. 1 School ID-1821018),& 2<sup>nd</sup> shift (SBV No. 2 School ID – 1821001)

2. Directorate of Education Old Secretariat Delhi – 110054

Following fire safety directives must be adhered to:-

- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

The trained staff should be available round the clock.

- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5 The certificate may not be treated in any case for the regularization of the unauthorized construction.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.

Basement shall be used strictly as per building bye laws.

8 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

## 1119

## INSPECTION REPORT

 Name & address of the building: Govt. Sarvodaya Kanya Vidyalaya, Located at No-01 Palam Enclave New Delhi.110045. (SKV No. 1 School ID-1821018), & 2<sup>nd</sup> shift SBV No. 2 (School ID-1821001)

2. Type of Occupancy : Educational Two Blocks ( Ground+ 3 Upper Floors)

3. Type of Case

: New

4. Details of previous NOC

: Nil

5. Fire Safety directives Letter No.: NBC

6. Date of inspection

: 11/07/2022

7. Name of the Inspecting Officer: Udai vir singh, ADO (DWK)

8. Name and designation of Officer

from the building side

: Mr. Punit Dutta

9. Year of Construction

: 2020-21

10. Applicant's letter No. :54(SPS School)/PWD Edu.Sub-Divn M1-1(N)2021-

22/ Dated-24/06/2022

S	Minimum standards on fire	. 33	NBC/UBI	3L	Provided at site		Rema MR/N		
No.	prevention and fire safety U/I Access of building	X 33						MR	
	Road width    Gate width	06mtr					MR		
	Width of internal	NA	•		NA			NA	
2.	road Number, width, Type & Arra	ngeme	nts of exits						
	a. Number of staircases								
	Upper floors	2		2 F	Provided			MR	
	Basements	NA		NA	A			NA	
	b. Width of staircases				N. 4 - 2-175 am			MR	
	<ul> <li>Upper floors</li> </ul>	1.5m			BL-A=2x175cm BL-B=2x175cm				
	<ul> <li>Basements</li> </ul>	NA		ì	NA			NA	
	c. Protection of exits					1			
	<ul> <li>Fire check door</li> </ul>	NA			NA NA NA				
	<ul> <li>Pressurization</li> </ul>	NA			NA NA Provided MR				
	d. No of continuous staircase to terrace	Required			Trovides				
	e. Width Of Corridor	150cı	m		160 cm	N	ИR		
	f. Door Size	120cı	<b>m</b> , 1	Prov	ided		M	R	
3.	Compartmentation		214	$\dashv$	NA		N	٨	
	Fire check door								
	<ul> <li>Sealing of electrical shafts</li> </ul>		NA		NA NA NA		N	NA	
	<ul> <li>Fire Rating of shaft de</li> </ul>	oor	NA					NA	
	<ul> <li>Water Curtain</li> </ul>		NA	_			_	NA	
	<ul> <li>Fire Dampers</li> </ul>		NA		NA		N	<u>A</u>	



nanagements		,	
la com anto	NIA	NIA	
			NA
	Required	Natural ventilation provided	MR
	26	Did-d	1.75
			MR
			MR
	151 markeu	Provided	MR
			1.00
ach floor			MR
ose ·			MR
		Provided	MR
ic fire detection and	alarming system		
ype of detectors	NA	NA	NA
	NA	NA	NA
	NA .	NA	NA
	NA	NA	NA
-			
•	NA	NA	NA
_			
	NA	NA	NA
			NA
adress System		17/1	
	NIA	NA	NA
	1471		NA
Jpper Floor	14/1		
	NA	NA ·	NA
		37.4	NA
Size of riser/down-	NA	NA	14/4
		214	NA
Number of hydrants	NA .	NA	11/1
			NA
	NA	NA NA	INA
			NIA
drants	NA	NA	NA
Total number of	11/17		
ydrants	NA	NA	NA
lose Box	INA .		
,			
¥ .			
		1/2	
	i .		
		1	1
	Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of loower Hooters' Location Address System	Basements Upper floors inguishers Cotal numbers Sypes S marking d Hose Reels Cotal numbers on each floor Length of hose reel lose Nozzle diameter Sire detection and alarming system Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of sower Hooters' Location Anddress System Stic Sprinkler System Basements Upper Floor Sprinkler above False ceiling Hydrants: Size of riser/down- comer Number of hydrants ber floor Hose Box Varants Fotal number of nydrants	Basements Joper floors Cotal numbers Cotal numbers Cotal numbers Smarking Gotal numbers on Each floor Length of hose reel Loose Loos

							M/2			
3	Pumping Arran	gements:		,						
7	<ul> <li>Ground</li> </ul>									
	<ul> <li>Discharge of main pump</li> </ul>			NA NA				NA		
	➤ Head of main pump					NA		NA		
	Number			NA NA NA		NA		NA		
	Jockey					NA		NA		
	> Jockey					NA		NA		
	> Standby Pump o		ut			NA		NA		
	<ul><li>Standby Pump Head</li><li>Auto Staring/Manual</li></ul>				NA NA			NA NA		
	stopping			1 2		NA		147		
	<ul><li>Pump House Access</li><li>Terrace level</li></ul>				NA			NA		
	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power supply</li> </ul>			450	Inm eac	h	Provided	MR		
				450 lpm each block		11	Tiovided	MR MR		
					40Mtr Required		Provided			
.							Provided			
	> Auto starting of pump						Provided	MR		
4	Captive water Storage for fire figh							IVIIX		
	Underground tank     NA					NA		NA		
		capacity								
	> Draw off NA					NA		NA		
	connec									
	> Fire se	rvice inlet	NA			NA		NA		
	· > Access	to tank	NA			NA		NA		
	Overhe	Overhead Tank		000Lt	rs	Pro	vided	MR		
	capacity									
15	Exit Signage		Rec	quired		Pro	vided	MR		
16	Provision of Lifts									
	Pressurization of Lift Shaft				NA	NA		NA		
					NA	NA	70	NA		
٠		unication in			NA	NA		NA		
		an's Groundir	ig Swit	ch	NA	NA		NA		
	> Lift Si	<ul><li>Lift Signage</li></ul>			NA	NA		NA		
17	Standby power	Standby power supply			NA	NA		NA		
18	Refuge Area									
					NIA	NT A		27.		
	<ul><li>Total area</li><li>Location</li></ul>				NA.	NA NA		NA		
19	Fire control room				NA	NA		NA		
19	The condition									
	> Detector system panel				NA	NA		NA		
	Flow Switch Panel				NA	NA		NA		
	<ul> <li>PA System Panel</li> <li>Battery backup</li> <li>Building Floor Plans</li> </ul>				NA	NA		NA		
					NA	NA		NA		
					NA	NA		NA		
	1 3		7.							
					1					

20 Special Fire D.			
20 Special Fire Protection Systems for Protection of special Risks, if any:	NA	NA	NA
The fire protection systems provide functional at the time of inspection.	ded in the	building were t	est checked and found

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under Rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name Uday Vir Designation