Darlan- 17 0

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2022/ 786

Dated: 26/7 /2022

FIRE SAFETY CERTIFICATE

Certified that the Guru Harkrishan Public School (Code-20133531) Located at G-8, Nihal Vihar, Chander Vihar, New Delhi-110041, comprised of Basement + Ground + 03 Upper Floors only owned/occupied by Guru Harkrishan Public School was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/School/2019/1428 Dated 12.07.2019. The said premise was re-inspected by the officer concerned of this department on 06.07.2022 in the presence of Ms. Ranjeet Kaur (Principal) and found that the premises / building have deemed complied with the fire prevention and fire safety requirements in accordance D.O.E., GNCT of Delhi, Circular no. 3298-3398 dated 01.03.2011/NBC (Part-IV) and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from $\frac{26/7/22}{}$ for a period of three years, in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 26 7 22 at New Delhi by.

(Dharampal Bhardwaj) Dy. Chief Fire Officer

(West Zone)

Copy to: -

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054.

2. The Principal, Guru Harkrishan Public School (Code-20133531). G-8, Nihal Vihar, Chander Vihar, New Delhi-110041.

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its
- 9. The basement shall be used as per BBL.

INSPECTION REPORT Y-2

1. Name & address of the building : Guru Harkrishan Public School (Code-

201335531), G-8, Nihal Vihar, Chander Vihar,

New Delhi-110041

2. Type of Occupancy Educational (Basement+Ground+03 Upper floors)

3. Type of Case Renewal

4. Details of previous NOC : F6/DFS/MS/School/2019/1428 dated 12.07.2019

5. Fire Safety directives Letter No. : D.O.E. Cr. No. 3298-3398 dated 01.03.2011

6. Date of inspection : 06.07.2022

7. Name of the Inspecting Officer : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer from the building side : Ms. Ranjeet Kaur (Principal)

9. Year of Construction : 2008

10. Applicant's letter no. email dated 09.06.2022

Ю	Minimum standards on fire prevention and fire safety U/R	BBL/ Requirement as per FSC dated	s/ Provided at site	Remarks MR/NMR		
T	Access of building					
	 Road width 	Accessible	09 m	MR		
ı	 Gate width 	Accessible	4.5 m	MR		
	 Width of internal road 	NA	NA	NA		
	Number, width. Type & Arrangements of exits					
	a. Number of staircases					
	 Upper floors 	02	03	MR		
	 Basements 	02	03	MR		
	b. Width of staircases					
	 Upper floors 	1.5 m	1.54 m, 1.28m & 1.35m	MR		
	• Basements	1.5 m	1.54 m, 1.28m & 1.35m	MR		
	c. Protection of exits					
	Fire check doorPressurization	Required	Provided	MR		
		NA	NA	NA		
	d. No of continuous staircase to terrace	02	Provided	MR		
ı	e. Width Of Corridor	1.5 m	Provided	MR		
	f. Door Size	1 m	Provided	MR		
	Compartmentation					
-	Fire check door	NA	NA	NA		
	 Sealing of electrical shafts 	NA	NA	NA		
	Fire Rating of shaft door	NA	NA	NA		
	Water Curtain Fire Dampers	NA	NA	NA		
		NA	NA	NA		
	Smoke managements System					
	Basements	Required	Provided	MR		
		NA	NA	NA		
-	Upper floors					
	Fire Extinguishers	16 nos. ABC	Provided	MR		
	 Total numbers 	ABC & CO2	Provided	MR		
	 Types 	ISI marked	Provided	MR		
	 IS marking 	1.71 11141110				
	First - Aid Hose Reels • Total numbers on each	01	Provided	MR		
	floor	20	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	Norzle diameter	5 mm	THOUSE			

Autor	matic fire detection and alarming sys		11-12	
	Type of detectors			
	l continue Chi	NA	NA	NA
	Carron of Main Panel	NA	NA	NA
•	repeater Panel	NA	NA	NA
•	Alternate source of power		NA	
•	 Hooters' Location 			NA
MO	EFA		NA	NA
		NA	Provided	NA
Ave	lic Address System	NA	Provided	NA
~ (1)	iomatic Sprinkler System			100
	 Basements 	Required	Provided	MD
	 Upper Floor 	NA	NA	MR
	 Sprinkler above false ceiling 	NA		NA
lm	ernal Hydrants	1474	NA	NA
	 Size of riser/down-comer 			
	Number Ch	NA	100 mm	NA
	Number of hydrants per	NA	01	NA
	floor			
	 Hose Box 	NA	01	NA
Y:	ard Hydrants		01	17/1
	 Lotal number of hydrants 	NA	NIA	
	Hose Box		NA	NA
P	umping Arrangements	NA	NA	NA
	Ground Level			
	 Discharge of main pump 	NA	NA	NA
	 Head of main pump 	NA	NA	NA
	 Number of main pumps 	NA	NA	NA
	 Jockey pump out put 	NA	NA	
	Jockey pump head	NA		NA
	 Standby Pump out put 	NA	NA	NA
	Standby Pump Head		NA	NA
	Auto Staring/Manual	NA	NA	NA
	stopping	NA	NA	NA
	➤ Pump House Access			
	Terrace level	NA	NA	NA
	Discharge of pump	900 lpm & 180	lpm Provided	MR
	Head of the pump	40 m	Provided	MR
	Power supply	Required	Provided	MR
	 Auto starting of pump 	Required	Provided	MR
14	Captive water Storage for fire fighting			
	 Under ground tank capacity 	NA	NA	NA
	Draw off connection	NA	NA	NA NA
	Fire service inlet	NA		
	Access to tank		NA	NA
		NA V5 (200 le	NA	NA
	Overhead Tank capacity	15,000 ltrs.	Provided	MR
1.5	Exit Signage	Required	Provided	MR
1.6	Provision of Lifts			
	 Pressurization of Lift Shaft 	NA	NA	NA
	 Pressurization of lift lobby 	NA	NA	NA
	 Communication in lift Car 	NA	NA	NA
	 Fireman's Grounding 	NA	NA	NA
	Switch			
	 Lift Signage 	NA	NA	NA
			13/3	1.00
	Standby power supply	NA	NA	NA
17.				
	Retuge Atea	NA	NA	NA
17.		1 7 7 8	NA	NA
	➤ Total area	N.A	1 7 7 %	
18	Location	NA		
	lotal area location lire control room			
18	Location Lire control room Detector system panel	NA	NA	NA
18	Location Lire control room Detector system panel Llow Switch Panel	NA NA	NA	NA
18	Location Lire control room Detector system panel Llow Switch Panel PA System Panel	NA		NA NA
18	Location Lire control room Detector system panel Llow Switch Panel	NA NA	NA	NA
18	Location Lire control room Detector system panel Llow Switch Panel PA System Panel	NA NA NA	NA NA	NA NA
18	- Total area - Location - Detector system panel - How Switch Panel - PA System Panel - Battery backup - Building Hoor Plans	NA NA NA NA	NA NA NA	NA NA NA

11.23

Fire protection systems provided in the building were checked and found functional at the time of inspection

In view of the deemed compliance of the minimum standards on fire prevention and fire safety requirements as per D.O.E. Cr. No. 3298-3398 dated 01.03.2011, renewal of Fire Safety Certificate issued vide letter no. F6/DFS/MS/School/2019/1428 dated 12.07.2019 is recommended.

Accordingly DFA is prepared & put up for approval please

ADO (JWP)

F.7. letter is put-up for vigorature 101.