

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

No.F.6/DFS/MS/EH/2022/SZ/ 2- []

FIRE SAFETY CERTIFICATE

Dated: 27/7/22

Certified that the M/s Bamisaal The Food Court running at lower ground floor in a building comprised of lower ground & upper ground floor located at G-6, Janak Palace, District Center, Janakpuri, New Delhi-110058, owned/occupied by M/s JMD Hotel Pvt. Ltd have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules 2010 and verified by the officers concerned of this department on 13/07/2022 in the presence of Sh. Sazy Malik (Manager) and found that the building is fit for occupancy class Group-D "Assembly Building" w.e.f. the date of issue of this certificate for a period of **three years** in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed below.

C-26,

Director Delhi Fire Service

Copy to:-

- The Manager, M/s Bamisaal The Food Court, G-6, Janak Palace, District Center, Janakpuri, New Delhi-110058.
- The Dy. Health Officer,
 S.D.M.C, Public Health Department, West Zone,
 Vishal Enclave, Rajouri Garden, New Delhi-110027

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

| Se | NIA |
|---|--|
| Name & address of the building Building comprised of Type of Occupancy Type of Case Details of Previous NOC Fire Safety directives letter No Date of inspection Name of Inspecting Officers Name and designation of officers From the building side Year of Construction Applicant's letter No. | Janakpuri, New Delhi-110058. : Lower ground & upper ground (Eating house at lower ground only) : Group D (Assembly Building) : New : N/A : N/A : 13\$/07/2022 : A D O R K Yaday |

| S. No. | Minimum Stand fire safety U/R 3 | ards on fire prevention and 3 | NBC/UBBL Requirement | Provided at site | Remarks | |
|-----------|--|----------------------------------|-------------------------|------------------------|------------------|--|
| 1. | Access to buildi | ng | Requirement | site | MR/NMR | |
| | Road wid Gate wid Width of | | 09 mtrs N/A N/A | Provided N/A N/A | MR N/A N/A | |
| 2. | Number, Width | , Type & Arrangement of Exi | ts | | | |
| | a. Number of sta | ircases | | | | |
| | • Upper F | loors | N/A | N/A | N/A | |
| | Basemer | nts | N/A | N/A | N/A N/A | |
| | | | | | | |
| | b. Width of stair | | N/A | N/A | N/A | |
| | • Upper F | | N/A | N/A | N/A | |
| | • Baseme c. Protection of | | | | | |
| | • Fire che | | N/A | N/A | N/A | |
| | Pressurization | | N/A | N/A | N/A | |
| | | nuous staircases to | | | | |
| | terrace | | N/A | N/A | N/A | |
| | e. Width of Co | rridor | N/A | N/A | N/A | |
| | f. Door Size | 1. | .5 M each | 2X1.5 M each | MR | |
| 3. | Compartmenta | tion | | | | |
| | • Fire chee | ck door | N/A | N/A | N/A | |
| | Sealing | of electrical shafts | N/A | N/A | N/A | |
| | | ng of shaft door | N/A | N/A | N/A | |
| | • Water C | | N/A | N/A | N/A | |
| | • Fire Dar | npers | N/A | N/A | N/A | |
| 4. | Smoke Manage | ement System | | | | |
| | • Basemen | nts | N/A | N/A | N/A | |
| | • Upper fl | oors F | Required | Natural Ventilation | MR | |
| 5. | Fire Extinguishers | | | | | |
| | Total nu | | 05 No.'s | Provided | MR | |
| | • Types | A | BC/CO ₂ | Provided | MR | |
| | IS mark | ing | I marked | ISI marked | MR | |

c

`_(

| Ν | [] | | | | |
|---|---|--|--|--|--|
| | 110 | | 4 | | |
| | 0 | Durvided | | | |
| | | | MR | | |
| | | | MR | | |
| | | Flovided | MR | | |
| | | NI/A | | | |
| | | | N/A | | |
| | | | N/A | | |
| | N/A | | N/A N/A | | |
| | N/A | | N/A | | |
| MOEFA | Required | Provided | MR | | |
| Public Address System | | | N/A | | |
| | IN/A | IN/A | N/A | | |
| Automatic Sprinkler System | | | | | |
| • Basement | N/A | N/A | N/A | | |
| Ground Floor & Upper floor | N/A | N/A | N/A | | |
| Sprinkler above false ceiling | N/A | N/A | N/A | | |
| Internal Hydrants | | I | | | |
| Size of riser/down-comer | 100 mm | Provided | MR | | |
| | 01 No. | | MR | | |
| • Hose Box | 01 No. | Provided | MR | | |
| Yard Hydrants | | | | | |
| Total number of hydrants | N/A | N/A | N/A | | |
| | | | N/A N/A | | |
| Pumping Arrangements | 1.011 | 1071 | | | |
| Ground Level | | | | | |
| | | | | | |
| | N/A | N/A | N/A | | |
| Number of main pumps | N/A | N/A | N/A | | |
| | N/A | N/A | N/A | | |
| Jockey pump head | N/A | N/A | N/A | | |
| Standby During and made | N/A | N/A | N/A | | |
| | N/A | N/A | N/A | | |
| • • | N/A | N/A | N/A | | |
| | N/A | N/A | N/A | | |
| | N/A | N/A | N/A | | |
| | | | | | |
| | 450 LPM | Provided | MR | | |
| | 40 mtrs | Provided | MR | | |
| | Required | Provided | MR | | |
| Auto Starting of pump | Required | Provided | MR | | |
| Captive Water Storage for fire fighting | | | | | |
| | NI/A | NI/A | X () | | |
| Draw-off connection | | | N/A | | |
| | | | N/A | | |
| Access to tank | | | N/A | | |
| Overhead Tank capacity | | | N/A | | |
| • • | | | MR | | |
| Exit Signage. | Required | Provided | MR | | |
| | First-Aid Hose Reels • Total numbers on each floor • Length of hose reel hose • Nozzle diameter Automatic fire detection and alarming system • Location of Main Panel • Location of Repeater Panel • Alternate source of power • Hooters' Location MOEFA Public Address System Automatic Sprinkler System • Basement • Ground Floor & Upper floor • Sprinkler above false ceiling Internal Hydrants • Size of riser/down-comer • Number of hydrants • Hose Box Yard Hydrants • Total number of hydrants • Hose Box Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump | • Total numbers on each floor One • Length of hose recl hose 30 m • Nozzle diameter 30 m Automatic fire detection and alarming system • Type of detectors N/A • Location of Main Panel N/A • Location of Repeater Panel N/A • Alternate source of power N/A • Hooters' Location N/A MOEFA Required Public Address System N/A Automatic Sprinkler System N/A • Basement N/A • Ground Floor & Upper floor N/A • Size of riser/down-comer 100 mm • Number of hydrants 01 No. • Hose Box 01 No. • Total number of hydrants N/A • Total number of hydrants N/A • Total number of hydrants N/A • Discharge of main Pump N/A > Head of Main pump N/A > Head of Main pump N/A > Auto Starting/Manual Stopping N/A > Pump House Access N/A • Discharge of pump 450 LPM > Auto Starting of pum | First-Aid Hose Reels One Provided Length of hose reel hose 30 m Provided Automatic fire detection and alarming system N/A N/A Type of detectors Location of Main Panel N/A Public Address System N/A N/A Automatic Sprinkler System N/A N/A Basement N/A N/A Ground Floor & Upper floor N/A N/A N/A Internal Hydrants 01 No. Size of riser/down-comer 100 mm Provided | | |

Rs.

NI

| | M [*] Provision of Lifts. | | (No Lift) | | | |
|----------------------------------|--|----------|-----------|-----|--|--|
| | Pressurization of Lift Shaft | N/A | N/A | N/A | | |
| | • Pressurization of Lift lobby | N/A | N/A | N/A | | |
| | • Communication In lift Car | N/A | N/A | N/A | | |
| | Fireman's Grounding Switch Lift Signage | N/A | N/A | N/A | | |
| Lift Signage | N/A | N/A | N/A | | | |
| 7. | Standby power supply | Required | Provided | MR | | |
| 8. | Refuge Area. | | | | | |
| | > Total Area | N/A | N/A | N/A | | |
| | Location | N/A | N/A | N/A | | |
| 19. | Fire Control Room | | | | | |
| | Detector System Panel | N/A | N/A | N/A | | |
| | Flow Switch Panel | N/A | N/A | N/A | | |
| | • PA System Panel | N/A | N/A | N/A | | |
| | Battery backup | N/A | N/A | N/A | | |
| | Building Floor Plans | N/A | N/A | N/A | | |
| 20. | Special Fire Protection System for Protection of special Risks, if any: | N/A | N/A | N/A | | |

The fire protection systems provided in the building were tested, checked and found not functional at the time of inspection. The shortcomings issued vide letter no. F6/DFS/MS/EH/2021/SZ/428 dated 01/10/2021 has been complied.

Keeping in view of the above compliance of the minimum standards of fire prevention and fire safety measures under Rule 35 of the Delhi Fire Service Rules 2010 it is recommended to grant Fire Safety Certificate.

18/712022 Signature of Inspecting Officer Name:-R.K.Yadav Designation:-Asstt. Divisional Officer

D.O.(South West)

Ig/o/n on/cease

Director

25/2/22

ADD (JAKBUN)