

## -----GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110001** Dated: 29,07 /2022

No. F.6/DFS/MS/School/2022/SZ/ S2/

## FIRE SAFETY CERTIFICATE

Certified that Mata Gujri Public School, at Gurdwara Singh Sabha (opp. C Block), Greater Kailash -I, New Delhi-110048 comprised of 03 Blocks, Block 01- G+3, Block 02- G+1, Block 03-B+G+2 upper floors owned/occupied by Mata Gujri Public School, was issued Fire Safety Certificate by this department vide letter no. F6/MS/DFS/School/2019/SZ/1445 Dated 16-07-2019. The premises was re-inspected by officer concerned by this department on 14/07/2022 in the presence of Mrs. Daljeet Kaur Bhandari of the school and observed that the premises have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education circular no 262-362 dated 17/01/2005 and that the building is fit for occupancy class "Educational" Group-B (School) as above with effect from  $\frac{29}{7}/\frac{7}{2022}$  for period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of conditions mentioned below.

Issued  $\frac{29}{7}$  at New Delhi by

## (SUNIL CHAWDHARY) **DY. CHIEF FIRE OFFICER (SZ)** 91A

Copy to: -

- 1. The Principal, Mata Gujri Public School, Gurdwara Singh Sabha (opp. C Block, Greater Kailash -I, New Delhi-110048
- The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi 110054 2.

## Conditions for the validity of Fire Safety Certificate: -

- All the means of escape/entry/exit shall be kept free from any obstruction. 1.
- All the fire safety arrangement provided therein shall be maintained in good working condition at 2. all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- All the staff members must know the correct method of operation of fire fighting system. 3.
- The basement shall be used as per the provisions of BBL/NBC Part IV. 4.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first 5. schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-6. 2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL- 2016), if any.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' 7. [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

**INSPECTION REPORT** Name & Address of the Building 1 Mata Guiri Public School, Gurdwara Singh Sabha (opp. C Block, Greater Kailash -I, New Delhi-110048 2 Type of Occupancy Educational, Group-B (School) 3 Building Comprised of Three Blocks :-1<sup>st</sup> Block- Ground + Three Upper floor, 2<sup>nd</sup> Block- Ground plus First floor, 3<sup>rd</sup> Block-Basement, Ground + 02 upper floors Type of Case 4 Renewal Details of Previous NOC 5 F6/MS/DFS/School/2019/SZ/1445 Dated 16-07-2019 Fire Safety Directives Letter No 6 DOE circular no 262 to 362 dated 17/01/2005 Date of Inspection 7 14-07-2022 8 Name of the Inspecting Officers Sh. Rajesh Kumar, ADO (BCP) Q Name & Designation of Officers Mrs. Daljeet Kaur Bhandari from the building side 10 Year of construction 2007 11 Applicant letter No. MGPS dated 05-07-2022 S. No. Minimum standards on Fire Prevention Old NOC Remarks **Provided at Site** and Fire Safety U/R 33 requirements MR/NMR 1. Access to Building. Road width Accessible 06 mtr MR Gate width NA 4.5 mtr NA Width of internal road NA NA NA 2. Number, width, type & arrangement of exits. a) Number of Staircase Blk-1- Ground to terrace Upper floors. 02 No, ground to 2nd -01 02 No's ground to 3rd -01 no MR Blk-2-02 No's Basement floor. Blk -3-02 No's 02 No's 02 no's MR b) Width of Staircase Upper floors 1.50m/0.75m Blk-1- Ground to terrace-MR 1.30 & 1.1.m (old Case) ground to 2nd -3.40m. ground to 3rd -1.39m Blk-2-1.40m each Blk -3-1.50 m each Basement floor MR 1.50m/0.75m 1.45m & 1.20 m (old case) c) Protection of exits Fire check door -NA--NA--NA-Pressurization -NA--NA--NAd) No. of continuous staircase to terrace Blk- 02 No Blk- 02 No MR Blk- 01 No Blk- 01 No MR Blk-01 No Blk- 01 No MR e) Width of corridor 1.50 m Provided MR Door size f) 1m Provided 3. MR Compartmentation. Fire check door. -NA--NA--NA-Sealing of electrical shafts. -NA--NA--NA-Fire rating of shaft door. -NA-Water curtain -NA--NA-Fire dampers. -NA--NA--NA--NA--NA-4. Smoke Management system. -NA-Basement 30 ACPH Exhaust fan provided MR Upper floors 12 ACPH -NA-5. Fire Extinguishers. -NA-Total numbers Required 36 Nos MR Types ABC / CO2 ABC & CO2 MR **ISI** Marking ISI marked Provided 6. First Aid Hose Reels. MR

ोें। न महोत्खव

	NHS	
Total numbers on each floor	01 No's at each	Provided
<ul> <li>Length of hose-reel hose</li> </ul>	30m	Provided
<ul> <li>Nozzle Diameter</li> </ul>	Smm	Provided
Automatic fire detection & alarming system.	the second se	11041060
Type of detectors     Location of Main Panel	-NA-	-NA-

7.

22.0				
11-	-	-	Pare-	
1) a i	51			
212	11		e R	

MR

MR

MR

-NA-

١.	
1	func
- \	

20.

Sa F

	<ul> <li>Location of Main Panel</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Location of Repeater Panel</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Alternate source of power</li> </ul>	-NA-	-NA- -NA-	-NA-
	<ul> <li>Hooter's location</li> </ul>	-NA-		-NA-
8.	MOEFA	-NA-	-NA-	-NA-
9. 1	Public Address System	Required	-NA-	-NA-
	Automatic Sprinkler System	Required	Provided	MR
	<ul> <li>Basement</li> </ul>	Required	D	
	<ul> <li>Upper floors</li> </ul>	-NA-	Provided	MR
	<ul> <li>Sprinkler above false ceiling</li> </ul>	-NA-	-NA-	-NA-
11. 1	Internal Hydrants.	-1974-	-NA-	-NA-
	<ul> <li>Size of Riser/Down-comer</li> </ul>	-NA-	<b>N</b> T 1	
	Number of Hydrant per floor	-NA-	-NA-	-NA-
	<ul> <li>Hose box.</li> </ul>	-NA-	-NA-	-NA-
12.	Yard Hydrants.	-NA-	-NA-	-NA-
	• Total number of hydrants.	NIA		
	<ul> <li>Hose box.</li> </ul>	-NA-	-NA-	-NA-
13.	Pumping arrangements.	-NA-	-NA-	-NA-
	Ground Level			
-	<ul> <li>Discharge of main pump.</li> </ul>	NT -		
	<ul> <li>Head of main pump.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Number of main pumps.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Jockey Pump output.</li> </ul>	-NA-	-NA-	-NA-
	> Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA- -NA-	-NA-	-NA-
	Auto Starting/Manual Stopping.	-NA- -NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
-	Terrace Level	-NA-	-NA-	-NA-
	<ul> <li>Discharge of pump.</li> </ul>	2 x 450 LPM	2 x 450 LPM	
	<ul> <li>Head of pump.</li> </ul>	40m each	Provided	MR
	<ul><li>Power supply.</li></ul>	Required	Provided	MR
	> Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.	Required	TIOVIded	MR
	<ul> <li>Underground tank capacity.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Draw-off connection.</li> </ul>	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	<ul> <li>Overhead tank capacity.</li> </ul>	15,000 Ltrs	15,000 Ltrs	MR
15.	Exit Signage.	Required	Provided	MR
	Provision of Lifts.			
	<ul> <li>Pressurization of lift shaft.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Pressurization of lift lobby.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Communication in lift car.</li> </ul>	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
	<ul> <li>Lift signage.</li> </ul>	-NA-	-NA-	-NA-
	Standby Power Supply	-NA-	-NA-	-NA-
	Refuge Area			
	Total area	-NA-	-NA-	-NA-
	Location	-NA-	-NA-	-NA-
19.	Fire Control Room.			1
	Detector system panel.	-NA-	-NA-	-NA-
	<ul> <li>Flow switch panel.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>PA system panel.</li> </ul>	-NA-	-NA-	-NA-
		In the other works the second contraction of the second second second second second second second second second	the second s	NIA
	Battery backup.	-NA-	-NA-	-NA-

NILL FIRET ħ Special Fire Protection System for the Protection of special Risk, if any. 20. -NA-The fire protection systems provided in the premises were test checked at random and found functional at the time of inspection. Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under No. the rules, the FSC issued vide letter F6/MS/DFS/School/2019/SZ/1445 Dated 16-07-2019, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended. Accordingly DFA is put up for approval and signature please. Signature of the Inspecting Officer Name: Sh. Rajesh Kumar Design: ADO (BCP) Dy. CFO(SZ) approved, F.T. Letter ei Jone synature Pl 1 y cfg.