

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/Business/SZ/2022 \sqrt{56}

## Dated: <u>0/</u> / <u>08</u> /2022

## FIRE SAFETY CERTIFICATE

Delhi 110019 comprises of two blocks i.e. Block E (Basement, LGF + Loft, UGF + Loft, 1st Floor +Loft service floor, 2nd to 11 floors, service floor, 12th floor+ small Loft) & Block F (LGF+ Mazz, UGF+ Loft, 1st floor + Loft, 2nd Floor & 3rd Floor) was issued FSC by this department vide letter no. F.6/DFS/MS/Business/SZ/2019/1112 Dated 23/05/2019. The premise was re-inspected by the officers concerned of this department on 27/07/2022 in the presence of Sh. Jitender Singh (Manager Fire) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy Class E "Business" with effect from O/ 108/2022 for period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Rules 2010.

Issued on 0/08 2022 at New Delhi by

Copy to: -

- 1. Sh. Paramjeet Singh/ Director Engineering, International Trade Tower (Eros Group) situated at Nehru Place New Delhi 110019.
- 2. The Executive Engineer (Bldg) SDMC, Jal Vihar, Lajpat Nagar, New Delhi 110024.

## Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. This fire safety certificate may not be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 5. The owner/occupier shall submit a declaration every year in form 'K' provided in the First schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."
- 7. The use of basement shall be strictly in accordance with the provision contained in Building Bye Laws-1983.

	Cake Quilding	ON REPOR		da Towar (Erre ()			
/	Name & Address of the Building	International Trade Tower (Eros Group) Nehru Place New Delhi 110019					
	Type of Occupancy	Class- E Business Building Two Blocks: Block-E, (B + LGF + Loft, IGF+ Floor+ Loft, Service Floor, 2 <sup>nd</sup> to 11 <sup>th</sup> Floo					
	Type of Occupancy Building Comprised of	Floort L	KS: Bloc	K-L, (B + LGF + Loft,	IGF+ LOFT		
	Bullding	Floor 12	Floor, Ser				
		Mezzanine	LIGE	+Small Loft) & Bloc	ond a order		
		Renewal	Mezzanine, UGF + Loft, 1st Floor + Loft, 2nd & 3rd Flo				
	Type of Case		IC/Di.	/C7/2010/1112 Dec	1 22/05/20		
	1. at previous NOC	-		ness/SZ/2019/1112 Da			
	Fire Safety Directives Letter No		MS/FAC/DDA/85/362-63 dated 26/08/1985				
	a sef Inspection	27/07/2022					
	of the Inspecting Officers	ADO (BCP) & Dy.CFO(SZ)					
	Name & Designation of Officers	Sh. Jitend	Sh. Jitender (Manager Fire)				
	from the building side						
	Year of construction	1988					
		Email dat	- J 10 A	7 2022			
	Applicant letter No.	Email dat	ea 18.0	7.2022			
	Minimum standards on Fire Prevention	Requirements Provided at Site Remar			Remarks		
No.	and Fire Safety U/R 33	under rule 35/6			MR/NM		
	Access to Building.						
				1 =	1		
	a) Road width	9 mtr		Provided	MR		
	b) Gate width	6 mtr		Provided	MR		
	c) Width of internal road	6 mtr		Provided	MR		
	Number, width, type & arrangement of exit	S.					
	a) Number of Staircase						
			Blk-E	:- 2 Nos	MR		
	Limar floors	Required	Blk-F	- LGF to UGF: 2 No	S Old case		
	Upper floors. Basement floor.	1	& UG	F to Terrace: 1 No			
	Basement 1100r.	D		& 01 Ramp	MR		
		Required		•	Old case		
	b) Width of Staircase						
	c) Upper floors			1.3-2m, 1.3-1.4m			
		Required	1	LGF to UGF: 1.39-	MR		
		1		2.98-3.46m & UGF to	Old case		
	Basement floor			ce 1.4m-2.4m, 1.22, 1.19, 1.3,1.16, 1.18, MR			
		Doguirod		1.14, 1.12 mtr Old c			
	d) Protection of exits						
	,				7		
	Fire check door	Required		Provided	MR		
	Pressurization	Required		Provided	MR		
	e) No. of continuous staircase to	1 Nos in e	ach	Provided	MR		
	terrace	block					
	f) Width of corridor	Required		1.5 m	MR		
	g) Door size	Required		1 m (final exit)	MR		
	Compartmentation.	1 1			1		
	Fire check door.	Required		Provided	MR		
	Sealing of electrical shafts.	Required		Provided	MR		
	Fire rating of shaft door.	NA		NA	NA		
	Water curtain	NA		NA	NA		
	Fire dampers	Required		Provided	MR		
	Smoke Management system.						
	Basement	Required		Provided	MR		
	Upper floors	Required		Provided	MR		
	Fire Extinguishers.						
_		152 nos.		Provided	MR		
	Total numbers	ABC/W.co2/M.Foa					
	Total numbers		M.Foa				
	Types	m & CO <sub>2</sub>		Provided	MR		
	Types ISI Marking	ABC/W.co2/		Provided Provided	MR MR		
	Types ISI Marking First Aid Hose Reels.	m & CO <sub>2</sub> ISI marked					
	Types ISI Marking	m & CO <sub>2</sub> ISI marked		Provided	MR		
	Types ISI Marking First Aid Hose Reels.	ABC/W.co2/ m & CO2 ISI marked Blk E: 2 Nos Blk F: 2 Nos GF to Mezzani	ine & 1				
	Types ISI Marking First Aid Hose Reels.	ABC/W.co2/ m & CO <sub>2</sub> ISI marked Blk E: 2 Nos Blk F: 2 Nos GF to Mezzani No for above f	ine & 1	Provided Provided	MR MR		
	Types ISI Marking First Aid Hose Reels.	ABC/W.co2/ m & CO2 ISI marked Blk E: 2 Nos Blk F: 2 Nos GF to Mezzani	ine & 1	Provided	MR		

				1
,			Provided	MR
	ength of hose-reel hose lozzle Diameter	5mm	Provided	
1	Automatic fire detection & alarming system	)		MD
		Heat & Smoke	Heat & Smoke	MR MR
1	Type of detectors ocation of Main Panel	Ground floor	Ground floor	NA
	ocation of Repeater Panel	NA	NA	MR
1	Alternate source of power	Required	Provided	MR
	Aooter's location	Untire building	Provided	MR
	MOEFA	Required	Provided	
1.5	Public Address System	Required	Provided	MR
0	Automatic Sprinkler System			T van
	Basement	Required	Provided	MR
	Upper floors (except EE area)	Required	Provided	MR
	Sprinkler above false ceiling	Required	Provided	MR
1	Internal Hydrants			
	Size of Riser/Down-comer	150mm	150mm	MR
		Blk 1/- 2 Nos		
	Number of Hydrant per floor	Blk F 2 Nos OF to Mezzanine & 1 No for Provided		MR
		above floors		
	Hambay	Blk F. 2 Nos Blk F. 2 Nos	Described and	MR
	Hose box.	GF to Mezzanine & 1	No for Provided	IVIK
12	Yard Hydrants.	above floors		1
	Total number of hydrants.	07 nos.	Provided	MR
	Hose box.	07 nos.	Provided	MR
13	Pumping Arrangements.	O7 HOS.	Frovided	IVII
	Ground Level			
	Discharge of main pump.	2850 LPM	Duanidad	MD
	Head of main pump.	115m	Provided Provided	MR
	Number of main pumps.	2 nos.	Provided	MR MR
	Jockey Pump output.	2 x 180 LPM	Provided	MR
	Jockey Pump head.	115 mtr	Provided	MR
	Standby Pump output.	2850 LPM	Provided	MR
	Standby Pump head.	115m	Provided	MR
	Auto Starting/Manual Stopping.	Required	Provided	MR
	Pump house access.	Required	Provided	MR
	Terrace Level			
	Discharge of pump.	450 LPM	Provided	MR
	Head of pump. Power supply.	30 m	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14	Captive water storage for fire fighting.	Required	Provided	MR
	Underground tank capacity.	4,00,000 Ltrs	Provided	MR
	Draw-off connection. Fire Service Inlet.	Required	Provided	MR
	Access to tank.	Required	Provided	MR
	Overhead tank capacity.	Required	Provided	MR
15	Exit Signage.	30,000 Ltrs	Provided	MR
16	Provision of Lifts.	Required	Provided	MR
	Pressurization of lift shaft.			
	Pressurization of lift lobby.	Required	Provided	MR
	Communication in lift car.	Required	Provided	MR
	Fireman's switch.	Required	Provided	MR
	Lift signage.	Required	Provided	MR
17	Standby Power Supply	Required Required	Provided	MR
18	Refuge Area	required	Provided	MR
	Total area	NΛ	10-2	NA
	Location	NA	1.0.11	
19	Fire Control Room.	11/1	3 , 6 & 9" floor	NA
	Detector system panel.	Required	Provided	
	Flow switch panel.	Required	Provided	MR
	PA system panel.	Required	Provided	MR
	Battery backup.	Required	Provided	MR
			Jorded	MR



Battery backup.			Meholwiv
quiump flor	B		
The cold is the D	Required	Provided	MR
Special Fire Protection System for the Protection of special Risk, if any.	Required	Provided	MR
Fire protection system provides to	NA		
the time of the ti			

Fire protection system provided in the building were tested/ checked and found functional at the time of inspection.

The shortcomings issued by this department vide letter of even no.33 dated 22.07.2022 have been compiled by the management.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules Fire Safety Certificate issued by this department letter no. F.6/DFS/MS/Business/SZ/2019/1112 Dated 23/05/2019 is recommended for renewal under Rule 37 (3) of

Accordingly, DFA is put up for perusal and signature please.

Signature of the Inspecting Officer

Name: Sunil Chawdhary Designation: Dy. CFO (SZ)

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar, Designation: ADO (BCP)