## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

No.F.6/DFS/MS/Metro/2022/SZ/ 🤧 🤇

Dated: 12/08/202 7

## FIRE SAFETY CERTIFICATE

Certified that the Additional Staff Quarters Najafgarh Depot of line-3 of Delhi MRTS New Delhi-110043, comprised of Seven Blocks having ground plus six upper floors, owned/occupied by Delhi Metro Rail Corporation Ltd. was issued NOC by this department vide letter No. F6/DFS/MS/2007/3071 dated 16/10/2007. The building was re-inspected by the officer concerned of this department on 28/07/2022 in the presence of Sh. Pushpender Singh (Sr. Fire Inspector) and found that the buildings have deemed complied with the fire prevention and fire safety requirements in accordance with the Rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class (Residential Building) with effect from ...) 2/08/29 the date of issue of this certificate for a period of Five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed as below.

Issued on |2|08/9.99 at New Delhi.

DELŤII FIRE SERVICE

Copy to:-

Sh. Vivek Shrivastava (JGM/E&M), Delhi Metro Rail Corporation Ltd., Metro Bhawan, Fire Brigade Lane, Barakhamba Road, New Delhi-110001

## Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

N/12

S. No.

3.

4.

5.

6.

Nozzle diameter

1.

INSPECTION REPORT Additional Staff Quarters Najafgarh Depot of line-3 of Delhi MRTS, Name & address of the building: New Delhi-110043. 7 blocks having ground plus six upper floors Building comprised of 2. Type of Occupancy Residential 3. 4. Type of Case Renewal F6/DFS/MS/2007/3071 dated 16.10.2007 5. Details of Previous NOC F6/DFS/MS/CGHS/BP/2006/63 dated 08.01.2007 6. Fire Safety directives letter No 28/07/2022 Date of inspection A.D.O. R.K. Yadav Name of Inspecting Officer Name and designation of officers Sh. Pushkar Singh (Sr. Fire Inspector) From the building side 10. Year of Construction : 2007 : Nil dated 18/07/2022 11. Applicant's letter No. Remarks Requirements as Provided at Minimum Standards on fire prevention MR/NMR per FSC dt. site and fire safety U/R 33 16.10.2007 Access to building M/R Provided 09 m Road width M/R Provided 05 m M/R Gate width Provided 06 m Width of internal road Number, Width, Type & Arrangement of Exits a. Number of staircases M/R 02 no.'s in each 02 no.'s in each Upper Floors block block Basements N/A  $N/\Lambda$  $N/\Lambda$ b. Width of staircases M/R, being 1.40 m (02 no.s) in A blk, 1.50 m old case in A 1.50 m (02 no.'s) in B, C & Upper Floor blk & D blk & 1.55m (02 no.'s) in MR E, F & G blk N/A N/A  $N/\Lambda$ Basements c. Protection of exits N/A N/A Fire check door N/A N/A N/APressurization N/A d. No. of continuous staircases to MR One in A blk & Two in Required terrace B. C. D. E. F & G blk M/R, being old case 14.0 m in A blk & 1.50 m in A blk & MR 2 60 in others e. Width of Corridor M/R 1.0 m 1.0 m Door Size Compartmentation N/A N/A N/A Fire check door M/R Sealing of electrical shafts Provided Required Fire Rating of shaft door M/RRequired 02 hrs Provided Water Curtain N/A N/A N/A Fire Dampers N/A N/A  $N/\Lambda$ Smoke Management System N/A N/A N/A Basements M/R Natural Required Upper floors Ventilation Fire Extinguishers Two/floor Provided M/R Total numbers each block Provided M/R W/CO/ CO-type Types M/RProvided ISI marked 1S marking First-Aid Hose Reels Provided M/R One floor Total numbers on each floor M/RProvided 36 m Length of hose reel hose M/R Provided 5 mm

	Automatic fire detection and alarming     Type of detectors	N/A	N/A	N/A
	Location of Main Panel	N/A	N/A	N/A
	Location of Repeater Panel	N/A	N/A	N/A N/A
	<ul> <li>Alternate source of power</li> </ul>	N/A	N/A N/A	N/A N/A
	Hooters' Location	N/A	N/A	N/A
3.	MOEFA	Required	Provided	M/R
),	Public Address System	Required	Provided	M/R
10.	Automatic Sprinkler System			
	Basement	N/A	N/A	N/A
	Ground Floor	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
1.	Internal Hydrants	1377		
	Size of riser/down-comer	01 No. per floor	Provided	M/R
	<ul> <li>Number of hydrants per floor</li> </ul>	01 No. per floor	Provided	M/R
	Hose Box	01 No. per floor	Provided	M/R
2.	Yard Hydrants			
	Total number of hydrants	Twenty eight	Provided	M/R
	Hose Box	Twenty eight	Provided	M/R
3.	Pumping Arrangements	, ,		
	Ground Level			
	Discharge of main Pump	N/A	2250 LPM	N/A
	<ul><li>Head of Main pump</li><li>Number of main pumps</li></ul>	N/A	60 mtrs	N/A
	> Jockey Pump out put	N/A	One Provided	N/A
	Jockey pump head	N/A	225 LPM Provided	N/A
	Standby Pump out put	N/A	60 mtrs Provided	N/A
	<ul><li>Standby Pump Head</li><li>Auto Starting/Manual</li></ul>	N/A	2250 LPM Provided	N/A
	Stopping Stopping	N/A	60 mtrs Provided	N/A
		N/A	Not provided	N/A
	<ul> <li>Pump House Access</li> <li>Terrace level</li> <li>Discharge of pump</li> <li>Head of the pump</li> </ul>	N/A	Provided	N/A
		900 LPM	450 LPm & 900 LPM Provided	M/R
	> Power Supply	35 m	Provided	M/R
	➤ Auto Starting of pump	Required	Provided	M/R
		Required	Provided	M/R
14.	Captive Water Storage for fire fighting			
	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> </ul>	N/A	200000 ltrs Provided	N/A
	Fire service inlet	N/A	Provided	N/A
	Access to tank	Required	Provided	M/R
	<ul> <li>Overhead Tank capacity</li> </ul>	Required 25,000 ltrs on each	Provided	M/R
		block	Provided	M/R
15.	Exit Signage.	Required	Provided	M/R
16.	Provision of Lifts.			
	Pressurization of Lift Shaft	N/A	N/A	N/A
	<ul><li>Pressurization of Lift lobby</li><li>Communication In lift Car</li></ul>	N/A	N/A	N/A
	Fireman's Grounding Switch	Required	Provided	M/R
	Lift Signage	Required	Provided	M/R
		Required	Provided	
	Standby power supply	Required	Provided	M/R M/R
17.				

1

NILY

18.	Refuge Area.			
	➤ Total Area ➤ Location	N/A	N/A	N/A
		N/A	N/A	N/A
9.	Fire Control Room			
	<ul> <li>Detector System Panel</li> <li>Flow Switch Panel</li> <li>PA System Panel</li> <li>Battery backup</li> <li>Building Floor Plans</li> </ul>	N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
0.	Special Fire Protection System for Protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. The shortcoming issued vide letter no.F.6/DFS/MS/2022/SZ/1110 dated 18/05/2022 has been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the Rules the NOC issued vide letter number F6/DFS/MS/2007/3071 dated 16/10/2007 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of Inspecting Officer

Name:- RK. Yadav

Designation:- Asstt. Divisional Officer

DO (South West)

Dyelo (SL)

Myelo (SL)

M