GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/Hospital/NDZ/2022/ 3 8 8

Dated: 62/09/2022

FIRE SAFETY CERTIFICATE

Issued - 2 2 2 2 at New Delhi by.

DIRECTOR Delhi Fire Service

Copy to:-

1. The Medical Superintendent, Lok Nayak Hospital, New Delhi.

2. The Executive Engineer (E), Health Maint. Elect. Division (C), PWD, Lok Nayak Hospital, New Delhi.

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This certificate does not give guarantee that there will be no fire incident.

2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. Any flammable material shall strictly be prohibited.

NILY

INSPECTION REPORT

1. Name & address of the building : M.R.D. Block at L.N. Hospital, New Delhi.

2. Type of occupancy : Business Building

Basement + Ground + 06 Upper floors

3. Type of case:- : Renewal (12 point inspection)

4. Details of previous FSC : F6/DFS/MS/Hosp/NDZ/2018/466 dated

21.03.18

5. Fire safety directives No.6. Date of inspection:22/08/22

7. Name of the inspecting officer : Sh. Rajinder Atwal DO/CD,

Sh. Ravinder Singh ADO/CC

8. Name & designation of officer

from the building side

: Sh. Manish Pandey

9. Year of construction : 1960

10. Applicant's letter No : eeepwdhmedc@gmail.com dated

19.71pmant stetter 140		12.07.2022.				
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	06 mtr.	15 mtr.	MR		
	2) Gate width	05 mtr.	05 mtr.	MR		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases					
	1. Upper floors	01 No.	02 No.	MR		
	2. Basements	01 No.	01 No. & 01	MR		
			ramp	-		
	B. Width of staircase					
	1. Upper floors	1.25 mtr.	1.25 mtr.	MR		
	2. Basements	1.25 mtr.	1.25 mtr. & Ramp 2 mtr.	MR		
	C. Protection of exits					
	1. Fire check door	Required	Provided	MR		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	01	MR		
	staircase to terrace	1.2	1.5	140		
	E. Width of corridor	1.2 mtr. 1.2 mtr.	1.5 mtr	MR		
	F. Door size	1.2 mtr.	1.2 mtr.	MR		
3.	Compartmentation	D 1	D :1.1	1.70		
	1) Fire check door	Required	Provided	MR		
	2) Sealing of electrical shafts	Required N/A	Provided N/A	MR		
	3) Fire rating of shaft door4) Water curtain	N/A	N/A N/A	N/A		
		N/A	N/A N/A	N/A		
4.	5) Fire Dampers N/A N/A Smoke Management System					
	1) Basements	30 ACPH	Exhaust fan	MR		
	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers	1531				
	1) Total numbers	45 Nos.	50 Nos	MR		

2) Types 3) ISI marking First-Aid Hose Reel 1)Total number of each	ABC & CO2 Required	ABC, CO2 & Provided	MR MR
First-Aid Hose Reel 1)Total number of each			MR
1)Total number of each	01		
	0.1	0.4	
	01	01	MR
floor			
2) Length of hose reel hose	36 m	36 m	MR
	5 mm	5 mm	MR
Automatic Fire Detection & A	larming System		
		Smoke/ heat	MR
			MR
			MR
			MR
5) Hooter's Location			MR
			MR
			MR
	required	Tunctional	IVIIC
	Required	Provided	MR
			N/A
		IN/A	IN/A
	NA	NA	NA
		+	
	. 150 MM	150 MM	MR
			MR
	01	01	IVIK
	01	01	MR
		101	IVIIC
	05	105	MR
2) Hose box			MR
			IVIIC
	MAIDS		
 Ground level 			
 a) Discharge of main 	2850 LPM	2850 LPM	MR
pump			
		70 mtr.	MR
		02	MR
	180 LPM	180 LPM	MR
		70 mtr.	MR
			MR
			MR
	Required	Provided	MR
	- Annual		
	NI/A	27/4	
			N/A
			N/A
			N/A
Captive Water Storage for Fire F	IN/A Gighting	N/A	N/A
superior mater storage for Fire F		2.00.000 !:	
1) Under ground tank			1 1 1 1
Under ground tank capacity	2,00,000 ltr.	2,00,000 ltr.	MR
capacity			
capacity	Required Required	Provided Provided	MR MR MR
	3) Nozzle diameter Automatic Fire Detection & A 1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box each floor Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main	3) Nozzle diameter	3) Nozzle diameter 5 mm 5 mm Automatic Fire Detection & Alarming System 1) Type of detectors Smoke/ heat 2) Location of main panel C. Room Provided 3) Location of repeater panel floor wise floor wise 4) Alternate source of power D.G. set. Provided 5) Hooter's Location Every floor Provided MOEFA Required Provided Provided Public Address System Required functional Automatic Sprinkler System 1) Basement Required Provided 2) Upper floors N/A N/A 3) Sprinkler above false ceiling NA NA Internal Hydrants 1) Size of riser/down-comer 150 MM 150 MM 2) Number of hydrants per floor 3) Hose box each floor 01 01 Yard Hydrants 1) Total number of hydrants 05 2) Hose box 05 Pumping Arrangement Common pump with MAIDS 1) Ground level a) Discharge of main pump 02 d) Jockey pump out put (2 Nos.) e) Jockey pump head 70 mtr. 70 mtr. f) Stand by pump output 2850 LPM 2850 LPM g) Stand by pump head 70 mtr. 70 mtr. f) Stand by pump head 70 mtr. 70 mtr. f) Comping Provided Provided N/A N/A N/A b) Head of pump N/A N/A b) Head of pump N/A N/A c) Power supply N/A N/A

	d) Over head tank capacity	20,000 Ltrs.	20,000 Ltrs.	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.				
	Pressurization of lift shaft	N/A	N/A	N/A	
	 Pressurization of lift lobby 	N/A	N/A	N/A	
	c) Communication in lift	Required	Provided	MR	
	d) Fireman's switch	Required	Provided	MR	
	e) Lift signage	Required	Provided	MR	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room				
	a) Detector system panel	Required	Provided	MR	
	b) Flow switch panel	Required	Provided	MR	
	c) PA system panel	Required	Provided	MR	
	d) Battery backup	Required	Provided	MR	
	e) Building floor plan	Required	Provided	MR	
20.	Special Fire Protection System f any: Co2 & DCP			MR	

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved we may renew the FSC issued vide letter no. F6/DFS/MS/Hosp/NDZ/2018/466 dated 21.03.18 rule 35 of the Delhi Fire Service rules 2010. accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Rajinder Atwal Designation: - DO (CD) Signature of the Inspecting Officer

Name: - Ravinder Singh

Designation: - ADO (CC)