

No. 1.6/DES/MS/GH/SZ/2022/ 411

Dated: 07/08/22

(\_ \

C-63

## FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Amrit Villa located at 15/10169, Gurudwara Road, Karol Bagh, New Delhi- 110005, was granted Fire Safety Certificate vide this department letter No. E.6/DFS/MS/G11/SZ/2019/2058 dated 25.10.2019, for basement as hall, stilt floor as parking, ground floor as reception & 04 guest rooms, first, second & third floor each having 04 guest rooms respectively (total 16 guest rooms). The guest house was re-inspected by the officer concerned of this department on 31.08.2022 in presence of Sh. Rajinder Singh Khurana (owner) and found that the guest house management have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules. 2010 and that the premises is fit for occupancy class residential (guest house) for ground floor having 04 guest rooms, first, second & third floor each having 04 guest rooms respectively (total 16 guest rooms only), with effect from  $\frac{07}{09/22}$  for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 07/09/22 at New Delhi by.

(Sunil Chaudhary) Dy. Chief Fire Officer (SZ) Delhi Fire Service

Application ID No. 2022040205125 dated 15.04.2022

51

## Following Fire Safety Directives must be adhered to: -

- 1. No occupancy used above third floor and basement used for storage purpose only shall be strictly adhered by Owner/Occupier.
- 2. All the means of escape shall be kept free of all type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 6. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 7. All comments / directions of licensing department shall always be permitted and followed.
- 8 The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on own dt delhigovt mem
- 9. The owner <sup>-</sup> occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

	INSPEC	TION REPORT						
	r r	M's Hotel Amrit V Carol Bagh, New I	'illa, 15/10169. Gurt Delhi- 110005	idwara Road				
	Building Composition : Said g plus three ground floo	upper floors, using or as reception & 0	ng comprised of base g basement as storag 14 guest rooms, 1 <sup>st</sup> , 2	e. stilt as parking.				
4	1		respectively (total 1)	6 guest rooms)				
		Renewal						
Ĩ.	Details of previous NOC E F 6/DFS/MS/GH/SZ/2019/2058 dated 25.10.2019							
6.	Tire Safety directives letter No :	Nil						
7	Date of inspection : 3	31.08.2022						
8	Name of the Inspecting Officers : P	.V. Rathee, ADO (	(SRD)					
9.	Name and designation of officers	h. Rajinder Singh						
9	Year of Construction : E	Before 2010						
10.	Applicant's letter No. A	pplication ID No.	2022040205125 date	d 15.04.2022				
S. No	Minimum Standards on fire prevention and fire safety U/R 33	Requirement as per FSC dt 25.10.2019	Provided at site	Remarks MR/NMR				
1	Access to building	25.10.2019						
	Road width	Accessible	Provided (04 mts.)	MR. Old Case				
	<ul> <li>Gate width</li> </ul>	N/A	Directly accessible	N/A				
	• Width of internal road	N/A	N/A	N/A				
2	Number, Width, Type & Arrangemen	nt of Exits						
	a. Number of staircases	-	-	-				
	Upper I loors	01	01	MR being old case				
	Basements	01	01	MR being old case				
	b. Width of staircases	-	-	-				
	Upper Floors	Old Case	1.25 Mts	MR being old case				
	Basements	Old Case	1.25 Mts	MR being old case				
	c. Protection of exits	-	-	-				
	Fire check door	N/A	N/A	N/A				
	• Pressurization	ΝA	N/A	N/A				
	e. No. of continuous staircases to terrace	01	01	MR				
	g. Width of Corridor h. Door Size	N 'A	N/A	N/A				
		N A	N/A	N/A				
3	Compartmentation.							
	Fire check door	N/.A		N/A				
f.	Sealing of electrical shafts     Sealing of electrical shafts	N A		N A				
	<ul><li>Fire Rating of shaft door</li><li>Water Curtain</li></ul>	N 'A	<u> </u>	N A N A				
	<ul> <li>Water Curtain</li> <li>Fire Dampers</li> </ul>	N A	N/A	N/A				
	Smoke Management System.	ΝA	N/ ZN					
4	Basements	30 a/c per hour	Exhaust fan provided	MR				
	<ul><li>Dasements</li><li>Upper floors</li></ul>	12 a c per hour	Natural Ventilation	MR				
5	Fire Extinguishers	1						
-	Total numbers	12	Provided	MR				
	<ul> <li>Types</li> </ul>	Co <sub>2</sub> . ABC type	Provided	MR				
	• IS marking	ISI marked	Provided	MR				

Þ

÷¢

N-23

		N-25						
0	Provision of Lifts.							
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	$N'\Delta$	N/A	N/A				
1	Pressurization of Lift lobby	N/A	N/A	N/A				
	Communication In lift Car	Required	Provided	MR				
	<ul><li>Fireman's Grounding Switch</li><li>Lift Signage</li></ul>	Required	Provided	MR				
		Required	Provided	MR				
17	Standby power supply	Required	Provided	MR				
18								
	- Total Area	N/A	N/A	N'A				
	<ul> <li>Location</li> </ul>	N/A	N/A	N/A				
19								
	Detector System Panel	N/Λ	Ν/Α	N/A				
	Flow Switch Panel	N/A	N/A	N/A				
	PA System Panel	N/A	N/A	N/A				
	Batter backup	N/A	N/A	N/A				
	Building Floor Plans	N'A	N/A	N/A				
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	One ABC type fire extinguisher found provided near elect, panel	MR				

The fire protection systems provided in the building were checked at random and found satisfactory at the time of inspection.

Note:- Fire Check Door not required as owner/occupier has applied in CAF MHA Portal. Number of beds is less than 10 at each floor.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No. F.6/DFS/MS/GH/NDZ/2019/1418 dated 11.07.2019, renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name P.V. Rathee Asstt. Div. Officer (SRD)

D.O (SW) ilshr Dyefo (J2) F.A. ADO SRO

0	First-Aid Hose Reels.			
	<ul> <li>Lotal numbers on each floor</li> </ul>	01	Provided	MR
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR
	Nozzle diameter	5 mm	Provided	MR
7	Automatic fire detection and alarmin			
	<ul> <li>Type of detectors</li> </ul>	Carbon Monoxid		MR
	<ul> <li>Location of Main Panel</li> </ul>	Required	Provided	MR
	<ul> <li>Location of Repeater Panel</li> </ul>	N/A	N'A	N/A
	<ul> <li>Alternate source of power</li> </ul>	Required	Provided	MR
	<ul> <li>Hooters' Location</li> </ul>		N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.			
	Basement	NA	Provided	Area less than 200 sq. mts
	Upper Floor	NA	N/A	N/A
	<ul> <li>Sprinkler above false ceiling</li> </ul>	NA	NA	N/A
11	Internal Hydrants			
	Size of riser down-comer	NA	N/A	N/A
	• Number of hydrants per floor	N/A	N/A	N/A
	Hose Box	NA	N/A	N/A
12	Yard Hydrants.			
	<ul> <li>Total number of hydrants</li> </ul>	NA	N/A	N/A
	Hose Box	NA	N/A	
13	Pumping Arrangements.			
	Ground Level			
	<ul> <li>Discharge of main Pump</li> </ul>	N/A	NA	N/A
	<ul> <li>Head of Main pump</li> </ul>	N/A	N/A	N/A
	<ul> <li>Number of main pumps</li> </ul>	N/A	N/A	N/A
	<ul> <li>Jockey Pump out put</li> </ul>	N/A	N/A	N/A
	<ul> <li>Jockey pump head</li> </ul>	N/A	N/A	N/A
	<ul> <li>Standby Pump out put</li> </ul>	$\land A$	N/A	N/A
	<ul> <li>Standby Pump Head</li> </ul>	NA	NA	N/A
	<ul> <li>Auto Starting Manual stopping</li> <li>During Harman Annual Stopping</li> </ul>	N'A	N/A	N/A
	<ul> <li>Pump House Access</li> <li>Ferrace level</li> </ul>	N/A	N/A	N/A
	<ul> <li>Discharge of pump</li> </ul>			
	<ul> <li>Head of the pump</li> </ul>	450 LPM	450 LPM	MR
	<ul> <li>Power Supply</li> </ul>	40 mts	40 mts	MR
	<ul> <li>Auto Starting of pump</li> </ul>	Required	Provided	MR
		Required	Provided	MR
ŧ	Captive Water Storage for fire fighting	<u>g</u> .		
	<ul> <li>Underground tank capacity</li> </ul>	N/A	N/A	N/A
	<ul> <li>Draw-off connection</li> </ul>	×	N <sup>7</sup> A	N/A
	<ul> <li>Fire service inlet</li> </ul>	NA	NA	N/A
1	<ul> <li>Access to tank</li> </ul>	N. N	N A	N/A
	Overhead Tank capacity	5.000 lts	5000 1	MR being old case
				e una case



17

pro

10

Ø