

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / 2022 /School/WZ/ 996

001 Dated: 13/9/22

FIRE SAFETY CERTIFICATE

Certified that the M.C. Primary Boys/Girls School located at Bhorgarh, Delhi-110040 comprised of Ground and first floor owned/occupied by M C Primary School was issued FSC by this department vide letter No F6/DFS/MS/2019/2156 dated 15.11.2019. The premise was inspected by the officer concerned of this department on 06.09.2022 in the presence of Sh. Rajesh (Teacher Incharge), and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises have deemed complied with requirements of circular issued by Director of Education letter no 3298-3398 dated 01.03.2011 and the building/ premise is fit for occupancy Group B Educational with conditions mentioned below:

Issued on 1919 at New Delhi

(Dharampal Bhardw Dy. CHIEF FIRE OFFICER WEST ZONE

Copy to: -

1. The Director, Education, North MCD, Civic Center, New Delhi.

2. The Principal, MC Primary Boys/Girls School, Bhorgarh, Delhi-40.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on **WWW.dfs.Delhigovt.nic.in**

INSPECTION REPORT Name & address of the building : M.C. Primary Boys/Girls School, Bhorgarh, Delhi-110040. Type of Occupancy : Educational Building comprised : Ground+ One upper floor Type of Case : Renewal 5. Details of Previous NOC : Letter No. F.6/DFS/MS/2019/2156 Dated-15/11/2019 6. Fire Safety directives letter No : Dir of Edu. Cir 01/03/2011 7. Date of inspection 06/09/2022 8. Name of Inspecting Officer : ADO R.K Sinha 9. Name and designation of officers : Sh. Rajesh (Teacher In-charge) From the building side 10. Year of Construction 2013 : E Mail id, Dated-22/08/2022 11. Applicant's letter No. Remarks Provided at Dir. Of Edu. Minimum Standards on fire prevention and S. No. MR/NMR site Requirement fire safety U/R 33 Access to building MR 1. 6.0 m 6.0 m Road width MR 4.5 m 4.5 m Gate width NA NA NA Width of internal road Number, Width, Type & Arrangement of Exits NA 2. NA NA a. Number of staircases MR 02 02 Upper Floors NA NA NA Basements NA NA b. Width of staircases NA MR 1.55 m each Upper Floor 1.50 m NA NA NA Basements NA NA NA c. Protection of exits NA NA NA NA NA NA Fire check door NA NA Pressurization NA NA NA NA d. No. of continuous staircases to NA NA NA terrace Width of Corridor MR 1.16 m double 1.00 m door Door Size f. Compartmentation NA 3. NA NA

en

m

2

4.

NA

NA

NA

NA

30 a/c per hour

NA

Fire check door

Water Curtain

Fire Dampers Smoke Management System

Basements

Sealing of electrical shafts

Fire Rating of shaft door

| | Upper floors | 12 a/c per hour | Natural Ventilated | MR | | | | |
|----------|--|-----------------|-----------------------|----|---|--|--|--|
| 5. | Fire Extinguishers | | | | | | | |
| ٥, | Total numbers | 05 | 06 | MR | | | | |
| | Types | ABC | ABC | MR | | | | |
| | 1S marking | Yes | Yes | MR | | | | |
| 6. | First-Aid Hose Reels | | | | | | | |
| | Total numbers on each floor | NA | NA | NA | | | | |
| | Length of hose reel hose | 30 m | NA | NA | | | | |
| | Nozzle diameter | 5 mm | NA | NA | | | | |
| 7. | Automatic fire detection and alarming system | 1 | | | | | | |
| / * | Type of detectors | NA | NA | NA | | | | |
| | Location of Main Panel | NA | NA | NA | | | | |
| | Location of Repeater Panel | NA | NA | NA | | | | |
| | Alternate source of power | NA | NA | NA | | | | |
| | VI a VI and a | NA | NA | NA | | | | |
| 0 | Hooters' Location | NA | NA | NA | | | | |
| 8. 9. | MOEFA Public Address System | NA | NA | NA | | | | |
| 10. | Automatic Sprinkler System | | | | | | | |
| | Basement | NA | NA | NA | | | | |
| | BasementGround Floor | NA | NA | NA | | | | |
| | Sprinkler above false ceiling | NA | NA | NA | | | | |
| 1. | Internal Hydrants | | | | | | | |
| | | NA | NA | NA | | | | |
| | Size of riser/down-comer Note that a few dramts per floor. | NA | NA | NA | | | | |
| | Number of hydrants per floorHose Box | NA | NA | NA | | | | |
| 2. | Hose Box Yard Hydrants | | | | | | | |
| | • | NA | NA | NA | | | | |
| 3. | Total number of hydrants | NA NA | NA | NA | | | | |
| | Hose Box Pumping Arrangements | NA | 1471 | | _ | | | |
| | Tumping Arrangements | | | | | | | |
| | Ground Level | 274 | NIA | NA | | | | |
| | Discharge of main Pump | NA | NA | NA | | | | |
| | Head of Main pumpNumber of main pumps | NA | NA | | _ | | | |
| | > Jockey Pump out put | NA | NA | NA | | | | |
| | > Jockey pump head | NA | NA | NA | | | | |
| | Standby Pump out put | NA | NA | NA | | | | |
| | Standby Pump Head | NA | NA | NA | | | | |
| | | NA | NA | NA | | | | |
| | Auto Starting/Manual Stopping | NΛ | NA | NA | | | | |

| | > Pump House Access | | T | |
|-----|---|----------------|----------------|----------------|
| (| Fullip House Access | NA | NA | NA |
| | Terrace level | _ | | |
| | Discharge of pump | NA | NA | NA |
| | Head of the pump | NA | NA | NA |
| 7" | Power Supply | NA | NA | NA |
| | | - | - | _ |
| | > Auto Starting of pump | NA | NA | NA |
| 14. | Captive Water Storage for fire fighting | | | |
| 14. | Underground tank capacity | NA | NA | NA |
| | ▶ Draw-off connection | NA | NA | NA |
| | Fire service inlet | NA NA | NA | NA |
| | Access to tank | NA | NA NA | NA |
| | Overhead Tank capacity | NA | NA | NA |
| | | NA NA | NA NA | NA NA |
| 15. | Exit Signage. | INA | 19/4 | |
| | | | | |
| 16. | Provision of Lifts. | | | |
| | Pressurization of Lift Shaft | NA | NA | NA |
| | Pressurization of Lift lobby Communication In lift Car | NA | NA | NA |
| | Fireman's Grounding Switch | NA | NA | NA |
| | . Fernan 3 Grounding Switch | NA | NA | NA |
| | Lift Signage | NA | NA | NA |
| 17. | Standby power supply | NA | NA | NA |
| | | | | |
| 18. | Refuge Area. > Total Area | NA | NA | |
| | | 1973 | INA | 314 |
| | Location | | | NA |
| | > Location | NA | NA | NA NA |
| 19. | Fire Control Room | | NA | |
| 19. | Fire Control Room • Detector System Panel | NA NA | NA NA | NA |
| 19. | Fire Control Room Detector System Panel Flow Switch Panel | | | NA NA |
| 19. | Fire Control Room • Detector System Panel | NA | NA NA | NA NA NA |
| 19. | Fire Control Room Detector System Panel Flow Switch Panel | NA NA NA | NA NA NA | NA NA NA |
| 19. | Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Battery backup | NA NA | NA NA | NA NA NA |
| 19. | Fire Control Room | NA NA NA | NA NA NA | NA NA NA |

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under DOE circular no. 3298-3398 dated 01.03.2011 it is recommended to renew the Fire Safety Certificate issued vide letter no. F6/DFS/MS/2019/2156.

Do(NX) on gre H

Decto(wz)

Signature of Inspecting Officer

Name: Rajeev Kumar Sinha

Designation: ADO/BW

Aleten Putes for symbology

De (folior)

) [x/9] rm

ms) all