

FORM 'H'
FORM FOR ISSUING FIRE SAFETY CERTIFICATE
[Refer sub - rule (1) of rule 35]
GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI
HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE
NEW DELHI

No. F6/DFS/MS/SZ/2022/CNG/403

Dated: 13/09/2022

FIRE SAFETY CERTIFICATE

Certified that the M/s Hybrid CNG Filling Station (IGL) Located at outside DTC Depot, Sector - 2, Dwarka, New Delhi - 110075 comprised of Ground Floor only owned / occupied by Indraprastha Gas. Limited was issued NOC by this department vide Letter No. F6/DFS/MS/CNG/2019/SZ/1699 dated- 29/08/2019. The premises was re inspected by the officer concerned of this department on 02/09/2022 in the presence of Mr Ajay (Technician) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Hazardous" (CNG filling station) with effect from 13/09/2022 for a period of three years.

Issued on 13/09/2022 at New Delhi by.

(Sunil Chaudhary)

Dy.Chief Fire Officer,
Delhi Fire Service.

Copy to:

1. Mr Ajay (Technician) M/s Hybrid CNG Filling Station (IGL) Located at outside DTC Depot, Sector - 2, Dwarka, New Delhi - 110075.
2. Sh. Ajay Khatri DGM - Fire & Safety Indraprastha Gas Limited New Delhi.

Following fire safety directives must be adhered to:-

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
3. The trained staff should be available round the clock.
4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
5. The basement shall be used as per building bye laws 1983.
6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Hybrid CNG Filling Station (IGL) Located at outside DTC Depot, Sector - 2, Dwarka, New Delhi - 110075.
2. Type of Occupancy : Group J: Hazardous (CNG Filling Station)
3. Type of Case : Renewal
4. Details of previous NOC: F6/DFS/MS/CNG/2019/SZ/1699 dated- 29/08/2019
5. Fire Safety directives, Letter No. : UBBL / NBC Requirements / OISD -179
6. Date of inspection : 02/09/2022
7. Name of the Inspecting Officer : Sh. Udayvir Singh, ADO (DWK)
8. Name and designation of Officer from the building side : Mr Ajay (Technician)
9. Year of Construction : 2017
10. Applicant's letter No. : IGL/F&S/2022/15/106/2 dated 24/08/2022

S No	Minimum standards on fire prevention and fire safety U/R 33	As per N/8, N/9 & N/10	Provided at site	Remarks MR/NMR															
1.	Access of building																		
	<ul style="list-style-type: none"> • Road width • Gate width • Width of internal road 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">6m</td> <td>30 m</td> </tr> <tr> <td>4.5m</td> <td>Directly accessible from road</td> </tr> <tr> <td>NA</td> <td>NA</td> </tr> </table>	6m	30 m	4.5m	Directly accessible from road	NA	NA		<ul style="list-style-type: none"> MR MR NA 									
6m	30 m																		
4.5m	Directly accessible from road																		
NA	NA																		
2.	Number, width, Type & Arrangements of exits																		
	a. Number of staircases																		
	<ul style="list-style-type: none"> • Upper floors • Basements 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>NA</td> <td>Cascade at ground</td> <td>NA</td> </tr> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> </table>	NA	Cascade at ground	NA	NA	NA	NA											
NA	Cascade at ground	NA																	
NA	NA	NA																	
	b. Width of staircases																		
	<ul style="list-style-type: none"> • Upper floors • Basements 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> </table>	NA	NA	NA	NA	NA	NA											
NA	NA	NA																	
NA	NA	NA																	
	c. Protection of exits																		
	<ul style="list-style-type: none"> • Fire check door • Pressurization 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> </table>	NA	NA	NA	NA	NA	NA											
NA	NA	NA																	
NA	NA	NA																	
	d. No of continuous staircase to terrace																		
	<ul style="list-style-type: none"> • No of continuous staircase to terrace 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>NA</td> <td>01</td> <td>NA</td> </tr> </table>	NA	01	NA														
NA	01	NA																	
	e. Width Of Corridor																		
	<ul style="list-style-type: none"> • Width Of Corridor 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> </table>	NA	NA	NA														
NA	NA	NA																	
	f. Door Size																		
	<ul style="list-style-type: none"> • Door Size 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> </table>	NA	NA	NA														
NA	NA	NA																	
3.	Compartmentation																		
	<ul style="list-style-type: none"> • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> </table>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA		
NA	NA	NA																	
NA	NA	NA																	
NA	NA	NA																	
NA	NA	NA																	
NA	NA	NA																	
4.	Smoke managements System																		
	<ul style="list-style-type: none"> • Basements • Upper floors 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> <tr> <td>NA</td> <td>NA</td> <td>NA</td> </tr> </table>	NA	NA	NA	NA	NA	NA											
NA	NA	NA																	
NA	NA	NA																	

(Signature)

5.	Fire Extinguishers			
	<ul style="list-style-type: none"> Total numbers Types 	04 nos. DCP 10 kg, 1 no 75 kg & 1 no CO ₂ 4.5 kg for 25 sq.m each floor area, Advance fire water mist cum foam trolley Required	Provided	MR
	<ul style="list-style-type: none"> IS marking 		Provided	MR
			Provided	MR
6.	First - Aid Hose Reels			
	<ul style="list-style-type: none"> Total numbers on each floor 	NA	NA	NA
	<ul style="list-style-type: none"> Length of hose reel hose 	NA	NA	NA
	<ul style="list-style-type: none"> Nozzle diameter 	NA	NA	NA
7.	Automatic fire detection and alarming system			
	<ul style="list-style-type: none"> Type of detectors 	Gas & Flame & hand held detector	Provided	MR
	<ul style="list-style-type: none"> Location of Main Panel 	NA	NA	NA
	<ul style="list-style-type: none"> Location of Repeater Panel 	NA	NA	NA
	<ul style="list-style-type: none"> Alternate source of power 	NA	NA	NA
	<ul style="list-style-type: none"> Hooters' Location 	NA	NA	NA
8.	MOEFA	Required	Provided	MR
9.	Public Address System	NA	NA	NA
10.	Automatic Sprinkler System			
	<ul style="list-style-type: none"> Ground Floor 	NA	NA	NA
	<ul style="list-style-type: none"> Upper Floor 	NA	NA	NA
	<ul style="list-style-type: none"> Sprinkler above false ceiling 	NA	NA	NA
11.	Internal Hydrants:			
	<ul style="list-style-type: none"> Size of riser/down-comer 	NA	NA	NA
	<ul style="list-style-type: none"> Number of hydrants per floor 	NA	NA	NA
	<ul style="list-style-type: none"> Hose Box 	NA	NA	NA
12.	Yard Hydrants			
	<ul style="list-style-type: none"> Total number of hydrants 	NA	NA	NA
	<ul style="list-style-type: none"> Hose Box 	NA	NA	NA
13.	Pumping Arrangements:			
	<ul style="list-style-type: none"> Ground Level 			
	<ul style="list-style-type: none"> Discharge of main pump 	NA	NA	NA
	<ul style="list-style-type: none"> Head of main pump 	NA	NA	NA
	<ul style="list-style-type: none"> Number of main pumps 	NA	NA	NA
	<ul style="list-style-type: none"> Jockey pump out put 	NA	NA	NA
	<ul style="list-style-type: none"> Jockey pump head 	NA	NA	NA
	<ul style="list-style-type: none"> Standby Pump out put 	NA	NA	NA
	<ul style="list-style-type: none"> Standby Pump Head 	NA	NA	NA
	<ul style="list-style-type: none"> Auto Starting/Manual stopping 	NA	NA	NA
	<ul style="list-style-type: none"> Pump House Access 	NA	NA	NA
	<ul style="list-style-type: none"> Terrace level 			
	<ul style="list-style-type: none"> Discharge of pump 	NA	NA	NA
	<ul style="list-style-type: none"> Head of the pump 	NA	NA	NA
	<ul style="list-style-type: none"> Power supply 	NA	NA	NA
	<ul style="list-style-type: none"> Auto starting of pump 	NA	NA	NA

J.B.

14.	Captive water Storage for fire fighting:			
	• Under ground tank capacity	NA	NA	NA
	➤ Draw off connection	NA	NA	NA
	➤ Fire service inlet	NA	NA	NA
	➤ Access to tank	NA	NA	NA
	• Overhead Tank capacity	NA	NA	NA
15.	Exit Signage	Required no smoking board	Provided	MR
16.	Provision of Lifts			
	➤ Pressurization of Lift Shaft	NA	NA	NA
	➤ Pressurization of lift lobby	NA	NA	NA
	➤ Communication in lift Car	NA	NA	NA
	➤ Fireman's Grounding Switch	NA	NA	NA
	➤ Lift Signage	NA	NA	NA
17.	Standby power supply	Required	Provided DG set 25 kva	MR
18.	Refuge Area			
	➤ Total area	NA	NA	NA
	➤ Location	NA	NA	NA
19.	Fire control room			
	➤ Detector system panel	NA	NA	NA
	➤ Flow Switch Panel	NA	NA	NA
	➤ PA System Panel	NA	NA	NA
	➤ Battery backup	NA	NA	NA
	➤ Building Floor Plans	NA	NA	NA
20.	Special Fire Protection Systems for Protection of special Risks, if any:	CO2 Flooding	Provided for compressor	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/CNG/2019/SZ/1699 dated-29/08/2019 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer
 Name *[Handwritten Signature]*
 Designation *ADO/DWR*

[Handwritten Signatures and Dates]
 DFSU
 6/9/22
 Dsefo (sz)
 ADO/DWR