

No: F.6/DFS/MS/School/WZ/2022 / ししる

Dated: 1579/22

FIRE SAFETY CERTIFICATE

(Dharampal Bhardwaj) Dy. Chief Fire Officer West Zone

Copy to: -

- 1. Govt. Sarvodaya Bal Vidyalaya, located at Lalita Block. Shastri Nagar, New Delhi-110052.
- 2. Director of Education, Old Secretariat, New Delhi-110054.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

(NIIP							
	INSP	ECTION REPOR	Γ						
1	Name & address of the building : Govt. Sarvodaya Bal Vidyalaya Located at Lalita Block. Shastri Nagar, New Delhi - 110052								
2									
3	Type of Case Rene	awal							
4									
5		DF 5/MS/WZ/2019/	1698 dated 29/08/2019						
6	Fire Safety directives letter No : DO		01/03/2011						
	Date of inspection : 03/09/2022								
7	and of the inspecting Officers Sar	abject Singh ADO(N	MN)						
8	from the building side : Smt.	K.M. Tiwari (HOS)						
9	Year of Construction : 2014	(As Per Prev. Insp.	Report dated: - 19/08/2	2019)					
10		il dated: - 05/08/202							
5.	Minimum Standards on fire	DOE 3298-3398 da	ted Provided at sit	e Remarks					
No	prevention and fire safety U/R 33	01/03/2011 As Per Insp. Report dtd 19/08/2019		MR/NMR					
	Access to building								
	Road width	5 mts	Provided	MR					
	Gate width	3.5 mts	Provided	MR					
	Width of internal road	NA	NA	NA					
	Number, Width, Type & Arrangement of Exits								
	a. Number of staircases								
	Upper Floors	02	02 Provided	MR					
	Basements	NA	NA	NA					
	b. Width of staircases		2 1/0	N 4D					
	Upper Floors	1.5 mts	2 x 160 cm	MR					
	Basements	NA	NA						
	c. Protection of exits	NA	NA	NA					
	Fire check door	NA	NA	NA					
	 Pressurization 	01	Provided	MR					
	e. No. of continuous staircases to terrace	1.5 m	233 cm Provided	MR					
	f. Width of Corridor	1 mts	Provided (including	MR (old case					
	g. Door Size		door Frame)						
	Compartmentation.								
	Fire check door	NA	NA NA	NA NA					
	 Sealing of electrical shafts 	NA NA	NA	NA					
	 Fire Rating of shaft door 	NA	NA	NA					
	Water Curtain	NA	NA	NΛ					
	Fire Dampers	1.17							
4	Smoke Management System.		NA	NΔ					
	Basements	NA	NA	NA					
	Upper floors	NA							
5	Fire Extinguishers			MR					
,	Total numbers	06 nos.	24 Provided						
	• Types	CO_2 , ABC type	Provided	MR					
	IS marking	ISI marked	Provided	MR					
				05					

NII

8si_

6	E i	MIT			
	First-Aid Hose Reels.				
	 Total numbers on each floor Length e Gl 				
	 Length of hose reel hose Nozzla di 	NA		1	
	 Nozzle diameter 	NA	NA	NA	
7	Automatic 5	NA	NA	NA	
	 Automatic fire detection and alarmi Type of detectors 	D.C. Strat	NA	NA	
		NA			
	Location of Main Panel		NA		
	 Location of Repeater Panel Alternate 	NA	NA	NA	
	internate source of power	NA	NA	NA	
8	Hoolers Location	NA	NA	NA	
9	MOEFA	NA	NA	NA	
	Public Address System.	NA	NA	NĄ	
10	Automatic Sprinkler System.	Required	Provided	NA	
	 Basement 			MR	
	Upper Floor	NA	NA		
	• Sprinklas -1	NA		NA	
11	• Sprinkler above false ceiling Internal Hydrants	NA	NA NA	NA	
	in Hydrants			NA	
	• Size of riser/down-comer	NA			
	 Number of hydrants per floor 	NA	NA	NA	
12	- Hose Box	NA	NA	NA	
2	Yard Hydrants. NA NA				
	• Total number of t				
	 Hose Box 	NA	NA	NA	
3	Pumping Arrangements.	NA	NA	NA	
	Ground Level				
	Discharge of main Pump	NA	NA		
	riedd of Main pump	NA	NA	NA	
	runnoer of main pumps	NA	NA	NA NA	
	Jockey Pump out put	NA	NA		
	 Jockey pump head 	NA	NA	NA	
	Standby Pump out put	NA	NA	NA	
	Standby Pump Head	NA	NA	NA	
	Auto Starting/ Manual stopping	NA	NA	NA NA	
	Pump House Access	NA	NA		
	• Terrace level		• • •	NA	
	 Discharge of pump 	NA	NT A		
	 Head of the pump 		NA	NA	
	 Power Supply 	NA NA	NA	NA	
	 Auto Starting of pump 	NA	NA NA	NA	
			INA	NA	
	Captive Water Storage for fire fighting.				
	 Underground tank capacity 	NA	NA	NA	
	Draw-off connection	NA	NA	NA	
	 Fire service inlet 	NA	NA	NA	
	Access to tank	NA	NA	NA	
	 Overhead Tank capacity 	NA	NA	NA	
F	Exit Signage.	Required	Provided	MR	

240

		r/18		
	Provision of Lifts.			
	Pressurization of Lift Shaft	NA	NA	NA NA
	Pressurization of Ent Shart Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage	NA	NA	NA
		NA	NA	NA
		NA	NA	
		NA	NA	NA
			NA	NA
_	Standby power supply	NA		
	Refuge Area.		27.4	NA
		NA	NA	NA
	- Total Area	NA	NA	1.00
	- Location			
	Fire Control Room	NIA	NA	NA
	Detector System Panel	NA	NA	NA
	Flow Switch PanelPA System Panel	NA	NA	NA
		NA	NA	NA
		NA		NA
	Batter backup	NA	NA	NA
	Building Floor Plans	NA	NA	
	Special Fire Protection Systems for			
	Protection of special Risks, if any:			

NA NA

 $\frac{N_A}{N_A}$

NA NA

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules DOE Circular no. 3298-3398 dated 01/03/2011, the NOC issued vide letter no. F6/DFS/NIS/WZ/2019/1698 dated: - 29/08/2019 renewal under 35 of the Delhi Fire Service Rules 2010

is recommended. ATTO9/WM ,o(upor) Signature of the Inspecting Officer Name: Sarabjeet Singh Designation: ADO (MN) 289 ADOIMN 9 9 2022 9/9/20 we) Jour kind persuel & Step 2/9/2012 N ١ T is put up ignature please to (w2)