

# GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6/DFS/MS/School/WZ/2022/ / O | Y

Dated: 157 9 /2022

### FIRE SAFETY CERTIFICATE

Certified that the S. D. Sarswati Bal Mandir, C-5, Rajiv Nagar, Ph-II, (Sec-22, Rohini), Delhi-86, comprised of Ground and 02 upper floors owned/ occupied by the S. D. Sarswati Bal office this vide certificate safety granted fire F.6/DFS/MS/2017/School/WZ/706 dated 17/05/2017 have deemed complied with the fire safety Mandir requirements in accordance with rile 33 of Delhi Fire Service Rules, 2010 and verified by the officer concerned of Fire Service on 02.09.2022 in the presence of Mrs. Veena Sharma (Principal) and that the building/premises is fit for occupancy Group B Educational with effect under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on \_\_\_\_ | \$\frac{1}{2} \rangle \rangle \rangle at New Delhi by

(Dhrampal Bhardwaj) Dy.Chief Fire Officer Tel;-01123414250

210

#### Copy to: -

- 1. The Director of Education, Old Secretariat, Delhi.
- 2. The Manager, S.D. Sarswati Bal Mandir, C-5, Rajiv Nagar, Ph-II,(Sec-22, Rohini), Delhi-86

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/ http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Forms

## INSPECTION REPORT

1. Name & address of the building

: S.D. Sarswati Bal Mandir, C-5, Rajiv Nagar, Phase -II.

(Sector-22, Rohini), Delhi-110086.

2. Type of Occupancy

: Educational

3 Type of Case

: Renewal (Ground + 02 floor)

4 Details of previous NOC

: F6/DFS/MS/2017/School/WZ/706 Dated: 17/05/2017

5 Fire Safety directives letter No

: NBC Part- 4

6 Date of inspection

: 02.09.2022

7 Name of the Inspecting Officers : A.K.Sharma ADO (Rohini)

8 Name and designation of officers

from the building side

: Mrs. Veena Sharma / Principal

9. Year of Construction

: 1994

10. Applicant's letter No.

: Online e-mail dated 01.09.2022

	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR		
	Access to building					
	Road width	6m	6m	MR		
	Gate width	4.50m	3.65m	MR(Old case		
	<ul> <li>Width of internal road</li> </ul>	6m	6m	MR		
	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases					
	Upper Floors	02	02	MR		
	Basements	NA	NA	NA		
	b. Width of staircases					
	<ul> <li>Upper Floors</li> </ul>	1.50 m	1.50m & 1.60m	MR		
	Basements	NA	NA	NA		
	c. Protection of exits		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	X1.		
	Fire check door	NA	NA NA	NA NA		
		NA 02	02	MR		
	<ul> <li>Pressurization</li> </ul>	02	02	MK		
	d. No. of continuous staircases to terrace	Required	2.14m	MR		
	e. Width of Corridor	1.0m	1.0m	MR		
3	f. Door Size  Compartmentation.					
	Fire check door	NA	NA	NA		
	Sealing of electrical shafts	NA	NA	NA		
	Fire Rating of shaft door	NA	NA	NA		
	Water Curtain	NA	NA	NA		
	• Fire Dampers	NA	NA	NA		
	Smoke Management System.  Basements	30 a/c per hour	NA	NA		
	Basements     Upper floors	12 a/c per hour	Natural Ventilated	MR		
		•				
	Fire Extinguishers	12000	15 nos	MR		
	Total numbers	12nos	ABC15	MR		
	• Types	ABC/Co2	ADC -15			

				1		
T	ISI marking  Circt, Aid Hose D.	Yes	Yes	100		
-	First-Aid Hose Reels.		•	MR		
	Total numbers on each floor	02	Provided	MR		
	<ul> <li>Length of hose reel hose</li> </ul>	30m	Provided			
	Nozzle diameter			MR		
A	Automatic fire detection and alarming system	5m	Provided	MR		
	Type of detectors	NA NA				
	Location of Main Panel	NA NA	NA NA	NA		
	Location of Repeater Panel	NA		NA		
	I		NA	NA		
	Alternate source of power	NA	NA	NA		
<del></del>	Hooters' Location	NA	NA	NA		
_	MOEFA Public Address System.	NA	NA	NA		
	Automatic Sprinkler System.	NA	NA	NA		
_						
	• Basement	NA	NA	NA		
	Upper Floor	NA	NA	NA		
	Sprinkler above false ceiling	NA	NA	NA		
1	Internal Hydrants					
	Size of riser/down-comer	100mm	100mm	MR		
	Number of hydrants per floor	01	01	MR		
	Hose Box	01	01	MR		
2	Yard Hydrants.					
	Total number of hydrants	NA	NA	NA		
	Hose Box	NA	NA	NA		
3	Pumping Arrangements.					
	Ground Level					
	<ul><li>Discharge of main Pump</li></ul>	N/A	N/A	N/A		
	Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	Jockey Pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	Standby Pump Head	N/A	N/A	N/A		
	Auto Starting/ Manual stopping			N/A		
	> Pump House Access	N/A	N/A	IN/A		
	Terrace level     Discharge of pump	4501	450 lpm	MR		
	> Discharge of pump	450lpm	450 lpm 40m	MR		
	> Head of the pump	40m	Provided	MR		
	> Power Supply	Required		MR		
	> Auto Starting of pump	Required	Provided	IVIK		
4	Captive Water Storage for fire fighting.					
-	Underground tank capacity	NA	NA NA	NA NA		
	> Draw-off connection	NA	NA NA	NA NA		
	Fire service inlet	NA	NA NA	NA		
	> Access to tank	NA	1474			

Provision Senage

5	Exit Signage.	10,00010	10,000 Iu	MIR
6	Provision of Lifts.	Required	Provided	MR
7	<ul> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> <li>Location</li> </ul>	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A
9	Fire Control Room	N/A	N/A	N/A
	Detector System Panel     Flow Switch Panel	N/A N/A	N/A N/A	N/A N/A
	PA System Panel     Batter backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any	N/A	N/A N/A	N/A N/A

The fire protection systems provided in the building were test checked and found in working conditions at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in NBC art 4, the FSC issued vide letter of even no F6/DFS/MS/2017/School/WZ/706 Dated: 17/05/2017 renewed under rule 37 of the Delhi Fire Service rules 2010 is recommended.

> Signature of the Inspecting Officer Name : Ajay Kumar Sharma Designation: ADO (Rohini)

Dyero (wz)

Adal fobini

FT letter is four up for kind bennsal and 8-grature please

DEFO(WZ)

20 of BI

/ith

h-l

·ck

lice ula

bl bn