

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6 DFS/MS/School/2022/SZ/ 10 4

Dated: 200 / 5 / 2022

## FIRE SAFETY CERTIFICATE

Certified that Govt. Girls Senior Secondary School No-1, East of Kailash, New Delhi (School ID 1924032) comprised of New Block, Ground plus Three upper floors owned/occupied by Directorate of Education, Govt. of NCT of Delhi have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by officer concern of this department on 12/09/2022 in the presence of Mr. Dinesh Sharma and that the premises is fit for occupancy class "Educational, Group–B" (School) as above with effect from 20/9/2022 for period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 20/92022 at New Delhi by

Copy to: -

- 1. The Assistant Engineer (E) Edu. Maint. Sub-div-M1, PWD, Hauz Khas, New Delhi 110016.
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi- 110054

## Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. This certificate cannot be treated as regularization of unauthorized construction, if any.
- 5. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>www.dfs.delhigovt.nic.in</u>
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

नायाकः तमत महोत्सव INSPECTION REPORT Name & Address of the Building Govt. Girls Senior Secondary School No-1, East of 1 Kailash, New Delhi (School ID 1924032) Type of Occupancy Educational, Group-B 2 Building Comprised of 3 New Building Blocks, G + 3 Upper Floor Type of Case 4 New Case Details of Previous NOC 5 Nil Fire Safety Directives Letter No 6 NBC/UBBL 2016 Date of Inspection 12-09-2022 8 Name of the Inspecting Officers Sh. Rajesh Kumar ADO (BCP) Name & Designation of Officers 9 Mr. Dinesh Sharma from the building side 10 Year of construction 2022 11 Applicant letter No. 54(SPS-School)PWD/Edu./Maint./Sub-Div/M-1-3/2021-22/184 dated 29/03/2022 Minimum standards on Fire Prevention S. No Remarks UBBL-2016 **Provided** at Site and Fire Safety U/R 33 MR/NMR requirements 1 Access to Building. MR Road width Required 9 mtr • -NA-Gate width -NA--NA-Width of internal road -NA--NA--NA-2 Number, width, type & arrangement of exits. Number of Staircase a) MR Upper floors. 03 Nos 03 Nos Basement floor. -NA--NA--NAb) Width of Staircase MR 1.50 mtr 1.50 m each Upper floors -NA-Basement floor -NA--NAc) Protection of exits -NA--NA-Fire check door -NA--NA--NA--NA-Pressurization MR 02 Nos Provided d) No. of continuous staircase to terrace -NA--NA--NA-Width of corridor e) 1.2 mtr MR 1.2 mtr **Door size** f) Compartmentation. 3 -NA--NA--NA-Fire check door. -NA--NA--NA-Sealing of electrical shafts. -NA--NA--NA-Fire rating of shaft door. -NA--NA--NA-Water curtain -NA--NA--NA-Fire dampers. Smoke Management system. 4. -NA--NA--NA-Basement -NA--NA--NA-Upper floors 5. Fire Extinguishers. 70 Nos 54 No's MR Total numbers ABC / co2 ABC / Co2 Type MR Types Provided ISI mark MR **ISI Marking** First Aid Hose Reels. 6. 03 at each Provided MR Total numbers on each floor. • 30 mm Provided MR Length of hose-reel hose. 5 m Provided MR Nozzle Diameter Automatic fire detection & alarming system. 7 -NA--NA--NA-Type of detectors -NA--NA--NA-Location of Main Panel -NA--NA--NA-Location of Repeater Panel -NA--NA--NA-Alternate source of power -NA--NA--NA-Hooter's location -NA--NA--NA-MOEFA 8. -NA--NA--NA-**Public Address System** 9.

N/19

		4		1
		N 20		
		1. 1	आज़ार्ट अमृत	त नहोत
10.	Automatic Sprinkler System			
	• Basement	-NA-		-
	Upper floors	-NA-	-NA-	-NA-
	<ul> <li>Sprinkler above false ceiling</li> </ul>	-NA-	-NA-	-NA-
11.	Internal Hydrants.	-INA-	-NA-	-NA-
	<ul> <li>Size of Riser/Down-comer</li> </ul>	NIA		
	• Number of Hydrant per floor	-NA-	-NA-	-NA-
	<ul> <li>Hose box.</li> </ul>	-NA-	-NA-	-NA-
12.	Yard Hydrants.	-NA-	-NA-	-NA-
	• Total number of hydrants.			-11/4-
	<ul> <li>Hose box.</li> </ul>	-NA-	-NA-	-NA-
13.	Pumping arrangements.	-NA-	-NA-	
	Ground Level			-NA-
	<ul> <li>Discharge of main pump.</li> </ul>			
	<ul> <li>Head of main pump.</li> </ul>	-NA-	-NA-	
	<ul> <li>Number of main pumps.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Jockey Pump output.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Jockey Pump head.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Standby Pump output.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Standby Pump head.</li> </ul>	-NA-	-NA- -NA-	-NA-
	<ul> <li>Auto Starting / Manual Stopping.</li> <li>Pump house</li> </ul>	-NA-		-NA-
	<ul> <li>Pump house access.</li> </ul>	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Terrace Level		-NA-	-NA-
	<ul> <li>Discharge of pump.</li> </ul>	2 x 450 LPM	Fach 11 1 P	
	<ul> <li>Head of pump.</li> </ul>	40 m	Each blocks Provided	MR
	Power supply.	Required	Provided	MR
14.	> Auto starting of pump.	Required	Provided	MR
	Captive water storage for fire fighting.	Inquired	Provided	MR
	<ul> <li>Underground tank capacity</li> </ul>	-NA-	NA	
	<ul> <li>Draw-off connection.</li> </ul>	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
5.	• Overhead tank capacity.	10,000 ltrs each	-NA-	-NA-
5. 6.	Exit Signage.	Required	Provided	MR
0,	Provision of Lifts.		Provided	MR
	<ul> <li>Pressurization of lift shaft.</li> </ul>	-NA-	NA	
	<ul> <li>Pressurization of lift lobby.</li> </ul>	-NA-	-NA- -NA-	-NA-
	<ul> <li>Communication in lift car.</li> </ul>	-NA-	-NA- -NA-	-NA-
1	• Firemon's antital	-NA-		-NA-
	• Fireman's switch.			
~	<ul> <li>Lift signage.</li> </ul>		-NA-	-NA-
	• Lift signage. Standby Power Supply	-NA-	-NA-	-NA-
	Lift signage.     Standby Power Supply     Refuge Area			
	• Lift signage. Standby Power Supply	-NA- -NA-	-NA- -NA-	-NA- -NA-
8.	Lift signage.     Standby Power Supply     Refuge Area	-NA- -NA-	-NA- -NA-	-NA-
8.	Lift signage.     Standby Power Supply     Refuge Area     Total area     Location	-NA- -NA-	-NA- -NA-	-NA- -NA-
8.	Lift signage.     Standby Power Supply Refuge Area     Total area     Location Fire Control Room.	-NA- -NA- -NA- -NA-	-NA- -NA-	-NA- -NA-
8.	Lift signage.     Standby Power Supply     Refuge Area     Total area     Location     Fire Control Room.     Detector system panel.	-NA- -NA- -NA- -NA-	-NA- -NA-	-NA- -NA- -NA- -NA-
8.	Lift signage.     Standby Power Supply     Refuge Area     Total area     Location     Fire Control Room.     Detector system panel.     Flow switch panel.	-NA- -NA- -NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA-
8.	Lift signage.     Standby Power Supply     Refuge Area     Total area     Location     Fire Control Room.     Detector system panel.     Flow switch panel.     PA system panel.	-NA- -NA- -NA- -NA- -NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA- -NA- -NA-
8.	Lift signage.     Standby Power Supply     Refuge Area     Total area     Location     Fire Control Room.     Detector system panel.     Flow switch panel.     PA system panel.     Battery backup.	-NA- -NA- -NA- -NA- -NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA- -NA- -NA- -NA-
8. 9.	Lift signage.     Standby Power Supply     Refuge Area     Total area     Location     Fire Control Room.     Detector system panel.     Flow switch panel.     PA system panel.     Battery backup.     Building floor plan	-NA- -NA- -NA- -NA- -NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA- -NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA- -NA- -NA- -NA- -NA-
7. 8. 9.	Lift signage.     Standby Power Supply     Refuge Area     Total area     Location     Fire Control Room.     Detector system panel.     Flow switch panel.     PA system panel.     Battery backup.	-NA- -NA- -NA- -NA- -NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA- -NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA- -NA- -NA- -NA-

The fire .

NB महोत्सव The fire protection system provided in the building were randomly checked and found functional at -NA -N the time of inspection. Keeping in view of the substantially satisfactory compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, it is recommended to issue Fire Safety Certificate under rule 35 (3) of the Delhi Fire Service Rules, 2010 Accordingly, DFA is put up for approval and signature please. Signature of the Inspecting Officer Name: Sh. Rajesh Kumar Design: ADO (BCP) Dy. CFO (SZ) Directo F=1. letter er portup ature Gl 1919 Direct

-1