GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI <u>HEAD QUARTERS, DELHI</u> FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2022/ 434

Dated : (.9.1.9.../2022

FIRE SAFETY CERTIFICATE

Certified that the Shailey Guest House located at 4256, Tel Mandi, Pahar Ganj, New Delhi comprised of Ground, Mezzanine + 03 Upper floors, Ground floor (01 guest rooms + reception + office), Mezzanine & 1st floor (03 guest rooms at each floors) 2nd to 3rd floor (04 guest rooms at each floors), total 15 guest rooms, was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/2019/2318 dated 13/12/19 for 15 guest room only and vide letter no. F6/DFS/MS/NDZ/2021/1058 dated 30.12.2021 for 11 guest room up to second floor. Now, the premises was re-inspected by the officer concerned of this department on 06/09/22 in the presence of Sh. Krishna Kumar and found that the said guest house building having given an Undertaking dated 08.09.2022 not to use any floor above second floor, has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, (Sub Division-A-1) Ground floor (01 guest rooms + office), Mezzanine & 1st floor (03 guest rooms at each floors), 2nd floor (04 guest rooms at each floors), total 11 guest rooms up to second floor only, renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

(S.K. Dua) Dy. Chief Fire Officer **Delhi Fire Service**

Copy to:-

- 1. The Commissioner, MCD, Civic Centre, New Delhi: kindly to ensure the occupancy as detailed above.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online id no. 2022062013182 dated 20.06.2022.
- The Manager, Shailey Guest House 4256, Tel Mandi, Pahar Ganj, New Delhi.

Condition for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>www.dfs.delhigovt.nic.in</u>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

		~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~				
	INS	PECTION REP	ORT			
1.	Name & address of the buildin		lest House at 4256	, Tel Mandi,		
	T f	Pahar Gar	nj, New Delhi.			
2.	Type of occupancy:- Residential, Sub Division-A-1					
	0	Gr. + Mezzanii	ne + 03 Upper floors (to	otal 11 Guest rooms)		
	L	Mezzanine & 1	guest rooms + receptions (100) st floor(03 guest rooms a	on + office),		
		floor (04 guest	rooms at each floors), tot	al 11 guest rooms, 3 rd		
		floor(an Unde	rtaking dated 08.09.2	022 not to use any		
		floor above	second floor)			
	Type of case:-	Renewal				
4.	Details of previous FSC:-	F6/DFS/M	S/GH/2019/2318 dat	ted 13/12/19.		
5.	Fire safety directives No	N/A				
	Date of inspection:-	06/09/22				
7.	Name of the inspecting officer	:- Sh. Ravin	der Singh (ADO/C	C)		
8.	Name & designation of officer	r	8	- /		
	From the building side:-	Sh. Krish	na Kumar			
9.	Year of construction:-	1982	na rtamai			
	. Applicant's letter No:-	.,	13182 dated 20.06	2022		
S.No.	Minimum Standards on fire	Requirement				
	Prevention and fire safety		Flovided at site	MR/NMR		
	U/R 33	Existing				
1.	Access to Building					
1.				- 100		
	1) Road width	06	06 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arr	angement of E	xits			
	A. Number of staircases					
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase	•				
	1. Upper floors	0.80 mtr.	1.0 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits	-				
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A N/A		
	5) Fire Dampers	N/A	N/A N/A	N/A N/A		
4	Smoke Management System			11/1		
4.	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 a/c per	Natural/Exhaust	MR		
		hour	fan			
5	Fine Extinguishers	noui	1411			
5.	Fire Extinguishers	10 Noc	10 Noc	MD		
	1) Total numbers	10 Nos.	10 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		

<i>.</i>	First-Aid Hose Reel		-		
	1) Total number of the				
	1) Total number of eachfloor	01	01	MR	
	2) Length of hose reel hose3) Nozzle diameter	30 mtr.	30 mtr.	MR	
7.	Automotic E:	05 mm		MR	
/.	Automatic Fire Detection &	Alarming Syste	em	IVIK	
		Required	Provided	MD	
	2) Location of main panel	Ground floor	Provided	MR	
	3) Location of repeater panel	N/A	N/A	MR	
	4) Alternate source of power	Required	Provided	N/A	
0	5) Hooter's Location	Required	Provided	MR	
8.	MOEFA	N/A	N/A	MR	
9.	Public Address System	Deni		N/A	
10.	Automatic Sprinkler System	required	Provided	MR	
	1) Dasement	N/A			
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
	ceiling		N/A	N/A	
11.	Internal Hydrants				
	1) Size of riser/down-comer	N/A	21/1		
	2) Number of hydrants per	N/A	N/A	N/A	
	floor	IN/A	N/A	N/A	
	3) Hose box	N/A			
12.	Yard Hydrants	IN/A	N/A	N/A	
	1) Total number of hydrants	N/A			
	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement	1N/A	N/A	N/A	
	1) Ground level	N/A			
	a) Discharge of main	N/A N/A	N/A	N/A	
	pump	IN/A	N/A	N/A	
	b) Head of main pump	N/A	27/1		
	c) Number of main	N/A	N/A	N/A	
	pump		N/A	N/A	
	d) Jockey pump out put	N/A	NUA		
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump	N/A	N/A	N/A	
	output		N/A	N/A	
	g) Stand by pump head	N/A	N/A		
	h) Auto	N/A	N/A N/A	N/A	
	starting/Manual			N/A	
	stopping				
	2) Terrace level				
	a) Discharge of pump	225 LPM	225 LPM		
	b) Head of pump	30 mtr.	30 mtr.	MR	
	c) Power supply	Required	Provided	MR	
	d) Auto starting of	Required	Provided	MR	
14.	pump			MR	
14.	Captive Water Storage for Fire Fighting				
	1) Under ground tank	N/A	N/A	NI/A	
	capacity			N/A	
	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A N/A	
	c) Access to tank	N/A	N/A	11/2	

~ NT/45 .

/	N	4	6	1
-		.,		

	d) Over head tank	2500 ltr.	2500 ltr.	MR
	capacity	Required	Provided	MR
E	Exit Signage.	Requires		
. F	a) Pressurization of lift	N/A	N/A	N/A
-	shaft b) Pressurization of lift	N/A	N/A	N/A
-	lobby c) Communication in lift	N/A	N/A	N/A
	car d) Fireman's switch	N/A	N/A	N/A
		N/A	N/A	N/A
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Refuge Area	N/A N/A	N/A	N/A
	Total area location			N/A
10	Fire Control Room	N/A	N/A	N/A
19.	a) Detector system panel	N/A	N/A	
		· N/A	N/A	N/A
	b) Flow switch panel	N/A N/A	N/A	N/A
	c) PA system panel d) Battery backup	N/A N/A	N/A	N/A
	D. 111 a floor plan	N/A	N/A	N/A
20.	e) Building floor plan Special Fire Protection Syst Risk, if any:	em for Prote	ction of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection. Also owner/Occupier has submitted an affidavit

In view of the deemed compliance of the minimum standards of fire prevention not to use above third floor. and fire safety measures as required under the rules the FSC issued vide letter no. DFS/MS/GH/2019/2318 dated 13/12/19, renewal under Rule 35 of the Delhi Fire Service Rules 2010, is recommended for approval up to second floor.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

Kiv Juppipu S (MDZ) ADD/CC) Arc Epoins FT putup for spended our Anolus Apen fi Riv falapping (9/3/22)