GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No. F6/DFS/MS/WZ/2022/CNG

FIRE SAFETY CERTIFICATE

Certified that the CNG Station Located at Rohtak Road (Near Electricity Colony) Delhi owned / occupied by Indraprastha Gas Limited was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/2019/CNG/1407 Dated 10.07.2019. The said premise was re-inspected by the officer concerned of this department on 16.09.2022 in the presence of Sh. Sachin (G.E.T.) and found that the premises/building have deemed complied with the fire prevention and fire safety requirements in accordance with the rule 33 of the Delhi Fire Service Rules, 2010 and that the premises/building is fit for occupancy class 'Hazardous Building' Group - J with effect from $\frac{98/05/3022}{05/3022}$ for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on ._at New Delhi by.

(Dharampal Bhardwaj) Dy. Chief Fire Officer (West Zone)

Copy to: -

1. Sh. Ajay Khatri, DGM (Fire & Safety), IGL Bhawan, Plot no. 4, Community Centre, Sector-9, R.K. Puram, New Delhi-110022.

Conditions for the validity of Fire Safety Certificate:-

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner /occupier shall submit a declaration every year in form 'K provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <u>www.dfs.delhigovt.nic.in</u>
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of authorized construction or alteration (Clause of 1.4.3 of UBBL-2016), if any.
- The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form J (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

Dated: 28/09/2029

1.	_	0	INSP	PECTION REPORT				
N	Van	ne 8	Address of the Building	CNG Station, Rohtak R	oad (Near Flectricity	Colores) D. H.		
2 1	Evn	e of	Occupancy	110041	(real Licethelly	Colony) Delhi-		
			Case	Hazardous'Group-"J				
	. 1		of Previous NOC	Renewal				
				F6/DFS/MS/2019/CNG/1407 dated 10.07.2019				
			fety Directives Letter No	OISD 179				
			Inspection	16.09.2022				
			of the Inspecting Officers	Aman Kumar Lathar, A				
8	Na	ne	& Designation of Officers	Sh. Sachin (G.E.T.)				
9	Iro. Ve	n ti	ne building side	2000				
10		-						
		pplicant letter No. Ainimum standards on Fire		IGL/F&S/2022/15/91/2 dated 24.08.2022				
S. No	M Pr			BBL/NBC-IV/OISD	Provided at	Remarks		
	11	1 ve	ntion and Fire Safety U/R 33	Requirements/as per	Site	NR/NMR		
1	A .	000	to Duild'	FSC dated 10.07.2019				
1	A	+	ss to Building.					
		•	Road width	6 m	30 m	MR		
		۰	Gate width	Required	Abot on Road	MR		
-	-	•	Width of internal road	-N/A-	-N/A-	-N/A-		
2			iber, width, type & arrangement	of exits.				
	a	-	Number of Staircase					
			Upper floors.	-N/A-	-N/A-	-N/A-		
	_	-	Basement floor.	-N/A-	-N/A-	-N/A-		
	ł	<u> </u>	Width of Staircase					
			Upper floors	-N/A-	-N/A-	-N/A-		
			Basement floor	-N/A-	-N/A-	-N/A-		
		c)	Protection of exits					
			 Fire check door 	-N/A-	-N/A-	-N/A-		
			Pressurization	-N/A-	-N/A-	-N/A-		
		d)	No. of continuous staircase to terrace	-N/A-	-N/A-	-N/A-		
	ŀ	e)	Width of corridor	-N/A-	-N/A-	-N/A-		
		f)	Door size	01 m	Provided	MR		
	3	'	mpartmentation.	0.1.11	Tiovided	IVIIX		
			Fire check door.	-N/A-	-N/A-	-N/A-		
			 Scaling of electrical shafts 		-N/A-	-N/A-		
			• Fire rating of shaft door.	-N/A-	-N/A-	-N/A-		
			Water curtain	-N/A-	-N/A-	-N/A-		
			• Fire dampers.	-N/A-	-N/A-	-N/A-		
	4.	Sı	noke Management system.					
		1	Basement	-N/A-	-N/A-	-N/A-		
			• Upper floors	-N/A-	-N/A-	-N/A-		
	5.	F	ire Extinguishers.					
			Total numbers	14 nos.	30 nos.	MR		
			TypesISI Marking	DCP & CO ₂	DCP 75 kg wheel mounted- 06 Nos. DCP 9 kg $-$ 20 Nos. CO ₂ 4.5 kg $-$ 04 Nos.	MR		
				ISI marked	Provided	MR		

. F	First Aid Hose Reels.						
	• Total numbers on each floor	-N/A-	-N/A-	-N/A-			
	• Length of hose-reel hose.	-N/A-	-N/A-	-N/A-			
	Nozzle Diameter	-N/A-	-N/A-	-N/A-			
7 /	Automatic fire detection & alarming system.						
	Type of detectors	Gas & Flame	Provided in	MR			
		detector	compressor	WIK			
	 Location of Main Panel 	-N/A-	-N/A-	-N/A-			
	 Location of Repeater Panel 	-N/A-	-N/A-	-N/A-			
	 Alternate source of power Hooter's location 	-N/A-	-N/A-	-N/A-			
	Hooter's location	-N/A-	-N/A-	-N/A-			
8. 1	MOEFA	Required	Provided	MR			
9.	Public Address System	-N/A-	-N/A-	-N/A-			
	CO ₂ flooding system						
	Ground Floor.	Required in	Provided	MR			
		compressor area	Trovided	IVIIX			
	• Upper floors	-N/A-	-N/A-	-N/A-			
	• Sprinkler above false ceiling	-NA-	-NA-	-NA-			
11.	Internal Hydrants.						
	• Size of Riser / Down-comer	-N/A-	-N/A-	-N/A-			
	 Number of Hydrant per floor 	-N/A-	-N/A-	-N/A-			
	• Hose box.	-N/A-	-N/A-	-N/A-			
12.	Yard Hydrants.						
	• Total number of hydrants.	-N/A-	-N/A-	-N/A-			
	• Hose box.	-N/A-	-N/A-	-N/A-			
13.							
	Ground Level						
	Discharge of main pump.	-N/A-	-N/A-	-N/A-			
	Head of main pump.	-N/A-	-N/A-	-N/A-			
	 Number of main pumps. Jockey Pump output. 	-N/A-	-N/A-	-N/A-			
	 Jockey Pump boulput. Jockey Pump head. 	-N/A-	-N/A-	-N/A-			
	 Standby Pump output. 	-N/A-	-N/A-	-N/A-			
	> Standby Pump head.	-N/A-	-N/A-	-N/A-			
	 Auto Starting/Manual stopping. 	-N/A-	-N/A-	-N/A-			
	Pump house access.	-N/A-	-N/A-	-N/A-			
		-N/A-	-N/A-	-N/A-			
	Terrace Level	21/4	N1/A	NT/A			
	 Discharge of pump. Used of pump. 	-N/A- -N/A-	-N/A- -N/A-	-N/A- -N/A-			
	Head of pump.Power supply.	-N/A-	-N/A-	-N/A-			
	 Auto starting of pump. 	-N/A-	-N/A-	-N/A-			
14.							
14.	• Underground tank capacity.	-N/A-	-N/A-	-N/A-			
	Draw-off connection.	-N/A-	-N/A-	-N/A-			
	Fire Service Inlet.	-N/A-	-N/A-	-N/A-			
	Access to tank.	-N/A-	-N/A-	-N/A-			
	• Overhead tank capacity.	-N/A-	-N/A-	-N/A-			
15	Exit Signage	Required	Provided	MR			
15.	Exit Signage						
1							

6.

111	16. Provision of Lifts.							
F	• Pressurization of fift shaft.	-N/A-	-N/A-	-N/A-				
	 Pressurization of lift lobby, Communication in lift car. Fireman's switch. Lift signage. 	-N/A-	-N/A-	-N/A-				
		-N/A-	-N/A-	-N/A-				
		-N/A-	-N/A-	-N/A-				
		-N/Λ-	-N/A-	-N/A-				
17	7 Standby Power Supply	Required	Provided	MR				
18.	Refuge Area							
	Total area	-N/A-	-N/A-	-N/Λ-				
	 Location 	-N/A-	-N/A-	-N/A-				
19.	Fire Control Room.							
	• Detector System Panel.	-N/A-	-N/A-	-N/A-				
	Flow Switch Panel.	-N/A-	-N/A-	-N/A-				
	• PA system Panel.	N/Λ-	N/A-	N/Λ-				
	 Battery backup Building floor plan 	-N/Λ-	-N/A-	-N/A-				
	• Building floor plan	-N/A-	-N/A-	-N/A-				
20.	Special Fire Protection System for the Protection of special Risk, if an	r	DCP Flooding in cascade, CO ₂ Flooding in Compressor & in addition 01 Generator operated water cum form mist trolley	MR				

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Note: - CNG Station running with 02 nos. Cascade, 02 nos. compressor & 06 nos. Dispenser.

In View of the deemed compliance of the minimum standards of fire prevention and fire safety requirements under the rules, renewal of FSC issued vide letter no. F6/DFS/MS/2019/CNG/1407 dated 10.07.2019 is recommended under the rule 37 of the Delhi Fire Service rule, 2010 under the DFS Act 2009.

Accordingly DEA is put up for approval and signature please.

Aman Kur ADO (JWP)

I.D.C. (NEST), 429

(W)

ØØ

·N/ ·N/A·

MR

W2 Fif letter is met-up for rignature pl. ECTO (W2)