## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE

NEW DELHI- 110001 0.F6/DFS/MS/School/2022/SZ/ { 0 88

Dated: 28/8/22

## FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Kanya Vidyalaya, Rajouri Garden Main, New Delhi-110027, Comprised of ground plus two upper floors (A- Block), owned/occupied by Sarvodaya Kanya Vidyalaya have complied with the fire prevention and fire safety requirements in accordance with the Rules 33 of the Delhi Fire Service Rules 2010 and verified by the officer concerned of this department on 15/09/2022 in the presence of Sh. Jeet (Estate Manager) and found that the school building (A Block only) is fit for occupancy class B 'Educational Building' for with effect from 29.1.9.1.2.2.for a period of three years in accordance with the Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on.....at New Delhi by

Director Delhi Fire Service

Copy to:-

- 1. The Principal, Sarvodaya Kanya Vidyalaya, Rajouri Garden Main, New Delhi.
- 2. Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054.

Following fire safety directives must be adhered to:-

- 1. This NOC is valid for A- block only.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 3. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 4. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 5. The trained staff should be available round the clock.

1

- 6. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 7. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <u>www.dfs.delhigovt.nic.in</u>.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

			NICY							
	1	INSPECTION	REPORT							
		Name & address of the building : Sarvodaya Kanya Vidyalaya, Rajouri Garden Main, New Delhi-27								
1	2. Bu									
	3. Ty	pe of Occupancy : Educationa		FSC)						
		pe of Case : New	11							
		tails of Previous NOC N/A								
(	6. Fir	e Safety directives letter No : N/A								
	7. Date of inspection : 15/09/2022									
	8. Name of Inspecting Officer : A.D.O.R.K.Yaday									
1		me and designation of officers								
			Estate Manager)							
		ear of Construction : 1956 & bo								
	11. Applicant's letter No. : Nil dated 10/08/2022 Minimum Standards on fire prevention and NBC/ Dt. of cdu. Provided at Remarks									
No.		imum Standards on fire prevention and	NBC/ Dt. of edu. Requirement	Provided at site	MR/NMR					
	1	safety U/R 33 ess to building	Requirement	site						
	Acc	Road width	Accessible	09 mtrs	M/R					
		Gate width	100031010	3.8 & 7.5 mtrs						
		Width of internal road								
	N	nber, Width, Type & Arrangement of Exit	S							
		umber of staircases								
		Upper Floors	02 No's in A	02 No's in A	M/R					
		Basements	Blk,	Blk						
			$N/\Lambda$	$N/\Lambda$	N/A					
	b.	Width of staircases								
		Upper Floor	1.5 m cach	1.60 m each	M/R					
		Basements	$N/\Lambda$	$N/\Lambda$	$N/\Lambda$					
		Protection of exits		-						
	c.	Fire check door	N/A	N/A	N/A					
		<ul> <li>Pressurization</li> </ul>	N/A	N/A	N/A					
		• Tressurization	IN/ A							
				One	N/A					
	d.	No. of continuous staircases to	N/A		M/R					
		terrace	1.5 m	3.15 m in A Blk	1v1/1X					
	e.	Width of Corridor	1.0 m	1.05 m	M/R					
			1.0 m	(Double doors)						
	f.	Door Size			-					
,		ompartmentation								
3.	C	-	$N/\Lambda$	N/A	N/A					
		<ul><li>Fire check door</li><li>Sealing of electrical shafts</li></ul>	$N/\Delta$	$N/\Lambda$	N/A					
		<ul> <li>Scaling of electrical strates</li> <li>Fire Rating of shaft door</li> </ul>		N/A	N/A					
		<ul> <li>Fire Rating of shart door</li> <li>Water Curtain</li> </ul>	N/A		N/A					
		E' D	$N/\Lambda$	N/A	N/A N/A					
		• Fire Dampers	N/A	N/A	IN/A					
4	e	moke Management System								
4.	3		$N/\Lambda$	$N/\Lambda$	$N/\Lambda$					
		Basements	N/A	Natural	N/A					
		• Upper floors		ventilation	1					
5.	ŀ	ire Extinguishers	45 no's	Provided	M/R					
		Total numbers	ABC/CO2 typ	·	M/R					
		• Types								
		IS marking	ISI marked	ISI markee						
		First-Aid Hose Reels (A Block)	the second s		M/F					
6.		Total numbers on each floor	Two	Provided						
		<ul> <li>Length of hose reel hose</li> </ul>	30 mtrs	Provided						
		<ul> <li>Nozzle diameter</li> </ul>	5 mm	Provided	M/I					

١

2

I

ι

:1

1 c

	<ul> <li>Type of detectors</li> </ul>	N/A	N/A	
	<ul> <li>Location of Main Panel</li> </ul>	N/A	$N/\Lambda$	
	<ul> <li>Location of Repeater Panel</li> </ul>	N/A	N/A	
	<ul> <li>Alternate source of power</li> </ul>	N/A	N/A	
	<ul> <li>Hooters' Location</li> </ul>	N/A	N/A	
	MOEFA	N/A	N/A	
	Public Address System	N/A	Provided	
	Automatic Sprinkler System		Trovided	1
	• Basement	Ñ/Λ	N/A	N
	Ground Floor	N/A	N/A	Ν
	<ul> <li>Sprinkler above false ceiling</li> </ul>	N/A	N/A	N
	Internal Hydrants	N/A	N/A	
	<ul> <li>Size of riser/down-comer</li> </ul>	N/A	100	
	<ul> <li>Number of hydrants per floor</li> </ul>	N/A N/A	100 mm Two	M
	<ul> <li>Number of hydrants per floor</li> <li>Hose Box</li> </ul>	$\frac{N/\Lambda}{N/\Lambda}$		M
	Yard Hydrants	N/A	Two	M
	Total number of hydrapts	<b>1</b> 11		
	<ul><li>Total number of hydrants</li><li>Hose Box</li></ul>	N/A	N/A	N/.
	Pumping Arrangements	N/A	N/A	N/
	Ground Level		1	
	<ul> <li>Ground Level</li> <li>Discharge of main Pump</li> </ul>	N1/ A	NUA	
	<ul> <li>Head of Main pump</li> </ul>	N/A	N/A	N/
	<ul> <li>Number of main pumps</li> </ul>	N/A	N/A	N//
	Jockey Pump out put	N/A	N/A	N/M
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	$N/\Lambda$	N/A	N/A
	Standby Pump Head Auto Starting/Manual Starping	N/A	N/A	$N/\Lambda$
	Auto Starting/Manual Stopping	N/A	N/A	NA
		N/A	N/A	NA
	Pump House Access	N/A	N/A	NA
	Terrace level     Discharge of nump	450 LPM	Provided	MR
	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> </ul>	30 m	Provided	MR
	<ul> <li>Power Supply</li> </ul>	N/A	N/A	NA
	Auto Starting of pump	Required	Provided	MR
		1		
	Captive Water Storage for fire fighting	N/A	N/A	
	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> </ul>	N/A	N/A	N/A
	<ul> <li>Fire service inlet</li> </ul>	N/A	N/A	N/A
	Access to tank	N/A	N/A	N/A
	Overhead Tank capacity	10,000 ltrs	Provided	M/R
		Required	Provided	M/R
5.	Exit Signage.			
				0.16
5.	Provision of Lifts.	N/A	N/A	(No Lift) N/A
	<ul> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift Johny</li> </ul>	N/A		N/A
	<ul><li> Pressurization of Lift lobby</li><li> Communication In lift Car</li></ul>	N/A N/A	N/A N/A	N/A N/A
		N/A		N/A
	<ul> <li>Fireman's Grounding Switch</li> </ul>			
	<ul><li>Fireman's Grounding Switch</li><li>Lift Signage</li></ul>	N/A	N/A .	-
		N/A N/A N/A	N/A N/A N/A	- N/A N/A

MIS

14

ó.

Standby power supply 17.

> Refuge Area. 4

18.

		MLG		
	Total Area	$N/\Lambda$	$N/\Lambda$	$N/\Lambda$
^	Location	$N/\Lambda$	$N/\Lambda$	$N/\Lambda$
N Ng.	Fire Control Room	$N/\Lambda$	N/A	N/A
19.	<ul><li>Detector System Panel</li><li>Flow Switch Panel</li></ul>	$N/\Lambda$	$N/\Lambda$	$N/\Lambda$
	<ul><li>Providence</li><li>PA System Panel</li></ul>	$N/\Lambda$	N/A	$N/\Lambda$
	Battery backup	$N/\Lambda$	$N/\Lambda$	N/A
	Building Floor Plans	$N/\Lambda$	$N/\Lambda$	N/A
20.	Special Fire Protection System for Protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were tested, checked and found not functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety as required under the Rule 35 of the Delhi Fire Service Rules 2010 it is recommended to grant Fire Safety Certificate.

This FSC's for ARechonly Gt27 Signature of Inspecting :- R.K.Yadav Name Designation:- Asstt. Divisional Officer D.O. (South West) 20/9/22 91 29 Directo w an 26/9 JAX POR) ADO