

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/2022/SZ/ 478

Dated: **3**0 109 12022

## FIRE SAFETY CERTIFICATE

building located at Okhla Phase-III, New Delhi-110020, comprised of Six Blocks (Residential Block: Stilt + 11 upper floors, Academic Block: Ground + 5 upper floors, Boys Hostel Block: Ground + 5 upper floors, Girls Hostel Block: Ground + 4 upper floors, Dining Block: Ground + 3 upper floors & Library Block: Ground + 3 upper floors) owned/occupied by Govt. of NCT of Delhi was issued FSC by this department vide letter No. F.6/DFS/MS/2019/SZ/1612 dated 13/08/2019. The premise was re-inspected by officer concerned of this department on 19/09/2022 in the presence of Mr. Ashok Kumar Solanki and found to have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for class "Mixed Occupancy" with effect from 30/09/2022 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 30/05/2022 at New Delhi by

Copy to: -

 Sh. Arun Verma (Estate Officer), Indraprastha Institute of Information Technology, Delhi, Okhla Phase–III, New Delhi–110 020

## Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

M)15



1	INSPECTIO	N DEPODT				
1	Name & Address of the Building		Comme			
/ ·		M/s IIIT Delhi, Campus extension of G.B. Pant				
2	Type of Occupancy	Polytechnic campus building, Okhla Ph–III, ND-20 Mixed Occupancy				
3	Building Comprised of	Residential Blk: Stilt + 11 upper floors, Academ				
		Blk: G+5, Boy	s Hostel Blk: G+5,	Girls Hos	tel Blk	
	Towns	G+4, Dining B	lk: G+3 & Library E	3lk: G+3	+3	
4	Type of Case	Renewal				
5	Details of Previous NOC		019/SZ/1612 dated			
6	Fire Safety Directives Letter No	F.6/DFS/MS/E	3P/2010/1049 dated	15-04-201	0	
8	Date of Inspection	19-09-2022				
9	Name of the Inspecting Officers		mar, ADO (BCP)			
7	Name & Designation of Officers from the building side	Mr. Ashok Ku	mar Solanki			
10	Year of construction	2012				
11	Applicant letter No.	2012	N. 4270 1 . 116/0	0/2022		
S. No.	Minimum standards on Fire Prevention	Outdoor diary No. 4378 dated 16/08/2022  As Per old NOC   Provided at Site   Remarks			marke	
3. 7.0.	and Fire Safety U/R 33	Requirements			Remarks MR/NMR	
1	Access to Building.	- requirement		IVIII	UI VIVEI	
	Road width	12 mtr	Provided		MR	
	Gate width	6 mtr	Provided		MR	
	Width of internal road	6 mtr	Provided		MR	
2			11011464			
	Number, width, type & arrangement of ex  a) Number of Staircase	its.				
	> Upper floors.	Resdl Blk= 2nos.	Academic Blk= 5nos			
	p opper noors.	(GF-Terr.=2no, C	F-FF=1no, FF-Terr.=	Provided	MR	
		Ino, GF-SF= Ino & Ino ramp GF-SF) Boys Hostel=5nos., Girls Hostel=4nos.,			1,11	
		Dining Blk=3nos, Library Blk=2nos			27/4	
	Basement floor.	N/A N/A N/A			N/A	
	b) Width of Staircase	1.50 (	1.50m (each)		MR	
	> Upper floors	1.50m (each) N/A	N/A		N/A	
	Basement floor	IN/A	1071			
	c) Protection of exits  > Fire check door	Required	Provided		MR	
	> Pressurization	N/A	N/A		N/A	
	d) No. of continuous staircase to terrace	Required	17 Nos provid	ed	MR	
	e) Width of corridor	Required	1.5m		MR	
	f) Door size	Required	1.5m		MR	
3	Compartmentation.				\ (D)	
	Fire check door.	Required	Provided		MR	
	<ul> <li>Sealing of electrical shafts.</li> </ul>	Required	Provided		MR	
	• Fire rating of shaft door.	Required	Provided		MR	
	Water curtain	N/A	N/A		N/A	
	Fire dampers.	Required	Provided		MR	
	-					
4	Smoke Management system.  Basement	30 ACPH	N/A		N/A	
		12 ACPH	Natural Ventila	tion	MR	
	Upper floors					
5	Fire Extinguishers.		263 Nos		MR	
	Total numbers	ISI marked	ABC & CO	ABC & CO <sub>2</sub>		
	• Types	101 markou	Provided		MR	
	ISI Marking	11041000				
6	First Aid Hose Reels.	1	Resdl Blk=1no, Acad.	Blk=5 no,		
	Total numbers on each floor.		Boys HB=5nos., Girls !	HB=4 nos.	MF	
		Hose Reel	Dining Blk=3nos, Lib.	.Blk=1no	) (T	
		1103C ICCCI				
	<ul> <li>Length of hose-reel hose.</li> </ul>	Tiose Reel	30m 5mm		MR	

M/s IIIT Delhi, Campus extension of G.B. Pant Polytechnic campus building, Okhla Phase-III, New Delhi

1/10

Type of detectors  Required  Location of Main Panel  Location of Repeater Panel  Alternate source of power  Hooter's location  Required  Required  Required  Required  Provided  Manuel  Required  Provided  Manuel  Required  Required  Provided  Manuel  Required			,			
Tope of detectors      Location of Main Panel     Location of Repeater Panel     Alternate source of power     Alternate source of power of power of provided of power     Alternate source of power of po	7	Automatic fire detection & alarming s	system.			
Location of Repeater Panel   Alternate source of power   Hooter's location   Required   Provided   M   Moret   Provided   M   Required   Provided   M   Required   Provided   M   Required   Provided   M   M   Required   Provided   M   M   M   N/A   N   M   M   M   M   M   M   M   M   M		Type of detectors	Required Smoke & Heat in all bloc except in Residential blo		ocks lock	M
Alternate source of power			The second secon			M
Hooter's location						M
8 MOFFA 9 Public Address System 10 Automatic Sprinkler System  • Basemen • Upper floors • Sprinkler above false ceiling N/A N/A N/A N/A NIA NIA NIA NIA NIA NIA NIA NIA NIA NI						M
9 Public Address System 10 Automatic Sprinkler System  • Basement • Upper floors • Sprinkler above false ceiling 11 Internal Hydrants. • Size of Riser/Down-comer • Number of Hydrant per floor  • Hose box.  • Hose box.  12 Yard Hydrants. • Total number of hydrants • Hose box.  13 Pumping arrangements. • Ground Level  > Discharge of main pump. > Jockey Pump head. > Standby Pump head. > Auto Staring/Manual Stopping. > Pump head of pump. > Power supply. > Pressurization of lift shaft. > Access to tank • Pressurization of lift shaft. • Fire Service late. • Fire Service late. • Fire Service	8		the same of the sa			Mi
Automatic Sprinkler System   Basement   Basement   Upper floors   Upper floors   Sprinkler above false ceiling   N/A						MI
Basement   Upper floors   Sprinkler above false ceiling   N/A			Require	ed Provided		MF
Upper floors   Sprinkler above false ceiling   N/A   N/A   N/A   N/A			NI/A			
Sprinkler above false ceiling  N/A  Internal Hydrants.  Size of Riser/Down-comer  Number of Hydrant per floor  Hose box.  12 Yard Hydrants.  Total number of hydrants.  Total number o				N/A		N/A
Internal Hydrants.   Size of Riser/Down-comer   100 mm   Provided   Miles of Required   Resi Bik-Ino, Acad Bik-5 nos, Boys HB-5nos, Girls HB-4 nos Drining Bik-5nos, Lib Bik-Ino Resi Bik-Ino, Acad Bik-5 nos, Boys HB-5nos, Girls HB-4 nos Drining Bik-5nos, Lib Bik-Ino Resi Bik-Ino, Acad Bik-5 nos, Boys HB-5nos, Girls HB-4 nos Drining Bik-5nos, Lib Bik-Ino Resi Bik-Ino, Acad Bik-5 nos, Boys HB-5nos, Girls HB-4 nos Drining Bik-5nos, Lib Bik-Ino Resi Bik-Ino, Acad Bik-5 nos, Boys HB-5nos, Girls HB-4 nos Drining Bik-5nos, Lib Bik-Ino Resi Bik-Ino, Acad Bik-5 nos, Boys HB-5nos, Girls HB-4 nos Drining Bik-5nos, Lib Bik-Ino Resi					Blk	MR
Size of Riser/Down-comer Number of Hydrant per floor  Number of Hydrant per floor  Hose box.  Hose box.  Provided Required Resi Bik—Ino, Acad Bik—5 nos, Boys HB—5 nos, Girls HB—4 nos Diming Bik—3 nos, Lib Bik—Ino Resi Bik—Ino, Acad Bik—5 nos, Boys HB—5 nos, Girls HB—4 nos Diming Bik—3 nos, Lib Bik—Ino Resi Bik—1 no, Acad Bik—5 nos, Boys HB—5 nos, Girls HB—4 nos Diming Bik—3 nos, Lib Bik—Ino Resi Bik—1 no, Acad Bik—5 nos, Boys HB—5 nos, Girls HB—4 nos Diming Bik—3 nos, Lib Bik—Ino Resi Bik—1 no, Acad Bik—5 nos, Boys HB—5 nos, Girls HB—1 nos Diming Bik—3 nos, Lib Bik—Ino Resi Bik—1 no, Acad Bik—5 nos, Boys HB—5 nos, Girls HB—1 nos Diming Bik—3 nos, Lib Bik—Ino Resi Bik—1 no, Acad Bik—5 nos, Boys HB—5 nos, Girls HB—1 nos Diming Bik—3 nos, Lib Bik—Ino Resi Bik—1 no, Acad Bik—5 nos, Boys HB—5 n	11		IVA	N/A		N/A
Number of Hydrant per floor      Number of Hydrants.      Number of Hydrants.      Total number of hydrants.     Number of Hydrants.      Total number of hydrants.     Number of Mydrants.      Number o			100 mm			
Hose box.  Hose box.  Provided   MR   MR   MR   MR   MR   MR   MR   M		or Albert Bown-conici	100 11111	Provided		MF
Hose box.   Required   Rest. Bik-Ino, Acad Bik-5 nos. Girls Bit-3 nos. Lib Bik-1 nos Diming Bik-3 nos. Robert Diming Bick & 0 Ino 2280 LPM Gro Boys, Girls Hostel, Diming block & 0 Ino 2280 LPM Gro Boys, Girls Bis Level Diming Bick & 0 Ino 180 LPM Ilom (each) MR Required Diming Bick & 0 Ino 180 LPM Ilom (each) MR Required Diming Bick & 0 Ino 180 LPM Gro Boys, Girls Bis Lib		Number of Hydrant per floor	Required	Boys HB=5nos., Girls HB=4 Dining Blk=3nos. Lib. Blk=	4 nos.	MR
Total number of hydrants. Hose box.  Total number of hydrants. Hose box.  Pumping arrangements.  Ground Level  Head of main pump. Head of main pumps. Jockey Pump head. Standby Pump output. Standby Pump output. Standby Pump head. Pump house access. Terrace Level  Head of pump. Pump house access. Terrace Level  Discharge of pump.  Head of pump. Pump house access. Terrace Level  Discharge of pump.  Head of main pumps.  Auto Starting/Manual Stopping. Pump house access.  Terrace Level  Discharge of pump.  Head of main pumps.  Auto Starting/Manual Stopping. Pump house access.  Terrace Level  Discharge of pump.  Head of main pumps.  Auto Starting/Manual Stopping. Pump house access.  Terrace Level  Discharge of pump.  Head of main pumps.  Auto Starting/Manual Stopping. Power supply. Auto starting of pump.  Required Provided MR Required Provided	12		Required	Resi. Blk=1no, Acad. Blk=5 Boys HB=5nos., Girls HB=4	nos.,	MR
Name	12			J. Hoo, Dio, Dik	1110	
13 Pumping arrangements.			28 Nos	Provided		MD
Fumping arrangements.   Solution   Solutio	12		28 Nos			_
Discharge of main pump.   2850 LPM   2nos. 2850 LPM for Boys, Girls Hostel, Dining block & 01 no 2280 LPM for Acad. Lib & Resi block LPM for Boys, Girls 110stel, Dining block & 01 no 180 LPM for Boys, Girls 110stel, Dining block & 01 no 180 LPM for Boys, Girls 110stel, Dining block & 01 no 180 LPM for Acad. Lib & Resi block LPM for Boys, Girls 110stel, Dining block & 01 no 180 LPM for Acad. Lib & Resi block LPM for Boys, Girls 110stel, Dining block & 01 no 180 LPM for Acad. Lib & Resi block LPM for Boys, Girls 110stel, Dining block & 01 no 180 LPM for Acad. Lib & Resi block LPM for Boys, Girls 110stel, Dining block & 01 no 180 LPM for Boys, Girls	13					IVIIC
Head of main pump.  Head of main pump.  Number of main pumps.  Jockey Pump nead.  Standby Pump output.  Standby Pump head.  Head of pump.  Pump house access.  Pump house access.  Terrace Level  Discharge of pump.  Head of pump.  Auto starting of pump.  Head of pump.  Power supply.  Auto starting of pump.  Power supply.  Power-off connection.  Fire Service Inlet.  Access to tank.  Overhead tank capacity.  Power-off connection.  Fire Service Inlet.  Access to tank.  Overhead tank capacity.  Provided  Provided  MR  Required						
Number of main pump.   Number of main pumps.   Number of main pumps.   2 Nos   3 Nos   3 Nos   200s. ISD LPM for Boys. Girls   180 LPM   110m (each)   MR   180 LPM   110m (each)   MR				Hostel, Dining block & 01no 22	280	MR
Jockey Pump output.    180 LPM						MR
Sockey Pump output.   180 LPM   180 t.PM   110stcl, Dining block & Olno 180 LPM (provided provided provided provided mix power supply.   2850 LPM (2850 LP		Number of main pumps.	2 Nos			MR
Scandby Pump output.   Standby Pump phead.   Standby Pump phead.   Standby Pump head.   Auto Starting/Manual Stopping.   Pump house access.   Pump house access.   Required   Provided   MR   Required   Provided   MR   Required   Provided   MR   Provided   Provided   MR   Provided   Provided   MR   Provided   Provided   MR   Provided   Provi		Jockey Pump output.	180 LPM	Hostel, Dining block & 01no 18	30	
Standby Pump head.  Standby Pump head. Auto Starting/Manual Stopping. Pump house access.  Terrace Level  Discharge of pump.  Head of pump. Power supply. Auto starting of pump.  Underground tank capacity. Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Provided Required Provided Provided MR Required Provided MR		Jockey Pump head.	Required		-	MR
Auto Starting/Manual Stopping. Pump house access.  Terrace Level  Discharge of pump.  Head of pump. Power supply. Auto starting of pump.  Underground tank capacity. Fire Service Inlet. Access to tank. Overhead tank capacity. Overhead tank capacity. Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift car. Fireman's switch. Lift signage. Provided MR Required Provided MR		Standby Pump output.		2850 LPM (2 Nos)		
Pump house access.  Required Provided MR  Terrace Level  Discharge of pump.  Resi. Blk=900 LPM Other Blk=450 LPM x 3nos each MR  Required Provided Provided MR  Required Provided MR  Captive water storage for fire fighting.  Underground tank capacity. Pire Service Inlet. Provided MR  Required Provided MR		Standby Pump head.		110m (each)		MR
• Terrace Level  → Discharge of pump.  → Head of pump.  → Power supply.  → Auto starting of pump.  ● Underground tank capacity.  → Draw-off connection.  → Fire Service Inlet.  → Access to tank.  ● Overhead tank capacity.  ■ Overhead tank capacity.  ■ Provision of Lifts.  ● Pressurization of lift shaft.  ● Lift signage.  17 Standby Power Supply  ■ Total area  ● Total area		Auto Starting/Manual Stopping.				MR
Discharge of pump.   Resi. Blk=900 LPM   Other Blk=450 LPM   A 50 & 180 LPM x 3nos each   MR			Required	Provided		MR
Head of pump.   Required   Between 80m to 55m   MR						MR
Power supply. Auto starting of pump.  Captive water storage for fire fighting.  Underground tank capacity. Fire Service Inlet. Access to tank. Overhead tank capacity.  Provided Provided Provided NIR Required Provided NIR NIR  Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. N/A Pressurization of lift car. Prireman's switch. Fireman's switch. Required Provided NIR N/A N/A N/A N/A N/A N/A Provided MR Required Provided MR N/A						MR
14 Captive water storage for fire fighting.  ■ Underground tank capacity.  ⇒ Draw-off connection.  ⇒ Fire Service Inlet.  ⇒ Access to tank.  ● Overhead tank capacity.  15 Exit Signage.  ■ Provision of Lifts.  ■ Pressurization of lift shaft.  ■ Pressurization of lift lobby.  ■ Communication in lift car.  ■ Fireman's switch.  ■ Lift signage.  17 Standby Power Supply  Required Provided MR  Required Provided MR  N/A N/A N/A  Required Provided MR  N/A N/A N/A  Required Provided MR  Refuge Area			Required	Provided	_	
Underground tank capacity.  Draw-off connection.  Fire Service Inlet.  Access to tank.  Overhead tank capacity.  Exit Signage.  Provided  Provided  NIR  Required  Provided  NIR  NIR  Provision of Lifts.  Pressurization of lift shaft.  Pressurization of lift lobby.  Communication in lift car.  Fireman's switch.  Lift signage.  Required  Provided  NIR  Required  Provided  NIR  NIA  NIA  NIA  NIA  NIA  NIA  Required  Provided  NIR  NIA  NIA  NIA  NIA  NIA  Required  Provided  NIR  NIA  NIA  NIA  NIA  NIA  NIA  NIA	14		Required	Provided	1	MR
Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity.  Exit Signage. Provided Provided MR  Required Provided MR  Required Provided MR  Required Provided MR  Required Provided MR  Provided MR  Required Provided MR  Required Provided MR  NA  Pressurization of lift shaft. Pressurization of lift shaft. Pressurization of lift lobby. Pressurization of lift car. Prireman's switch. Fireman's switch. Prireman's switch. Required Provided MR  NA  NA  NA  NA  NA  NA  NA  NA  NA  N	14					
Fire Service Inlet.  Access to tank. Overhead tank capacity.  Exit Signage.  Provided Provided NIR  Required Provided NIR  Required Provided NIR  25,000 Lts each Blk NIR  Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Fireman's switch. Lift signage.  Required Provided NIR  N/A N/A N/A N/A N/A N/A Required Provided NIR  N/A N/A N/A N/A N/A Pressurization of lift lobby. Required Provided NIR  N/A N/A N/A N/A N/A Required Provided NIR  N/A N/A N/A N/A N/A N/A N/A N/A N/A N/						
Access to tank. Overhead tank capacity.  Required Provided NIR  25,000 Lts 25,000 Lts each Blk NIR  Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Required Provided NIR  N/A N/A N/A  Required Provided NIR  N/A N/A N/A  Required Provided NIR  N/A N/A  N/A N/A  Location N/A N/A						
• Overhead tank capacity.  15 Exit Signage.  Provision of Lifts.  • Pressurization of lift shaft. • Pressurization of lift lobby. • Communication in lift car. • Fireman's switch. • Lift signage.  17 Standby Power Supply  Required  • Total area • Total area • Location						
15 Exit Signage.  Required Provided MR  Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Required Provided MR Refuge Area  Total area Total area Location N/A N/A N/A N/A N/A N/A N/A N/A N/A						
16 Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. N/A Pressurization of lift lobby. N/A Communication in lift car. Fireman's switch. Lift signage. Required Provided MR Provided MR Required Provided MR Required Provided MR Required Provided MR Required Provided MR Refuge Area  Provided MR N/A	15					
• Pressurization of lift lobby. • Communication in lift car. • Fireman's switch. • Lift signage.  17 Standby Power Supply  18 Refuge Area  • Total area • Location  • Provided MR  Required Provided MR  Required Provided MR  Required Provided MR  N/A  N/A  N/A  N/A  N/A  N/A	16		required	Tiorided	1411	•
• Pressurization of lift lobby. • Communication in lift car. • Fireman's switch. • Lift signage.  17 Standby Power Supply  18 Refuge Area  • Total area • Location  • Provided MR  Required Provided MR  Required Provided MR  Required Provided MR  N/A  N/A  N/A  N/A  N/A  N/A		<ul> <li>Pressurization of lift shaft.</li> </ul>	N/A	N/A	N/A	1
• Communication in lift car. • Fireman's switch. • Lift signage.  17 Standby Power Supply  Required  • Total area • Location  • Communication in lift car.  Required  Required  Provided  MR  Provided  MR  Provided  MR  Provided  MR  Provided  MR  N/A  N/A  N/A  N/A  N/A		<ul> <li>Pressurization of lift lobby.</li> </ul>			-	
• Fireman's switch. • Lift signage.  Required Provided MR  Required Provided MR  17 Standby Power Supply Required Provided MR  18 Refuge Area  • Total area N/A N/A N/A • Location N/A N/A N/A		<ul> <li>Communication in lift car.</li> </ul>				
• Lift signage.  Required Provided MR  17 Standby Power Supply Required Provided MR  18 Refuge Area  • Total area N/A N/A N/A  • Location N/A N/A N/A		<ul> <li>Fireman's switch.</li> </ul>			The state of the s	-
17         Standby Power Supply         Required         Provided         MR           18         Refuge Area         N/A         N/A         N/A           • Total area         N/A         N/A         N/A           • Location         N/A         N/A         N/A					MR	
18 Refuge Area  • Total area N/A N/A N/A • Location N/Δ N/Δ N/Δ		Standby Power Supply			MR	
• Location N/A N/A	18		1			
• Location N/A N/A			N/A	N/A	N/A	
			N/A	N/A	N/A	

M/s IIIT Delhi, Campus extension of G.B. Pant Polytechnic campus building, Okhla Phase-III, New Delhi



1	Fire Control Room.			
19	<ul> <li>Detector system panel.</li> </ul>	Required	Provided	MR
1	<ul> <li>Flow switch panel.</li> </ul>	N/A	N/A	N/A
1	<ul> <li>PA system panel.</li> </ul>	Required	Provided	MR
	<ul> <li>Battery backup.</li> </ul>	Required	Provided	MR
	<ul> <li>Building floor plan.</li> </ul>	Required	Provided	MR
20	Special Fire Protection System for the	20 Nos CO <sub>2</sub> type fire extinguishers		MR
	Protection of Special Risk, if any.	provided for HT / LT Panel		

M/s IIIT Delhi, Campus extension of G.B. Pant Polytechnic campus building, Okhla Phase-III, New Delhi

The fire protection system provided in the building/ premises were checked, tested at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F.6/DFS/MS/2019/SZ/1612 dated 13-08-2019, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

Dy. CFO (\$Z

 $\widehat{MR}$ MR MR MR MR MR  $\widehat{MR}$ 

As approved f.t. letter is youtry for your synature !!