

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2022/ \\40

Dated: \ \ \ \ \ / \ \ \ /2022

FIRE SAFETY CERTIFICATE

Certified that the M. S. Memorial Public School Located at E-106, Saini Vihar, Laxmi Park, Nangloi, Delhi-110041, comprised of Ground + 03 Upper Floor was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/School/2016/WZ/1244 Dated 08.08.2016. The said premise was re-inspected by the officer concerned of this department on 20.09.2022 in the presence of Sh. Rajeev Saini (Owner) and found that the premises / building have deemed complied with the fire prevention and fire safety requirements in accordance with D.O.E Cr. No. 3298-3398 dated 01.03.2011/NBC (Part-IV) and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 12 10 2021 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010, printed below.

Issued on 12 10 202 Lat New Delhi by.

(Dharampal Bhardwaj)
Dy. Chief Fire Officer
(West Zone)

Copy to: -

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054.

2. The Principal, M. S. Memorial Public School, E-106, Saini Vihar, Laxmi Park, Nangloi, Delhi-110041

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.
- 9. Ms. Shilpa Saini, Manager of M. S. Memorial Public School have submitted an undertaking alongwith photograph that one room on terrace floor is sealed by brick wall & the same will not be opened in future. If it is opened, FSC will be null & void.

INSPECTION REPORT

1 Name & address of the building M. S. Memorial Public School, Located at E-106, Saini Vihar, Laxmi Park, Nangloi, New Delhi-110041.

2. Type of Occupancy

: Educational (G + 03 Upper Floor only)

3. Type of Case

Renewal

4. Details of previous NOC : F6/DFS/MS/School/2016/WZ/1244 dated 08.08 2016

5. Fire Safety directives Letter No : NBC Part-IV

6. Date of inspection

: 20.09.2022

7. Name of the Inspecting Officer: Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side

: Sh. Rajeev Saini (Owner)

9. Year of Construction

: 2006 & 2013-14

10. Applicant's letter No.

: email dated 02.09.2022

S No	Minimum standards on fire prevention and fire safety U/R 33	NBC Requirement /as per FSC dated 08.08.2016		Provided at site	Remarks MR/NMR					
1.	Access of building				MD					
	 Road width 	Accessible		Provided	MR MR NA					
	 Gate width 	Accessible	;]	Provided						
	 Width of internal road 	NΛ		NA	NA					
2.	Number, width, Type & Arrangements of exits									
	a. Number of staircases				N (D (Old Case)					
	 Upper floors 	01		03	MR(Old Case)					
	• Basements	NΛ		NA	NA					
	b. Width of staircases	1.5 m 1.6 m, 1.2 m & 1.10 m MR(Old Ca								
	 Upper floors 	1.5 m	1.6 m, 1	NA 1.10 III	NA					
	Basements	NA		NA	IVA					
	e. Protection of exits	NΛ		NA	NA					
	Fire check door	NΛ	NA		NA					
	 Pressurization d. No of continuous 	01	Provided		MR					
	staircase to terrace	O1		riovided						
	e. Width Of Corridor	1.5mtr		Provided	MR					
	f. Door Size	1mtr		Provided	MR					
3	Compartmentation									
	Fire check door	NΛ		NA	NA					
	 Sealing of electrical shafts 	NΛ		NA	NA					
	 Fire Rating of shaft door 	NΛ		NA	NA					
	 Water Curtain 	NΛ		NA	NA					
	 Fire Dampers 	NΛ		NA	NA					
4.	Smoke managements System				N. A					
	 Basements 	NΛ		NA NA	NA NA					
	 Upper floors 	NΛ		NA	. N/A					
5.	Fire Extinguishers	00 20		12 nos.	MR					
	 Total numbers 	09 nos. ABC &	.1	Provided	MR					
	TypesIS marking	CO_2 ISI marked		Provided	MR					
		Qe								

		, 0, 4			
- I-1	rst Aid Hose Reels				MR
	 Lotal numbers on each floor 	0.1		Provided	MR
	 Length of hose reel hose 	30m		Provided	MR
	Nozzle diameter	5mm		Provided	VIII
	utomatic fire detection and alarming s	system			NA
	6.1.4.4.4.	NA		NA	NA
	 Type of defectors Location of Main Panel 	NA		NΛ	NA
		NA		NΛ	
	Location of Repeater Panel	NA		NA	NA
	Alternate source of power	NA		NA	NA
	 Hooters' Location 	NA		NA	NA
	4OLFA	NA		NA	NA
	Public Address System				
0. A	Automatic Sprinkler System	NA		NA	NA
	 Basements 	NA		NA	NA
	 Upper Hoor 			NA	NA
	 Sprinkler above false ceiling 	\sim		1171	
1. I	nternal Hydrants:			NA	NA
	 Size of riser/down-comer 	NA		NA.	NA
	 Number of hydrants per floor 	NA		NA	NA
	Hose Box	NA		18/1	
2.	Yard Hydrants			X 1 A	NA
	 Total number of hydrants 	NA		NA NA	NA
	Hose Box	NA		NA	INA
3.	Pumping Arrangements:				
	Ground Level				NIA
	 Discharge of main pump 	NA		NA	NA NA
	 Head of main pump 	NA		NA	NA NA
	Number of main pumps	NA	-	NA	
	 Jockey pump out put 	NΛ		NA	NA NA
	 Jockey pump head 	NA		NA	+
	 Standby Pump out put 	NΛ	- +	NA	NA NA
	 Standby Pump Head 	NΛ		NA	NA NA
	 Auto Staring/Manual stopping 			NA	NA
	Pump House Access	NΛ		NA	INA
	Terrace level	150		Provided	MR
	Discharge of pump	450		Provided	MR
	Head of the pump		Mtr	Provided	MR
	Power supplyAuto starting of pump	Requ		Provided	MR
			uired	Flovided	IVIIC
14.	Captive water Storage for fire fighting	g:	NA.	NA	NA
	Under ground tank capacity		IA	NA	NA
	Draw off connection		NA .	NA	NA
	Fire service inletAccess to tank		VA	NA	NA
		10.000		Provided	MF
1.5	Overhead Tank capacity Evit Signage		uired	Provided	MR
15	Exit Signage Provision of Lifts	ixeq		1	1
16.	Pressurization of Lift Shaft	N	ŠΛ	NΛ	NA
	Pressurization of lift lobby	the second second	NA.	NA	NA
	Communication in lift Car		NA.	NA	NA
	Fireman's Grounding Switch		۱A	NA	NA
	 Lift Signage 		VΛ	NA	NA
17.	Standby power supply		NA	NA	NA
18.	Refuge Area	-		,	
	➤ Total area		NΛ	NA	NA
	Location	1	NA	NΛ	NA
19.	Fire control room				-
	 Detector system panel 		NA	NΛ	NA
	 Flow Switch Panel 		$\wedge \Lambda$	NA	NA
	 PA System Panel 		NA.	NΛ	NA
	 Battery backup 	Sukar !	NΛ	NΛ	NA