

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2022/SZ/

Dated 14/10 /2022

FIRE SAFETY CERTIFICATE

Certified that Govt. Boys Sr. Secondary School, Moti Bagh-I, New Delhi 110021 (School ID 1719010) comprised of Ground plus Two upper floors owned/occupied by Directorate of Education Govt of NCT of Delhi was issued Fire Safety Certificate by this department vide letter No F6/DFS/MS/School/2019/SZ/1914 Dated 07/10/2019 The said premise was re-inspected by officer concerned of this department on 27/09/2022 in presence of Sh. D. S Rawat (HOS) and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education Circular No F.16//Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011 issued by Director of Education, Govt. of NCT of Delhi and the building is fit for occupancy class "Educational Building Group - B" with effect from 14 / 10 / 2022 for a period of Three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 14 / 10 2022 at New Delhi by

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER

Copy to: -

- The Principal, Govt Boys Sr Secondary School, Moti Bagh-I, New Delhi 110021
- The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054

Conditions for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management
- All the staff members must know the correct method of operation of firefighting system
- 3. This certificate cannot be treated as regularization of unauthorized construction, if any
- 4 The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt nic in
- This fire safety certificate may not in any way be treated as regularization (Clause 2 8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its



-	INSPEC	TION REPORT				
1	Name & Address of the Building Govt Boys Sr Secondary School, Moti Bagh-I, 1					
		Delhi 11002	Delhi 110021 (School ID 1719010)			
2	Type of Occupancy	Education ID III "G PR (G I I)				
3		Educational Building "Group-B" (School)				
4		Ground + 02 Upper Floors				
5	Details of Previous NOC		Renewal			
6	Fire Safety Directives Letter No	F6/DFS/MS/School/2019/SZ/1914 Dated 07/10/2019 DOE Circular date 01/03/2011				
7	Date of Inspection					
8	Name of the Inspecting Officers	27/09/2022 Sh. Bouerk Kurrers ADO (BCB)				
9	Name & Designation of Officers	Sh. Rajesh Kumar ADO (BCP) Sh. D. S. Rawat (HOS)				
	from the building side	Sil. D. S Rawat (FIOS)				
10		1957				
11			/2022/123 dated 16/09/2	022		
S. N	177	GBSSS/MB/-1/2022/123 dated 16/09/2022 Old NOC Provided at Site Remarks				
3. 140	and Fire Safety U/R 33	Requirement		MR/NMR		
1	Access to Building.	Requirement				
	Road width	05 mtr	05 mtr	MR		
	Gate width	4.5m	4 5m	NA		
	Width of internal road	-NA-	-NA-	-NA-		
2	Number, width, type & arrangement of ex					
	a) Number of Staircase	AILS.				
	> Upper floors	02 No's	2 No's	M/R		
	Basement floor	-NA-	-NA-	-NA-		
	b) Width of Staircase					
	> Upper floor	1.50 mtr	1.95 mtr & 1.70m	M/R		
	> Basement floor	-NA-	-NA-	-NA-		
	c) Protection of exits					
	Fire check door	-NA-	-NA-	-NA-		
	> Pressurization	-NA-	-NA-	-NA-		
	d) No. of continuous staircase to terrace	Required	02 Nos	MR		
	e) Width of corridor	1 50 m	Provided	M/R		
	f) Door size	01 m	Provided	M/R		
3_	Compartmentation.		1	27.4		
	Fire check door.	-NA-	-NA-	-NA-		
	Sealing of electrical shafts.	-NA- -NA-	-NA-	-NA- -NA-		
	Fire rating of shaft door	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
	Fire dampers.	-INA-	-NA-	-INA-		
4	Smoke Management system.	-NA-	-NA-	-NA-		
	Basement	-NA-	-NA-	-NA-		
	Upper floors	-INA-	-INA-	-INA-		
5	Fire Extinguishers.		22 No's	MR		
	Total numbers	ISI mark	ABC-12 & CO2 -12	MR		
	• Types	151 mark	Provided	MR		
	ISI Marking		Flovided	IVIK		
6	First Aid Hose Reels.	Hose reel	02 Nos	M/D		
	Total numbers on each floor	30 M	Provided	M/R M/R		
			rrovided	IVI/K		
	Length of hose-reel hose.			M/D		
	Length of hose-reel hose. Nozzle Diameter	5MM	Provided	M/R		
	Length of hose-reel hose Nozzle Diameter Automatic fire detection & alarming system.	5MM	Provided			
7	Length of hose-reel hose. Nozzle Diameter			M/R -NA-		

गानादी आजादी अमृत महोत्सव

	Location of Repeater Panel	-NA-	-NA-	-NA-	
	 Alternate source of power 	-NA-	-NA-	-NA-	
	 Hooter's location 	-NA-	-NA-	-NA-	
8	MOEFA	-NA-	Provided	-NA-	
9	Public Address System	-NA-	-NA-	-NA-	
10	Automatic Sprinkler System				
	Basement	-NA-	100 mm	-NA-	
	 Upper floors 	-NA-	02 Nos	-NA-	
	Sprinkler above false ceiling	-NA-	02 Nos	-NA-	
11	Internal Hydrants.				
	Size of Riser/Down-comer	-NA-	-NA-	-NA-	
	Number of Hydrant per floor	-NA-	-NA-	-NA-	
10	Hose box.	-NA-	-NA-	-NA-	
12	Yard Hydrants.			1	
	 Total number of hydrants. 	-NA-	-NA-	-NA-	
	Hose box.	-NA-	-NA-	-NA-	
13	Pumping arrangements.				
	Ground Level				
	Discharge of main pump	-NA-	-NA-	-NA-	
	Head of main pump.	-NA-	-NA-	-NA-	
	Number of main pumps.	-NA-	-NA-	-NA-	
	Jockey Pump output.	-NA-	-NA-	-NA-	
	Jockey Pump head.	-NA-	-NA-	-NA-	
	Standby Pump output.	-NA-	-NA-	-NA-	
	Standby Pump head	-NA-	-NA-	-NA-	
	 Auto Starting/Manual Stopping. 	-NA-	-NA-	-NA-	
	Terrace Level			1	
	Discharge of pump.	2 x 450 LPM	2 x 450 LPM	MR	
	Head of pump.	40 m each	Provided	MR	
	Power supply.	Required	Provided	MR	
	Auto starting of pump.	Required	Provided	MR	
14	Captive water storage for fire fighting.				
	 Underground tank capacity. 	-NA-	-NA-	-NA-	
	Draw-off connection.	-NA-	NIA	-	
			-NA-	-NA-	
	Fire Service Inlet.	-NA-	-NA- -NA-	-NA-	
			-NA- -NA-	-NA-	
	Fire Service Inlet.	-NA- -NA-	-NA- -NA-	-NA-	
15	 Fire Service Inlet. Access to tank. Overhead tank capacity. 	-NA- -NA- 10,000 Ltrs	-NA- -NA- Provided	-NA- -NA- MR	
	Fire Service Inlet.Access to tank.	-NA- -NA-	-NA- -NA-	-NA-	
	 Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. 	-NA- -NA- 10,000 Ltrs	-NA- -NA- Provided Provided	-NA- -NA- MR M/R	
	 Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. 	-NA- -NA- 10,000 Ltrs Required	-NA- -NA- Provided Provided -NA-	-NA- -NA- MR M/R	
	 Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. 	-NA- -NA- 10,000 Ltrs Required -NA- -NA-	-NA- -NA- Provided Provided -NA- -NA-	-NA- -NA- MR M/R	
	 Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. 	-NA- -NA- 10,000 Ltrs Required -NA- -NA- -NA-	-NA- -NA- Provided Provided -NA- -NA-	-NA- -NA- MR M/R -NA- -NA-	
	 Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. 	-NA- -NA- 10,000 Ltrs Required -NA- -NA- -NA- -NA-	-NA- -NA- Provided Provided -NA- -NA- -NA-	-NA- -NA- MR M/R -NA- -NA- -NA-	
6	 Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. 	-NA- -NA- 10,000 Ltrs Required -NA- -NA- -NA- -NA- -NA-	-NANA- Provided Provided -NANANANANA-	-NA- -NA- MR M/R -NA- -NA- -NA- -NA-	
7	 Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply 	-NA- -NA- 10,000 Ltrs Required -NA- -NA- -NA- -NA-	-NA- -NA- Provided Provided -NA- -NA- -NA-	-NA- -NA- MR M/R -NA- -NA- -NA-	
7	 Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area 	-NA- -NA- 10,000 Ltrs Required -NA- -NA- -NA- -NA- -NA- -NA-	-NANANANANANANANA-	-NA- -NA- MR M/R -NA- -NA- -NA- -NA- -NA- -NA-	
7	 Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply 	-NANA- 10,000 Ltrs Required -NANANANANANANAN	-NANA- Provided Provided -NANANANANA-	-NA- -NA- MR M/R -NA- -NA- -NA- -NA-	
7	 Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area 	-NA- -NA- 10,000 Ltrs Required -NA- -NA- -NA- -NA- -NA- -NA-	-NANANANANANANANA-	-NA- -NA- MR M/R -NA- -NA- -NA- -NA- -NA-	
7 8	Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area Total area	-NANA- 10,000 Ltrs Required -NANANANANANANAN	-NANA- Provided Provided -NANANANANANANA- NA	-NA- -NA- MR M/R -NA- -NA- -NA- -NA- -NA- -NA-	
7 8	Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area Total area Location Fire Control Room.	-NANA- 10,000 Ltrs Required -NANANANANANANAN	-NANA- Provided Provided -NANANANANANANA- NA	-NA- -NA- MR M/R -NA- -NA- -NA- -NA- -NA- -NA-	
7 8	Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area Total area Location Fire Control Room.	-NANA- 10,000 Ltrs Required -NANANANANANANAN	-NANA- Provided Provided -NANANANANANANA- NA	-NA- -NA- MR M/R -NA- -NA- -NA- -NA- -NA- -NA-	

/2

Vina. via			p115	11101	month interes	
-NA-			-NA-	-NA-	-NA-	
-NA-	Battery backup Building floor plan	-NA-	-NA-	-NA-		
-NA- -N/	20. Speci	ipecial Fire Protection System for the Protection of special Risk, if any.		-NA-	-NA-	

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/School/2019/SZ/1914 Dated 07/10/2019, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please

Signature of the Inspecting Officer

Accordingly, DFA is put up for approvar and argument

Dy. CFO (SZ)

Name Sh Rajesh Kumar Design ADO (BCP)

ADIBIP

As approved, F.T. Ichel.

your synature 81

10/10/2003

Dy 451 /2

n.1. W