

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001**

No. F6/DFS/MS/Hotel/2022/NDZ/59

Dated: -02/11/2022

FIRE SAFETY CERTIFICATE

Certified that The Connaught Hotel located at 37, Shaheed Bhagat Singh Marg, New Delhi comprised of Basement, ground + 07 upper floor was granted FSC by this department vide letter No. F6/DFS/MS/Hotel/2020/NDZ/193 dated 04/05/2020. Now, the premises was re-inspected by the officers concerned of this department on 20/10/2022 in the presence of Mr. Ashutosh and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Hotel Building with effect from [02.11.]. No.2 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ...O. J. 11 1. 20. L. at New Delhi by.

Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S., Defence Colony, New Delhi -110049.

The Manager, The Connaught Hotel, 37, Shaheed Bhagat Singh Marg, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT

1. Name & address of the building:- The Connaught Hotel, 37, Shaheed Bhagat

Singh Marg, New Delhi. Type of occupancy:-

Hotel 3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/Hotel/2020/NDZ/193 dated

04/05/2020.

5. Fire safety directives No.-N/A

6. Date of inspection:-20/10/2022

7. Name of the inspecting officer:-Sh. Rajinder Atwal (DO/CD) & Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer From the building side:-

Mr. Ashutosh 1987

9. Year of construction:-10. Applicant's letter No:

letter no nil dated 26/09/2022

10	. Applicant's letter No:-	letter no <u>ni</u>	<u>ll</u> dated 26/09/2022.	Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Required/ Existing fire safety	Provided at site	Remarks MR/NMR
1.	A 4. P. 3.11	arrangements		'
1.	Access to Building			
	1) Road width	6 mtr.	12 mtr.	MR
	2) Gate width	-	Direct access from main road	MR
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Ar	rangement of Ex	kits	
	A. Number of staircases			
	1. Upper floors	3 Nos.	3 Nos.	MR
	2. Basements	3 Nos.	03 + 01 ramp	MR
	B. Width of staircase			
	1. Upper floors	1.20 mtr.(1),	1.20, 0.76 &	MR
		0.90 mtr.(2)	0.76 mtr.	
	2. Basements	1.20 mtr.	1.20 mtr. each.	MR
	C. Protection of exits			
	1. Fire check door	Required	Provided	MR
	2. Pressurization	Required	Provided	MR
	D. No. of continuous	03 Nos.	03 Nos.	MR
	staircase to terrace		33 1103.	IVIIC
	E. Width of corridor	1.25 mtr.	1.5 mtr.	MR
	F. Door size	1.25 mtr.	1.5 mtr.	MR
	Compartmentation		1.5 IIII.	IVIK
	1) Fire check door	Required	Provided	MD
	2) Sealing of electrical shafts	Required	Provided	MR
	3) Fire rating of shaft door	Required	Provided	MR
	4) Water curtain	Required		MR
	5) Fire Dampers	Required	Provided	MR
	Smoke Management System	Required	Provided	MR
	1) Basements	20 0/2	-	
		30 a/c per hour	Provided	MR
	2) Upper floors	12 a/c per hour	N/A	N/A
	Fire Extinguishers			
	1) Total numbers	70 Nos.	Provided	MR

2) Types DCP,WCO2 ABC & CO2 3) ISI marking ISI Yes MR 6. First-Aid Hose Reel 1) Total number of eachfloor 01 Provided MR 2) Length of hose reel hose 30 m Provided MR 3) Nozzle diameter 5 mm Provided MR 7. Automatic Fire Detection & Alarming System 1) Type of detectors Smoke/heat Provided MR 2) Location of main panel Basement Provided MR 3) Location of repeater panel Each floor Provided MR 4) Alternate source of power Required Provided MR 5) Hooter's Location Each floor Provided MR 8. MOEFA Required Provided MR 9 Public Address System Required Provided MR
ABC & CO2 3) ISI marking ISI Yes MR 6. First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 30 m Provided MR 3) Nozzle diameter 5 mm Provided MR 7. Automatic Fire Detection & Alarming System 1) Type of detectors Smoke/heat Provided MR 2) Location of main panel Basement Provided MR 3) Location of repeater panel Each floor Provided MR 4) Alternate source of power Required Provided MR 5) Hooter's Location Each floor Provided MR 8. MOEFA Required Provided MR
3) ISI marking ISI Yes 6. First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter 5 mm Provided MR 7. Automatic Fire Detection & Alarming System 1) Type of detectors Smoke/heat Provided MR 2) Location of main panel Basement Provided MR 3) Location of repeater panel Each floor Provided MR 4) Alternate source of power Required Provided MR 5) Hooter's Location Each floor Provided MR 8. MOEFA Required Provided MR
6. First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter 5 mm Provided MR 7. Automatic Fire Detection & Alarming System 1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location 8. MOEFA Provided MR MR MR
1) Total number of eachfloor 2) Length of hose reel hose 3) Mozzle diameter 5 mm Provided MR 7. Automatic Fire Detection & Alarming System 1) Type of detectors Smoke/heat Provided MR 2) Location of main panel Basement Basement Provided MR 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location Each floor Each floor Provided MR 8. MOEFA Required Provided MR Provided MR Provided MR Provided MR Provided MR Provided MR
2) Length of hose reel hose 3) Nozzle diameter 5 mm Provided MR 7. Automatic Fire Detection & Alarming System 1) Type of detectors Smoke/heat 2) Location of main panel Basement Basement Provided MR 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location Each floor Frovided MR Required Provided MR MR 8. MOEFA Required Provided MR
7. Automatic Fire Detection & Alarming System 1) Type of detectors Smoke/heat Provided MR 2) Location of main panel Basement Provided MR 3) Location of repeater panel Each floor Provided MR 4) Alternate source of power Required Provided MR 5) Hooter's Location Each floor Provided MR 8. MOEFA Required Provided MR
7. Automatic Fire Detection & Alarming System 1) Type of detectors Smoke/heat Provided MR 2) Location of main panel Basement Provided MR 3) Location of repeater panel Each floor Provided MR 4) Alternate source of power Required Provided MR 5) Hooter's Location Each floor Provided MR 8. MOEFA Required Provided MR
1) Type of detectors Smoke/heat Provided 2) Location of main panel Basement Provided MR 3) Location of repeater panel Each floor Provided MR 4) Alternate source of power Required Provided MR 5) Hooter's Location Each floor Provided MR 8. MOEFA Required Provided MR
2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location Each floor Each floor Frovided Provided(D.G. set) MR Provided MR
3) Location of repeater panel Each floor Provided 4) Alternate source of power Required Provided MR 5) Hooter's Location Each floor Provided MR 8. MOEFA Required Provided MR
4) Alternate source of power Required Provided MR 5) Hooter's Location Each floor Provided MR 8. MOEFA Required Provided MR
5) Hooter's Location Each floor Provided MR 8. MOEFA Required Provided MR
8. MOEFA Required Provided MR
9. Public Address System Required Provided
10 Automotic Sprinkler System
1) Personnet Required Provided
2) Harrier floors Required Provided Mix
2) Upper floors Required Provided MR 3) Sprinkler above false Required Provided
ceiling
11 Internal Hydronts
1) Gine of ricor/down comer 100 mm. Provided
1) Size of riser/down-comer 100 mm. 2) Number of hydrants per 01 Provided MR
g
3) Hose box at each floor 01 Provided MR
10 Vand Hydrants
1) Total number of hydrants Required Provided
2) Hose box Required Provided MR
13. Pumping Arrangement
1) Ground level
a) Discharge of main 2850 LPM Provided MR
pump
b) Head of main pump 70 mtr. Provided 14th
c) Number of main 2 Nos. Provided MR
pump
d) Jockey pump out put 390 LPM Provided 1VIK
e) Jockey pump head 70 mtr. Provided 1/1R
f) Stand by pump 2850 LPM Provided MR
output
g) Stand by pump head 70 mtr. Provided NR
h) Auto starting/Manual Required Provided MR
stopping
i) Pump House Access Required Provided MR
2) Terrace level
a) Discharge of pump N/A N/A N/A
b) Head of pump N/A N/A N/A
c) Power supply Required Provided MR
d) Auto starting of Required Provided MR
pump
14 Captive Water Storage for Fire Fighting
1) Under ground tank 1,00,000 ltrs. Provided MR
capacity
a) Draw-off connection Required Provided MR

		NITY		
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	20,000 ltrs.	Provided	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	Required	Provided	MR
	b) Pressurization of lift lobby	Required	Provided	MR
	c) Communication in lift	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room			
	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	Required	Provided	MR
	c) PA system panel	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Building floor plan	Required	Provided	MR MR
20.	Special Fire Protection System for Protection of special Risk, if any: MMO clean Agent 10 kg and CO2- 22.5 kg, 01 no. near each transformer.			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection. In view of the deemed compliance of the minimum standards of fire prevention

and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/Hotel/2020/NDZ/193 dated 04/05/2020, renewal under Rule 35 of the Delhi Fire Service Rules 2010, is recommended for approval.

Signature of the Inspecting Officer

Name :- Rajinder Atwal

Signature of the Inspecting Officer

Name :- Ravinder Designation:- ADO (CC)

Designation:- DO (CD)