FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE [Refer sub - rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS /SZ/2022/ 507

Dated: 14 ////2022

(Atul Ga Director

Delhi Fire Service

## FIRE SAFETY CERTIFICATE

Certified that the building (S-2 Block (SSLS, SMS & SIT Building) (Commonly known as C,D & E Blocks) GGSIP University Located at Sector 16C, Dwarka, New Delhi comprised of G+ 06 UF was issued Fire Safety Certificate vide Letter No: F6/DFS/MS/2011/2320, dated 26/09/2011. The premises was re inspected by the team of officers concerned of this department on 20/10/2022 in the presence of Sh. Deepesh Singh Bhati A.E(E) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules 2010 and that the premises is fit for occupancy class "Educational" Group B with effect from  $\frac{12}{11}\frac{2022}{2022}$  for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Ryle 38 of the Delhi Fire Service Rules, 2010.

Issued on .1.4.11.1.2022 at New Delhi by.

Copy to:

- 1. The Registrar (E&S), GGSIPU, Sector-16-C, Dwarka, New Delhi-110078.
- 2. The Astt. Registrar to the Hon'ble Vice Chancellor, GGSIPU, Sector-16-C, Dwarka, New
- 3. The Executive Engineer (UWD, GGSIPU) University Works Division, Ground Floor, Library Block, Guru Gobind Singh Indraprastha University, Sector 16-C, Dwarka New Delhi-110078.

## Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning
- 5. The certificate may not be treated in any case for the regularization of the unauthorized
- construction, if any. 6. Basement shall be used strictly as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its

## **INSPECTION REPORT**

- Name & address of the building: GGSIP University Located at Sector 16C, Dwarka, New Delhi.
- 2. Type of Occupancy : Educational

3. Type of Case : Renewal (S-2 Block (SSLS, SMS & SIT Building)( Commonly known as C,D & E Blocks Ground + 06 Upper Floors)

- 4. Details of previous NOC: F6/DFS/MS/2011/2320, dated 26/09/2011
- 5. Fire Safety directives L. No. : F6/DFS/MS/BP/2006/1208, dated 25/05/2006

: 2006

- 6. Date of inspection : 20/10/2022
- 7. Name of the Inspecting Officer : DO/SW & ADO (DWK)
- 8. Name and designation of Officer

from the building side

: Sh. Deepesh Singh Bhati J.E(E)

Year of Construction
 Applicant's letter No.

:Email Dated-08/10/2022

	Minimum standards on fire	Requirement As	Provided at site		Remarks			
No	prevention and fire safety U/R 33	N/62, N/63 & N				MR/NMR		
1.	Access of building							
	<ul> <li>Road width</li> </ul>	12 mtrs P		Provided		MR		
	<ul> <li>Gate width</li> </ul>	05 mtrs		ovided	MR			
	<ul> <li>Width of internal road</li> </ul>	06 mtr		d case	being old case			
2.	Number, width, Type & Arrangements of exits							
	a. Number of staircases							
	<ul> <li>Upper floors</li> </ul>	03 No's each block		Provided		MR		
	<ul> <li>Basements</li> </ul>	NA			NA			
	b. Width of staircases							
	<ul> <li>Upper floors</li> </ul>	1.5mtr each Provided				MR		
	<ul> <li>Basements</li> </ul>	NA NA				NA		
	c. Protection of exits							
	<ul> <li>Fire check door</li> </ul>	Required · Provided			MR			
	<ul> <li>Pressurization</li> </ul>	NA			NA			
	d. No of continuous	03 No's each bloc	k	Provided		MR		
	staircase to terrace	1.5m	Prov	Provided				
	e. Width Of Corridor f. Door Size	1.5 mtr		Provided (Old case)				
2				(	,	MR		
3.	Compartmentation     Fire check door	Required	Pro	vided	MR			
			Sealed					
	<ul> <li>Sealing of electrical shafts</li> </ul>	Required	Sea	led		MR		
	<ul> <li>Fire Rating of shaft door</li> </ul>	02 Hrs rating	Pro	vided		MR		
	Water Curtain	NA		NA			NA	
	<ul> <li>Fire Dampers</li> </ul>	NA	NA			NA		
4.	Smoke managements System							
	Basements	NA	NA			NA		
	• Upper floors	Required in seminar		ar hall Provided		MR		

6

				^	11	170				1
5	5. Fire Extinguishers			(	. /				100	
-	Total numbers	- 04	6	a anal O		1.45.2				
				os each flo	or	45 N			MR	
	• Types			& $CO_2$			$\& CO_2$		MR	
6	IS marking	15	1 m	arked		Prov	ided		MR	
6	The most me most receis									
	<ul> <li>Total numbers on each</li> </ul>		0	2 nos.		Provid	led		MR	
	<ul> <li>Length of hose reel hose</li> </ul>	ose	3	0m		Provid	ed		MR	-
	<ul> <li>Nozzle diameter</li> </ul>		5	mm		Provid	ed		MR	
7.	. Automatic fire detection and a	alarmin	g sy	stem					IVIIX	
	<ul> <li>Type of detectors</li> </ul>		<u> </u>	NA			NA		NA	_
	<ul> <li>Location of Main Pane</li> </ul>	el		NA			NA		NA	
	<ul> <li>Location of Repeater I</li> </ul>	Panel		NA			NA		NA	_
	Alternate source of power			NA NA					_	
	<ul> <li>Hooters' Location</li> </ul>	wei		NA					NA	
8.							NA		NA	
9.				Required		Provi			MR	
10				Required		Provie	led		MR	
	Basements									
				NA		NA		NA		
	opper ribbi			NA		NA		NA		-
11.	Sprinkler above false c	eiling		NA		NA		NA		-
11.	and try drams.									-
	<ul> <li>Size of riser/down- con</li> </ul>	ner		150 mm	1	50 mm		MR		-
	<ul> <li>Number of hydrants per</li> </ul>	r floor	t	02 Nos.		rovide		MR		-
	<ul> <li>Hose Box</li> </ul>		ľ	02 Nos.		rovided		MR		-
12.					-	uct		IVIR		_
	<ul> <li>Total number of hydran</li> </ul>	ts		12 Nos.		Prov	idad	100		1
	Hose Box			Required	1	Prov		MR		
13.	Pumping Arrangements:	Hun	h	in Ac		remen		MR		1
	Ground Level	1.4.	~1/	Ing H	ra	ngmen	y Comm	on for	entirelini	urnis
	<ul> <li>Discharge of main pump</li> </ul>	228	1 O	nm						
	Head of main pump	70 n	atr	pm	D		Provi	-	MR	
	Number of main pumps	01	ILI			ovided		MR		
	<ul> <li>Jockey pump out put</li> </ul>	180	ID	M		ovided		MR		
	<ul> <li>Jockey pump head</li> </ul>	70 m		VI		ovided		MR		1
	Standby Pump out put					ovided		MR		1
	Standby Pump Head	2850		M		ovided		MR		1
	<ul> <li>Auto Staring/Manual</li> </ul>	70 mtr		Provideo						1
	stopping	Requ	ure	d	Pre	ovided		MR		1
	<ul> <li>Pump House Access</li> </ul>	-				2				
	<ul> <li>Terrace level</li> </ul>	Requ	irea	d	Pro	ovided		MR		1
	<ul> <li>Discharge of pump</li> </ul>									
	<ul> <li>Head of the pump</li> </ul>	NA			NA	1		NA		
	<ul> <li>Power supply</li> </ul>	NA			NA			NA		
		NA			NA					
	pullip of pullip	NA			NA			NA		
.	Captive water Storage for fire fig	hting:		Common			tige in	NA		
	<ul> <li>Under ground tank</li> </ul>	2,00,0	000		Pro	vided	tize Unine	untz	· `	
	capacity	_,,.	00		110	vided		MR		
	Draw off connection	Requi	red		D-					
	Fire service inlet	Requi	_			vided		MR		
	Access to tank					vided		MR		
	<ul> <li>Overhead Tank capacity</li> </ul>	Required			Provided M		MR			
F	Exit Signage					Pro	vided	MR		
	- Bunde	Requi	red	1	Pro	vided		MR		

10.

a

.

h

.



NA NA NA NA MR MR

210

MR

NIZI

PT	<ul> <li>Pressurization of Lift Shaft</li> </ul>	NA	NA	NA	
	Pressurization of lift lobby	NA	NA	NA	
	Communication in lift Car	Required	Provided	MR	
	Fireman's Grounding Switch	Required	Provided	MR	
	Lift Signage	Required	Provided MR		
	Standby power supply	Required	Provided	MR	
8.	Refuge Area				
	Total area	NA	NA	NA	
	· Locution	NA	NA	NA	
19.	Fire control room			1971	
	Detector system panel	Required	Provided	MR	
	Flow Switch Panel	NA	NA	NA	
	PA System Panel	Required	Provided	MR	
1	<ul> <li>Battery backup</li> <li>Building Floor Plans</li> </ul>	Required	Provided	MR	
		Required	Provided MR		
20		Required	CO2 fire extinguisher		M
	Protection of special Risks, if any;		provided near electric panels		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter F6/DFS/MS/2011/2320, dated 26/09/2011 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

10)2

Signature of the Inspecting OfficerSignName:Sh. VedpalNamDesignation:DO/SWDes

is

Jul 9/11/22

Signature of the inspecting Officer Name: Udai Vir Singh Designation: ADO/DWK

Dereela

()wark )

DO