

No. F6/DFS/MS/2022/SZ/ 533

Dated: 29/11/2022

## FIRE SAFETY CERTIFICATE

Certified that the M/s Anubhav Community Hall running at ground & first floor in a building comprised of basement, ground plus two upper floors at CH-6, J-Block, Vikas Puri, New Delhi was granted NOC vide letter No. F.6/DFS/MS/09/1717 dated 10.06.09 for occupancy of the building, owned/occupied by M/s Arorbans Sabha (Regd.). The premises have deemed complied with the fire prevention and fire safety requirements in accordance with the Rule 33 of the Delhi Fire Service Rules 2010 and verified by the officer concerned of this department on 07/11/2022 in the presence of Sh. Harish Pandey (Manager) of the Banquet Hall and found that the building (ground & first floor only ) is fit for occupancy class "D" 'Assembly Building' with effect from 29/11/2022 for a period of three years in accordance with the Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, subject to conditions printed below.

> (Sunil Chawdhary) Dy. Chief Fire Officer Delhi Fire Service

To,

Sh. Harish Pandey (Manager), M/s Anubhav Community Hall at CH-6, J-Block, Vikas Puri, New Delhi.

## Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

INSPECTION REPORT Name & address of the building: M/s Anubhav Community Hall, CH-6, J-Block, Vikas Puri, New Delhi Building comprised of Basement, ground plus two upper floors (  $2^{nd}$  floor not in use) 2. Type of Occupancy 3. Assembly Building. Type of Case 4. Renewal Details of Previous NOC 5. : F.6/DFS/MS/09/1717 dated 10.06.09 Fire Safety directives letter No : F.6/DFS/MS/BP/2005/1299 dated 17.06.2005 & F.6/DFS/MS/2008/1832 dated 01.07.08 Date of inspection : 07/11/2022 Name of Inspecting Officer 8. : A.D.O. R.K.Yadav Name and designation of officers From the building side : Sh. Harish Pandey (Manager) 10. Year of Construction : Before 2009 11. Applicant's letter No. : Nil dated 08/10/2022 Remarks Provided at S. No. Minimum Standards on fire prevention **NBC** MR/NMR site and fire safety U/R 33 Requirements 1. Access to building M/R Provided 09 mtrs. Road width M/R Provided 05 mtrs. Gate width N/A N/A N/A Width of internal road Number, Width, Type & Arrangement of Exits 2. a. Number of staircases M/R Two Upper Floors Two M/R Two Basements Two b. Width of staircases M/R 1.50 &1.25 m 1.50 &1.25 m Upper Floor M/R 2x1.5 m & 1x1.20 1.50m Basements m c. Protection of exits N/A N/A Fire check door N/A N/A Pressurization N/A N/A d. No. of continuous staircases to N/A N/A N/A terrace N/A N/A N/A e. Width of Corridor 2 m & 1.5 m & 1.0 m M/R 1.50 m on GF, 2 M &1.5 M Door Size on FF Compartmentation 3. M/R Provided Required Fire check door Sealing of electrical shafts N/A N/A N/A Fire Rating of shaft door N/A N/A N/A Water Curtain N/A N/A N/A Fire Dampers N/A N/A N/A Smoke Management System 4. Required Provided M/R Basements Provided Required M/R Upper floors Fire Extinguishers 5. Provided Total numbers 06 no.'s M/R ABC & CO<sub>2</sub> type **Types** Provided M/R ISI marked IS marking ISI marked M/R

Basement use as storage purpose, ground & first floor use for banquet hall & second floor not in use.

. 1	10
И	17

	First-Aid Hose Reels				6			
•	Total numbers on each floor	One	Provided		M/R			
	<ul> <li>Length of hose reel hose</li> </ul>	36 mtrs.	Provided Provided		MR MR			
	<ul> <li>Nozzle diameter</li> </ul>	5 mm	Tiorida					
	Automatic fire detection and alarming s	ystem						
	Type of detectors	N/A	N/A		N/A			
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A		N/A			
		N/A	N/A		N/A			
	Location of Repeater Panel	N/A	N/A		N/A			
	Alternate source of power	N/A	N/A		N/A			
	Hooters' Location	NI/A	N/A		N/A			
	MOEFA	N/A Required	Provided		M/R			
	Public Address System	Required	TTOVIGEG					
0.	Automatic Sprinkler System	Required	Provided		M/R			
	Basement     Basement	Required	NP	M/R	old accepted			
	Ground & First Floor     Ground & First Floor     Ground & First Floor     Ground & First Floor     Ground & First Floor	N/A	N/A	·	N/A			
	Sprinkler above false ceiling	IN/M	1471					
1.	Internal Hydrants     Size of riser/down-comer	100 mm	Provided		MR			
		One	Provided		M/R			
	Number of hydrants per floor	One	Provided		M/R			
	Hose Box	00						
12.	Yard Hydrants	77/4	N/A		N/A			
	<ul> <li>Total number of hydrants</li> </ul>	N/A	N/A N/A		N/A			
	Hose Box	N/A	IN/A		IVIA			
13.	Pumping Arrangements							
	Ground Level	1 (20 1 7) (	Provided		M/R			
	Discharge of main Pump	1620 LPM						
	<ul><li>Head of Main pump</li><li>Number of main pumps</li></ul>	55 mtrs.	Provided		M/R			
	> Jockey Pump out put	One	Provided		M/R			
	> Jockey pump head	180 LPM	Provided		M/R			
	Standby Pump out put	55 mtrs.	Provided		M/R			
	Standby Pump Head	1620 LPM	Provided		M/R			
	Auto Starting/Manual	55 mtrs.	Provided		M/R			
	Stopping	Required	Provided		M/R			
		Required	Provided		M/R			
	Pump House Access	Reduired	11011404					
	Terrace level	450 LPM	Provided		M/R			
	> Discharge of pump	30 Mtrs	Provided		M/R			
	<ul><li>Head of the pump</li><li>Power Supply</li></ul>	Required	Provided		M/R			
	> Auto Starting of pump	Required	Provided		M/R			
		1.0441104	1.0300					
14.	Captive Water Storage for fire fighting							
	Underground tank capacity	50000 ltrs	Provided		M/R			
	> Draw-off connection	Required	Provided		M/R			
	> Fire service inlet	Required	Provided		M/R			
	Access to tank	Required	Provided		M/R			
	Overhead Tank capacity	10,000 Ltrs.	Provided		M/R			
15.	Exit Signage.	Required	Provided		M/R M/R			
		Required	Fiovided		IVI/ IX			

Guidelines was issued vide letter No. F6/DFS/MS/BP/2005/299 dated 17/06/2009 but previous NOC was issued vide letter No. F6/DFS/MS/09/1717 dated 10/06/2009 with out sprinklers system for upper floors.

10
I X
1-0

		N JX						
1	Provision of Lifts.							
1	<ul> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> </ul>	N/A	N/A	N/A				
		N/A	N/A	N/A				
		N/A	N/A	N/A				
Lift Signage	N/A	N/A	N/A					
		N/A	N/A	N/A				
17.	Standby power supply	N/A	N/A	N/A				
18.	Refuge Area.							
	<ul><li>Total Area</li><li>Location</li></ul>	N/A	N/A	N/A				
	Location	N/A	N/A	N/A				
19.	Fire Control Room							
	Detector System Panel	N/A	N/A	N/A				
	<ul><li>Flow Switch Panel</li><li>PA System Panel</li><li>Battery backup</li></ul>	N/A	N/A	N/A				
		N/A	N/A	N/A				
	Building Floor Plans	N/A	N/A	N/A				
	8 * * * * * * * * * * * * * * * * * * *	N/A	N/A	N/A				
20.	Special Fire Protection System for Protection of special Risks, if any:	N/A	N/A	N/A				

The fire protection systems provided in the building were tested, checked and found not functional at the time of inspection. The shortcoming issued vide letter No. F6/DFS/MS/Assembly/2019/SZ/5746 Dated 23/09/2019 has been complied.

In view of the compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter number F.6/DFS/MS/09/1717 dated 10.06.09 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Note:- The staircase requirement of 1.50 M (02 no.'s) has been accepted as 1.50 M and 1.25 M being fate accompli in previous NOC dated 10.06.2009. There is no mention of basement in previous NOC although as per the guidelines issued by this department vide letter dated 17.06.2005 has mention of basement.

Signature of Inspecting

Name: - R.K. Yadav

Designation:- Asstt. Divisional Officer

DYCF0(5>)