Dated: 05/12/22 **DVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI** HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/GH/SZ/2022/ 526

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Intercity located at 17A/42, WEA, Karol Bagh, New Delhi- 110005, was granted Fire Safety Certificate vide this department letter No. F6/DFS/MS/GH/SZ/2019/1880 dated 01.10.2019, for use basement as storage, ground floor as reception and 03 guest rooms, first, second & third floor each having 07, 06 and 07 guest rooms respectively (total 23 guest rooms). The guest house was re-inspected by the officer concerned of this department on 28.11.2022 in presence of Sh. Arvind, manager and found that the guest house owner have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) for ground floor having 03 guest rooms, first floor having 07 guest rooms, second floor having 06 guest rooms & third floor 07 guest rooms respectively (total 23 guest rooms only), with effect from ostive for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on at New Delhi by.

(Sunil Chaudhary) Dy. Chief Fire Officer (SZ) Delhi Fire Service

Application ID No. No. 2022111520205 dated 15.11.2022

Following Fire Safety Directives must be adhered to: -

- No occupancy used above third floor and basement used for storage purpose only shall be 1. strictly adhered by Owner/Occupier.
- All the means of escape shall be kept free of all type of obstruction all the time. 2.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency. 3.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be 4.
- Any deviation, with regards to construction, ventilation, occupation, electric installation 5. etc. may be got verified from the concerned authorities.
- The Fire Safety Certificate may not be treated in any case for regularizations of 6. unauthorized construction / unauthorized use of land if any.
- All comments / directions of licensing department shall always be permitted and 7. followed.
- The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on 8. www.dfs.delhigovt.nic.in
- The owner / occupier shall apply for renewal of this Fire Safety Certificate to the . 9. Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.
- Owner/Occupier will use each room for single person occupancy. 10.

INSPECTION REPORT

Name & address of the building

: M/s Hotel Intercity, 17A/42, WEA, Karol Bagh, New

Delhi- 05.

2. Type of Occupancy

: Lodging House

3 Building Composition

: Said guest house building comprised of basement, ground plus three upper floors, using basement as storage, ground floor as reception, & 03 guest rooms, 1st, 2nd & 3rd floor each having 07, 06 & 07 guest rooms respectively (total 23 guest rooms)

4. Type of Case

: Renewal

5. Details of previous NOC

: F6/DFS/MS/GH/SZ/2019/1880 dated 01.10.2019

6. Fire Safety directives letter No

: Nil

7. Date of inspection

: 28.11.2022

: Before 2010

8. Name of the Inspecting Officers

: P.V. Rathee, Asstt. Div. Officer (SRD)

9. Name and designation of officers

from the building side 9. Year of Construction

: Sh. Arvind, manager

Access to building Road width Gate width Width of internal road N/A Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors Basements Upper Floors Basements Upper Floors The check door Pressurization C. Protection of exits Fire check door No. of continuous staircases to terrace Width of Corridor Provided MR N/A		Minimum Standards on fire	Existing fire safety requirements as per	r Provided at	Remarks		
Road width Gate width Width of internal road N/A Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors Basements Upper Floors Basements C. Protection of exits Fire check door Pressurization C. No. of continuous staircases to terrace g. Width of Corridor h. Door Size Compartmentation. Road width N/A	lo.	prevention and me safety 0/18 35	FSC dated 01.10.201	9 site	MR/NMR		
Gate width Width of internal road N/A Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors Basements Upper Floors Upper Floors Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Basements Upper Floors Upper Floors Basements Upper Floors Upper F		Access to building					
Width of internal road N/A Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors Basements Upper Floors Upper Floors Upper Floors Basements Upper Floors Upper Floors Upper Floors Basements Upper Floors Upper Floo		Road width	06 mts		MR		
2. Number, Width, Type & Arrangement of Exits a. Number of staircases • Upper Floors • Basements • Upper Floors • Upper Floors • Basements • Upper Floors • Basements • Upper Floors • Basements • C. Protection of exits • Fire check door • Pressurization • No. of continuous staircases to terrace g. Width of Corridor h. Door Size Compartmentation. • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers • Basements 12 a/c per hour Exhaust fan provided MR Presurisation MR being old case 1.30 mts MR being old case 0.90 mts MR being old case 0.90 mts MR being old case 1.30 mts MR be		Gate width	N/A	Directly accessible	N/A		
a. Number of staircases Upper Floors Basements Upper Floors Upper Floors Upper Floors Upper Floors Upper Floors Upper Floors Basements Upper Floors Upper Floors Basements Upper Floors Upper Very Upper Up		Width of internal road	N/A	N/A	N/A		
Upper Floors Basements b. Width of staircases Upper Floors Basements c. Protection of exits Fire check door Pressurization c. No. of continuous staircases to terrace g. Width of Corridor h. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Dame MR being old case 1.25 mts 1.30 mts MR being old case N/A N/A N/A N/A N/A N/A N/A N/A N/A N/	2	Number, Width, Type & Arrangement of Exits					
Basements b. Width of staircases Upper Floors Basements 1.25 mts 1.30 mts MR being old cares 1.25 mts 1.35 & 1.30 mts MR being old cares 1.25 mts Indicates to terrace Width of Corridor Dor Size Old case Old case		a. Number of staircases	-	-	-		
Basements b. Width of staircases Upper Floors Basements C. Protection of exits Fire check door No. of continuous staircases to terrace g. Width of Corridor h. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Dampers Damper Survivation Sealor of the continuous staircases to terrace 1.25 mts 1.30 mts MR being old care N/A N/A N/A N/A N/A N/A N/A N/		Unner Floors	01	01	MR being old case		
b. Width of staircases Upper Floors Basements C. Protection of exits Fire check door No. of continuous staircases to terrace g. Width of Corridor h. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Basements 1.25 mts 1.30 mts MR being old case N/A N/A N/A N/A N/A N/A N/A N/A N/A N/			02	02	MR		
• Upper Floors • Basements c. Protection of exits • Fire check door • Pressurization c. No. of continuous staircases to terrace g. Width of Corridor h. Door Size Compartmentation. • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers 1.25 mts 1.35 & 1.30 mts MR being old care N/A N/A N/A N/A N/A N/A N/A N/A N/A N/			-	-	-		
c. Protection of exits Fire check door Pressurization N/A N/A N/A N/A N/A N/A N/A N/			1.25 mts	1.30 mts	MR being old case		
Fire check door Pressurization No. of continuous staircases to terrace g. Width of Corridor h. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Basements N/A N/A N/A N/A N/A N/A N/A N/		 Basements 	1.25 mts	1.35 & 1.30 mts	MR being old case		
Pressurization e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size Compartmentation. Prire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Basements N/A N/A N/A N/A N/A N/A N/A N/		c. Protection of exits	-	-			
e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size Old case Old cas		Fire check door	N/A	N/A	N/A		
terrace g. Width of Corridor h. Door Size Old case Old ca				N/A	N/A		
h. Door Size Old case Ol				01	MR		
Compartmentation. Sealing of electrical shafts Required Sealed MR Sealing of shaft door N/A N/A N/A N/A Fire Rating of shaft door N/A N/A N/A N/A Water Curtain N/A N/A N/A N/A Fire Dampers N/A N/A N/A Smoke Management System. 12 a/c per hour Exhaust fan provided MR Basements 12 a/c per hour Natural Ventilation MR New York N		g. Width of Corridor	Old case	1.30 mts	MR being old cas		
• Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers • Basements • Fire check door • N/A • Required • Sealed • MR • N/A		h. Door Size	Old case	0.90 mts	MR being old cas		
• Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers • Basements • Fire check door • N/A • Required • Sealed • MR • N/A	3	Compartmentation.					
Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements N/A N/A N/A N/A N/A N/A N/A N/			N/A	N/A	N/A		
Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Basements N/A N/A N/A N/A N/A N/A N/A N/		 Sealing of electrical shafts 	Required	Sealed	MR		
Water Curtain Fire Dampers N/A Smoke Management System. Basements Basements Basements N/A			N/A	N/A			
• Fire Dampers N/A N/A N/A Smoke Management System. • Basements 12 a/c per hour Exhaust fan provided MR Natural Ventilation MR			N/A	N/A			
Basements 12 a/c per hour Exhaust fan provided MR Basements		 Fire Dampers 	N/A	N/A	N/A		
Basements	4	Smoke Management System.			1.1.		
12 -/- mor hour Natural Ventilation MK		Basements	1				
			12 a/c per hour	Natural Ventilation	on MR		



		N125				
	Total numbers	12	Provided	MR		
		CO ₂ , ABC, WCO ₂	Provided	MR		
	TypesIS marking	ISI marked	Provided	MR		
	First-Aid Hose Reels.					
6	Total numbers on each floor	01	Provided	MR		
		30 m	Provided	MR		
	Length of hose reel hose	5 mm	Provided	MR		
	Nozzle diameter		Tiovided	IVIIC		
7	Automatic fire detection and alarming	Carbon Monoxid	1	NAD		
	Type of detectors			MR		
	Location of Main Panel	Required	Provided near rec			
	 Location of Repeater Panel 	N/A	N/A	N/A		
	 Alternate source of power 	Required	Provided	MR		
	 Hooters' Location 	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Basement	Required	Provided	MR		
	Upper Floor	N/A	N/A	N/A		
	 Sprinkler above false ceiling 	N/A	N/A	N/A		
11	Internal Hydrants					
	Size of riser/down-comer	N/A	N/A	N/A		
	 Number of hydrants per floor 	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
12	Yard Hydrants.					
	Total number of hydrants	N/A	N/A	N/A		
	Hose Box	. N/A	N/A	N/A		
13	Pumping Arrangements.					
	Ground Level					
	 Discharge of main Pump 	N/A	N/A	N/A		
	 Head of Main pump 	N/A	N/A	N/A		
	 Number of main pumps 	N/A	N/A	N/A		
	 Jockey Pump out put 	N/A	N/A	N/A		
	 Jockey pump head 	N/A	N/A	N/A		
	 Standby Pump out put 	N/A	N/A	N/A		
	Standby Pump Head	N/A	N/A	N/A		
	 Auto Starting/ Manual stopping 	N/A	N/A	N/A		
	Pump House Access	N/A	N/A	N/A		
	Terrace level			IN/A		
	 Discharge of pump 	450 LPM				
	Head of the pump	450 LPM 40 mts	450 LPM 40 mts	MR		
	Power Supply	Required	Provided	MR		
	Auto Starting of pump	Required	Provided	MR		
14						
	 Underground tank capacity 	N/A	N/A	N/A		
	 Draw-off connection 	N/A	N/A	N/A		
1	T:	-				



N/A

N/A

5,000 lts

N/A

N/A

5,000 lts

N/A

N/A

MR

Fire service inlet

Overhead Tank capacity

Access to tank

l.		N/26					
E	it Signage.	Required	Provided	MR			
Pr	C1:640						
10	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	Required	Provided	MR			
	Fireman's Grounding Switch	Required	Provided	MR			
	Lift Signage	Required	Provided	MR			
Sta	andby power supply	Required	Provided (85.5 KVA)	MR			
	Refuge Area.						
0	Total Area	N/A	N/A	N/A			
	Location	N/A	N/A	N/A			
9 Fir	re Control Room						
	Detector System Panel	N/A	N/A	N/A			
	Flow Switch Panel	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
	Battery backup	Required	Provided	MR			
	Building Floor Plans	N/A	N/A	N/A			
20 Sp	ecial Fire Protection Systems for	Required	One ABC type fire	MR			

MR MR MR

> MR MR M

> > 20

Protection of special Risks, if any:

otion

The fire protection systems provided in the building were checked at random and found satisfactory at the time of inspection.

Note:- Fire Check Door not required as owner/occupier has applied in CAF MHA Portal. Number of beds is less than 10 at each floor and owner/occupier has submitted an undertaking that we will not use any type of occupancy above 3rd floor and basement will be used for storage purpose only (undertaking placed at C-80).

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter F6/DFS/MS/GH/SZ/2019/1880 dated 01.10.2019, renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA letter is put up for approval & signature please.

Signature of the Inspecting Officer Name P.V. Rathee

extinguisher found

provided near elect. panel

Asstt. Div. Officer (SRD)