

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2022/ NDZ 513

Dated 15 /11 /2022

FIRE SAFETY CERTIFICATE

Certified that the Hriday Palace Guest House located at 3649, Gali Ram Nath Patwa, Dariba Pan, Pahar Ganj, New Delhi is comprised of Ground + 04 Upper floors, Ground floor (reception + 02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor) and 4th floor (01 staff room), total 14 guest rooms, was earlier granted FSC by this department vide letter No. F6/DFS/MS/GH/2020/69 dated 20/02/2020 for 14 guest rooms only upto third floor. Now, the premises was re-inspected by the officer concerned of this department on 09/11/2022 in the presence of Manager and found that the said guest house building having given an affidavit dated 22.10.2019 regarding not to use any floor above third floor, has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class -Residential (Sub Division-A-1) Ground floor (reception + 02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor) total 14 guest rooms up to third floor only, with effect from ...\5...\11...\20.2......for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued. 15 11 2022 at New Delhi by.

Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Commissioner, MCD, Civic Centre, New Delhi: kindly to ensure the occupancy as detailed above.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online id no. 2022092218002 dated 22.09.2022.
- 3. The Manager, Hriday Palace Guest House, 3649, Gali Ram Nath Patwa, Dariba Pan, Pahar Ganj, New Delhi.

Conditions for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. The clarification /compliance with regard to electrical installation ,ventilation , structural stability , set back area, occupancy and any deviation w.r.t. construction shall be got verified from the authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT

1. Name & address of the building Hariday Palace Guest House located at 3649,

Gali Ram Nath Patwa, Dariba Pan, Pahar

Ganj, New Delhi

2. Type of occupancy:- Residential, Sub Division-A-1

Gr. + 04 Upper floors (total 14 Guest rooms)
Ground floor (reception + 02 guest rooms),
1st floor to 3rd floor (04 guest rooms at each floor)
And staff room at terrace floor and affidavit given
by owner dated 22.10.2019 not to use any floor

above third floor.

3. Type of case:- Renewal

4. Details of previous FSC:- No. F6/DFS/MS/GH/2020/69 dated

20/02/2020.

N/A

5. Fire safety directives No.-

6. Date of inspection: 09/11/2022

7. Name of the inspecting officer:- Sh. Ravinder Singh ADO (CC)

8. Name & designation of officer From the building side:-

Sh. Anand

9. Year of construction:-

2007 ID no. 2022092218002 dated 22.09.2022

10. Applicant's letter No:-Old Case Remarks Provided at site Requirement/ Minimum Standards on fire S.No. MR/NMR Existing fire Prevention and fire safety safety U/R 33 arrangements Access to Building 1. MR 03 mtr. N/A 1) Road width N/A N/A N/A 2) Gate width N/A N/A N/A 3)Width of internal road Number, Width Type & Arrangement of Exits 2. A. Number of staircases MR 01 Nos. 01 Nos. 1. Upper floors N/A N/A N/A 2. Basements B. Width of staircase MR 1.25 to 1.32 0.80 mtr. 1. Upper floors mtr. N/A N/A N/A 2. Basements C. Protection of exits N/A N/A N/A 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous staircase to terrace N/A N/A N/A E. Width of corridor 206 cms X 90 cms N/A N/A F. Door size Compartmentation 3. N/A N/A N/A 1) Fire check door N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers Smoke Management System 4. 30 ACPH N/A N/A 1) Basements MR Exhaust fan 12 ACPH 2) Upper floors Fire Extinguishers 5.

4/16

1) Total numbers			HIII				
1 Total numbers ABC & CO2 ABC & CO2 MR			10 Nos	10 Nos.	MR		
2) Types		1) Total numbers	ARC & CO2		MR		
3) ISI marking		2) Types			MR		
1) Total number of eachfloor 2) Length of hose reel hose 30 mtr. 30		3) ISI marking	Required				
1) Total number of eartheol 2) Length of hose reel hose 3) Mozzle diameter 05 mm 05 mm MR 3) Nozzle diameter 05 mm 05 mm MR 4) Automatic Fire Detection & Alarming System	6.	First-Aid Hose Reel	01	functional	MR		
2) Length of hose reter lose 50 mm 05 mm MR		1) Total number of eachfloor			MR		
3) Nozzle diameter		2) Length of hose reel hose			MR		
1) Type of detectors CO		3) Nozzle diameter					
1) Type of defectors CO	7.	Automatic Fire Detection &	Alarming System	Provided	MR		
2) Location of main painer 3) Location of repeater panel 4) Alternate source of power 8		1) Type of detectors CO					
3) Location of repeater paner 4) Alternate source of power Required Provided MR		Location of main panel					
Alternate source of power Equitor S) Hooter's Location Each floor Provided MR		Location of repeater panel					
S							
Note		5) Hooter's Location					
Public Address System	8.	MOEFA					
1) Basement		Public Address System	Required	Provided	MR		
1) Deper floors N/A N/	10.	Automatic Sprinkler System					
3) Sprinkler above false ceiling		1) Basement					
11. Internal Hydrants 1 Size of riser/down-comer N/A N		2) Upper floors	N/A	N/A			
11.		3) Sprinkler above false	N/A	N/A	N/A		
1) Size of riser/down-comer N/A N/A N/A N/A							
2) Number of hydrants per floor N/A	11.	Internal Hydrants					
Stand by pump output N/A		1) Size of riser/down-comer	N/A	N/A			
3) Hose box		2) Number of hydrants per	N/A	N/A	N/A		
12. Yard Hydrants 1) Total number of hydrants N/A		floor					
1) Total number of hydrants N/A N/A N/A N/A 2) Hose box N/A N/A N/A N/A 3. Pumping Arrangement		3) Hose box	N/A	N/A	N/A		
2) Hose box	12.	Yard Hydrants					
13. Pumping Arrangement 1) Ground level N/A N/A N/A N/A a) Discharge of main N/A N/A N/A N/A b) Head of main pump N/A N/A N/A c) Number of main pump N/A N/A N/A d) Jockey pump out put N/A N/A N/A e) Jockey pump head N/A N/A N/A N/A f) Stand by pump output N/A N/A N/A g) Stand by pump head N/A N/A N/A N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump 450 LPM 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to tank		1) Total number of hydrants	N/A	N/A	N/A		
1) Ground level N/A N/A N/A N/A a) Discharge of main pump N/A N/A N/A b) Head of main pump N/A N/A N/A c) Number of main pump N/A N/A N/A d) Jockey pump out put N/A N/A N/A e) Jockey pump head N/A N/A N/A f) Stand by pump output N/A N/A N/A g) Stand by pump head N/A N/A N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A c) Access to tank		2) Hose box	N/A	N/A	N/A		
a) Discharge of main pump b) Head of main pump c) N/A c) Number of main pump N/A d) Jockey pump out put N/A e) Jockey pump head N/A	13.	Pumping Arrangement					
b) Head of main pump N/A N/A N/A c) Number of main pump N/A N/A N/A d) Jockey pump out put N/A N/A N/A e) Jockey pump head N/A N/A N/A f) Stand by pump output N/A N/A N/A N/A h) Auto starting/Manual N/A N/A N/A stopping 2) Terrace level a) Discharge of pump 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A S) Access to task		Ground level	N/A	N/A	N/A		
b) Head of main pump N/A N/A N/A c) Number of main pump N/A N/A N/A d) Jockey pump out put N/A N/A N/A e) Jockey pump head N/A N/A N/A N/A f) Stand by pump output N/A N/A N/A g) Stand by pump head N/A N/A N/A h) Auto starting/Manual N/A N/A N/A stopping 2) Terrace level a) Discharge of pump 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to took		_	N/A	N/A	N/A		
c) Number of main pump N/A N/A N/A d) Jockey pump out put N/A N/A N/A e) Jockey pump head N/A N/A N/A f) Stand by pump output N/A N/A N/A g) Stand by pump head N/A N/A N/A h) Auto starting/Manual N/A N/A N/A stopping 2) Terrace level a) Discharge of pump 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to took			N/A	N/A	N/A		
d) Jockey pump out put e) Jockey pump head N/A		c) Number of main pump					
e) Jockey pump head N/A N/A N/A f) Stand by pump output N/A N/A N/A g) Stand by pump head N/A N/A N/A h) Auto starting/Manual N/A N/A N/A stopping 2) Terrace level a) Discharge of pump 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A 14. C. Access to took							
f) Stand by pump output N/A N/A N/A N/A g) Stand by pump head N/A N/A N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to took							
g) Stand by pump head N/A N/A N/A N/A h) Auto starting/Manual Stopping 2) Terrace level a) Discharge of pump 450 LPM MR b) Head of pump 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to task							
h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A N/A							
stopping 2) Terrace level a) Discharge of pump 450 LPM 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank N/A N/A N/A N/A a) Draw-off connection N/A N/A N/A N/A N/A N/A N/A N/							
2) Terrace level a) Discharge of pump 450 LPM 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to took			1	14/71	IN/A		
a) Discharge of pump 450 LPM 450 LPM MR b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to task							
b) Head of pump 30 mtr. 30 mtr. MR c) Power supply Required Provided MR d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to took			450 LPM	450 I DM	MD		
c) Power supply d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to took							
d) Auto starting of pump Required functional MR 14. Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to took							
1) Under ground tank capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A C) Access to took							
a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A c) Access to took	14.	Captive Water Storage for	Fire Fighting	Tunctional	MK		
capacity a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A c) Access to took		1) Under ground tank	77/4				
a) Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A c) Access to took			177	IN/A	N/A		
b) Fire service inlet N/A N/A N/A			N/A	NI/A			
c) Access to tople N/A N/A N/A							
, recess to talk N/A N/A N/A		/ The state of the					
		-/ 1100033 to talk	IN/A	N/A	N/A		

	 d) Over head tank capacity 	5000 ltr.	5000 ltr.	MR
15.	Exit Signage.	Doguina 1	_	
16.	Provision of Lifts.	Required	Provided	MR
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	 c) Communication in lift car 	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syster Risk, if any:	tion of special	N/A	

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

The shortcomings issued earlier vide letter no. F6/DFS/MS/NDZ/2022/558 dated 11.07.2022 has been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no. F6/DFS/MS/GH/2020/69 dated 20/02/2020, up to third floor only under rule 35 of the Delhi Fire Service rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation - ADO (CC)

MR MR MR

MR MJ