FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/SZ/2022/METRO 550

Dated: 06 /12 /2022

FIRE SAFETY CERTIFICATE

Certified that the building Multi Level Car Parking (Pacific Metro Mall) Located at Sector – 21, Dwarka Metro Station, Dwarka, New Delhi, comprised of Ground, + 03 Upper Floors was issued FSC vide Letter No F6/DFS/MS/Storage/2019/SZ/2246 dated 02-12-2019. The premises was re inspected by the officers concerned of this department on 29/11/2022 in the presence of Sh. Bharat Bhusan (Director) & Sh. Shiv Partap singh (Manager Tech.) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Storage building" (car parking))with effect from 66 12 2022 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .0.6. 12.20.22 at New Delhi by.

Sunil Chaudhary

Dy. Chief Fire Officer, Delhi Fire Service

Copy to:

 Sh. Inder Kumar Thakur, Director (Commercial) Pacific Mall, Plot No-01, 5th floor Site 04, Sahibabad, Industrial Area, Ghaziabadh (Utter Pardesh).

 The Manager, Multi Level Car Parking (Pacific Metro Mall) Located at Sector – 21, Dwarka Metro Station, Dwarka, New Delhi

3. The Director/Asstt. General Manager, Pacific Metro Mall Located at Sector – 21, Dwarka Metro Station, Dwarka, New Delhi

4. The Vice Chairman, DDA, INA Vikas Sadan New Delhi-110023.

Following fire safety directives must be adhered to:-

- 1 All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3 The trained staff should be available round the clock.
- 4 Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5 The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6 The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7 Basement shall be used strictly as per building bye laws.
- 8 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1/20

INSPECTION REPORT

Name & address of the building: MLCP Located at (Commercial Area)
 Dwarka Sector 21 Metro Station of Line 3 & Airport Express Line New Delhi.

2. Type of Occupancy : Storage

3. Type of Case : Renewal (Ground + 03 Upper Floors)

4. Details of previous NOC:F6/DFS/MS/Storage/2019/SZ/2246 dated 02-12-19

5. Fire Safety directives L. No. :. F6/DFS/MS/BP/2019/154 dated 18/04/2019

6. Date of inspection : 29-11-2022

7. Name of the Inspecting Officer: DO/SW & ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Bharat Bhusan (Director) &

Sh Shiv Partap singh (Manager Tech.)

9. Year of Construction : 2019

10. Applicant's letter No. : Email dated 24/11/2022

S No	Minimum standards on fire prevention and fire safety U	/R 33		As per inspection report dated 18/11/2019		on Provide at site		d Remarks MR/NMR		
1.	Access of building									
	Road width	12 m		Provided			MI			
	Gate width	06 m		Provided NA Building is lowrise			MI			
	Width of internal road	NA					MR Being old case			
2.	Number, width, Type & Arr	angemen	ts o	of exits						
	a. Number of .									
	staircases						\dashv	m		
	 Upper floors 	02 Nos.				Provided		MR		
	 Basements 	NA			NA		1	NA		
	 b. Width of staircases 					- m /m /				
	 Upper floors 	1.5 m each Provided			MR(Being					
	 Basements 	NA		N.	Α			NA		
	c. Protection of exits		•							
	 Fire check door 	Required			Provided			MR		
	 Pressurization 	NA		NA Pro		A ovided		NA		
	d. No of continuous staircase to terrace	02 Nos.	•					MR		
	e. Width Of Corridor	NA		NA			N.	NA		
	f. Door Size	1.5 m		•	Pr	Provided		MR(Old Case)		
	,									





7/

heck door ng of ical shafts Cating of shaft r Curtain Dampers gements refloors ishers numbers arking lose Reels numbers on floor th of hose reel le diameter re detection an of detectors tion of Main Pation of Repeate nate source of ers' Location	NA Requ NA NA NA 18 no ABC Requ 02 N 30 m 5 mm d alarm	os. & CO2 uired os. each		N N Pr N N Pr A Pr Pr Pr		MR NA NA NA NA MR NA NA NA NA	
ng of ical shafts Cating of shaft r Curtain Dampers gements ments r floors ishers numbers arking lose Reels numbers on floor th of hose reel le diameter re detection an of detectors tion of Repeate mate source of	NA Required NA NA NA 18 ne ABC Required 02 N 30 m 5 mm and alarm	os. & CO2 aired os. each n ning syste NA NA NA		N Pr A Pr Pr Pr NA NA	A A rovided A A A rovided BC & CO2 rovided rovided rovided rovided	NA NA MR NA NA MR	
Cating of shaft r Curtain Dampers gements refloors ishers numbers arking fose Reels numbers on floor th of hose reel le diameter re detection an of detectors tion of Repeate	NA Requ NA NA NA 18 no ABC Requ 02 N 30 m 5 mm d alarm	os. & CO2 aired os. each n ning syste NA NA NA		N Pr NA NA NA	A A A A Tovided BC & CO2 Tovided Tovided Tovided Tovided Tovided Tovided	NA MR NA NA NA MR MR MR MR MR MR MR MR NA	
pampers gements refloors refloors refloors refloors refloor refloor refloor th of hose reel refloor	NA NA 18 m ABC Requ 02 N 30 m 5 mm d alarm	os. & CO2 aired os. each n ning syste NA NA NA		Pr Pr Pr NA	A A rovided BC & CO2 rovided rovided rovided	MR NA NA MR MR MR MR MR MR NA NA	
pampers gements refloors refloors refloors refloors refloor refloor refloor th of hose reel refloor	NA NA 18 m ABC Requ 02 N 30 m 5 mm d alarm	os. & CO2 aired os. each n ning syste NA NA NA		Pr Pr Pr NA	A A rovided BC & CO2 rovided rovided rovided	MR NA NA MR MR MR MR MR MR NA NA	
ments r floors ishers numbers s arking lose Reels numbers on floor th of hose reel le diameter re detection an of detectors tion of Repeate	NA NA 18 m ABC Requ 02 N 30 m 5 mm and alarm	os. & CO2 aired os. each n ning syste NA NA NA		Pr Pr Pr NA	A A rovided BC & CO2 rovided rovided rovided	MR MR MR MR MR MR MR MR	
ments r floors r floors r floors r floors r floors r floor r floor th of hose reel le diameter re detection an of detectors tion of Repeate mate source of	18 ne ABC Requirement of the ABC Requirement	is CO2 ired os. each ning syste NA NA NA		Pr Pr Pr NA	ovided BC & CO2 rovided rovided rovided rovided	MR MR MR MR MR MR MR MR MR	
r floors numbers numbers surking fose Reels numbers on floor th of hose reel le diameter re detection an of detectors tion of Repeate	18 ne ABC Requirement of the ABC Requirement	is CO2 ired os. each ning syste NA NA NA		Pr Pr Pr NA	ovided BC & CO2 rovided rovided rovided rovided	MR MR MR MR MR MR MR MR MR	
r floors numbers numbers surking fose Reels numbers on floor th of hose reel le diameter re detection an of detectors tion of Repeate	18 ne ABC Requirement of the ABC Requirement	is CO2 ired os. each ning syste NA NA NA		Pr Pr Pr NA	ovided BC & CO2 rovided rovided rovided rovided	MR MR MR MR MR MR NA	
numbers surking lose Reels numbers on floor th of hose reel le diameter re detection an of detectors tion of Repeate	18 no ABC Required 12 No 30 mm and alarmouth anel er	is CO2 ired os. each ning syste NA NA NA		Pr Pr Pr NA	rovided BC & CO2 rovided rovided rovided	MR MR MR MR MR NA NA	
numbers s arking lose Reels numbers on floor th of hose reel le diameter re detection an of detectors tion of Main Pa tion of Repeate	02 N 30 m 5 mm d alarm	is CO2 ired os. each ning syste NA NA NA		A Pr	BC & CO2 rovided rovided rovided	MR MR MR MR MR NA NA	
s arking lose Reels numbers on floor th of hose reel le diameter re detection an of detectors tion of Main Pation of Repeate	02 N 30 m 5 mm d alarm	is CO2 ired os. each ning syste NA NA NA		A Pr	BC & CO2 rovided rovided rovided	MR MR MR MR NA	
arking lose Reels numbers on floor th of hose reel le diameter re detection an of detectors tion of Main Pa lion of Repeate	02 N 30 m 5 mm d alarm	os. each nning syste NA NA NA		Pr Pr Pr NA	ovided ovided ovided	MR MR MR NA	
numbers on floor th of hose reel le diameter re detection an of detectors tion of Repeate nate source of	02 N 30 m 5 mm d alarm anel	n ning syste NA NA NA		Pr Pr Pr NA	ovided ovided	MR MR NA NA	
numbers on floor th of hose reel le diameter re detection an of detectors tion of Main Pa tion of Repeate	30 m 5 mm od alarm anel	n ning syste NA NA NA		Pr Pr NA	ovided	MR MR NA NA	
floor th of hose reel le diameter re detection an of detectors tion of Main Pa tion of Repeate mate source of	30 m 5 mm od alarm anel	n ning syste NA NA NA		Pr NA NA	ovided	MR NA NA	
th of hose reel le diameter re detection an of detectors tion of Main Pa tion of Repeate	5 mm od alarm anel	n ning syste NA NA NA	m	Pr NA NA	ovided	MR NA NA	
re detection an of detectors tion of Main Pa tion of Repeate nate source of	d alarm anel	NA NA NA NA	m	NA NA		NA NA	
re detection an of detectors tion of Main Pa tion of Repeate nate source of	d alarm anel	NA NA NA NA	m	NA NA		NA	
of detectors tion of Main Pation of Repeate nate source of	anel	NA NA NA	-11	NA		NA	
tion of Main Pation of Repeate nate source of	टा	NA NA		NA			
ion of Repeate	टा	NA NA		_		NA	
nate source of	power					NA	
	power			NA NA		NA	
ers' Location						NA	
			d	Den	vided	MR	
C		Require		Provided		MR	
ss System	n	Require	equired		1,000		
orinkler Systen nents		NA		NA		NA	
BasementsUpper Floor			Required		vided	MR	
r Floor kler above fals	e	NA		NA		NA	
g							
Internal Hydrants				nm 150 mm		MR	
 Size of riser/down- comer Number of hydrants per floe Hose Box 			_			MR MR MR	
		Kequ		Hovided			
	06	Nos		Pro	vided	MR	
nts							
Box	06	Nos.		Pro	vided	MR	
֡	of riser/down-of riser/down-of hydrants Box s number of nts	of riser/down- comer her of hydrants per flo Box s number of 06	of riser/down- comer wer of hydrants per floor Box s number of 06 Nos.	of riser/down- comer 150 n wer of hydrants per floor Requires 150 n 02 No Requires 150 n 06 Nos.	of riser/down- comer ber of hydrants per floor Box Required shows a show of the first show	of riser/down- comer ber of hydrants per floor Box Required Provided Required Provided Regulared Provided Research Regulared Regulared Provided Regulared Provided Regulared Provided Regulared Regulared Provided Regulared Regul	

W

4/22

		ng Arrangements Conn						1		
		Ground Level	-	2051) lpm		Provided		MR	
		bisenaige of main pains				Provided		MR		
					1	Provided		MR		
	Number of main pumps			2 Nos.			Provided		MR	
		Jockey pump out put		2X180 lpm 88 m			Provided		MR	
	\succ						Provided		MR	
		Standby Pump out put		2850 lpm			Provided		MR	
	\triangleright			88 m			Provided		MR	
	\succ	Auto Staring/Manual		Required						
		stopping	-	Required			Provided		MI	R
		Pump House Access		Required						
	•	Terrace level	-	900 LPM Prov			vided	MR	MR	
	>	Discharge of pump			Mtrs	Pro	vided	MR	MR	
		> Head of the pump					vided	MR	MR	
	> Power supply						rovided		MR	
		Auto starting of pump			luirea	110	Vicioti			
4.	Captive water Storage for fire fighting			2 0	o ooo litres	Provided		M		
	 Under ground tank capacity Draw of connection 			Required		Provided		MR		
						Provided			R	
	\triangleright	Access to tank			Required		Provided			R
					quired		Provided	d MI		IR
					000 litres	Provided		MR		
15	Exit S	ignage		Red	quired		riovided			
16.	Provision of Lifts				1		Provided		MR	
	Pressurization of Lift Shaft				Required				NA	
	Pressurization of lift lobby				NA		NA Provided		MR	
	>	Communication in lift Car			Required					
	~				Required		Provided		MR MR	
	>				Required		Provided			IVIIC
				-	Required		DG Set Prov		ided MR	
	Standby power supply		Required							
18.	Refuge Area > Total area > Location			NA		NA		NA		
					1 47 6				NA	
					NA.					
19.		ontrol room ·				Dr	ovided	M	IR	
	> Detector system Required Required			a	C .				MR	
						ovided		MR		
	\triangleright	> PA System Panel Require				rovided rovided		MR		
	>									
	\triangleright	Battery backup	Require	ed	Pr		Provided		MR	
	~	Building Floor								
		Plans								
						1				
-		·								
			1							

h

MR CO2 Flooding System Special Fire Protection Required provided in HT & LT Systems for Protection of Panel special Risks, if any;

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter no. F6/DFS/MS/Storage/2019/SZ/2246 dated 02-12-2019 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name: Sh. Vedpal Designation: DO/SW Signature of the Inspecting Officer

Name: Udai Vir Singh Designation: ADO/DWK

letter port up for