

rit Mahotsav

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/MS/School/2022/NDZ/ 1357

Dated: 27/12/2022

FIRE SAFETY CERTIFICATE

Certified that the Kendriya Vidhyalaya located at Shahdara, Delhi-110032, comprised of ground plus three upper floors, owned/occupied by Kendriya Vidhyalaya. The premises was inspected by the officers concerned of this department on 12/12/2022 in the presence of Mr. Akash Mittal and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have complied with rule 33 of Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class 'Educational (Group-B)' with effect from 27/12/202 for a period of **three** years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 & also conditions printed below.

GARG) DIRECTOR **DELHI FIRE SERVICE**


To,

The Mr. Ashok Kumar Sharma (Chief Architect) Central Public Work Department Room No. 217-218, "A" Wing, Nirman Bhawan, New Delhi-110011

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <u>www.dfs.delhigovt.nie.in</u>
- The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry

e.16



NIS

 Name and designation of Officer from the building side

10. Year of Construction

1

1

¢.,

- 11. Applicant's letter No
- : ADG(DR)CA(DR)20180613/2006 Dated- 12/10/2022

Sr. No.	Minimum Standards on Fire Prevention and Fire Safety U/R33	Directive Requirement	Provided at Site	Remarks MR/NMR			
01	Access to Building.						
	Road width	12 mtr.	12 mtr.	MR			
	Gate width	6.00 mtr	6.00 mtr	MR			
	 Width of internal road 	6.00 mtr	6.00 mtr	MR			
02	Number, Width, Type and Arrangement of Exits.						
	a. Number of Staircases						
	 Upper floor 	02 Nos.	02 Nos.	MR			
	 Basement 	N/A	N/A.	N/A			
	b. Width of Staircases						
	 Upper floor 	1.50 mtr.	1.50 mtr	MR			
	 Basement 	N/A	N/A	N/A			
	c. Protection of exits						
	 Fire check door 	Required	Provided	MR			
	 Pressurization 	N/A	N/A	N/A			
	d. No. of Continuous Staircases to Terrace	02 Nos.	02 Nos.	MR			
	e. Width of Corridor	1.50 mtr.	2.40 mtr.	MR			
	f. Door Size	1.20 mtr.	1.20 mtr.	MR			
03	Compartmentation.						
	Fire check door	Required	Provided	MR			
	 Sealing of electrical shafts 	Required	Provided	MR			
	 Fire rating of shaft door 	Required	Provided	MR			
	 Water curtain 	N/A	N/A	N/A			
	 Fire dampers 	N/A	N/A	N/A			
04	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	 Upper floor 	Required	Ventilated	MR			
05.	Fire Extinguishers.						
	Total numbers	18 nos.	18 nos.	MR			
	 Types 	ABC /CO ₂	ABC /CO ₂	MR			
	 IS marking 	ISI marked	ISI marked	MR			

Mr. Akash Mittal

: 2021



N))	3
1	1	2

	First-Aid-Hose Reels			
	Total numbers on each floor	02 No.	02 No.	M
	Length of hose reel hose	30 mtr.	30 mtr.	M
07	Nozzle diameter	05 mm	05 mm	M
07	Automatic Fire Detection and Alarming	System.		
	 Type of detectors 	N/A	N/A	N/
	 Location of main panel 	N/A	N/A	N/
	 Location of repeater panel 	N/A	N/A	N/
	 Alternate source of power 	N/A	N/A	N/
08	Hooter's location	N/A	N/A	N/.
	MOEFA	Required	Provided	M
09	Public Address System.	Required	Provided	MF
10	Automatic Sprinkler System.			
	Basement	N/A	N/A	N/A
	 upper floor 	N/A	N/A	N/A
	 sprinkler above false ceiling 	N/A	N/A	N/A
1	Internal Hydrants			11/7
	 size of riser/down-comer 	100 mm	100 mm	MR
	 Number of hydrants per floor 	01 no.	01 no.	MR
-	Hose box	01 no.	01 no.	MR
2	Yard Hydrants.			
	 Total number of hydrants 	N/A	N/A	N/A
-	Hose box	N/A	N/A	N/A
3	Pumping Arrangements.			
	Ground Level			
	Discharge of main pump	N/A	N/A	N/A
	 Head of main pump 	N/A	N/A	N/A
	 Number of main pumps 	N/A	N/A	N/A
	 Jockey pump out put 	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby pump out put	. N/A	N/A	N/A
	Standby pump head	N/A N/A	N/A	N/A
	Auto starting /manual stopping	N/A N/A	N/A	N/A
+	Pump house access Farrace Level	IN/A	N/A	N/A
	Discharge of pump	900 Lpm.	900 Lpm.x 02	145
	 Head of the pump 	40 M	40 M	MR MR
	 Power supply 	Required	Provided	MR
	Auto Starting of pump	Required	Provided	MR
С	aptive Water Storage for Fire Fighting.	• • • • •		
	Underground tank capacity	N/A	N/A	N/A
	 Draw-off connection 	N/A	N/A	N/A
	Fire service inlet	N/A	N/A	N/A
	Access to tank	N/A	N/A	N/A
	 Overhead tank capacity 	25,000 Ltr.	25,000 Ltr.	MR



	NL		and the standard st	Contraction (and) the set			
15	Provision of Lifts.						
	Pressurization of lift shaft	N/A	NVA	PL/A			
	Pressurzation of lift lobby	N/A	14/A	86/A			
	Communication in lift car	N/A	1NA	BUA.			
	Firemen's grounding switch	NIA	N/A	NUA.			
	Lift signage	NA	BNA	BLA.			
17	Standby Power Supply	Required	Provided	MR			
18	Refuge Area						
			N/A	Ph/A			
	Total area	AVA	N/A	BUA			
	Location	11/A	PNP				
19	Fire Control Room						
	• Octocher enters accord	NIA	IN/A	1.A			
	Detector system panel	NA	N/A	1NA			
	Flow switch panel	Required	Provided	MR			
	PA system panel	Required	Provided	MR			
	Battery backup	Required	Provided	MR			
0	Building floor plans Special Fire Protection Systems for Protection of Special Risks, if any	Required	Provided in all LT & HT Panels	MR			

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rule. It is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

15/12/2022

Signature of the Inspecting Officer

" Same Designation

: A.K. Jaiswal : D.O. (ED)

12/12/2022 Signature of the Inspecting Officer

: Deepak Kumar tiame Designation : A.D.O. (SHD)

4. CFO(1)22

Directo

Figure

loure

sir, fi lesser je par af for you d. Dubars. 23 [12]2022