GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001 No. F6/DFS/MS/2022/WZ/school 1347 Dated: 22/12/2022

FIRE SAFETY CERTIFICATE

Certified that the Rohini Educational Society, (Gitarattan Jindal Public School) Sector, 7, Rohini, Delhi-85, comprised of Basement + Ground + 03 upper floors has already been issued FSC by this department vide letter No. F.6/DFS/MS/2019/1511 dated 23.07.2019. The premises was re-inspected by the officer concerned of this department on 05.12.2022 in the presence of Sh. R N. Jindal (Chariman) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Educational "Group B" with effect from 22 12 2022 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subjected to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .2.2. [12.]. 20.2.2. at New Delhi by

(Dhrampal Bhardwaj) Dy.Chief Fire Officer Tel;-01123414250

one

Copy to :-

- 1. The Principal, Rohini Educational Society, (Gitarattan Jindal Public School) Sector, 7, Rohini, Delhi-85.
- 2. The Director, Education, Government of N.C.T of Delhi. Old Sect. Delhi 54

Conditions for the validity of fire safety certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Fire+Safety+Acts+and +Rules/ http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms

| | · | | | | | | | |
|--------|---|-----------------------|-------------------|----------------------|---------|--|--|--|
| | | | | | | | | |
| 1 | Name & address of the building | INSPECT Rohini Edu | ION REPORT | | | | | |
| 2 | Name & address of the building : Rohini Educational Society, (Gitarattan Jindal Public School) Society of Occupancy : Educational | | | | | | | |
| 3. | | : Renewal (F | asemant 1 C | | | | | |
| 5. | Fire Safety directives letter No | : F.6/DFS/M | S/2019/1511 dated | d + 03 upper floors) | | | | |
| 6. | Date of inspection : 05.12.2022 | | V | | | | | |
| 7. | | | | | | | | |
| 8. | Name and designation of officer | S. A.K. Sharma | a ADO(Rohini) | | | | | |
| | riom the building side | | dal (Chariman) | | | | | |
| 9. | | : 1988-89 | (Chariman) | | | | | |
| S. No. | Applicant's letter No | OD N | dated 11.11.2022. | | | | | |
| 5.110 | | revention | NBC-2016 | Provided at site | Remarks | | | |
| 1. | and fire safety U/R 33 | | Requirement | riovided at site | MR/NMR | | | |
| | Access to building | | - | | | | | |
| | Gate width | Road width | | | MR | | | |
| | • Width of internal road | | 4.45m | 20m 4.5m | MR | | | |
| 2. | | | NA | NA | NA | | | |
| 2. | Number, Width, Type & Arrangement of Exite | | | | | | | |
| | a. Number of staircases | | | | | | | |
| | Upper Floors | 03 | 03 | MR | | | | |
| | • Basements | 02 | 02 | MR | | | | |
| | b. Width of staircases | | | 02 | with | | | |
| | Upper Floor | | 1.5m | 160m, 1.45m & 1.5m | MR | | | |
| | • Basements | | 1.5m | 1.5m & 1.45m | MR | | | |
| | c. Protection of exits | | | 1.511 @ 1.4511 | IVIIX | | | |
| | Fire check door | | NA | NA | NA | | | |
| | Pressurizationd. No. of continuous staircases to terrace | | NA | NA | NA | | | |
| | e. Width of Corridor | 01 | 02 | MR | | | | |
| | f. Door Size | | NA | NA | NA | | | |
| | | | 1.0m | 1.0m | MR | | | |
| 3. | Compartmentation Image: Compartmentation | | | | | | | |
| | | The check door | | | NA | | | |
| | Sealing of electrical shaf | | NA | NA | NA | | | |
| | Fire Rating of shaft door Water Curtain | | NA | NA | NA | | | |
| | Fire Dampers | NA | NA | NA | | | | |
| | - | | NA | NA | NA | | | |
| 4. | Smoke Management System | | | | | | | |
| | Basements | | 30 a/c per hour | Exhaust fan | | | | |
| | Upper floors | | 12 a/c per hour | Natural ventilated | MR | | | |
| 5. | | | 12 are per nour | Natural ventilated | MR | | | |
| 5. | Fire Extinguishers | | 20 | | | | | |
| | • Total numbers | 32nos. | 32nos. | MR | | | | |
| | TypesIS marking | | ABC/CO2 | ABC-20/CO2-12 | MR | | | |
| 6. | First-Aid Hose Reels | | ISI marked | Yes | MR | | | |
| | | 00 | . | | | | | |
| | • Total numbers on each fl | oor | 02 | Provided | MR | | | |
| | Length of hose reel hose Nozzle diameter | | 30mm | Provided | MR | | | |
| - | | | 5m | Provided | MR | | | |
| 7. | Automatic fire detection and alarming system • Type of detectors NA NA | | | | | | | |
| _ | Type of detectors | | | NA | NA | | | |
| | Location of Main Panel | | NA | NA | NA | | | |

M/18

Batter

•

1

| | Location of Repeater Panel | NA | NA | NA |
|-------------------------------|---|---|---|--|
| | Alternate source of power | NA | NA | NA |
| | Hooters' Location | NA | NA | NA |
| 8. | MOEFA | NA | NA | NA |
| 9. | Public Address System | NA | NA | NA |
| 10. | Automatic Sprinkler System | | | |
| | Basement | Required | Provided | MR |
| | Ground & Upper Floors | NA | NA | NA |
| | Sprinkler above false ceiling | NA | NA | NA |
| 11. | Internal Hydrants | | | |
| | Size of riser/down-comer | NA | NA | NA |
| | • Number of hydrants per floor | NA | NA | NA |
| | Hose Box | NA | NA | NA |
| 12. | Yard Hydrants | | | |
| | • Total number of hydrants | NA | NA | NA |
| | Hose Box | NA | NA | NA |
| 13. | Pumping Arrangements | | | |
| | Ground Level | | | |
| | Discharge of main Pump | NA | NA | NA |
| | Head of Main pump | NA | NA | NA |
| | Number of main pumps | NA | NA | NA |
| | Jockey Pump out put | NA | NA | NA |
| | Jockey pump head | NA | NA | NA |
| | Standby Pump out put | NA | NA | NA |
| | Standby Pump Head | NA | NA | NA |
| | Auto Starting/Manual Stopping | NA | NA | NA |
| | Pump House Access | NA | NA | NA |
| | Terrace level | | | |
| | Discharge of pump | 2x 450lpm | 2x 450lpm | MR |
| | Head of the pumpPower Supply | 40m | 40m | MR |
| | Power Supply Auto Starting of pump | Required | Provided | MR |
| | | Required | Provided | MR |
| 14. | Captive Water Storage for fire fighting | | | |
| | Underground tank capacity | NA | NA | NA |
| | | | | |
| | Draw-off connection | NA | NA | NA |
| | Fire service inlet | NA | NA NA | NA NA |
| | Fire service inletAccess to tank | NA NA | NA NA | |
| 1.5 | Fire service inlet Access to tank Overhead Tank capacity | NA NA 15,000ltr | NA NA 15,000ltr | NA |
| | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. | NA NA | NA NA | NA NA |
| | Fire service inlet Access to tank Overhead Tank capacity | NA NA 15,000ltr | NA NA 15,000ltr | NA NA MR |
| | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft | NA NA 15,000ltr | NA NA 15,000ltr | NA NA MR |
| | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby | NA NA 15,000ltr Required | NA NA 15,000ltr Provided | NA NA MR MR |
| | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car | NA NA 15,000ltr Required NA | NA NA 15,000ltr Provided NA | NA NA MR MR NA |
| | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch | NA NA 15,000ltr Required NA NA | NA NA 15,000ltr Provided NA NA | NA NA MR MR NA NA NA |
| | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car | NA NA 15,000ltr Required NA NA NA | NA NA 15,000ltr Provided NA NA NA NA NA | NA NA MR MR NA NA NA NA |
| 16. | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch | NA NA 15,000ltr Required NA NA NA NA | NA NA 15,000ltr Provided NA NA NA NA NA NA | NA NA MR MR NA NA NA NA NA NA |
| 7. | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage | NA NA 15,000ltr Required NA NA NA NA NA NA | NA NA 15,000ltr Provided NA NA NA NA NA | NA NA MR MR NA NA NA NA |
| 16. | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. | NANA15,000ltrRequiredNANANANANANANANANA | NA NA 15,000ltr Provided NA NA NA NA NA NA NA NA | NA NA MR MR NA NA NA NA NA NA NA |
| 7. | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply | NANA15,000ltrRequiredNANANANANANANANANA | NA NA 15,000ltr Provided NA NA NA NA NA NA NA NA | NA NA MR MR NA NA NA NA NA NA NA |
| 16. 7. 8. | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location | NANA15,000ltrRequiredNANANANANANANANANA | NA NA 15,000ltr Provided NA NA NA NA NA NA NA NA | NA NA MR MR NA NA NA NA NA NA NA |
| 15. 16. 17. 8. 9. | Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area | NANA15,000ltrRequiredNANANANANANANANANA | NA NA 15,000ltr Provided NA NA NA NA NA NA NA NA | NA NA MR MR NA NA NA NA NA NA NA |

| | NA | NA | NA |
|--|----|----------------|------------|
| PA System Panel | NA | NA | NA |
| Battery backup | NA | NA | NA |
| Building Floor Plans | NA | NA | NA |
| 20. Special Fire Protection System for Protection of special Risks, if any: | | lead and found | Gunational |

NIG

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/2019/1511 dated 23.07.2019 is recommended for renewal under rule 37 of the Delhi Fire Service rules 2010.

11222

Signature of the Inspecting Officer Ajay Kumar Sharma Name Designation ADO(Rohini)

DO OWW

ET letter is put up for kind peusal and signature place. Rohm

Co

DOFOLUNS

IN 200

nuel cel