

GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/Petrol/2023/SZ/ 14

Dated: 05/01/2023

FIRE SAFETY CERTIFICATE

Certified that **M/s Bedi Moters,** Retail Outlet of (Petrol, Diesel & CNG) located at Kemal Attaturk Marg, Near Race Course, New Delhi 110003 comprised of Ground floor only was issued FSC by this department vide letter No. F6/DFS/MS/2019/SZ//Petrol/1209 Dated 06/06/2019. The premises was re-inspected by the officer concerned of this department on 22/12/2022 in the presence of Mr. Manish Dagar (Partner) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy **class Hazardous (Group-J)** with effect from OS / O1 / 2023 for a period of **three years** in accordance with rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010.

Issued on 05/01/2023 at New Delhi by

(SUNIL CHAUDHARY) DY. CHIEF FIRE OFFICER (SZ)

Copy to: -

1. M/s Bedi Moters, Retail Outlet of (Petrol, Diesel & CNG) located at Kemal Attaturk Marg, Near Race Course, New Delhi 110003.

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. Any deviation, with regard to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>www.dfs.delhigovt.nic.in</u>
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

INSPECTION REPORT

N123

BITOTIE 201 1810

KI-A

| ľ | Name & Address of the Building | M/s Bedi Moters (Retail Outlet of Petrol, Diesel & CNG) At Kemal Attaturk Marg, Near Race Course, New Delbi 110002 | | | |
|-------|---|--|---------------------------------|--------------|--|
| 2 | Type of Occupancy | Thew Denn 1100 | | | |
| 3 | Building Comprised of | Group "J" Hazardous Building | | | |
| 4 | Type of Case | Ground Floor only | | | |
| 5 | Details of Previous NOC | Renewal | | | |
| 6 | | F6/DFS/MS/2019/SZ//Petrol/1209 Dated 06/06/2019 | | | |
| 7 | Fire Safety Directives Letter No Date of Inspection | Nil | | | |
| 8 | | 2412-2022 | | | |
| 9 | Name of the Inspecting Officers | Sh. Rajesh Kumar ADO (BCP) | | | |
| 9 | Name & Designation of Officers from the building side | Mr. Manish Dagar (Partner) | | | |
| 10 | Year of construction | 1000 | | | |
| 11 | Applicant letter No. | 1998 Outdoor diary no 8346 Dated 22-11-2022 | | | |
| S. No | Minimum et al. | | | | |
| | Minimum standards on Fire Prevention and Fire Safety U/R 33 | Old NOC | Provided at Site | Remarks | |
| 1 | Access to Building. | requirements | | MR/NMR | |
| | Road width | 09m | 12 mtr | MR | |
| | • Gate width | -NA- | -NA- | -NA- | |
| | Width of internal road | -NA- | -NA- | -NA- | |
| 2 | Number, width, type and arrangements | of exits. | -147 - | -11/4- | |
| | a. Number of Staircase | | | | |
| | Upper floors | -NA- | -NA- | -NA- | |
| | Basement floor | -NA- | -NA- | -NA- | |
| | b. Width of Staircase | | -11/1- | -184- | |
| | Upper floors | -NA- | -NA- | -NA- | |
| | Basement floor | -NA- | -NA- | -NA- | |
| | c. Protection of exits | | | -14/4- | |
| | Fire check door | -NA- | -NA- | NIA | |
| | • Pressurization | -NA- | | -NA- | |
| | d. No. of continuous staircase to terrace | -NA- | -NA- | -NA- | |
| | e. Width of corridor | -NA- -NA- | -NA- | -NA- | |
| | f. Door size | | -NA- | -NA- | |
| 3 | Compartmentation. | 1 m | Provided | MR | |
| | • Fire check door. | NA | | | |
| | File check door. Sealing of electrical shafts. | -NA- -NA- | -NA- | -NA- | |
| | Fire rating of shaft door. | -NA- | -NA- -NA- | -NA- | |
| | Water curtain | -NA- | -NA- -NA- | -NA- -NA- | |
| | • Fire dampers. | -NA- | -NA- | | |
| 4. | Smoke Management system. | | -11/7- | -NA- | |
| | Basement | -NA- | -NA- | NT A | |
| | Upper floors | -NA- | | -NA- | |
| 5. | Fire Extinguishers. | -14/3- | -NA- | -NA- | |
| | Total numbers | | 25 31- | 1 | |
| | Types | Required | 25 Nos | MR | |
| | | ABC/CO2/DCP | (75KG, 10KG & 4.5KG) | | |
| | ISI Marking | | CO ₂ ABC, DCP & AFFF | MR | |
| 6. | First Aid Hose Reels. | Required | Provided | MR | |
| | • Total numbers on each floor. | -NA- | -NA- | NI A | |
| | Length of hose-reel hose. | -NA- -NA- | -NA- -NA- | -NA- | |
| | Nozzle Diameter | -NA- | | -NA- | |
| | | _NΔ_ | -NA- | -NA- | |

N124

| | | NIZU | 3115 | | |
|-----|--|-----------------|------------------------------|--------------|--|
| 7 | Automatic Fire Detection and Alarming | vstem | 31 | मृत महोत | |
| | | | | | |
| | Type of detectorsLocation of Main Panel | Gas & Flame | portable detector with staff | MR | |
| | Location of Repeater Panel | -NA- | -NA- | -NA- | |
| | Alternate source of power | -NA- | -NA- | -NA- | |
| | Hooter's location | -NA- | -NA- | -NA- | |
| 8. | MOEFA | Technician room | Provided | MR | |
| | | -NA- | -NA- | -NA- | |
| | Public Address System | -NA- | -NA- | -NA- | |
| 10. | Automatic Sprinkler System | | | | |
| | • Basement | -NA- | -NA- | -NA- | |
| | • Upper floors | -NA- | -NA- | -NA- | |
| | • Sprinkler above false ceiling | -NA- | | | |
| 11. | Internal Hydrants. | -NA- | -NA- | -NA- | |
| | Size of Riser / Down-comer | | | | |
| | | -NA- | -NA- | -NA- | |
| | Number of Hydrant per floor | -NA- | -NA- | -NA- | |
| 12. | Hose box. | -NA- | -NA- | -NA- | |
| 12. | Yard Hydrants. | | | | |
| | • Total number of hydrants. | -NA- | -NA- | -NA- | |
| 12 | • Hose box. | -NA- | -NA- | -NA- | |
| 13. | Pumping arrangements. | | | | |
| | Ground Level | | | | |
| Γ | Discharge of main pump. | -NA- | -NA- | -NA- | |
| | Head of main pump. | -NA- | -NA- | -NA- | |
| | Number of main pumps. | -NA- | -NA- | -NA- | |
| | Jockey Pump output. | -NA- | -NA- | -NA- | |
| | Jockey Pump head. Standby Pump output | -NA- | -NA- | -NA- | |
| | Standby Pump output. Standby Pump head. | -NA- | -NA- | -NA- | |
| | Auto Starting/Manual Stopping. | -NA- | -NA- | -NA- | |
| ŀ | Terrace Level | -NA- | -NA- | -NA- | |
| ł | Discharge of pump. | NA | | | |
| | Head of pump. | -NA- -NA- | -NA- | -NA- | |
| | Power supply. | -NA- | -NA- -NA- | -NA- | |
| | Auto starting of pump. | -NA- | -NA- -NA- | -NA- | |
| 14. | Captive water storage for fire-fighting. | | | -NA- | |
| | Underground tank capacity. | -NA- | -NA- | NT A | |
| | Draw-off connection. | -NA- | -NA- | -NA- -NA- | |
| | Fire Service Inlet. | -NA- | -NA- | -NA- | |
| | Access to tank. | -NA- | -NA- | -NA- | |
| | • Overhead tank capacity. | -NA- | -NA- | -NA- | |
| 15. | No Smoking Signage (Hindi & English) | Required | Provided (Hindi & English) | MR | |
| 16. | Provision of Lifts. | | | | |
| | • Pressurization of lift shaft. | -NA- | -NA- | N 7.4 | |
| | Pressurization of lift lobby. | -NA- | -NA- | -NA- -NA- | |
| | Communication in lift car. | -NA- | -NA- | -NA- -NA- | |
| | • Fireman's switch. | -NA- | -NA- | -NA- | |
| | Lift signage. | -NA- | -NA- | -NA- | |
| 17 | Standby Power Supply | NA | | | |
| 18. | Refuge Area | INA | Provided (DG Set) | NA | |
| | Total area | NI A | | | |
| | Location | -NA- | -NA- | -NA- | |
| | | -NA- | -NA- | -NA- | |

19.

FireCe

N/25



| | Fire Control Room. | | | | | |
|-----|---|------|---|------|--|--|
| | Detector System Panel. Flow Switch Panel. PA system Panel. Battery backup Building floor plan | -NA- | -NA- | -NA- | | |
| | | -NA- | -NA- | -NA- | | |
| | | -NA- | -NA- | -NA- | | |
| | | -NA- | -NA- | -NA- | | |
| | | -NA- | -NA- | -NA- | | |
| 20. | Special Fire Protection System for the Protection of special Risk, if any. | -NA- | Co2 flooding system provided in compressor, connected through gas detectors | -NA- | | |

The fire protection system such as fire extinguisher of different type and capacity, Fire buckets filled with loose dry sand & water provided at suitable places in the retail outlet area were checked and found functional at the time of inspection. "No Smoking" sign board were found displayed both Hindi & English at conspicuous places. No loose electrical wiring was seen in the premises.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under rules, renewal of the FSC issued vide letter No. F6/DFS/MS/2019/SZ//Petrol/1209 Dated 06/06/2019, under rules 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Un am

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar Designation: ADO(BCP)

DO (SD) Depots approved F.T. Letter i public for ignative PI Dylfy ICT