



## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DE LHI FIRE SERVICE, NEW DELHI-110001

No.F.6/DFS/MS/Indl./2023/NDZ/ 2 2

Dated: 13 /0) /2023

## **FIRE SAFETY CERTIFICATE**

Certified that the Plot No. 346, FIE Patparganj Industrial Area, Delhi-92, building comprised of Basement, Ground plus One Upper Floor, owned/occupied by Sage Metals Ltd., have already been issued NOC/FSC vide letter No. F6/DFS/MS/Indl./2019/NDZ/2137Dt. 14/1/2019. The premises was reinspected by the officers concerned of this department on 07/01/2023 in presence of Sh. Parvez Ansari and observed that all the Fire Prevention and Fire Safety arrangements provided in the premises, found in good working condition. The Premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Industrial" (Group G-1) with effect from 13/21/2012. For a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 13/01/2023 at New Delhi by

DY. CHIEF FIRE OFFICER
DELHI FIRE SERVICE

Copy to: -

1. The Manager, Plot No. 346, FIE Patparganj Industrial Area, Delhi-92.

## **Conditions for the validity of Fire Safety Certificate:**

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

NID

## INSPECTION REPORT 1. Name & address of the building: Plot No. 346, FIE Patparganj Industrial Area, Delhi-92

1. IV	wilding is commissed of	No. 346, FIE Patp	oarganj Industrial Area, D	elhi-92.
Z. B	unding is comprised of : Base	ment, Ground + 🤈	l Upper Floor	,
	ype of Occupancy : Indus	strial (Low Haza	rd) G-1	2
	ype of Case : Rene			1
5. D	etails of previous NOC : F6/D	FS/MS/Indl./20	19/NDZ/2137Dt. 14/1/2	2019 🖊 )
7 D	ire Safety directives Letter No.: Nil ate of inspection : 07/0	4 (2022		
		1/2023		
0. N	ame of the Inspecting Officer: A.K. Jame and designation of Officer	aiswal, D.O. (E.D	.) & Deepak Kumar ADO	(Shahd)
o, It				1
10 V		arvez Ansari		3
			0 : 1	1
S.No.	pplicant's Letter No. : Nil D.  Minimum Standards on fire	ated 02/11/2022	Outdoor Dairy No. 21/11/	2022
3.110.	prevention and fire safety U/R 33	BBL/	Provided at Site	Remarks 3
1	Access to building	NBC Part-IV		1
-	• Road width	12	12	M/D n
	Gate width	12 m	12 m	M/R n
	Width of internal road	4.5 m	4.5 m	M/R_r
2		N/A	N/A	N/A
	Number, Width, Type and Arrange a. Number of Staircases	ment of Exits		
	• Upper Floor	02 200	02 02	MD
	Basement	02 nos.	02 nos.	MRl
	b. Width of Staircases	02 nos.	02 nos.	MR
	• Upper Floor	1 40 9 0 00 m	1 10 0 0 00 m	MD
	Basement	1.40 & 0.90 m 1.40 & 1.25 m	1.40 & 0.90 m 1.40 & 1.30 m	MR
	c. Protection of exits	1.40 & 1.25 111	1.40 & 1.30 III	MR
	• Fire check door	Required	Provided	MD
	Pressurization	N/A	N/A	MR
	d. No. of continuous staircases to	01 nos.	01 nos.	N/A
	terrace	01 1105.	UT nos.	MR J
	e. Width of Corridor	1.5 m	1.5 m	MR
	f. Door size	N/A	N/A	
3	Compartmentation	11/11	N/A	N/A
	• Fire check Door	Required	Provided	MR
	<ul> <li>Sealing of electrical Shafts</li> </ul>	N/A	N/A	N/A
	• Fire rating of Shaft Door	N/A	N/A	
	Water Curtain	N/A	N/A	N/A N/A
	Fire Dampers	N/A	N/A	
4	Smoke Management System	.,	11/11	N/A
	Basement	Required	Provided	MR -
	Upper Floors	N/A	N/A	
5	Fire Extinguishers	/	N/A	N/A
	Total Numbers	10 Nos.	Provided	MD
	<ul><li>Types</li></ul>	ABC & Co2	ABC & Co2	MR /
	•IS Marking	ISI Marked	ABC & COZ	MR

e. Her

ISI Marked

ISI Marked

• IS Marking

MR

4/4

		411				
	First-aid-Hose Reels					
	• Total numbers of each floor	01 Nos.	04.11			
	• Length of hose reel hose	30 M	01 Nos.	MR		
	Nozzle diameter	05 mm	30 M	MR		
7	Automatic fire detection and alarming	US mm	05 mm	MR		
	• Type of detectors		NI /A	N. / A		
	• Location of main panel	N/A	N/A	N/A		
	Location of manipalier     Location of repeater panel	N/A	N/A	N/A		
	Alternate source of power	N/A N/A	N/A	N/A		
	Hooter's location	N/A	N/A	N/A		
8	MOEFA	<del></del>	N/A	N/A		
9	Public address System	N/A	N/A	N/A		
10	Automatic Sprinkler System	N/A	N/A	N/A		
	Basement	Doguinad	D	140		
	• Upper Floor	Required	Provided	MR		
	Sprinkler above false Ceiling	N/A	N/A	N/A		
11	Internal Hydrants	N/A	N/A	N/A		
	• Size of rise/down-comer	100 MM	100 101	140		
	Number of Hydrants per Floor	01 No.	100 MM	MR		
	Hose Box	01 No.	01 No.	MR		
12	Yard Hydrants	UI NO.	01 No.	MR		
	Total number of Hydrants	NI / A	NI /A	127.4		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements	N/A	N/A	N/A		
	• Ground Level					
	> Discharge of main Pump	NI / A	NI / A	N. (4		
	➤ Head of Main Pump	N/A	N/A	N/A		
	Number of main Pumps	N/A	N/A	N/A		
	Jockey pump output	N/A N/A	N/A	N/A		
	Jockey pump head		N/A	N/A		
	Standby pump output	N/A	N/A	N/A		
	Standby pump head	N/A N/A	N/A	N/A		
	Auto starting/Manual stopping	N/A	N/A	N/A		
	Pump house access	N/A	N/A	N/A		
	Terrace Level	N/A	N/A	N/A		
	Discharge of pump	900 LPM	Duncidad			
	> head of the pump	40 M	Provided	MR		
	> Power supply		Provided	MR		
	> Auto Starting of pump	Required Required	Provided	MR		
14			Provided	MR		
11	e Underground tonk consists.					
	> Draw-off connection	N/A	N/A	N/A		
	> Fire service inlet	N/A	N/A	N/A		
	> Access to tank	N/A	N/A	N/A		
	• overhead Tank capacity	N/A	N/A	N/A		
15		N/A	N/A	N/A		
12	Exit Signage	15,000 Ltı	rs.   15,000 Ltrs.	MR		

4/8.

16	Provision of Lifts				
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	N/A	N/A	N/A	
	<ul> <li>Pressurization of Lift lobby</li> </ul>	N/A	N/A	N/A	
	<ul> <li>Communication in lift car</li> </ul>	N/A	N/A	N/A	
	<ul> <li>Firemen's grounding switch</li> </ul>	N/A	N/A	N/A	
	Lift Signage	N/A	N/A	N/A	
17	Standby power supply	N/A	N/A	N/A	
18	Refuge Area				
	• Total area	N/A	N/A	N/A	
	• Location	N/A	N/A	N/A	
19	Fire Control Room				
	Detector system panel	N/A	N/A	N/A	
	• Flow switch panel	N/A	N/A	N/A	
	PA system panel	N/A	N/A	N/A	
	Battery backup	N/A	N/A	N/A	
	Building floor plans	N/A	N/A	N/A	
20	Special Fire Protection systems	N/A	N/A	N/A	
	for protection of special Risks, if	,			
	anv:				

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter

No. F6/DFS/MS/Indl./2019/NDZ/2137Dt. 14/1/2019, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer Name: Ashok Kumar Jaiswal Designation: D.O. (East. Div.)

Signature of the Inspecting Officer

Name: Deepak Kumar Hooda Designation: ADO (Shahdara)

F.T. is added.